

AD7506/AD7507

FEATURES

R_{ON} : 300 Ω
Power Dissipation: 1.5mW
TTL/DTL/CMOS Direct Interface
Break-Before-Make Switching
Standard 28-Pin DIPs and 28-Terminal Surface Mount Packages

GENERAL DESCRIPTION

The AD7506 is a monolithic CMOS 16-channel analog multiplexer packaged in a 28-pin DIP or a 28-terminal surface mount package. It switches a common output to one of 16 inputs, depending on the state of four address lines and an "enable." The AD7507 is identical to the AD7506 except it has two outputs switched to two of 16 inputs depending on three binary address states and an "enable."

ABSOLUTE MAXIMUM RATINGS*

$(T_A = +25^\circ\text{C}$ unless otherwise noted)
 $V_{DD} - GND$ +17V
 $V_{SS} - GND$ -17V
 V Between Any Switch Terminals (see Note 1) 25V
 Digital Input Voltage Range V_{DD} to GND
 Overvoltage at V_{OUT} (V_S) V_{SS} , V_{DD}
 Switch Current (I_S , Continuous One Channel) 20mA
 Switch Current (I_S , Surge One Channel)
 1ms Duration, 10% Duty Cycle 35mA
 Power Dissipation (Any Package)
 Up to $+50^\circ\text{C}$ 1000mW
 Derates above $+50^\circ\text{C}$ by 10mW/ $^\circ\text{C}$
 Operating Temperature
 Commercial (KN Versions) 0 to $+70^\circ\text{C}$
 Industrial (KQ Versions) -25°C to $+85^\circ\text{C}$
 Extended (TQ, TE Versions) -55°C to $+125^\circ\text{C}$
 Storage Temperature -65°C to $+150^\circ\text{C}$
 Lead Temperature (Soldering, 10sec) $+300^\circ\text{C}$

CAUTION:

¹Do not apply voltage higher than V_{DD} and V_{SS} to any other terminal, especially when $V_{SS} = V_{DD} = 0\text{V}$ all other pins should be at 0V.


²The digital control inputs are diode protected; however, permanent damage may occur on unconnected units under high energy electrostatic fields. Keep unused units in conductive foam at all times.

*Stresses above those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. This is a stress rating only and functional operation of the device at these or any other conditions above those indicated in the operational sections of this specification is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability. Only one Absolute Maximum Rating may be applied at any one time.


REV. A

Information furnished by Analog Devices is believed to be accurate and reliable. However, no responsibility is assumed by Analog Devices for its use, nor for any infringements of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Analog Devices.

FUNCTIONAL DIAGRAMS



AD7506



AD7507

ORDERING GUIDE

Model ¹	Temperature Range	Package Option ²
AD7506KN	0°C to $+70^\circ\text{C}$	N-28
AD7506KQ	-25°C to $+85^\circ\text{C}$	Q-28
AD7506TQ	-55°C to $+125^\circ\text{C}$	Q-28
AD7506TE	-55°C to $+125^\circ\text{C}$	E-28A
AD7507KN	0°C to $+70^\circ\text{C}$	N-28
AD7507KQ	-25°C to $+85^\circ\text{C}$	Q-28
AD7507TQ	-55°C to $+125^\circ\text{C}$	Q-28
AD7507TE	-55°C to $+125^\circ\text{C}$	E-28A

NOTES

¹To order MIL-STD-883, Class B, processed parts, add/883B to part number. See Analog Devices Military Products Databook (1990) for military data sheet.

²N = Plastic DIP; Q = Cerdip; E = Leadless Ceramic Chip Carrier (LCCC).

One Technology Way, P.O. Box 9106, Norwood, MA 02062-9106, U.S.A.
 Tel: 617/329-4700 Fax: 617/326-8703 Twx: 710/394-6577
 Telex: 924491 Cable: ANALOG NORWOODMASS

AD7506/AD7507 — SPECIFICATIONS ($V_{DD} = +15V$, $V_{SS} = -15V$ unless otherwise noted.)

Parameter	Version ¹	Switch Condition	@ +25°C	Over Specified Temperature Range	Test Conditions
ANALOG SWITCH					
R _{ON}	K T	ON ON	300Ω typ, 450Ω max 400Ω max	550Ω max 500Ω max	V _S =−10V to +10V, I _S =1mA
R _{ON} vs. V _S	All	ON	15% typ		V _S =0V, I _S =1mA
R _{ON} vs. Temperature	All	ON	0.5%/°C typ		
ΔR _{ON} Between Switches	All	ON	4% typ		
R _{ON} vs. Temperature Between Switches	All	ON	0.05%/°C typ		
I _S (OFF)	K T	OFF OFF	0.05nA typ, 5nA max 0.05nA typ, 1nA max	50nA max 50nA max	V _S =−10V, V _{OUT} =+10V and
I _{OUT} (OFF)	AD7506	K T	OFF OFF	0.3nA typ, 20nA max 0.3nA typ, 10nA max	V _S =+10V, V _{OUT} =−10V “Enable” Low
	AD7507	K T	OFF OFF	0.3nA typ, 10nA max 0.3nA typ, 5nA max	
I _{OUT} −I _S (Any Switch ON)	AD7506	K T	ON ON	0.3nA typ, 20nA max 0.3nA typ, 10nA max	V _S =0V
	AD7507	K T	ON ON	0.3nA typ, 10nA max 0.3nA typ, 5nA max	
DIGITAL CONTROL					
V _{INL}	All			0.8V max	
V _{INH}	All			2.4V min	
I _{INL} or I _{INH}	All		10μA max	30μA max	
C _{IN}	All		3pF typ		
DYNAMIC CHARACTERISTICS ²					
t _{TRANSITION}	All		700ns typ, 1000ns max		V _{IN} : 0 to 3.0V
t _{OPEN}	All		100ns typ		
t _{ON} (En)	All		1.5μs max		V _{EN} : 0 to 3.0V
t _{OFF} (En)	All		1μs max		
“OFF” Isolation	All		70dB typ		V _{EN} =0, R _L =200Ω, C _L =3.0pF, V _S =3.0V rms, f=50kHz
C _S	All	OFF	5pF typ		
C _{OUT}	AD7506	All	OFF	40pF typ	
	AD7507	All	OFF	20pF typ	
C _{S-OUT}	All	OFF	0.5pF typ		
C _{SS} Between Any Two Switches	All	OFF	0.5pF typ		
POWER SUPPLY					
I _{DD}	K T	OFF OFF	0.05mA typ, 1mA max 0.05mA typ, 1mA max	2mA max	All Digital Inputs Low
I _{SS}	K T	OFF OFF	0.05mA typ, 1mA max 0.05mA typ, 1mA max	2mA max	
I _{DD}	K T	ON ON	0.3mA typ, 1mA max 0.3mA typ, 1mA max	2mA max	All Digital Inputs High
I _{SS}	K T	ON ON	0.05mA typ, 1mA max 0.05mA typ, 1mA max	2mA max	

NOTES

¹KN Version specified for 0 to +70°C; KQ Version for -25°C to +85°C; and TQ, TE Versions for -55°C to +125°C.

²Sample tested to ensure compliance.

Specifications subject to change without notice.

CAUTION

ESD (electrostatic discharge) sensitive device. The digital control inputs are diode protected; however, permanent damage may occur on unconnected devices subject to high energy electrostatic fields. Unused devices must be stored in conductive foam or shunts. The protective foam should be discharged to the destination socket before devices are removed.




TRUTH TABLES


AD7506					
A ₃	A ₂	A ₁	A ₀	E _N	"ON"
0	0	0	0	1	1
0	0	0	1	1	2
0	0	1	0	1	3
0	0	1	1	1	4
0	1	0	0	1	5
0	1	0	1	1	6
0	1	1	0	1	7
0	1	1	1	1	8
1	0	0	0	1	9
1	0	0	1	1	10
1	0	1	0	1	11
1	0	1	1	1	12
1	1	0	0	1	13
1	1	0	1	1	14
1	1	1	0	1	15
1	1	1	1	1	16
X	X	X	X	0	None

AD7507				
A ₂	A ₁	A ₀	E _N	"ON"
0	0	0	1	1 & 9
0	0	1	1	2 & 10
0	1	0	1	3 & 11
0	1	1	1	4 & 12
1	0	0	1	5 & 13
1	0	1	1	6 & 14
1	1	0	1	7 & 15
1	1	1	1	8 & 16
X	X	X	0	None

PIN CONFIGURATIONS




LCCC




Typical Performance Characteristics

1. R_{ON} vs. V_S




At Different Power Supplies




At Different Temperatures


2. I_{OUT} vs. V_{OUT}




3. I_{OUT} vs. T_A




4. t_{TRANSITION} vs. V_{IN}




5. P_D vs. Logic Frequency



TEST CIRCUIT 1



TEST CIRCUIT 2



Dimensions shown in inches and (mm).

0.2 (5.08) MAX

1.45 (36.83)

1.44 (36.58)

0.55 (13.97)

0.53 (13.47)

0.065 (1.66)

0.045 (1.16)

0.02 (0.508)

0.015 (0.381)

0.105 (2.67)

0.095 (2.42)

0.175 (4.45)

0.12 (3.05)

0.606 (15.4)

0.594 (15.09)

0.16 (4.07)

0.14 (3.56)

0.012 (0.305)

0.008 (0.203)

15°

0

LEAD NO. 1 IDENTIFIED BY DOT OR NOTCH
LEADS WILL BE EITHER GOLD OR TIN PLATED

1.490 (37.84) MAX

0.06 (1.52)
0.05 (1.27)

0.525 (13.33)
0.515 (13.08)

0.22 (5.59) MAX

GLASS SEALANT

0.125 (3.175) MIN

0.62 (15.74)
0.59 (14.93)

0.012 (3.05)
0.008 (20.3)

15°

0.11 (2.79)
0.099 (2.28)

0.02 (0.5)
0.016 (0.406)

1. LEAD NO. 1 IDENTIFIED BY DOT OR NOTCH
2. CERDIP LEADS WILL BE EITHER TIN PLATED OR SOLDER DIPPED
IN ACCORDANCE WITH MIL-M-38510 REQUIREMENTS

[illegible]

PRINTED IN U.S.A.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.