

# NVMFD5483NL

## Power MOSFET

60 V, 36 mΩ, 24 A, Dual N-Channel

### Features

- Small Footprint (5x6 mm) for Compact Designs
- Low  $R_{DS(on)}$  to Minimize Conduction Losses
- Low Capacitance to Minimize Driver Losses
- 175°C Operating Temperature
- NVMFD5483NLWF – Wettable Flank Option for Enhanced Optical Inspection
- AEC-Q101 Qualified and PPAP Capable
- This is a Pb-Free Device

### MAXIMUM RATINGS ( $T_J = 25^\circ\text{C}$ unless otherwise noted)

| Parameter                                                                                                                                                |                                                   | Symbol                    | Value      | Unit             |
|----------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------|---------------------------|------------|------------------|
| Drain-to-Source Voltage                                                                                                                                  |                                                   | $V_{DSS}$                 | 60         | V                |
| Gate-to-Source Voltage                                                                                                                                   |                                                   | $V_{GS}$                  | $\pm 20$   | V                |
| Continuous Drain Current $R_{\theta JC}$ (Notes 1, 2, 4)                                                                                                 | Steady State                                      | $T_C = 25^\circ\text{C}$  | $I_D$ 24   | A                |
|                                                                                                                                                          |                                                   | $T_C = 100^\circ\text{C}$ | 17         |                  |
| Power Dissipation $R_{\theta JC}$ (Notes 1, 2)                                                                                                           | Steady State                                      | $T_C = 25^\circ\text{C}$  | $P_D$ 44.1 | W                |
|                                                                                                                                                          |                                                   | $T_C = 100^\circ\text{C}$ | 22.1       |                  |
| Continuous Drain Current $R_{\theta JA}$ (Notes 1, 3 & 4)                                                                                                | Steady State                                      | $T_A = 25^\circ\text{C}$  | $I_D$ 6.4  | A                |
|                                                                                                                                                          |                                                   | $T_A = 100^\circ\text{C}$ | 4.5        |                  |
| Power Dissipation $R_{\theta JA}$ (Notes 1 & 3)                                                                                                          | Steady State                                      | $T_A = 25^\circ\text{C}$  | $P_D$ 3.1  | W                |
|                                                                                                                                                          |                                                   | $T_A = 100^\circ\text{C}$ | 1.5        |                  |
| Pulsed Drain Current                                                                                                                                     | $T_A = 25^\circ\text{C}$ , $t_p = 10 \mu\text{s}$ | $I_{DM}$                  | 153        | A                |
| Operating Junction and Storage Temperature                                                                                                               |                                                   | $T_J, T_{stg}$            | -55 to 175 | $^\circ\text{C}$ |
| Source Current (Body Diode)                                                                                                                              |                                                   | $I_S$                     | 39         | A                |
| Single Pulse Drain-to-Source Avalanche Energy ( $T_J = 25^\circ\text{C}$ , $V_{GS} = 10 \text{ V}$ , $I_{L(pk)} = 28 \text{ A}$ , $L = 0.1 \text{ mH}$ ) |                                                   | $E_{AS}$                  | 39         | mJ               |
| Lead Temperature for Soldering Purposes (1/8" from case for 10 s)                                                                                        |                                                   | $T_L$                     | 260        | $^\circ\text{C}$ |

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

### THERMAL RESISTANCE MAXIMUM RATINGS (Note 1)

| Parameter                                   | Symbol          | Value | Unit               |
|---------------------------------------------|-----------------|-------|--------------------|
| Junction-to-Case – Steady State (Note 2)    | $R_{\theta JC}$ | 3.4   | $^\circ\text{C/W}$ |
| Junction-to-Ambient – Steady State (Note 3) | $R_{\theta JA}$ | 49    |                    |

1. The entire application environment impacts the thermal resistance values shown, they are not constants and are only valid for the particular conditions noted.
2. Surface-mounted to an ideal (infinite) heat sink.
3. Surface-mounted on FR4 board using a 650 mm<sup>2</sup>, 2 oz. Cu pad.
4. Maximum current for pulses as long as 1 second are higher but are dependent on pulse duration and duty cycle.




ON Semiconductor®

[www.onsemi.com](http://www.onsemi.com)


| $V_{(BR)DSS}$ | $R_{DS(on)}$ MAX | $I_D$ MAX |
|---------------|------------------|-----------|
| 60 V          | 36 mΩ @ 10 V     | 24 A      |
|               | 45 mΩ @ 4.5 V    |           |

### Dual N-Channel



### MARKING DIAGRAM

DFN8 5x6  
(SO8FL)  
CASE 506BT



XXXXXX = 5483NL  
(NVMFD5483NL) or  
5483LW  
(NVMFD5483NLWF)

A = Assembly Location  
Y = Year  
W = Work Week  
ZZ = Lot Traceability

### ORDERING INFORMATION

| Device           | Package           | Shipping†            |
|------------------|-------------------|----------------------|
| NVMFD5483NLT1G   | DFN8<br>(Pb-Free) | 1500/<br>Tape & Reel |
| NVMFD5483NLT3G   | DFN8<br>(Pb-Free) | 5000/<br>Tape & Reel |
| NVMFD5483NLWFT1G | DFN8<br>(Pb-Free) | 1500/<br>Tape & Reel |
| NVMFD5483NLWFT3G | DFN8<br>(Pb-Free) | 5000/<br>Tape & Reel |

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specification Brochure, BRD8011/D.

# NVMFD5483NL

## ELECTRICAL CHARACTERISTICS ( $T_J = 25^\circ\text{C}$ unless otherwise specified)

| Parameter                                                 | Symbol            | Test Condition                                                    | Min                       | Typ | Max       | Unit                 |
|-----------------------------------------------------------|-------------------|-------------------------------------------------------------------|---------------------------|-----|-----------|----------------------|
| <b>OFF CHARACTERISTICS</b>                                |                   |                                                                   |                           |     |           |                      |
| Drain-to-Source Breakdown Voltage                         | $V_{(BR)DSS}$     | $V_{GS} = 0\text{ V}, I_D = 250\text{ }\mu\text{A}$               | 60                        |     |           | V                    |
| Drain-to-Source Breakdown Voltage Temperature Coefficient | $V_{(BR)DSS}/T_J$ | Reference to $25^\circ\text{C}$<br>$I_D = 250\text{ }\mu\text{A}$ |                           | 63  |           | mV/ $^\circ\text{C}$ |
| Zero Gate Voltage Drain Current                           | $I_{DSS}$         | $V_{GS} = 0\text{ V},$<br>$V_{DS} = 60\text{ V}$                  | $T_J = 25^\circ\text{C}$  |     | 1.0       | $\mu\text{A}$        |
|                                                           |                   |                                                                   | $T_J = 125^\circ\text{C}$ |     | 10        |                      |
| Gate-to-Source Leakage Current                            | $I_{GSS}$         | $V_{DS} = 0\text{ V}, V_{GS} = \pm 20\text{ V}$                   |                           |     | $\pm 100$ | nA                   |

## ON CHARACTERISTICS (Note 5)

|                                                |                  |                                                                   |     |      |     |                      |
|------------------------------------------------|------------------|-------------------------------------------------------------------|-----|------|-----|----------------------|
| Gate Threshold Voltage                         | $V_{GS(TH)}$     | $V_{GS} = V_{DS}, I_D = 250\text{ }\mu\text{A}$                   | 1.5 |      | 2.5 | V                    |
| Gate Threshold Voltage Temperature Coefficient | $V_{GS(TH)}/T_J$ | Reference to $25^\circ\text{C}$<br>$I_D = 250\text{ }\mu\text{A}$ |     | -5.2 |     | mV/ $^\circ\text{C}$ |
| Drain-to-Source On Resistance                  | $R_{DS(on)}$     | $V_{GS} = 10\text{ V}, I_D = 15\text{ A}$                         |     | 29   | 36  | m $\Omega$           |
|                                                |                  | $V_{GS} = 4.5\text{ V}, I_D = 15\text{ A}$                        |     | 36   | 45  |                      |

## CHARGES AND CAPACITANCES

|                              |              |                                                                      |  |      |  |    |
|------------------------------|--------------|----------------------------------------------------------------------|--|------|--|----|
| Input Capacitance            | $C_{iss}$    | $V_{GS} = 0\text{ V}, f = 1.0\text{ MHz}, V_{DS} = 25\text{ V}$      |  | 668  |  | pF |
| Output Capacitance           | $C_{oss}$    |                                                                      |  | 152  |  |    |
| Reverse Transfer Capacitance | $C_{rss}$    |                                                                      |  | 67   |  |    |
| Total Gate Charge            | $Q_{G(TOT)}$ | $V_{GS} = 10\text{ V}, V_{DS} = 48\text{ V},$<br>$I_D = 10\text{ A}$ |  | 23.4 |  | nC |
| Threshold Gate Charge        | $Q_{G(TH)}$  |                                                                      |  | 0.65 |  |    |
| Gate-to-Source Charge        | $Q_{GS}$     |                                                                      |  | 2.14 |  |    |
| Gate-to-Drain Charge         | $Q_{GD}$     |                                                                      |  | 9.16 |  |    |
| Total Gate Charge            | $Q_{G(TOT)}$ | $V_{GS} = 4.5\text{ V}, V_{DS} = 48\text{ V}, I_D = 10\text{ A}$     |  | 13.2 |  | nC |

## SWITCHING CHARACTERISTICS (Note 6)

|                     |              |                                                                                                 |  |      |  |    |
|---------------------|--------------|-------------------------------------------------------------------------------------------------|--|------|--|----|
| Turn-On Delay Time  | $t_{d(on)}$  | $V_{GS} = 4.5\text{ V}, V_{DS} = 48\text{ V},$<br>$I_D = 5.0\text{ A}, R_G = 2.5\text{ }\Omega$ |  | 6.8  |  | ns |
| Rise Time           | $t_r$        |                                                                                                 |  | 10.3 |  |    |
| Turn-Off Delay Time | $t_{d(off)}$ |                                                                                                 |  | 37.5 |  |    |
| Fall Time           | $t_f$        |                                                                                                 |  | 23.5 |  |    |

## DRAIN-SOURCE DIODE CHARACTERISTICS

|                         |          |                                                                                   |                           |      |      |     |   |
|-------------------------|----------|-----------------------------------------------------------------------------------|---------------------------|------|------|-----|---|
| Forward Diode Voltage   | $V_{SD}$ | $V_{GS} = 0\text{ V},$<br>$I_S = 10\text{ A}$                                     | $T_J = 25^\circ\text{C}$  |      | 0.87 | 1.2 | V |
|                         |          |                                                                                   | $T_J = 125^\circ\text{C}$ |      | 0.82 |     |   |
| Reverse Recovery Time   | $t_{RR}$ | $V_{GS} = 0\text{ V}, d_I/d_t = 100\text{ A}/\mu\text{s},$<br>$I_S = 10\text{ A}$ |                           | 30   |      | ns  |   |
| Charge Time             | $t_a$    |                                                                                   |                           | 23.3 |      |     |   |
| Discharge Time          | $t_b$    |                                                                                   |                           | 6.7  |      |     |   |
| Reverse Recovery Charge | $Q_{RR}$ |                                                                                   |                           | 35   |      | nC  |   |

5. Pulse Test: pulse width = 300  $\mu\text{s}$ , duty cycle  $\leq 2\%$ .

6. Switching characteristics are independent of operating junction temperatures.

TYPICAL CHARACTERISTICS




Figure 1. On-Region Characteristics




Figure 2. Transfer Characteristics




Figure 3. On-Resistance vs.  $V_{GS}$




Figure 4. On-Resistance vs. Drain Current and Gate Voltage




Figure 5. On-Resistance Variation with Temperature




Figure 6. Drain-to-Source Leakage Current vs. Voltage

TYPICAL CHARACTERISTICS




Figure 7. Capacitance Variation




Figure 8. Gate-to-Source and Drain-to-Source Voltage vs. Total Charge




Figure 9. Resistive Switching Time Variation vs. Gate Resistance




Figure 10. Diode Forward Voltage vs. Current




Figure 11. Maximum Rated Forward Biased Safe Operating Area

TYPICAL CHARACTERISTICS





Figure 12. Thermal Response

# NVMFD5483NL

## PACKAGE DIMENSIONS

### DFN8 5x6, 1.27P Dual Flag (SO8FL-Dual) CASE 506BT ISSUE E



- NOTES:
1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
  2. CONTROLLING DIMENSION: MILLIMETERS.
  3. DIMENSION b APPLIES TO PLATED TERMINAL AND IS MEASURED BETWEEN 0.15 AND 0.30 MM FROM THE TERMINAL TIP.
  4. PROFILE TOLERANCE APPLIES TO THE EXPOSED PAD AS WELL AS THE TERMINALS.
  5. DIMENSIONS D1 AND E1 DO NOT INCLUDE MOLD FLASH, PROTRUSIONS, OR GATE BURRS.
  6. SEATING PLANE IS DEFINED BY THE TERMINALS. A1 IS DEFINED AS THE DISTANCE FROM THE SEATING PLANE TO THE LOWEST POINT ON THE PACKAGE BODY.
  7. A VISUAL INDICATOR FOR PIN 1 MUST BE LOCATED IN THIS AREA.

\*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

ON Semiconductor and are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of SCILLC's product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## PUBLICATION ORDERING INFORMATION

**LITERATURE FULFILLMENT:**  
Literature Distribution Center for ON Semiconductor  
P.O. Box 5163, Denver, Colorado 80217 USA  
Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada  
Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada  
Email: [orderlit@onsemi.com](mailto:orderlit@onsemi.com)

**N. American Technical Support:** 800-282-9855 Toll Free  
USA/Canada  
**Europe, Middle East and Africa Technical Support:**  
Phone: 421 33 790 2910  
**Japan Customer Focus Center**  
Phone: 81-3-5817-1050

**ON Semiconductor Website:** [www.onsemi.com](http://www.onsemi.com)  
**Order Literature:** <http://www.onsemi.com/orderlit>  
For additional information, please contact your local Sales Representative



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.