

## LED Lamp Module

# A60 F0 type module



- **Maximum up to 7W**
- **CREE LEDs**
- **E26 and E27 lamp base**
- **UL plastic material**

The lamp base can be compatible to either E26 or E27 standard base.

The Heat dissipation of A60 F0 type module heat sink can be up to maximum 7 wattage.

A60 F0 type module uses UL listed material for all the plastic components.

A60 F0 type module will be the best solution for bulb lamp.

# ▶▶ Table of Contents

<b>Specifications .....</b>	<b>P. 3</b>
<b>Exterior Dimensions .....</b>	<b>P. 4</b>
<b>Nomenclature .....</b>	<b>P. 4</b>
<b>Part Number .....</b>	<b>P. 5</b>
<b>The circuit design reference .....</b>	<b>P. 6</b>
<b>Life Time .....</b>	<b>P. 6</b>
<b>Package information .....</b>	<b>P. 7 ~ P. 10</b>
<b>Reference information .....</b>	<b>P. 11 ~ P. 20</b>

# Specifications



Module Name	A60 F0 type module	
With the use of LED	 CXA1512	
Rating Power	Maximum up to 7 Wattage	
LED Quantity	1pcs	
LED Dispose Mode	1S	
Lens efficiency	80%	
Lamp holder	E26 type	E27 type
Exterior Dimension	60*112 mm	60*115mm
Beam Angle	270 deg.	
Operate Temperature	-20°C~+50°C	
Storage Temperature	-20°C~+50°C	

Table 1 : The specifications for A60 F0 type.

## ▶▶ Exterior Dimension



Tolerance : 2.5 mm (1/10")

Figure 1 : The exterior dimension for A60 F0 type module.

## ▶▶ Nomenclature

**M A60F0 B E27 – L B7 01 – BAG 00**

X1   X2   X3   X4   X5   X6   X7   X8   X9

**X1**

Company Code

M : Ledlink Module

**X2**

Product Series Type

A60F0 : A60F0 type

**X3**

Exterior Color

W : White  
B : Black

**X4**

Lamp Holder

E26 : E26 type  
E27 : E27 type

**X5**

Lens type

L : Lampshade

**X6**

Beam Angle

B7 : 270 degrees

**X7**

Lens Quantity

01: Single

**X8**

Lens Number

BAG: BAG model

**X9**

Package

00 : series number

Figure 2 : The nomenclature for A60 F0 type module.

# ▶▶ Part Number

Part Number	Lamp Holder	Heat sink Material	Plastic Material	Plastic Color	Cover color
MA60F0BE26-LB701-BAG00	E26 type	ADC 12 + Anodized	UL approval Plastic*	Black	
MA60F0WE26-LB701-BAG00				White	
MA60F0BE27-LB701-BAG00	E27 type			Black	
MA60F0WE27-LB701-BAG00				White	

\* : Please refer to "reference information" in page 11 ~ 15.

Table 2 : The part number for A60 F0 type.

# ▶▶ The circuit design reference




Figure 3 : The maximum size of the circuit area for A60 F0 type module.

Notification : A60 F0 type module doesn't include the circuit part

# ▶▶ Life Time

Lighting Output

Ambient temperature





Figure 4: Lighting Output & Life Hours

# Package information


## Lamp shade part :



← Lamp shade



← Put Mode:  
 $1\text{PCS} * 36 = 36\text{pcs}$




← Inner Box:  
 $36\text{PCS} * 6 = 216\text{pcs}$



Figure 5: The package information for Lamp shade part.

# Package information



Lens part :



Lens



Put Mode:  
 $8\text{PCS} \times 9 = 72\text{pcs}$




Inner Box:  
 $72\text{PCS} \times 12 = 864\text{pcs}$

Figure 5: The package information for Lens part.





# Package information


Heat sink part :



Heat sink



Put Mode:  
20pcs



Inner Box:  
 $20 \times 3 = 60$ pcs


Figure 6 : The package information for heat sink part.

# Package information


## Lamp base part :



← Lamp Base



← Put Mode:  
1\*40=40pcs



← Inner Box:  
40\*6 Tier=240pcs

Figure 7 : The package information for lamp base part..

# ▶▶ Reference information

## The UL card of UL plastic material :


Component - Plastics							E135714
<b>NYTEX COMPOSITES CO LTD</b>							
6 LANE 468 CHANGSUI RD, SEC 4, PEITOU HSIANG CHANGHUA HSIEN 523 TW							
<b>CM-5000</b>							
Polyamide 66/6 (PA66/6), blend, mineral fiber, flame retardant, furnished as pellets							
	<b>Min Thk</b>	<b>Flame</b>			<b>RTI</b>	<b>RTI</b>	<b>RTI</b>
<b>Color</b>	<b>(mm)</b>	<b>Class</b>	<b>HWI</b>	<b>HAI</b>	<b>Elec</b>	<b>Imp</b>	<b>Str</b>
BK	1.6	V-0	2	1	65	65	65
	3.2	V-0	1	1	65	65	65
Comparative Tracking Index (CTI): -				Inclined Plane Tracking (IPT): -			
Dielectric Strength (kV/mm): -				Volume Resistivity (10 <sup>14</sup> ohm-cm): -			
High-Voltage Arc Tracking Rate (HVTR): -				High Volt, Low Current Arc Resis (D495): -			
Dimensional Stability (%): -							
ANSI/UL 94 small-scale test data does not pertain to building materials, furnishings and related contents. ANSI/UL 94 small-scale test data is intended solely for determining the flammability of plastic materials used in the components and parts of end-product devices and appliances, where the acceptability of the combination is determined by UL.							
Report Date: 2013-03-19							
Last Revised: 2013-03-19							
© 2013 UL LLC							
							
<b>IEC and ISO Test Methods</b>							
<b>Test Name</b>	<b>Test Method</b>	<b>Units</b>	<b>Thickness</b>	<b>Tested (mm)</b>	<b>Value</b>		
Flammability	IEC 60695-11-10	Class (color)	1.6		V-0 (BK)		
			3.2		V-0 (BK)		
Glow-Wire Flammability (GWFI)	IEC 60695-2-12	C	-		-		
Glow-Wire Ignition (GWIT)	IEC 60695-2-13	C	-		-		
IEC Comparative Tracking Index	IEC 60112	Volts (Max)	-		-		
IEC Ball Pressure	IEC 60695-10-2	C	-		-		
ISO Heat Deflection (1.80 MPa)	ISO 75-2	C	-		-		
ISO Tensile Strength	ISO 527-2	MPa	-		-		
ISO Flexural Strength	ISO 178	MPa	-		-		
ISO Tensile Impact	ISO 8256	kJ/m <sup>2</sup>	-		-		
ISO Izod Impact	ISO 180	kJ/m <sup>2</sup>	-		-		
ISO Charpy Impact	ISO 179-2	kJ/m <sup>2</sup>	-		-		
© 2013 UL LLC							

Figure8 : The UL card information of the sink part.

# Reference information

## The UL card of UL plastic material :


Component - Plastics							E206114
<b>STYRON (HONG KONG) LTD</b>							
TSING YI R & D LABORATORY, 40-50 TSING YI RD, TSING YI ISLAND N T HK							
<b>EMERGE PC 8130-(i)(f1)</b>							
Polycarbonate (PC), "EMERGE", furnished as pellets							
<b>Color</b>	<b>Min Thk (mm)</b>	<b>Flame Class</b>	<b>HWI</b>	<b>HAI</b>	<b>RTI Elec</b>	<b>RTI Imp</b>	<b>RTI Str</b>
ALL	1.5 3.0	V-0 V-0,5VA	2 2	1 1	130 130	115 115	130 130
Comparative Tracking Index (CTI): 2				Inclined Plane Tracking (IPT): -			
Dielectric Strength (kV/mm): -				Volume Resistivity (10 <sup>x</sup> ohm-cm) : -			
High-Voltage Arc Tracking Rate (HVTR): 1				High Volt, Low Current Arc Resis (D495): 7			
Dimensional Stability (%): -							
<b>(f1) - Suitable for outdoor use with respect to exposure to Ultraviolet Light, Water Exposure and Immersion in accordance with UL 746C.</b>							
<b>(i) - Followed by suffix numbers 3-15 incl. indicating melt flow rate</b>							
ANSI/UL 94 small-scale test data does not pertain to building materials, furnishings and related contents. ANSI/UL 94 small-scale test data is intended solely for determining the flammability of plastic materials used in the components and parts of end-product devices and appliances, where the acceptability of the combination is determined by UL.							
Report Date: 2011-07-12							
Last Revised: 2013-08-30							
© 2014 UL LLC							
							
<b>IEC and ISO Test Methods</b>							
Test Name	Test Method	Units	Thickness Tested (mm)	Value			
Flammability	IEC 60695-11-10, IEC 60695-11-20	Class (color)	1.5 3.0	V-0 (ALL) V-0,5VA (ALL)			
Glow-Wire Flammability (GWF1)	IEC 60695-2-12	C	-	-			
Glow-Wire Ignition (GWIT)	IEC 60695-2-13	C	-	-			
IEC Comparative Tracking Index	IEC 60112	Volts (Max)	-	-			
IEC Ball Pressure	IEC 60695-10-2	C	3.0	137			
ISO Heat Deflection (1.80 MPa)	ISO 75-2	C	-	-			
ISO Tensile Strength	ISO 527-2	MPa	-	-			
ISO Flexural Strength	ISO 178	MPa	-	-			
ISO Tensile Impact	ISO 8256	kJ/m <sup>2</sup>	-	-			
ISO Izod Impact	ISO 180	kJ/m <sup>2</sup>	-	-			
ISO Charpy Impact	ISO 179-2	kJ/m <sup>2</sup>	-	-			
© 2014 UL LLC							

Figure 9 : The UL card information of the Lamp shade part.

# Reference information

## The UL card of UL plastic material :


Component - Plastics							E48268
<b>IDEMITSU KOSAN CO LTD</b> BASIC CHEMICALS DEPT, 1-1 ANESAKI-KAIGAN, ICHIHARA-SHI CHIBA-KEN 299-0193 JP <b>LEV1700</b> Polycarbonate (PC), furnished as pellets							
Color	Min Thk (mm)	Flame Class	HWI	HAI	RTI Elec	RTI Imp	RTI Str
NC	0.42-1.9	V-2	-	-	80	80	80
Comparative Tracking Index (CTI): -				Dimensional Stability (%): -			
High-Voltage Arc Tracking Rate (HVTR): -				High Volt, Low Current Arc Resis (D495): -			
Dielectric Strength (kV/mm): -				Volume Resistivity (10 <sup>8</sup> ohm-cm) : -			
<small>ANSI/UL 94 small-scale test data does not pertain to building materials, furnishings and related contents. ANSI/UL 94 small-scale test data is intended solely for determining the flammability of plastic materials used in the components and parts of end-product devices and appliances, where the acceptability of the combination is determined by UL.</small>							
Report Date: 2010-04-06		Underwriters Laboratories Inc®					
Last Revised: 2010-04-06							
<b>IEC and ISO Test Methods</b>							
Test Name	Test Method	Units	Thickness Tested (mm)	Value			
Flammability	IEC 60695-11-10	Class (color)	0.42-1.9	V-2 (NC)			
Glow-Wire Flammability (GWFI)	IEC 60695-2-12	C	-	-			
Glow-Wire Ignition (GWIT)	IEC 60695-2-13	C	-	-			
IEC Comparative Tracking Index	IEC 60112	Volts (Max)	-	-			
IEC Ball Pressure	IEC 60695-10-2	C	-	-			
ISO Heat Deflection (1.80 MPa)	ISO 75-2	C	-	-			
ISO Tensile Strength	ISO 527-2	MPa	-	-			
ISO Flexural Strength	ISO 178	MPa	-	-			
ISO Tensile Impact	ISO 8256	kJ/m <sup>2</sup>	-	-			
ISO Izod Impact	ISO 180	kJ/m <sup>2</sup>	-	-			
ISO Charpy Impact	ISO 179-2	kJ/m <sup>2</sup>	-	-			
Underwriters Laboratories Inc®							

Figure 10 : The UL card information of the lens part.

# Reference information

## The UL card of UL plastic material :


Component - Plastics					E48268		
<b>IDEMITSU KOSAN CO LTD</b>							
1-1 MARUNOUCHI 3-CHOME, CHIYODA-KU, TOKYO 100-0005 JP							
<b>URC2500</b>							
Polycarbonate (PC), furnished as pellets							
	<b>Min Thk</b>	<b>Flame</b>			<b>RTI</b>	<b>RTI</b>	<b>RTI</b>
<b>Color</b>	<b>(mm)</b>	<b>Class</b>	<b>HWI</b>	<b>HAI</b>	<b>Elec</b>	<b>Imp</b>	<b>Str</b>
<b>WT</b>	1.5	V-0	-	-	80	80	80
	3.0	V-0	-	-	80	80	80
Comparative Tracking Index (CTI): -					Dimensional Stability (%): -		
High-Voltage Arc Tracking Rate (HVTR): -					High Volt, Low Current Arc Resis (D495): -		
Dielectric Strength (kV/mm): -					Volume Resistivity (10 <sup>X</sup> ohm-cm) : -		
<small>UL94 small-scale test data does not pertain to building materials, furnishings and related contents. UL94 small-scale test data is intended solely for determining the flammability of plastic materials used in the components and parts of end-product devices and appliances, where the acceptability of the combination is determined by ULI.</small>							
Report Date: 2006-09-18		Underwriters Laboratories Inc®					
Last Revised: 2006-09-18							
<b>IEC and ISO Test Methods</b>							
<b>Test Name</b>	<b>Test Method</b>	<b>Units</b>	<b>Thickness Tested (mm)</b>	<b>Value</b>			
IEC Flammability	IEC 60695-11-10	Class (color)	1.5	V-0 (WT)			
			3.0	V-0 (WT)			
Glow-Wire Flammability (GWFI)	IEC 60695-2-12	C	-	-			
Glow-Wire Ignition (GWIT)	IEC 60695-2-13	C	-	-			
IEC Comparative Tracking Index	IEC 60112	Volts (Max)	-	-			
IEC Ball Pressure	IEC 60695-10-2	C	-	-			
ISO Heat Deflection (1.80 MPa)	ISO 75-2	C	-	-			
ISO Tensile Strength	ISO 527-2	MPa	-	-			
ISO Flexural Strength	ISO 178	MPa	-	-			
ISO Tensile Impact	ISO 8256	kJ/m <sup>2</sup>	-	-			
ISO Izod Impact	ISO 180	kJ/m <sup>2</sup>	-	-			
ISO Charpy Impact	ISO 179-2	kJ/m <sup>2</sup>	-	-			
Underwriters Laboratories Inc®							

Figure 11 : The UL card information of the lamp base part.(White )

# Reference information

The UL card of UL plastic material :


Component - Plastics								E-18268
<b>IDEMITSU KOSAN CO LTD</b>								
1-1 MARUNOUCHI 3-CHOME, CHiyODA-KU, TOKYO 100-0005 JP								
<b>LE1700</b>								
Polycarbonate (PC), furnished as pellets								
<b>Color</b>	<b>Min Thk (mm)</b>	<b>Flame Class</b>	<b>HWI</b>	<b>HAI</b>	<b>RTI Elec</b>	<b>RTI Imp</b>	<b>RTI Str</b>	
NC	0.45-0.50	V-2	-	-	80	80	80	
	1.5	-	3	3	80	80	80	
Comparative Tracking Index (CTI): -				Inclined Plane Tracking (IPT): -				
Dielectric Strength (kV/mm): -				Volume Resistivity (10 <sup>x</sup> ohm-cm): -				
High-Voltage Arc Tracking Rate (HVTR): -				High Volt, Low Current Arc Resis (D495): -				
Dimensional Stability (%): -								
ANSI/UL 94 small-scale test data does not pertain to building materials, furnishings and related contents. ANSI/UL 94 small-scale test data is intended solely for determining the flammability of plastic materials used in the components and parts of end-product devices and appliances, where the acceptability of the combination is determined by UL.								
Report Date: 2000-03-31		© 2012 UL LLC						
Last Revised: 2009-03-30								
<b>IEC and ISO Test Methods</b>								
<b>Test Name</b>	<b>Test Method</b>	<b>Units</b>	<b>Thickness Tested (mm)</b>	<b>Value</b>				
Flammability	IEC 60695-11-10	Class (color)	0.45-0.50	V-2 (IIC)				
			1.5	- (IIC)				
Glow-Wire Flammability (GWFI)	IEC 60695-2-12	C	-	-				
Glow-Wire Ignition (GWIT)	IEC 60695-2-13	C	-	-				
IEC Comparative Tracking Index	IEC 60112	Volts (Max)	-	-				
IEC Ball Pressure	IEC 60695-10-2	C	-	-				
ISO Heat Deflection (1.80 MPa)	ISO 75-2	C	-	-				
ISO Tensile Strength	ISO 527-2	MPa	-	-				
ISO Flexural Strength	ISO 178	MPa	-	-				
ISO Tensile Impact	ISO 8256	kJ/m <sup>2</sup>	-	-				
ISO Izod Impact	ISO 180	kJ/m <sup>2</sup>	-	-				
ISO Charpy Impact	ISO 179-2	kJ/m <sup>2</sup>	-	-				
© 2012 UL LLC								


Figure 12 : The UL card information of the lamp base part.(Black)





# ▶▶ Reference information

## The SGS card of SGS plastic material :



**Test Report**                      No. CANEC1319750803                      Date: 26 Dec 2013                      Page 2 of 5

Test Results :

Test Part Description :

Specimen No.	SGS Sample ID	Description
SN1	CAN13-197508.003	Black powder

Remarks :


- (1) 1 mg/kg = 1 ppm = 0.0001%
- (2) MDL = Method Detection Limit
- (3) ND = Not Detected ( < MDL )
- (4) "-" = Not Regulated

RoHS Directive 2011/65/EU

Test Method : (1)With reference to IEC 62321-5:2013, determination of Cadmium by ICP-OES.  
 (2)With reference to IEC 62321-5:2013, determination of Lead by ICP-OES.  
 (3)With reference to IEC 62321-4:2013, determination of Mercury by ICP-OES.  
 (4)With reference to IEC 62321:2008, determination of Hexavalent Chromium by Colorimetric Method using UV-Vis.  
 (5)With reference to IEC 62321:2008, determination of PBBs and PBDEs by GC-MS.

Test Item(s)	Limit	Unit	MDL	/03
Cadmium (Cd)	100	mg/kg	2	ND
Lead (Pb)	1,000	mg/kg	2	ND
Mercury (Hg)	1,000	mg/kg	2	ND
Hexavalent Chromium (CrVI)	1,000	mg/kg	2	ND
Sum of PBBs	1,000	mg/kg	-	ND
Monobromobiphenyl	-	mg/kg	5	ND
Dibromobiphenyl	-	mg/kg	5	ND
Tribromobiphenyl	-	mg/kg	5	ND
Tetrabromobiphenyl	-	mg/kg	5	ND
Pentabromobiphenyl	-	mg/kg	5	ND
Hexabromobiphenyl	-	mg/kg	5	ND
Heptabromobiphenyl	-	mg/kg	5	ND
Octabromobiphenyl	-	mg/kg	5	ND
Nonabromobiphenyl	-	mg/kg	5	ND
Decabromobiphenyl	-	mg/kg	5	ND
Sum of PBDEs	1,000	mg/kg	-	ND
Monobromodiphenyl ether	-	mg/kg	5	ND

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-etc-Conditions.aspx> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-etc-Document.aspx>. Information is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained herein reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.



SGS-CTE (Shanghai) Technical Service Co., Ltd.  
 Shanghai Free Trade Zone  
 China

中国·广州·经济技术开发区科学城科韵路198号      邮编: 510663    1 (86-20) 82155555    1 (86-20) 82075113    www.sgs.com.cn


1 (86-20) 82155555    1 (86-20) 82075113    # sgschina@sgs.com

Member of the RFLS Group (RFLS S&S)

Figure 14 : The SGS card information of the lamp base part.(Black)

# Reference information

The SGS card of SGS plastic material :




**Test Report**
No. CANEC1319750803
Date: 26 Dec 2013
Page 3 of 5

Test Item(s)	Limit	Unit	MDL	003
Dibromodiphenyl ether	-	mg/kg	5	ND
Tribromodiphenyl ether	-	mg/kg	5	ND
Tetrabromodiphenyl ether	-	mg/kg	5	ND
Pentabromodiphenyl ether	-	mg/kg	5	ND
Hexabromodiphenyl ether	-	mg/kg	5	ND
Heptabromodiphenyl ether	-	mg/kg	5	ND
Octabromodiphenyl ether	-	mg/kg	5	ND
Nonabromodiphenyl ether	-	mg/kg	5	ND
Decabromodiphenyl ether	-	mg/kg	5	ND

Notes :

(1) The maximum permissible limit is quoted from the directive 2011/65/EU, Annex II

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-and-Conditions.aspx>. Sole responsibility is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained herein reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.



SGS-CTI (Suzhou) Technical Service Co., Ltd.  
 Suzhou, Jiangsu, China  
 中国·苏州·经济技术开发区科学城科胜路199号

TEL: +86 (0)512 82155555 | FAX: +86 (0)512 82155555 | www.sgs.com.cn  
 邮编: 215122 | TEL: +86 (0)512 82155555 | FAX: +86 (0)512 82155555 | sgschina@sgs.com

Member of the SGS Group (SGS SA)

Figure 15 : The SGS card information of the lamp base part.(Black)

# Reference information

The SGS card of SGS plastic material :




Figure 16 : The SGS card information of the lamp base part.(Black)

# ▶▶ Reference information

The SGS card of SGS plastic material :



Figure 17: The SGS card information of the lamp base part.(Black)



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.