

Cable tie - WT-STEEL SH 4,6X360 - 3240823

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Cable binders, made from rust-free stainless steel (AISI 316), suitable for the harshest of ambient conditions (for example, salt water), with ball lock, for quick and secure bundling and fastening



Key Commercial Data

| | |
|--------------------------------------|----------------|
| Packing unit | 1 pc |
| Minimum order quantity | 100 pc |
| Weight per Piece (excluding packing) | 4.2 g |
| Custom tariff number | 73269098 |
| Country of origin | United Kingdom |

Technical data

Dimensions

| | |
|-------------------------|---------|
| Length (b) | 360 mm |
| Width (a) | 4.6 mm |
| Max. material thickness | 0.25 mm |

Ambient conditions

| | |
|---------------------------------|-------------------|
| Ambient temperature (operation) | -80 °C ... 538 °C |
|---------------------------------|-------------------|

General

| | |
|------------|---------------------------------|
| Color | silver |
| Type | Steel strip |
| Components | free from silicone and halogen |
| Material | Stainless steel 1.4401/AISI 316 |

Standards and Regulations

| | |
|----------------------------|-----|
| Resistance to UV radiation | yes |
|----------------------------|-----|

Cable tie - WT-STEEL SH 4,6X360 - 3240823

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 4.0 | 27140702 |
| eCl@ss 4.1 | 27140702 |
| eCl@ss 5.0 | 27140702 |
| eCl@ss 5.1 | 27140702 |
| eCl@ss 6.0 | 27140702 |
| eCl@ss 7.0 | 27140702 |
| eCl@ss 8.0 | 27140702 |

ETIM

| | |
|----------|----------|
| ETIM 3.0 | EC000046 |
| ETIM 4.0 | EC000046 |
| ETIM 5.0 | EC000046 |

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 30212109 |
| UNSPSC 7.0901 | 27121703 |
| UNSPSC 11 | 27121703 |
| UNSPSC 12.01 | 27121703 |
| UNSPSC 13.2 | 27121703 |

Approvals

Approvals

Approvals

LR

Ex Approvals

Approvals submitted

Approval details

| |
|----|
| LR |
|----|

Cable tie - WT-STEEL SH 4,6X360 - 3240823

Accessories

Accessories

Universal tools

Cable tie tool - UNIFOX-CT M 7,9 - 1212610



Cable binder pliers, for steel cable binders with a width of up to 7.9 mm, for a material thickness of up to 0.3 mm



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.