

> MG06ACA SERIES ENTERPRISE CAPACITY HDD

The MG06ACA Enterprise Capacity HDD models provides up to 10TB^[1] of capacity and 7,200 rpm performance, in a robust design engineered for nearline business-critical workloads.

The MG06ACA model generation utilizes industry-standard 3.5-inch^[2] 26.1 mm height form factor and Advanced Format sector technologies for optimum capacity and data reliability. Models support Toshiba Persistent Write Cache technology^[3] which helps enhance performance while assuring the consistency of write operations in the event of a sudden loss of power. Equipped with SATA 6.0 Gbit/s^[4] interface, the Enterprise Capacity MG06ACA models help to save rack space and reduce the footprint and operational burden of business critical servers and storage systems.

The MG06ACA Series improves sustained transfer rate performance to 237 MiB/s^[5] and increases MTTF^[6] by 25% when compared to the prior MG05ACA series. 512e or 4Kn Advanced Format sector technology models are available. 4Kn sector models (MG06ACAxxxA) offer suitable performance and compatibility with the 4Kn-capable applications and operating environments. 512e sector models (MG06ACAxxxE) provide support for legacy applications and operating environments that require 512 byte sector lengths.



> KEY FEATURES

- Industry Standard 3.5-inch 26.1 mm Height Form Factor
- Large 10TB Capacity; plus 8TB and 6TB MG06 Series models
- 7,200 rpm Performance
- SATA 6.0 Gbit/s Interface
- MTTF 2.5 M hours
- 550 Total TB Transferred per Year Workload Rating^[7]
- 512e or 4Kn Advanced Format Sector Technology
- Toshiba Persistent Write Cache Technology for Data-Loss Protection in Sudden Power-Loss Events
- Improved sustained transfer rate
- Sanitize Instant Erase (SIE^[8]) option model available

> APPLICATIONS

- Mid-line / Nearline Business Critical Workloads
- Tier 2 Business-Critical Servers and Storage Systems
- Workloads and Use-Cases that Benefit from High Capacity per Spindle
- Capacity-Optimized Storage Systems
- Cloud-scale Storage Infrastructure
- Data Archive and Back-up Infrastructure

> SPECIFICATIONS

| Model Number | MG06ACA10TA MG06ACA10TE | MG06ACA800A MG06ACA800E | MG06ACA600A MG06ACA600E | |
|---------------------------|--|--------------------------------------|----------------------------|------------|
| Interface | SATA-3.3 | | | |
| Formatted Capacity | 10 TB | 8 TB | 6 TB | |
| Performance | Interface Speed | 6.0 Gbit/s, 3.0 Gbit/s, 1.5 Gbit/s | | |
| | Rotation Speed | 7,200 rpm | | |
| | Buffer Size | 256 MiB | | |
| | Data Transfer Speed (Sustained) | 237 MiB/s Typ. | 230 MiB/s Typ. | |
| Logical Data Block Length | MG06ACAxxxA (fixed length) | 4,096 B | | |
| | MG06ACAxxxE (emulation) | Host 512B Disk 4,096B ^[9] | | |
| Supply Voltage | Allowable Voltage 12 V ^[10] ± 10% / 5 V ^[10] +10/-7% ^[11] | | | |
| Power Consumption | Random Read/Write (4KB Q1) | 10.0 W Typ. | 9.1 W Typ. | 8.3 W Typ. |
| | Active Idle (Idle-A) | 7.3 W Typ. | 6.4 W Typ. | 5.6 W Typ. |
| Acoustics (Sound Power) | Idle ^[12] | 34 dB Typ. | | |

> ENVIRONMENTAL LIMITS

| Item | | Specification |
|---------------------------|-------------------------------|--|
| Ambient temperature | Operating | 5 °C to 55 °C |
| | Non-Operating | - 40 °C to 70 °C |
| Humidity | Operating | 5 % to 90 % R.H. |
| | Non-Operating | 5 % to 95 % R.H. |
| Shock | Operating | 686 m/s ² { 70 G } (2 ms duration) |
| | Non-Operating | 2,450 m/s ² { 250 G } (2 ms duration) |
| Vibration ^[13] | Operating ^[14] | 7.35 m/s ² { 0.75 G } (5- 300Hz) 2.45 m/s ² { 0.25 G } (300- 500Hz) |
| | Non-Operating ^[15] | 29.4 m/s ² { 3.0 G } (5- 500Hz) |
| Altitude | Operating | - 305 m to 3,048 m |
| | Non-Operating | - 305 m to 12,192 m |

[1] Definition of capacity: Toshiba defines a megabyte (MB) as 1,000,000 bytes, a gigabyte (GB) as 1,000,000,000 bytes and a terabyte (TB) as 1,000,000,000,000 bytes. A computer operating system, however, reports storage capacity using powers of 2 for the definition of 1GB = 2³⁰ = 1,073,741,824 bytes and therefore shows less storage capacity. Available storage capacity (including examples of various media files) will vary based on file size, formatting, settings, software and operating system, such as Microsoft Operating System and/or pre-installed software applications, or media content. Actual formatted capacity may vary.

[2] "2.5-inch" and "3.5-inch" mean the form factor of HDDs or SSDs. They do not indicate drive's physical size.

[3] PWC with PLP is a function to handle the write data that the drive reports "Normal completion" to the host but not being stored to hard disk media yet. The write data may be written to the commanded LBA on the hard disk media. The un-written data to hard disk media is stored to Flash memory using back up power by PLP when the power supply to the drive suddenly is shut down. And, after PLP operation, it may be required more time to start up the drive than in case of normal shutdown. 1) PLP does not secure data in the mode of all the power shutdowns. When power supplies other than recommended procedure are intercepted, data might be lost. 2) In the power shutdown before it reports on the Write completion, data not anticipated might be lost.

[4] Read and write speed may vary depending on the host device, read and write conditions, and file size.

[5] A kibibyte (KiB) means 2¹⁰, or 1,024 bytes, a mebibyte (MiB) means 2²⁰, or 1,048,576 bytes, and a gibibyte (GiB) means 2³⁰, or 1,073,471,824 bytes.

[6] MTTF (Mean Time to Failure) is not a guarantee or estimate of product life; it is a statistical value related to mean failure rates for a large number of products which may not accurately reflect actual operation. Actual operating life of the product may be different from the MTTF.

[7] Workload is defined as the amount of data written, read or verified by commands from host system.

[8] SIE: Sanitize Instant Erase. SIE is a function to invalidate the data recorded on the magnetic disks at a blink.

[9] Read-modify-write is supported.

[10] Input voltages are specified at the HDD connector side, during HDD ready state.

[11] Make sure the value is not less than -0.3V DC (less than -0.6V, 0.1ms) when turning on or off the power.

[12] The measuring method is based on ISO 7779. Idle is active idle mode

[13] Vibration applied to the HDD is measured at near the mounting screw hole on the frame as much as possible.

[14] At random seek write/read and default on retry setting with log sweep vibration.

[15] At power-off state after installation

Before creating and producing designs and using, customers must also refer to and comply with the latest versions of all relevant TOSHIBA information and the instructions for the application that Product will be used with or for.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Toshiba:

[MG06ACA600E](#) [MG06ACA10TA](#) [MG06ACA800A](#) [MG06ACA800E](#) [MG06ACA10TE](#) [MG06ACA600A](#)



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.