One-Time General Purpose Fuses NON and NOS

250 and 600 Volts, ⅛ to 600 Amps

Catalog Symbol: NON (250V); NOS (600V)
For general purpose application
Ampere Rating: ⅛ to 600A
Voltage Rating: NON: 250Vac, 125Vdc (0-100A);
NOS: 600Vac
Non-Current-Limiting
Interrupting Rating: 50,000A RMS Sym. (0-60A),
10,000A RMS Sym. (65-600A), 50,000A @ 125Vdc (NON 0-60),
10,000A @ 125Vdc (NON 65-100A)
Agency Information:
UL Listed - 250V: Class K5 (0-60A), Std. 248-9
Class H (65-600A), Std. 248-6
(125Vdc: NON 0-100)
600V: Class K5 (0-60A), Std. 248-9
Class H (70-600A), Std. 248-6
UL Guide JDDZ, File E4274
CSA Certified, Class 1421-01, File 53787 (0-12 & 65-600A)† 250V
(0-600A) 600V

Catalog Numbers—NON ONE-TIME (250Vac)

NON-⅛	NON-5	NON-40	NON-175
NON-½	NON-6	NON-45	NON-200
NON-¾	NON-6¼	NON-50	NON-225
NON-8/10	NON-7	NON-60	NON-250
NON-1	NON-8	NON-65	NON-300
NON-1¼	NON-9	NON-70	NON-350
NON-1½	NON-10	NON-75	NON-400
NON-1 6/10	NON-12	NON-80	NON-450
NON-2	NON-15	NON-90	NON-500
NON-2½	NON-20	NON-100	NON-600
NON-3	NON-25	NON-110	—
NON-3 2/10	NON-30	NON-125	—
NON-4	NON-35	NON-150	—

Carton Quantity and Weight—NON ONE-TIME (250Vac)

Catalog Number	Carton Qty.	Weight** Lbs.	Weight** Kg.
NON ⅛–30	10	0.38	0.172
NON 35–60	10	1.00	0.453
NON 65–100	5	0.79	0.358
NON 110–200	1	0.79	0.358
NON 225–400	1	1.65	0.748
NON 450–600	1	2.76	1.251

NON -(1/8-60) is rated at 125Vdc with 50,000 AIC Rating.
NON -(65-100) is rated at 125Vdc with 10,000 AIC Rating.
**Weight per carton.
† *For CSA Certified 15-60A Ratings, see PON Data Sheet: 4126*



Recommended fuseblocks for
Class H & K5, 250V & 600V fuses
See Data Sheets: 1112 (250V) and
1113 (600V)

Dimensions

All diameters (± 0.008)



General Information:

- Protect lighting, heating and other circuits not subject to temporary surges and where available short-circuit currents are relatively low.
- ONE-TIME fuses do not have any appreciable degree of time-delay and thus should not be specified in circuits where large transients or motor overloads occur. Use Buss FUSETRON® or LOW-PEAK® dual-element, time-delay fuses.
- For general purpose circuits, size at ampere rating of circuit.
- For motor circuits, size at 300% to 400%.

Catalog Numbers—NOS ONE-TIME (600Vac)

NOS-1	NOS-12	NOS-70	NOS-225
NOS-2	NOS-15	NOS-75	NOS-250
NOS-3	NOS-20	NOS-80	NON-300
NOS-4	NOS-25	NOS-90	NOS-350
NOS-5	NOS-30	NOS-100	NOS-400
NOS-6	NOS-35	NOS-110	NOS-450
NOS-7	NOS-40	NOS-125	NOS-500
NOS-8	NOS-45	NOS-150	NOS-600
NOS-9	NOS-50	NOS-175	—
NOS-10	NOS-60		

Carton Quantity and Weight—NOS ONE-TIME (600Vac)

Catalog Number	Carton Qty.	Weight** Lbs.	Weight** Kg.
NOS 1–30	10	1.45	0.657
NOS 35–60	10	2.6	1.179
NOS 70–100	5	2.80	1.270
NOS 110–200	1	1.24	0.562
NOS 225–400	1	3.03	1.374
NOS 450–600	1	4.63	2.100

**Weight per carton.

CE logo denotes compliance with European Union Low Voltage Directive (50-1000Vac, 75-1500Vdc). Refer to Data Sheet: 8002 or contact Bussmann Application Engineering at 636-527-1270 for more information. Applies to OPM-1038 and OPM-1038R.

One-Time General Purpose Fuses NON and NOS

250 and 600 Volts, ⅛ to 600 Amps

Time-Current Characteristic Curves–Average Melt

NON ONE-TIME (250Vac)



NOS ONE-TIME (600Vac)



The only controlled copy of this Data Sheet is the electronic read-only version located on the Bussmann Network Drive. All other copies of this document are by definition uncontrolled. This bulletin is intended to clearly present comprehensive product data and provide technical information that will help the end user with design applications. Bussmann reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Bussmann also reserves the right to change or update, without notice, any technical information contained in this bulletin. Once a product has been selected, it should be tested by the user in all possible applications.

Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits,General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.

Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)
Факс: 8 (812) 320-02-42
Электронная почта: org@eplast1.ru
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.