



SERIAL SERVER  
FOR HAZARDOUS  
LOCATIONS



# DIGI ONE® IAP HAZ

Serial-to-Ethernet connectivity, protocol conversion and interoperability for industrial applications in harsh and extreme conditions

Digi One IAP Haz combines reliable serial-to-Ethernet connectivity with protocol conversion and interoperability. Users can IP enable a broad range of serial devices, as well as link two industrial devices. Designed for use in harsh environments, this rugged serial server is ideal for device management applications where exposure to extreme temperatures, volatile liquids and gases are common.


Digi One IAP Haz is a serial server and a protocol bridge rolled into one. Applications may communicate with the serial device using TCP/UDP or Digi's patented RealPort® COM port redirection for remote native COM port access.

Digi One IAP Haz supports a variety of serial and Ethernet protocols, allowing users to bridge serial and Ethernet devices, or both. Multi-master access allows multiple masters to communicate with a single slave across protocols. An additional serial port allows local devices to communicate with a slave unit, without disrupting the serial-to-Ethernet connection.

## BENEFITS

- Hardened design with extended operating temperature (-35° C to +74° C) for hazardous locations
- Conformal coated circuit board
- Class 1, Division 2 certified
- Multi-master/Multi-protocol concurrent support for Allen-Bradley and Modbus protocols
- Serial and Ethernet protocol bridging support for Allen-Bradley and Modbus protocols promotes interoperability
- ASCII to protocol translation for Allen-Bradley and Modbus
- Switch selectable RS-232/422/485 serial port

## APPLICATION EXAMPLE



## RELATED PRODUCTS



DigiOne® IA



DigiOne® IAP



DigiOne® SP IA



PostServer® TS H  
MEI Haz



Power Supply  
76000736

## SPECIFICATIONS

## DigiOne® IAP Haz

FEATURES	
<b>MANAGEMENT</b>	HTTP configuration, Digi Port Authority – Remote management diagnostics and auto-discovery tool, SNMP (read/write)
<b>PROTOCOLS</b>	Telnet, Reverse Telnet, RFC2217, TCP/UDP Socket Services, PPP, DHCP/RARP, ARP-Ping, Static IP for IP address assignment, Support for 64 concurrent socket connections, ASCII, DF1, Modbus RTU/ASCII, Modbus/TCP, EtherNet/IP, Allen-Bradley Ethernet
<b>SOFTWARE</b>	Patented RealPort® for COM/TTY ports
<b>SECURITY</b>	SSHv2, SSL, TLS, HTTPS
<b>OPERATING SYSTEMS</b>	AIX, HP-UX, Solaris, Linux®, Windows® 2000, Windows® XP, Windows® 7, Windows® 8, Windows® 8.1, Windows® 10, Windows Server® 2003, Windows Server® 2008, Windows Server® 2012. Note: TCP/UDP socket services are operating system independent.
<b>STATUS LEDs</b>	Serial signals, Power, Ethernet, Diagnostics
<b>DIMENSIONS (L x W x D)</b>	4.70 in x 0.90 in x 4.0 in (12.00 cm x 2.30 cm x 10.10 cm)
<b>WEIGHT</b>	2.5 oz (64.0 g)
<b>OTHER</b>	Full modem and hardware flow control, Flash upgradeable firmware, 6 ms serial over Ethernet latency, Conformal coated PCB, 35 mm DIN rail mounting
INTERFACES	
<b>SERIAL PORTS</b>	1 RS-232/422/485 (switch selectable)
<b>SERIAL CONNECTOR</b>	Screw terminal connectors or DB-9M; DB-9M can act as a second direct RS-232 port connection when used as the second port
<b>SERIAL THROUGHPUT</b>	Up to 230 Kbps
<b>ETHERNET PHYSICAL LAYER</b>	10/100Base-T
POWER REQUIREMENTS	
<b>POWER INPUT</b>	9-30 VDC @ 0.5Amps max
<b>POWER SUPPLY</b>	Removable screw terminal for power (power supply not included)
<b>PRODUCT SURGE PROTECTION (ESD)</b>	2 kV isolation between power supply and serial ground
ENVIRONMENTAL	
<b>OPERATING TEMPERATURE</b>	-35° C to +74° C (-31° F to +165° F)
<b>RELATIVE HUMIDITY</b>	5% to 90% (non-condensing)
<b>ETHERNET ISOLATION</b>	1500 VAC min per IEEE 802.3/ANSI X3.263
<b>SERIAL PORT PROTECTION (ESD)</b>	15 kV human body model
REGULATORY APPROVALS	
<b>SAFETY</b>	UL 1950, UL 1604 (Class 1, Div. 2), CSA 22.2 No 950, EN60950
<b>EMISSIONS / IMMUNITY</b>	FCC Part 15 (Class A), ICES-003 (Class A), CE, AS3548, EN6100-6-2 + EN55024, EN55022 (Class A)



## PART NUMBERS

## DESCRIPTION

70002326	Digi One IAP Haz
----------	------------------

SLAVE	MB/RTU	MB SERIAL	MB/TCP	DF1	A-B ETH	ENET/IP*	ASCII
MASTER							
MB SERIAL	-	YES	YES	YES	YES	YES	YES
MB/TCP	YES	YES	-	YES	YES	YES	YES
DF1	YES	YES	YES	-	YES	YES	YES
A-B ETH	YES	YES	YES	YES	-	YES	YES
ENET/IP	YES	YES	YES	YES	YES	-	YES
ASCII	NO	NO	NO	NO	NO	NO	-

\*PCCC encapsulated under CIP only for EtherNet/IP



**DIGI SERVICE AND SUPPORT** / You can purchase with confidence knowing that Digi is always available to serve you with expert technical support and our industry leading warranty. For detailed information visit [www.digi.com/support](http://www.digi.com/support).

© 1996-2018 Digi International Inc. All rights reserved.  
All trademarks are the property of their respective owners.

91001409  
C3/618

**DIGI INTERNATIONAL WORLDWIDE HQ**  
877-912-3444 / 952-912-3444 / [www.digi.com](http://www.digi.com)

**DIGI INTERNATIONAL GERMANY**  
+49-89-540-428-0

**DIGI INTERNATIONAL JAPAN**  
+81-3-5428-0261 / [www.digi-intl.co.jp](http://www.digi-intl.co.jp)

**DIGI INTERNATIONAL SINGAPORE**  
+65-6213-5380

**DIGI INTERNATIONAL CHINA**  
+86-21-50492199 / [www.digi.com.cn](http://www.digi.com.cn)





Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.