



Product: [9641](#) 

IEEE-488, #26-6pr+10c, #24-1c, SR-PVC, O/A Foil+Braid, PVC Jkt, CMG

Product Description

Computer EIA RS-488 Cable, 26 AWG stranded (7x34) and 24 AWG stranded (7x32) tinned copper conductors, semi-rigid PVC insulation, overall Beldfoil® (100% Coverage) + Tinned copper braid shield (90% Coverage), drain wire, PVC jacket.

Technical Specifications

Product Overview

Suitable Applications:	IEEE 488 interface; computer communications; low voltage analog signals (4-20ma, 0-10v, ...); low voltage digital control (24v, ...); line level audio; panel wiring
------------------------	--

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material	No. of Conductors	No. of Pairs
26	7x34	TC - Tinned Copper		6
26	7x34	TC - Tinned Copper	10	
24	7x32	TC - Tinned Copper	1	

Conductor Count:	23
------------------	----

Insulation

Material
S-R PVC - Semi-Rigid Polyvinyl Chloride

Color Chart

Number	Color
1 26AWG Pair	Blue & White/Gray
2 26AWG Pair	Purple & White/Black/Brown
3 26AWG Pair	Gray & White/Black/Red
4 26AWG Pair	White & White/Black/Orange
5 26AWG Pair	White/Black & White/Black/Yellow
6 26AWG Pair	White/Brown & White/Black/Green
7 26AWG Conductor	Brown
8 26AWG Conductor	Red
9 26AWG Conductor	Orange
10 26AWG Conductor	Yellow
11 26AWG Conductor	Lt. Green
12 26AWG Conductor	White/Orange
13 26AWG Conductor	White/Yellow
14 26AWG Conductor	White/Green
15 26AWG Conductor	White/Blue
16 26AWG Conductor	White/Purple
17 24AWG Conductor	White/Black/Blue

Outer Shield Material

Type	Material	Coverage [%]	Drainwire Material	Drainwire AWG	Drainwire Construction n x D
Tape	Alum / Poly	100 %	TC - Tinned Copper	26	7x34
Braid	TC - Tinned Copper	90 %			

Outer Jacket Material

Material	Nominal Diameter	Separator Material
PVC - Polyvinyl Chloride	0.35 in	Polyester Tape

Electrical Characteristics

Conductor DCR

Element	Nominal Conductor DCR	Nominal Outer Shield DCR
24 AWG	23.3 Ohm/1000ft	2.6 Ohm/1000ft
26 AWG	37.3 Ohm/1000ft	

Current

Max. Recommended Current [A]
0.6 (26 AWG) Amps per conductor @ 25°C A
1.1 Amps per conductor @ 25°C (24 AWG)

Voltage

UL Voltage Rating
300 V RMS (UL AWM Style 2464)

Temperature Range

UL Temp Rating:	80°C (UL AWM Style 2464)
Operating Temp Range:	-20°C To +80°C

Mechanical Characteristics

Bulk Cable Weight:	71 lbs/1000ft
Max Recommended Pulling Tension:	140 lbs
Min Bend Radius/Minor Axis:	3.5 in

Standards

NEC/(UL) Specification:	CMG
CEC/C(UL) Specification:	CMG
UL AWM Style:	2464 (300 V 80°C)
CSA AWM Specification:	AWM I A
IEEE Specification:	488

Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-10-01
MII Order #39 (China RoHS):	Yes

Flammability, LS0H, Toxicity Testing

C(UL) Flammability:	FT4
UL voltage rating:	300 V RMS (UL AWM Style 2464)

Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

Part Number

Variants

Item #	Color	Putup Type	Length	UPC
9641 0081000	Gray	Reel	1,000 ft	612825256861

Footnote:	C - CRATE REEL PUT-UP.
-----------	------------------------

Update and Revision:	Revision Number: 0.293 Revision Date: 04-28-2020
----------------------	--

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.