



SAW Components

SAW Rx 2in1 input duplex filter

GSM1900 / GSM1800

Series/type:	B9513
Ordering code:	B39202B9513L310

Date:	May 27, 2010
Version:	2.0

© EPCOS AG 2015. Reproduction, publication and dissemination of this publication, enclosures hereto and the information contained therein without EPCOS' prior express consent is prohibited.

EPCOS AG is a TDK Group Company.


Data sheet

Application


- Low-loss 2in1 RF filter for mobile telephone GSM1900 and GSM1800 systems, receive path (Rx)
- Usable passband:
Filter 1 (GSM1900): 60 MHz
Filter 2 (GSM1800): 75 MHz
- Unbalanced to balanced operation for both filters
- Impedance transformation from 50 Ω to 150 Ω for both filters
- Low amplitude ripple
- Suitable for GPRS class 1 to 12


Features

- Package size 1.8 x 1.4 x 0.68 mm³
- Moisture Sensitive Level 3
- RoHS compatible
- Approx. weight 0.006g
- Package for Surface Mount Technology (SMT)
- Ni, gold-plated terminals
- **RoHS compatible**
- **Electrostatic Sensitive Device (ESD)**


Pin configuration

- 1 Input [Duplex]
- 8,9 Output balanced [Filter 1]
- 6,7 Output balanced [Filter 2]
- 2,3,4,5,10 Case-ground



SAW Components
B9513
SAW Rx 2in1 input duplex filter
1960.0 / 1842.5 MHz
Data sheet

Characteristics of Filter 1 (GSM1900)

Temperature range for specification: $T = -30\text{ }^{\circ}\text{C}$ to $+85\text{ }^{\circ}\text{C}$
 Terminating source impedance: $Z_S = 50\text{ }\Omega \parallel 3.3\text{nH}$
 Terminating load impedance: $Z_L = 150\text{ }\Omega \parallel 18\text{nH}$ (balanced)

		min.	typ. @ 25 °C	max.	
Center frequency	f_C	—	1960.0	—	MHz
Maximum insertion attenuation	$\alpha_{\max}$	—	2.2	3.0	dB
1930.0 ... 1990.0 MHz					
Amplitude ripple (p-p)	$\Delta\alpha$	—	0.9	1.8	dB
1930.0 ... 1990.0 MHz					
Input VSWR		—	1.5	2.0	
1930.0 ... 1990.0 MHz					
Output VSWR		—	1.6	2.1	
1930.0 ... 1990.0 MHz					
CMRR ($ S_{21}-S_{31} / S_{21}+S_{31} $)		22 ¹⁾	29	—	dB
1930.0 ... 1990.0 MHz					
Attenuation	α				
10.0 ... 1510.0 MHz		40	53	—	dB
1510.0 ... 1830.0 MHz		30	35	—	dB
1830.0 ... 1850.0 MHz		23	33	—	dB
1850.0 ... 1890.0 MHz		18	30	—	dB
1890.0 ... 1910.0 MHz		9	14	—	dB
2010.0 ... 2070.0 MHz		4	12	—	dB
2070.0 ... 2400.0 MHz		21	33	—	dB
2400.0 ... 6000.0 MHz		30	43	—	dB



¹⁾ A CMRR of 21.9dB corresponds to a phase balance of 7° together with an amplitude balance of 0.9dB



SAW Components		B9513
SAW Rx 2in1 input duplex filter		1960.0 / 1842.5 MHz
Data sheet		

Maximum ratings of Filter 1

Operable temperature range	T	−40/+85	°C	
Storage temperature range	T _{stg}	−40/+85	°C	
DC voltage	V _{DC}	5	V	
ESD voltage	V _{ESD}	50 ¹⁾	V	machine model, 1 pulse
Input Power at				
GSM 850, GSM 900	P _{IN}	15	dBm	effective power in the on-state, duty cycle 4:8
GSM 1800, GSM 1900	P _{IN}	15	dBm	
Tx bands				

¹⁾ acc. to JESD22-A115A (machine model), 1 negative & 1 positive pulse.

Transfer function Filter 1 (GSM1900)

Transfer function Filter 1 (GSM1900) - Wideband




SAW Components
B9513
SAW Rx 2in1 input duplex filter
1960.0 / 1842.5 MHz
Data sheet

Characteristics of Filter 2 (GSM1800)

Temperature range for specification:	T	=	-30 °C to +85 °C
Terminating source impedance:	Z_S	=	50 Ω 3.3nH
Terminating load impedance:	Z_L	=	150 Ω 15nH (balanced)

		min.	typ. @ 25 °C	max.	
Center frequency	f_c	—	1842.5	—	MHz
Maximum insertion attenuation 1805.0 ... 1880.0 MHz	$\alpha_{\max}$	—	2.2	2.8	dB
Amplitude ripple (p-p) 1805.0 ... 1880.0 MHz	$\Delta\alpha$	—	1.0	1.8	dB
Input VSWR 1805.0 ... 1880.0 MHz		—	1.5	2.0	
Output VSWR 1805.0 ... 1880.0 MHz		—	1.7	2.1	
CMRR ($ S_{21}-S_{31} / S_{21}+S_{31} $) 1805.0 ... 1880.0 MHz		20 ¹⁾	24	—	dB
Attenuation	α				
10.0 ... 940.0 MHz		45	62	—	dB
940.0 ... 1705.0 MHz		20	34	—	dB
1705.0 ... 1785.0 MHz		12	18	—	dB
1920.0 ... 1980.0 MHz		17	26	—	dB
1980.0 ... 2030.0 MHz		25	30	—	dB
2030.0 ... 2700.0 MHz		28	35	—	dB
2700.0 ... 6000.0 MHz		30	37	—	dB



¹⁾ A CMRR of 19.6dB corresponds to a phase balance of 10° together with an amplitude balance of 1.0dB





SAW Components		B9513
SAW Rx 2in1 input duplex filter		1960.0 / 1842.5 MHz
Data sheet		

Maximum ratings of Filter 2

Operable temperature range	T	−40/+85	°C	
Storage temperature range	T _{stg}	−40/+85	°C	
DC voltage	V _{DC}	5	V	
ESD voltage	V _{ESD}	50 ¹⁾	V	machine model, 1 pulse
Input Power at				
GSM 850, GSM 900	P _{IN}	15	dBm	effective power in the on-state, duty cycle 4:8
GSM 1800, GSM 1900	P _{IN}	15	dBm	
Tx bands				

¹⁾ acc. to JESD22-A115A (machine model), 1 negative & 1 positive pulse.

Transfer function Filter 2 (GSM1800)

Transfer function Filter 2 (GSM1800) - Wideband




SAW Components	B9513
SAW Rx 2in1 input duplex filter	1960.0 / 1842.5 MHz

Data sheet



References

Type	B9513
Ordering code	B39202B9513L310
Marking and package	C61157-A7-A153
Packaging	F61074-V8226-Z000
Date codes	L_1126
S-parameters	B9513_LB_NB.s3p B9513_LB_WB.s3p B9513_UB_NB.s3p B9513_UB_WB.s3p See file header for port/pin assignment table.
Soldering profile	S_6001
RoHS compatible	defined as compatible with the following documents: "DIRECTIVE 2002/95/EC OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 27 January 2003 on the restriction of the use of certain hazardous substances in electrical and electronic equipment. 2005/618/EC from April 18th, 2005, amending Directive 2002/95/EC of the European Parliament and of the Council for the purposes of establishing the maximum concentration values for certain hazardous substances in electrical and electronic equipment."
Moldability	Before using in overmolding environment, please contact your EPCOS sales office.

For further information please contact your local EPCOS sales office or visit our webpage at www.epcos.com.

Published by EPCOS AG

Surface Acoustic Wave Components Division

P.O. Box 80 17 09, 81617 Munich, GERMANY

© EPCOS AG 2010. This brochure replaces the previous edition.

For questions on technology, prices and delivery please contact the Sales Offices of EPCOS AG or the international Representatives.

Due to technical requirements components may contain dangerous substances. For information on the type in question please also contact one of our Sales Offices.

Important notes

The following applies to all products named in this publication:

1. Some parts of this publication contain **statements about the suitability of our products for certain areas of application**. These statements are based on our knowledge of typical requirements that are often placed on our products in the areas of application concerned. We nevertheless expressly point out **that such statements cannot be regarded as binding statements about the suitability of our products for a particular customer application**. As a rule, EPCOS is either unfamiliar with individual customer applications or less familiar with them than the customers themselves. For these reasons, it is always ultimately incumbent on the customer to check and decide whether an EPCOS product with the properties described in the product specification is suitable for use in a particular customer application.
2. We also point out that **in individual cases, a malfunction of electronic components or failure before the end of their usual service life cannot be completely ruled out in the current state of the art, even if they are operated as specified**. In customer applications requiring a very high level of operational safety and especially in customer applications in which the malfunction or failure of an electronic component could endanger human life or health (e.g. in accident prevention or life-saving systems), it must therefore be ensured by means of suitable design of the customer application or other action taken by the customer (e.g. installation of protective circuitry or redundancy) that no injury or damage is sustained by third parties in the event of malfunction or failure of an electronic component.
3. **The warnings, cautions and product-specific notes must be observed.**
4. In order to satisfy certain technical requirements, **some of the products described in this publication may contain substances subject to restrictions in certain jurisdictions (e.g. because they are classed as hazardous)**. Useful information on this will be found in our Material Data Sheets on the Internet (www.epcos.com/material). Should you have any more detailed questions, please contact our sales offices.
5. We constantly strive to improve our products. Consequently, **the products described in this publication may change from time to time**. The same is true of the corresponding product specifications. Please check therefore to what extent product descriptions and specifications contained in this publication are still applicable before or when you place an order.
We also **reserve the right to discontinue production and delivery of products**. Consequently, we cannot guarantee that all products named in this publication will always be available. The aforementioned does not apply in the case of individual agreements deviating from the foregoing for customer-specific products.
6. Unless otherwise agreed in individual contracts, **all orders are subject to the current version of the "General Terms of Delivery for Products and Services in the Electrical Industry" published by the German Electrical and Electronics Industry Association (ZVEI)**.
7. The trade names EPCOS, BAOKE, Alu-X, CeraDiode, CSMP, CSSP, CTVS, DeltaCap, DigiSiMic, DSSP, FormFit, MiniBlue, MiniCell, MKD, MKK, MLSC, MotorCap, PCC, PhaseCap, PhaseCube, PhaseMod, PhiCap, SIFERRIT, SIFI, SIKOREL, SilverCap, SIMDAD, SiMic, SIMID, SineFormer, SIOV, SIP5D, SIP5K, ThermoFuse, WindCap are **trademarks registered or pending** in Europe and in other countries. Further information will be found on the Internet at www.epcos.com/trademarks.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[EPCOS:](#)

[B39202B9513L310](#)



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.