

## MAX5110

# 9-Channel, 14-Bit Current DAC with SPI Interface

*Industry's First Multichannel Current-Output DAC Optimized to Bias Fiber Optic Tunable Laser Sources*

## Status

Active: Data sheet on request only

## Data Sheet

[Request Full Data Sheet](#)  
Custom Order

## Description

The MAX5110 is a 14-bit, 9-channel, current output digital-to-analog converter (DAC). The device operates from a low +3.0V power supply and provides 14-bit performance without any adjustment.

The device's output ranges are optimized to bias a high-power tunable laser source. Each of the 9 channels provides a current source. Connect DAC outputs in parallel to obtain additional current or to achieve higher resolution. The MAX5110 contains an internal reference.

An SPI™ interface drives the device with clock rates up to 25MHz. An active-high asynchronous CLR input resets DAC codes to zero independent of the serial interface. The device provides a separate power-supply input for driving the interface logic.

The MAX5110 is specified over a temperature range of -40°C to +105°C and are available in 3mm x 3mm 36-WLP and 5mm x 5mm 32-TQFN packages.

An evaluation board is available: [MAX5110EVKIT](#)

## Key Features

- Low 3.0V Supply
- Integrated Multiplexers for Outputs 1 and 2
- Increased Current or Resolution with Outputs Connected in Parallel
- SPI-Compatible Serial Interface
- Internal Reference
- Overtemperature Protection
- Operates Over the -40°C to +105°C Temperature Range
- Available in 36-Bump WLP or 32-Pin TQFN Packages

## Applications/Uses

- Tunable Laser Diode Biasing

## Technical Documents

App Note 4862 [Reserved or "Don't Care" Bit Programming in the MAX5110/MAX5111 Multichannel DACs](#)

## Product Guides

[Signal Chain](#) (PDF)

## Reliability Reports

Reliability Report: [MAX5110.pdf](#)

## Ordering Information

Part Number	Free Sample	Buy	Status	Package: TYPE PINS FOOTPRINT DRAWING CODE/VAR *	Temp	RoHS/Lead-Free? Materials Analysis
MAX5110GTJ+			Active: Data sheet on request only	TQFN;32 pin;26 mm <sup>2</sup> <a href="#">Package Details</a>	-40°C to +105°C	RoHS/Lead-Free: <a href="#">Lead Free Materials Analysis</a>
MAX5110GTJ+G074			Active: Data sheet on request only	QFN; <a href="#">Package Details</a>	-40°C to +105°C	See data sheet
MAX5110GTJ+T			Active: Data sheet on request only	TQFN;32 pin;26 mm <sup>2</sup> <a href="#">Package Details</a>	-40°C to +105°C	RoHS/Lead-Free: <a href="#">Lead Free Materials Analysis</a>
MAX5110GTJ+TG074			Active: Data sheet on request only	TQFN;32 pin;26 mm <sup>2</sup> <a href="#">Package Details</a>	-40°C to +105°C	RoHS/Lead-Free: <a href="#">Lead Free Materials Analysis</a>
MAX5110GWX+			Active: Data sheet on request only	WLP;36 pin;10.1 mm <sup>2</sup> <a href="#">Package Details</a>	-40°C to +105°C	RoHS/Lead-Free: <a href="#">Lead Free Materials Analysis</a>
MAX5110GWX+T			Active: Data sheet on request only	WLP;36 pin;10.1 mm <sup>2</sup> <a href="#">Package Details</a>	-40°C to +105°C	RoHS/Lead-Free: <a href="#">Lead Free Materials Analysis</a>
MAX5110GWX+TG074			Active: Data sheet on request only	WLP;36 pin;10.1 mm <sup>2</sup> <a href="#">Package Details</a>	-40°C to +105°C	RoHS/Lead-Free: <a href="#">Lead Free Materials Analysis</a>

Notes:

- Other options and links for purchasing parts are listed at: <http://www.maximintegrated.com/sales>.
- Didn't Find What You Need?** Ask our applications engineers. Expert assistance in finding parts, usually within one business day.
- Part number suffixes: T or T&R = tape and reel; + = RoHS/lead-free; # = RoHS/lead-exempt; -D = drypack; -U/+U on DS parts = cut tape. More: See [Full Data Sheet](#) or [Maxim Product Naming Conventions](#).
- \* Some packages have variations, listed on the drawing. "PkgCode/Variation" tells which variation the product uses. Note that "+", "#", "-" in the part number suffix describes RoHS status. Package drawings may show a different suffix character.

## Similar Products by Function

[MAX5111](#) 9-Channel, 14-Bit, Current DAC with I<sup>2</sup>C Interface

## Evaluation Kits

[MAX5110EVKIT](#) Evaluation Kit for the [MAX5110](#)

## Products with Similar Part Numbers

[MAX5110EVKIT](#) Evaluation Kit for the [MAX5110](#)

## Didn't Find What You Need?

- [Next Day Product Selection Assistance from Applications Engineers](#)
- [Parametric Search](#)
- [Applications Help](#)

## Information Index

### Overview

[Description](#)  
[Key Features](#)  
[Applications/Uses](#)  
[Key Specifications](#)  
[Diagram](#)  
[Notes and Comments](#)

### Design Resources

[Data Sheet](#)  
[Technical Documents](#)  
[Evaluation Kits](#)  
[Reliability Reports](#)  
[Software/Models](#)

### Ordering Info

[Price and Availability](#)  
[Samples](#)  
[Buy Online](#)  
[Package Information](#)  
[Lead-Free Information](#)

### Related Products

[Similar Products by Function](#)  
[Similar Products by Application](#)  
[Evaluation Kits](#)  
[Products with Similar Part Numbers](#)  
[Products Used With This](#)

Document Ref.: 19-5491 Rev 0; 2010-09-24  
This page last modified: 2011-03-22





Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.