

***RoHS Compliant***

**USB Flash Drive**

***AH322 Specifications***

**June 4<sup>th</sup>, 2014**

***Version 1.4***



**Apacer**  
*Access the best*

***Apacer Technology Inc.***

1F, No.32, Zhongcheng Rd., Tucheng Dist., New Taipei City, Taiwan, R.O.C

Tel: +886-2-2267-8000

Fax: +886-2-2267-2261

[www.apacer.com](http://www.apacer.com)

## **FEATURES:**

- **USB2.0 High-Speed and USB1.1 Full-Speed compatible interface**
- **Capacity**
  - For SLC: 128, 256, 512 MB  
1, 2, 4, 8, 16, 32 GB
  - For MLC: 4, 8, 16, 32 GB
- **Performance**
  - Sustained read: up to 34 MB/s
  - Sustained write: up to 22 MB/s
- **Intelligent USB Module**
  - Implements advanced wear-leveling algorithms to substantially increase longevity of flash media
  - ECC
- **Temperature ranges**
  - 0°C to 70°C (standard)
- **Power consumption (typical)**
  - Active mode: 185 mA
  - Idle mode: 65 mA
  - Operating voltage: 5V
- **RoHS Compliant**
- **Dimensions:** 55.29 x 18.00 x 8.50, unit: mm
- **LED indicator**
- **EMC: CE, FCC**

Notes: the results for performance and power consumption addressed here may vary in real world platforms.

---

## TABLE OF CONTENTS

|  |          |
|--|----------|
| <b>1. General Description .....</b>            | <b>3</b> |
| 1.1 Performance-optimized USB Controller ..... | 3        |
| 1.1.1 Error Correction Code (ECC) .....        | 3        |
| 1.1.2 Wear-Leveling .....                      | 3        |
| <b>2. General Specifications .....</b>         | <b>4</b> |
| 2.1 Performance Specifications – SLC .....     | 4        |
| 2.2 Performance Specifications – MLC .....     | 4        |
| <b>3. Electrical Specification .....</b>       | <b>5</b> |
| <b>4. Physical Dimensions .....</b>            | <b>5</b> |
| <b>5. Product Ordering Information .....</b>   | <b>6</b> |
| 5.1 Product Code Designation .....             | 6        |
| 5.2 Valid Combinations .....                   | 7        |

---

## **1. General Description**

Apacer's USB FLASH Drive (UFD) is a high performance, flash disk drive designed offering portable storage solutions. UFDs can be plugged into a standard USB 2.0 connector commonly found in desktops, portable computers and even enterprise PC systems. Apacer's UFDs have an efficient built-in microcontroller and file management firmware that ensures ideal performance, functionality and reliability. This product is well suited for portable flash storage applications while operating at minimal power consumption.

### **1.1 Performance-optimized USB Controller**

---

The heart of an UDM is the USB controller, which translates standard USB signals to the flash media and controls the data in/out between the controller itself and the flash media. This proprietary USB controller is specifically designed to attain high data throughput from host to flash.

#### **1.1.1 Error Correction Code (ECC)**

The UDM uses BCH Error Detection Code (EDC) and Error Correction Code (ECC) algorithms which correct up to 24 random single-bit errors for each 1024-byte block of data.

#### **1.1.2 Wear-Leveling**

Flash memory can be erased a limited number of times. In a typical application, and especially if a file system is used, specific pages are constantly updated (e.g., the page that contains the FAT, registry, etc.). Without any special handling, these pages would wear out more rapidly than other pages, reducing the lifetime of the entire flash. To overcome this inherent deficiency, Apacer's USB-Disk Module (UDM) uses wear-leveling algorithm. This wear-leveling algorithm ensures that consecutive writes of a specific sector are not written physically to the same page in the flash. This distributes flash media usage evenly across all pages, thereby maximizing flash lifetime. The wear-leveling mechanism provides write/erase cycles for reliable data storage over an extended period.

## 2. General Specifications

|              |  |
|--------------|--|
| Interface    | High-speed USB2.0 compliant; backward compatible with USB 1.1                            |
| Performance* | SLC: up to 34 MB/s (read); 22 MB/s (write)<br>MLC: up to 33 MB/s (read); 16 MB/s (write) |
| Temperature  | 0 to 70°C  |
| Shock        | Half sine wave 40 G, 11ms / Square wave 100 G, 6ms                                       |
| EMC          | FCC, CE  |
| MTBF         | 2,000,000 hours (SLC) / 1,000,000 (MLC)  |

\*Results may vary from flash configurations or host system settings.

### 2.1 Performance Specifications – SLC

**Table 2-1: SLC Performance Specifications**

| Capacity                      | 256 MB | 512 MB | 1 GB | 2 GB | 4 GB | 8 GB | 16 GB | 32 GB |
|-------------------------------|--------|--------|------|------|------|------|-------|-------|
| <b>Performance</b>            |        |        |      |      |      |      |       |       |
| <b>Sustained read (MB/s)</b>  | 31     | 31     | 32   | 34   | 28   | 32   | 34    | 31    |
| <b>Sustained write (MB/s)</b> | 10     | 15     | 19   | 19   | 21   | 15   | 22    | 21    |

Note: results may vary depending on flash configurations or host system settings

### 2.2 Performance Specifications – MLC

**Table 2-2: MLC Performance Specifications**

| Capacity                      | 4 GB | 8 GB | 16 GB | 32 GB |
|-------------------------------|------|------|-------|-------|
| <b>Performance</b>            |      |      |       |       |
| <b>Sustained read (MB/s)</b>  | 32   | 32   | 33    | 33    |
| <b>Sustained write (MB/s)</b> | 10   | 10   | 14    | 16    |

Note: results may vary depending on flash configurations or host system settings

### 3. Electrical Specification

**Caution: Absolute Maximum Stress Ratings** – Applied conditions greater than those listed under “Absolute Maximum Stress Ratings” may cause permanent damage to the device. This is a stress rating only and functional operation of the device at these conditions or conditions greater than those defined in the operational sections of this data sheet is not implied. Exposure to absolute maximum stress rating conditions may affect device reliability.

**Table: Absolute Stress Rating**

| Parameters   | Conditions                             |
|--|--|
| Ambient temperature                                    | 0 to 70 °C                             |
| Required power supply                                  | 4.5-5.5V                               |
| Input power ( $V_{DD}$ )                               | -0.3V (min.) to 5.5V (max.)            |
| Voltage on any pin except $V_{DD}$ with respect to GND | -0.3V (min.) to $V_{DD} + 0.3V$ (max.) |

### 4. Physical Dimensions



## 5. Product Ordering Information

### 5.1 Product Code Designation



---

## 5.2 Valid Combinations

### 5.2.1 AH322 (SLC)

| <b>Capacity</b> | <b>Standard</b>  |
|-----------------|------------------|
| 128MB           | APHA128MR23CG-2T |
| 256MB           | APHA256MR23CG-2T |
| 512MB           | APHA512MR23CG-2T |
| 1GB             | APHA001GR23CG-2T |
| 2GB             | APHA002GR23CG-2T |
| 4GB             | APHA004GR23CG-2T |
| 8GB             | APHA008GR23CG-2T |
| 16GB            | APHA016GR23CG-2T |
| 32GB            | APHA032GR23CG-2T |

### 5.2.2 AH322 (MLC)

| <b>Capacity</b> | <b>Standard</b>  |
|-----------------|------------------|
| 4GB             | APHA004GR23CG-CM |
| 8GB             | APHA008GR23CG-CM |
| 16GB            | APHA016GR23CG-CM |
| 32GB            | APHA032GR23CG-CM |

**Note:** For availability or customized requests, please consult with Apacer sales representatives.



---

## Revision History

| Revision | Description   | Date                           |
|----------|---|--------------------------------|
| 1.0      | Official Release  | August 11 <sup>th</sup> , 2011 |
| 1.1      | Updated Product Ordering Information  | June 20 <sup>th</sup> , 2012   |
| 1.2      | Updated Product Ordering Information<br>- contents relating to extended temperature are removed                                   | July 2 <sup>nd</sup> , 2012    |
| 1.3      | Updated read/write performance due to change in NAND flash use<br>Updated addresses of Taiwan headquarter and the office in India | August 6 <sup>th</sup> , 2013  |
| 1.4      | Added performance tables  | June 4 <sup>th</sup> , 2014    |

---

## Global Presence

|                              |   |
|------------------------------|---|
| <b>Taiwan (Headquarters)</b> | <b>Apacer Technology Inc.</b><br>Apacer Technology Inc.<br>1F., No.32, Zhongcheng Rd., Tucheng Dist.,<br>New Taipei City 236, Taiwan R.O.C.<br>Tel: 886-2-2267-8000<br>Fax: 886-2-2267-2261<br><a href="mailto:amtsales@apacer.com">amtsales@apacer.com</a> |
| <b>U.S.A.</b>                | <b>Apacer Memory America, Inc.</b><br>386 Fairview Way, Suite102,<br>Milpitas, CA 95035<br>Tel: 1-408-586-1291<br>Fax: 1-408-935-9611<br><a href="mailto:sa@apacerus.com">sa@apacerus.com</a>   |
| <b>Japan</b>                 | <b>Apacer Technology Corp.</b><br>5F, Matsura Bldg., Shiba, Minato-Ku<br>Tokyo, 105-0014, Japan<br>Tel: 81-3-5419-2668<br>Fax: 81-3-5419-0018<br><a href="mailto:jpservices@apacer.com">jpservices@apacer.com</a>   |
| <b>Europe</b>                | <b>Apacer Technology B.V.</b><br>Science Park Eindhoven 5051 5692 EB Son,<br>The Netherlands<br>Tel: 31-40-267-0000<br>Fax: 31-40-267-0000#6199<br><a href="mailto:sales@apacer.nl">sales@apacer.nl</a>   |
| <b>China</b>                 | <b>Apacer Electronic (Shanghai) Co., Ltd</b><br>1301, No.251,Xiaomujiao Road, Shanghai,<br>200032, China<br>Tel: 86-21-5529-0222<br>Fax: 86-21-5206-6939<br><a href="mailto:sales@apacer.com.cn">sales@apacer.com.cn</a>                                    |
| <b>India</b>                 | <b>Apacer Technologies Pvt. Ltd.</b><br># 535, 1st Floor, 8th cross, JP Nagar 3rd Phase,<br>Bangalore – 560078, India<br>Tel: 91-80-4152-9061<br><a href="mailto:sales_india@apacer.com">sales_india@apacer.com</a>   |



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.