



Dimension

DIM A	N×5.0+0.10
DIM B	(N-1)×5.0
Δ DIM C	(N+1)×5.0
Δ DIM D	N×5.0+10.6
Δ DIM E	N×5.0+0.4

N=Number of poles

POLES	TOL
2p-6p	±0.15
7p-12p	±0.20
13p-16p	±0.30
17p-24p	±0.40

SIGN	DATE	DESCRIPTION	APPROVER
Δ	06/22'13	Add the dimensional label	Jacky
Δ	06/22'13	Add the feminal lever colour	Jacky
Δ	06/22'13	Add the colour code	Jacky
Δ	06/22'13	Change the drawing number	Jacky
Δ	06/22'13	Add the view	Jacky
Δ	06/28'13	Change the dimension from 5.2 to 5.0	Jacky

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

Material

- Item a Terminal body:Thermoplastic (UL94V-0)
- Item b Terminal body:Thermoplastic (UL94V-0)
- Item c Terminal lever:Thermoplastic (UL94V-0)Orange
- Item d Wire guard:Stainless Steel
- Item e Male contacta pin:PhBz (CuSn) Tin plated
- Item f With flange Nut; Brass M2.5

Electrical

- Voltage rating: 300V
- Current rating: 10A
- Solid wire(AWG): 12-26
- Stranded wire(AWG): 12-26
- Wire strip length: 9-10mm
- Withstanding Voltage: 1.6KV
- Operating temperature: -40°C to +115°C
- Safety Approval:
- Critical dimension:

H5 xx 70 x 2 xxxx G

- |                |                        |                        |                 |
|----------------|------------------------|------------------------|-----------------|
| 02 2 CONTACTS  |                        | 0000 Standard @ Logo   | RoHS compliant  |
| 03 3 CONTACTS  | 0: BLACK               | 000A Standard ANY Logo | (lead<4%)       |
| ...            | 5: GREEN (RAL 6018/T)  | Any special item by    | In copper Alloy |
| 24 24 CONTACTS | 6: BLUE                | customer request,      |                 |
|                | 8: GREY (RAL 7035/D)   | please contact sales   |                 |
|                | ΔC: GREEN (RAL 6018/U) | department.            |                 |

**ANYTEK**

**CUSTOMER COPY**

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE		H5 5.0 Series ( 2P-24P ) Flange with Nut			
PART NO.	H5xx70x2xxxxG	DWG NO.	8H50303Δ		
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.	Tolerance
		Jacky 2013.06.28	Jacky 2013.06.28		X. ±0.50
					X.X ±0.30
					X.XX ±0.10
					X* ±1*
				SHEET: 01/01	REV.: C



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.