

2048-word × 8 bit High Speed CMOS Static RAM

Description

CXK5816PN/M is a 16,384 bits high speed CMOS static RAM organized as 2,048 words by 8 bits and operates from a single 5V supply. This device is suitable for use in high speed and low power applications in which battery back up for nonvolatility is required.

Features

- High speed operation (Access time)

CXK5816PN/M	-10, 10L	100ns (Max.)
CXK5816PN/M	-12, 12L	120ns (Max.)
CXK5816PN/M	-15, 15L	150ns (Max.)
- Low power consumption (Standby) (Operation)

CXK5816PN/M	-10, 12, 15	100 μ W(Typ.)	125mW(Typ.)
CXK5816PN/M	-10L, 12L, 15L	5 μ W(Typ.)	125mW(Typ.)
- Single +5V supply: 5V $\pm$ 10%.
- Fully static memory No clock or timing strobe required
- Equal access and cycle time
- Common data input and output: three-state output
- Directly TTL compatible: All inputs and outputs
- Low voltage data retention: 2.0V (Min.)


Function

2048-word $\times$ 8 bit static RAM

Structure


Silicon gate CMOS IC

Block Diagram




Package Outline

Unit: mm



Note) All Typical values are measured under the conditions $V_{CC}=5.0V$ and $T_a=25^{\circ}C$.

Pin Configuration (Top View)



Pin Description

Symbol	Description
A0 to A10	Address input
I/O1 to I/O8	Data input output
CE	Chip enable input
WE	Write enable input
OE	Output enable input
V _{CC}	+5V power supply
GND	Ground

Absolute Maximum Ratings

T_a = 25°C, GND = 0V

Item	Symbol		Rating	Unit
Supply voltage	V _{CC}		-0.5* to +7.0	V
Input voltage	V _{IN}		-0.5* to V _{CC} +0.5	V
Input and output voltage	V _{I/O}		-0.5* to V _{CC} +0.5	V
Allowable power dissipation	P _D	CXK5816PN/SP	1.0	W
		CXK5816M	0.7	
Operating temperature	T _{opr}		0 to +70	°C
Storage temperature	T _{stg}		-55 to +150	°C
Soldering temperature	T _{solder}		260*10	°C • sec

* V_{CC}, V_{IN}, V_{I/O} Minimum value = -3.0V, Pulse width is under 50 ns.

Truth Table

CE	OE	WE	Mode	I/O1 to I/O8	V _{CC} Current
H	X	X	Not selected	High Z	I _{SB1} , I _{SB2}
L	H	H	Output disable	High Z	I _{CC1} , I _{CC2}
L	L	H	Read	D out	I _{CC1} , I _{CC2}
L	X	L	Write	D in	I _{CC1} , I _{CC2}

Note) X: "H" or "L"

DC Recommended Operating Conditions

T_a = 0 to +70°C, GND = 0V

Item	Symbol	Min.	Typ.	Max.	Unit
Supply voltage	V _{CC}	4.5	5.0	5.5	V
Input high voltage	V _{IH}	2.2	—	V _{CC} +0.3	V
Input low voltage	V _{IL}	-0.3	—	0.8	V

DC and Operating Characteristics

 $V_{CC}=5V \pm 10\%$, $GND=0V$, $T_a=0$ to $+70^\circ C$

Item	Symbol	Test condition	CXK5816PN/M/SP -10/12/15			CXK5816PN/M/SP -10L/12L/15L			Unit
			Min.	Typ.**	Max.	Min.	Typ.**	Max.	
Input leakage current	I_{LI}	$V_{IN}=GND$ to V_{CC}	-2	—	2	-2	—	2	μA
Output leakage current	I_{LO}	$\overline{CE}=V_{IH}$ or $\overline{OE}=V_{IH}$ $V_{I/O}=GND$ to V_{CC}	-2	—	2	-2	—	2	μA
Operating power supply current	I_{CC1}	$\overline{CE}=V_{IL}$, $I_{OUT}=0mA$	—	25	60	—	25	60	mA
Average operating current	I_{CC2}	Cycle = Min, Duty = 100% $I_{OUT}=0mA$	—	28 *(31)	60 *(75)	—	28 *(31)	60 *(75)	mA
Standby current	I_{SB1}	$\overline{CE} \geq V_{CC}-0.2V$	—	0.02	1.0	—	0.001	0.05	mA
	I_{SB2}	$\overline{CE}=V_{IH}$	—	0.3	2	—	0.2	1	mA
Output high voltage	V_{OH}	$I_{OH}=-1.0mA$	2.4	—	—	2.4	—	—	V
Output low voltage	V_{OL}	$I_{OL}=4.0mA$	—	—	0.4	—	—	0.4	V

* **Note)** Shows CXK5816PN/M/SP-10, 10L value.** $V_{CC}=5V$, $T_a=25^\circ C$

Capacitance

 $T_a=25^\circ C$, $f=1\text{ MHz}$

Item	Test condition	Symbol	Min.	Max.	Unit
Input capacitance	$V_{IN}=0V$	C_{IN}	—	7	pF
Input/output capacitance	$V_{I/O}=0V$	$C_{I/O}$	—	10	pF


Note) This parameter is sampled and is not 100% tested.

AC Operating Characteristics

• AC test condition

 $V_{CC} = 5V \pm 10\%$, $T_a = 0$ to $+70^\circ C$

Item	Condition
Input pulse high level	$V_{IH}=2.4V$
Input pulse low level	$V_{IL}=0.6V$
Input rise time	$t_R = 5ns$
Input fall time	$t_F = 5ns$
Input and output timing reference level	1.5V
Output load	$CL^* = 100pF$, 1TTL

* CL includes scope and jig capacitance.

• Read cycle

Item	Symbol	CXK5816PN/M -10/10L		CXK5816PN/M -12/12L		CXK5816PN/M -15/15L		Unit
		Min.	Max.	Min.	Max.	Min.	Max.	
Read cycle time	t_{RC}	100	—	120	—	150	—	ns
Address access time	t_{AA}	—	100	—	120	—	150	ns
Chip enable access time	t_{CO}	—	100	—	120	—	150	ns
Output enable to output valid	t_{OE}	—	50	—	55	—	60	ns
Output hold from address change	t_{OH}	15	—	15	—	15	—	ns
Chip enable to output in low Z (CE)	t_{LZ}	15	—	15	—	15	—	ns
Output enable to output in low Z (OE)	t_{OLZ}	10	—	10	—	10	—	ns
Chip disable to output in high Z (CE)	$*t_{HZ}$	0	30	0	40	0	50	ns
Output disable to output in high Z (OE)	$*t_{OHZ}$	0	30	0	40	0	50	ns



* **Note** t_{HZ} and t_{OHZ} are specified by the time length until the output circuit is turned off and not specified by the output voltage level.


• Write cycle

Item	Symbol	CXK5816PN/M -10/10L		CXK5816PN/M -12/12L		CXK5816PN/M -15/15L		Unit
		Min.	Max.	Min.	Max.	Min.	Max.	
Write cycle time	t_{WC}	100	—	120	—	150	—	ns
Address valid to end of write	t_{AW}	80	—	100	—	120	—	ns
Chip enable to end of write	t_{CW}	80	—	100	—	120	—	ns
Data to write time overlap	t_{DW}	30	—	35	—	40	—	ns
Data hold from write time	t_{DH}	0	—	0	—	0	—	ns
Write pulse width	t_{WP}	60	—	75	—	90	—	ns
Address setup time	t_{AS}	0	—	0	—	0	—	ns
Write recovery time	t_{WR}	5	—	5	—	5	—	ns
Output active from end of write	t_{OW}	15	—	15	—	15	—	ns
Write to output in high Z	t_{WHZ}^*	0	30	0	40	0	50	ns

* **Note** t_{WHZ} is specified by the time length until the output circuit is turned off and not specified by the output voltage level.

Timing Waveform

(1) Read Cycle [$\overline{WE}=V_{IH}$](2) Write Cycle (1): $\overline{WE}$ Control [$\overline{OE}=V_{IH}$]

Write Cycle (2): $\overline{\text{CE}}$ Control [$\overline{\text{OE}} = \text{V}_{\text{IL}}$]

Note)

- *1 A write occurs during the low overlap of $\overline{\text{CE}}$ and $\overline{\text{WE}}$.
- *2 t_{WR} is measured from the earlier of $\overline{\text{CE}}$ or $\overline{\text{WE}}$ going high to the end of write cycle.
- *3 During this period, I/O pins are in the output state so that the input signals of opposite phase to the outputs must not be applied.


Data Retention Characteristics

 $T_a = 0 \text{ to } +70^\circ\text{C}$


Item	Symbol	Test condition	CXK5816PN/M -10/12/15			CXK5816PN/M -10L/12L/15L			Unit
			Min.	Typ.	Max.	Min.	Typ.	Max.	
Data retention voltage	V_{DR}	$\overline{\text{CE}} \geq V_{\text{CC}} - 0.2\text{V}$	2.0	5.0	5.5	2.0	5.0	5.5	V
Data retention current	I_{CCDR1}	$V_{\text{CC}} = 3.0\text{V}$, $\overline{\text{CE}} \geq 2.8\text{V}$	—	12	600	—	0.6	30	μA
	I_{CCDR2}	$V_{\text{CC}} = 2.0 \text{ to } 5.5\text{V}$, $\overline{\text{CE}} \geq V_{\text{CC}} - 0.2\text{V}$	—	20	1000	—	1.0	50	μA
Data retention set up time	t_{CDRS}	Chip disable to data retention mode	0	—	—	0	—	—	ns
Recovery time	t_{R}		t_{RC}^*	—	—	t_{RC}^*	—	—	ns

* t_{RC} : Read cycle time


Data Retention Waveform




Supply current vs. Supply voltage




Supply current vs. Ambient temperature




Supply current vs. Frequency




Access time vs. Load capacitance




Access time vs. Supply voltage




Access time vs. Ambient temperature




Standby current (1) vs. Supply voltage





Standby current (1) vs. Ambient temperature




Standby current (2) vs. Supply voltage



Standby current (2) vs. Ambient temperature

Output high current vs. Output high voltage
Output low current vs. Output low voltage

Input voltage vs. Supply voltage



T-90-20

7. Sony Package Product Name

Type	Package name		Package	Features			
	Symbol	Description		Material*	Lead pitch	Lead shape	Lead pull out direction
Inserted	Standard	D I P	DUAL IN LINE PACKAGE		P C	2.54mm (100MIL)	Through Hole Lead 2-direction
		S I P	SINGLE IN LINE PACKAGE		P	2.54mm (100MIL)	Through Hole Lead 1-direction
		Z I P	ZIG ZAG IN LINE PACKAGE		P	2.54mm (100MIL) Zig Zag inline	Through Hole Lead 1-direction
		P G A	PIN GRID ARRAY		C	2.54mm (100MIL)	Through Hole Lead 4-direction
		PIGGY BACK	PIGGY BACK		C	2.54mm (100MIL)	Through Hole Lead 2-direction
	Shrink	SDIP	SHRINK DUAL IN LINE PACKAGE		P	1.778mm (70MIL)	Through Hole Lead 2-direction
Surface mounted	Standard flat package	Q F P	QUAD FLAT PACKAGE		P	1.0mm 0.8mm	Gull-Wing 4-direction
		S O P	SMALL OUTLINE PACKAGE		P	1.27mm (50MIL)	Gull-Wing 2-direction
	Shrink flat package	VQFP	VERY SMALL QUAD FLAT PACKAGE		P	0.5mm	Gull-Wing 4-direction
		VSOP	VERY SMALL OUTLINE PACKAGE		P	0.65mm	Gull-Wing 2-direction
	Standard chip carrier	PLCC	PLASTIC LEADED CHIP CARRIER		P	1.27mm (50MIL)	J-bend 4-direction
		L C C	LEAD LESS CHIP CARRIER		C	1.27mm (50MIL)	Lead less Package side
	Shrink chip carrier	SPLCC (PLCC)	SHRINK PLASTIC LEADED CHIP CARRIER		P	1.27mm Max. (50MIL Max.)	J-bend 4-direction
	Standard 2-direction chip carrier	S O J	SMALL OUTLINE J-LEAD PACKAGE		P	1.27mm (50MIL)	J-bend 2-direction

*P.....Plastic, C.....Ceramic



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.