

FO cable - PSM-LWL-HCSO-200/230-METER - 2799445

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



HCS cable, duplex 200/230 µm, by the meter, without connector, for outdoor installation

Why buy this product

- Watertight lengthwise
- Integrated vapor barrier and rodent-proof scrim
- Extremely rugged polyethylene outer sheath
- Extremely rugged polyethylene outer sheath
- Rugged round cable for outdoor installation
- 2.9 mm individual wires made from highly flexible FRNC material
- Ozone and UV resistant
- Ozone and UV resistant

Key commercial data

Packing unit	1
Minimum order quantity	1
Catalog page	Page 530 (IF-2011)
GTIN	 4 017918 138813
Custom tariff number	85447000
Country of origin	GERMANY

Technical data

Mechanical characteristics

Fiber	HCS, 200/230 µm
Cable diameter	10.5 mm
Ambient temperature (operation)	-20 °C ... 70 °C
Ambient temperature (storage/transport)	-25 °C ... 70 °C

Material data

Outer sheath, material	PE
External sheath, color	black

Line characteristics

Cable type	HCS
------------	-----

FO cable - PSM-LWL-HCSO-200/230-METER - 2799445

Technical data

Line characteristics

Cable abbreviation	AT-VQHB2Y 2K200/230 10A17+8B20
Length of cable	Free entry (1.0 ... 1000.0 m)
External cable diameter	10.5 mm
Wire colors	Red/Green
External sheath, color	black
Cable, attenuation	10 dB/km (at 660 nm), 8 dB/km (at 850 nm)
Outer sheath, material	PE
Strain relief elements, external sheath	Non-metallic, aramide fiber
Cable weight	97 kg/km
Tensile strength short-term/long-term	1500 N / 200 N
Lateral pressure short term	500 N/cm
Lateral pressure, long-term	300 N/cm
Impact strength	1,5 Nm / 3 x
cable layer type	Outdoors
Halogen-free	According to IEC 60754-2

Temperature data

Ambient temperature (operation)	-20 °C ... 70 °C
Ambient temperature (storage/transport)	-25 °C ... 70 °C
Altitude	5000 m

Classifications

ETIM

ETIM 2.0	EC000752
ETIM 3.0	EC000752
ETIM 4.0	EC000752
ETIM 5.0	EC000830

UNSPSC

UNSPSC 11	26121607
UNSPSC 12.01	26121607
UNSPSC 13.2	26121607
UNSPSC 6.01	26121607
UNSPSC 7.0901	26121607

eCl@ss

eCl@ss 4.0	27061001
eCl@ss 4.1	27061001
eCl@ss 5.0	27061803
eCl@ss 5.1	27061803
eCl@ss 6.0	27061803
eCl@ss 7.0	27061803

FO cable - PSM-LWL-HCSO-200/230-METER - 2799445

Accessories

Accessories

Cable/conductor

FO patch cable - FOC-HCSO-1015/IP20/... - 2901557



Highly rugged HCS round cable (IP20 heads only) for assembly and for outdoor installation with integrated moisture barrier as well as rodent-proof scrim. Individual elements made from highly flexible FRNC material. The wire is ozone and UV resistant with a very rugged polyethylene outer sheath.

FO patch cable - FOC-HCSO-1015/... - 1402192



Highly rugged HCS round cable for assembly and for outdoor installation with integrated moisture barrier as well as rodent-proof scrim. Individual elements made from highly flexible FRNC material. The wire is ozone and UV resistant with a very rugged polyethylene outer sheath.

Plug/Adapter

FO plug connectors - PSM-SET-FSMA/4-HCS - 2799487



F-SMA plug set for HCS fiber, for self assembly consisting of 4 quick mounting connectors with bend protection sleeve

FO plug connectors - PSM-SET-B-FOC/4-HCS - 2708481



B-FOC (ST) connector set for HCS fiber, for self assembly consisting of 4 quick mounting connectors with bend protection sleeve

FO plug connectors - PSM-SET-SCRJ-DUP/2-HCS - 2313070



SCRJ connector set for HCS fiber, for self assembly, consisting of 2 duplex quick mounting connectors with bending protection

Tools

FO cable - PSM-LWL-HCSO-200/230-METER - 2799445

Accessories

Assembly tool - PSM-HCS-KONFTOOL - 2799526



HCS assembly kit for F-SMA quick mounting connectors, including stripping blade, stripping pliers, aramide yarn scissors, fiber stripper, microscope, fiber cleaving tool for standard HCS fibers, and documentation

Assembly tool - PSM-HCS-KONFTOOL/B-FOC - 2708465



HCS assembly kit for B-FOC (ST) quick mounting connectors, including stripping blade, stripping pliers, aramide yarn scissors, fiber stripper, microscope, fiber cleaving tool for standard HCS and HCS GI fibers, and documentation

Assembly tool - PSM-HCS-KONFTOOL/SC-RJ - 2708876



HCS assembly kit for SCRJ quick mounting connectors, including stripping blade, stripping pliers, aramide yarn scissors, fiber stripper, microscope, fiber cleaving tool for standard HCS and HCS GI fibers, and documentation

Assembly tool - PSM-HCS-CLEAVETOOL - 2744995



Fiber cleaving tool for HCS fibers, pin assignment: F-SMA for the assembly of F-SMA quick mounting connectors, supplements PSM-HCS-KONFTOOL...

Assembly tool - PSM-HCS-CLEAVETOOL/B-FOC - 2708478



Fiber cleaving tool for HCS fibers, pin assignment: B-FOC (ST) for the assembly of B-FOC quick mounting connectors, supplements PSM-HCS-KONFTOOL...

Assembly tool - PSM-HCS-CLEAVETOOL/SCRJ - 2313122



Fiber cleaving tool for HCS fibers, pin assignment: SCRJ or SC duplex for the assembly of SC quick mounting connectors, supplements PSM-HCS-KONFTOOL...

FO cable - PSM-LWL-HCSO-200/230-METER - 2799445

Accessories

© Phoenix Contact 2012 - all rights reserved
<http://www.phoenixcontact.com>



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.