- **1/2 V_I Virtual Ground for Analog Systems**
- **Self-Contained 3-terminal TO-226AA Package**
- **Micropower Operation . . . 170 μA Typ, V_I = 5 V**
- **Wide V_I Range . . . 4 V to 40 V**
- **High Output-Current Capability**
  - **Source . . . 20 mA Typ**
  - **Sink . . . 20 mA Typ**
- **Excellent Output Regulation**
  - **−45 μV Typ at I_O = 0 to −10 mA**
  - **+15 μV Typ at I_O = 0 to +10 mA**
- **Low-Impedance Output . . . 0.0075 Ω Typ**
- **Noise Reduction Pin (D, JG, and P Packages Only)**

INPUT/OUTPUT TRANSFER CHARACTERISTICS

description

In signal-conditioning applications utilizing a single power source, a reference voltage equal to one-half the supply voltage is required for termination of all analog signal grounds. Texas Instruments presents a precision virtual ground whose output voltage is always equal to one-half the input voltage, the TLE2426 "rail splitter."

The unique combination of a high-performance, micropower operational amplifier and a precision-trimmed divider on a single silicon chip results in a precise V_O/V_I ratio of 0.5 while sinking and sourcing current. The TLE2426 provides a low-impedance output with 20 mA of sink and source capability while drawing less than 280 μA of supply current over the full input range of 4 V to 40 V. A designer need not pay the price in terms of board space for a conventional signal ground consisting of resistors, capacitors, operational amplifiers, and voltage references. The performance and precision of the TLE2426 is available in an easy-to-use, space saving, 3-terminal LP package. For increased performance, the optional 8-pin packages provide a noise-reduction pin. With the addition of an external capacitor (C_{NR}), peak-to-peak noise is reduced while line ripple rejection is improved.

Initial output tolerance for a single 5-V or 12-V system is better than 1% with 3.6% over the full 40-V input range. Ripple rejection exceeds 12 bits of accuracy. Whether the application is for a data acquisition front end, analog signal termination, or simply a precision voltage reference, the TLE2426 eliminates a major source of system error.

AVAILABLE OPTIONS

PACKAGED DEVICES					CHIP FORM (Y)
T_A	SMALL OUTLINE (D)	CERAMIC DIP (JG)	PLASTIC (LP)	PLASTIC DIP (P)	
0°C to 70°C	TLE2426CD	—	TLE2426CLP	TLE2426CP	

Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet.

PRODUCTION DATA information is current as of publication date. Products conform to specifications per the terms of Texas Instruments standard warranty. Production processing does not necessarily include testing of all parameters.

Copyright © 1998, Texas Instruments Incorporated

−40°C to 85°C	TLE2426ID	—	TLE2426ILP	TLE2426IP	TLE2426Y
−55°C to 125°C	TLE2426MD	TLE2426MJG	TLE2426MLP	TLE2426MP	

The D and LP packages are available taped and reeled in the commercial temperature range only. Add R suffix to the device type (e. g., TLC2426CDR). Chips are tested at 25°C.

description (continued)

The C-suffix devices are characterized for operation from 0°C to 70°C. The I suffix devices are characterized for operation from −40°C to 85°C. The M suffix devices are characterized over the full military temperature range of −55°C to 125°C.

D, JG, OR P PACKAGE
(TOP VIEW)

NC − No internal connection

LP PACKAGE
(TOP VIEW)

TLE2426Y chip information

This chip, properly assembled, displays characteristics similar to the TLE2426C. Thermal compression or ultrasonic bonding may be used on the doped aluminum bonding pads. The chips may be mounted with conductive epoxy or a gold-silicon preform.

BONDING PAD ASSIGNMENTS

CHIP THICKNESS:
15 MILS TYPICAL

BONDING PADS:
4 × 4 MILS MINIMUM

$T_J$max = 150°C

TOLERANCES ARE ±10%.

ALL DIMENSIONS ARE IN MILS.

NOTE A: Both bonding pads numbered 1, both numbered 2, and both numbered 3, must be bonded out to the corresponding functions pin.

absolute maximum ratings over operating free-air temperature (unless otherwise noted)†

Continuous input voltage, V_I . . . . . 40 V
Continuous filter trap voltage . . . . . 40 V
Output current, I_O . . . . . ±80 mA
Duration of short-circuit current at (or below) 25°C (see Note 1) . . . . . unlimited
Continuous total power dissipation . . . . . See Dissipation Rating Table
Operating free-air temperature range, T_A: C suffix . . . . . 0°C to 70°C
I suffix . . . . . −40°C to 85°C
M suffix . . . . . −55°C to 125°C
Storage temperature range, T_{stg} . . . . . −65°C to 150°C
Lead temperature 1,6 mm (1/16 inch) from case for 10 seconds: D or P package . . . . . 260°C
Lead temperature 1,6 mm (1/16 inch) from case for 60 seconds: JG or LP package . . . . . 300°C

† Stresses beyond those listed under "absolute maximum ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under "recommended operating conditions" is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

NOTE 1: The output may be shorted to either supply. Temperature and/or supply voltages must be limited to ensure that the maximum dissipation rating is not exceeded.

DISSIPATION RATING TABLE

PACKAGE	$T_A \le 25°C$ POWER RATING	DERATING FACTOR ABOVE $T_A = 25°C$	$T_A = 70°C$ POWER RATING	$T_A = 85°C$ POWER RATING	$T_A = 125°C$ POWER RATING
D	725 mV	5.8 mW/°C	464 mW	377 mW	145 mW
JG	1050 mV	8.4 mW/°C	672 mW	546 mW	210 mW
LP	775 mV	6.2 mW/°C	496 mW	403 mW	155 mW
P	1000 mV	8.0 mW/°C	640 mW	520 mW	200 mW

recommended operating conditions

	C SUFFIX		I SUFFIX		M SUFFIX		UNIT
	MIN	MAX	MIN	MAX	MIN	MAX	
Input voltage, V_I	4	40	4	40	4	40	V
Operating free-air temperature, T_A	0	70	−40	85	−55	125	°C

electrical characteristics at specified free-air temperature, V_I = 5 V, I_O = 0 (unless otherwise noted)

PARAMETER	TEST CONDITIONS		T_A†	TLE2426C MIN	TLE2426C TYP	TLE2426C MAX	UNIT
Output voltage	V_I = 4 V		25°C	1.98	2	2.02	V
	V_I = 5 V			2.48	2.5	2.52	
	V_I = 40 V			19.8	20	20.2	
	V_I = 5 V		Full range	2.475		2.525	
Temperature coefficient of output voltage			Full range		25		ppm/°C
Supply current	No load	V_I = 5 V	25°C		170	300	µA
		V_I = 4 to 40 V	Full range			400	
Output voltage regulation (sourcing current)‡	I_O = 0 to −10 mA		25°C		−45	±160	µV
			Full range			±250	
	I_O = 0 to −20 mA		25°C		−150	±450	
Output voltage regulation (sinking current)‡	I_O = 0 to 10 mA		25°C		15	±160	µV
			Full range			±250	
	I_O = 0 to 20 mA		25°C		65	±235	
Output impedance			25°C		7.5	22.5	mΩ
Noise-reduction impedance			25°C		110		kΩ
Short-circuit current	Sinking current,	V_O = 5 V	25°C		26		mA
	Sourcing current,	V_O = 0			−47		
Output noise voltage, rms	f = 10 Hz to 10 kHz	C_{NR} = 0	25°C		120		µV
		C_{NR} = 1 µF			30		
Output voltage current step response	V_O to 0.1%, I_O = ±10 mA	C_L = 0	25°C		290		µs
		C_L = 100 pF			275		
	V_O to 0.01%, I_O = ±10 mA	C_L = 0	25°C		400		
		C_L = 100 pF			390		
Step response	V_I = 0 to 5 V, V_O to 0.1%	C_L = 100 pF	25°C		20		µs
	V_I = 0 to 5 V, V_O to 0.01%				160		

† Full range is 0°C to 70°C.
‡ The listed values are not production tested.

electrical characteristics at specified free-air temperature, V_I = 12 V, I_O = 0 (unless otherwise noted)

PARAMETER	TEST CONDITIONS		T_A†	TLE2426C MIN	TLE2426C TYP	TLE2426C MAX	UNIT
Output voltage	V_I = 4 V		25°C	1.98	2	2.02	V
	V_I = 12 V			5.95	6	6.05	
	V_I = 40 V			19.8	20	20.2	
	V_I = 12 V		Full range	5.945		6.055	
Temperature coefficient of output voltage			Full range		35		ppm/°C
Supply current	No load	V_I = 12 V	25°C		195	300	µA
		V_I = 4 to 40 V	Full range			400	
Output voltage regulation (sourcing current)‡	I_O = 0 to −10 mA		25°C		−45	±160	µV
			Full range			±250	
	I_O = 0 to −20 mA		25°C		−150	±450	
Output voltage regulation (sinking current)‡	I_O = 0 to 10 mA		25°C		15	±160	µV
			Full range			±250	
	I_O = 0 to 20 mA		25°C		65	±235	
Output impedance			25°C		7.5	22.5	mΩ
Noise-reduction impedance			25°C		110		kΩ
Short-circuit current	Sinking current,	V_O = 12 V	25°C		31		mA
	Sourcing current,	V_O = 0			−70		
Output noise voltage, rms	f = 10 Hz to 10 kHz	C_{NR} = 0	25°C		120		µV
		C_{NR} = 1 µF			30		
Output voltage current step response	V_O to 0.1%, I_O = ±10 mA	C_L = 0	25°C		290		µs
		C_L = 100 pF			275		
	V_O to 0.01%, I_O = ±10 mA	C_L = 0	25°C		400		
		C_L = 100 pF			390		
Step response	V_I = 0 to 12 V, V_O to 0.1%	C_L = 100 pF	25°C		20		µs
	V_I = 0 to 12 V, V_O to 0.01%				120		

† Full range is 0°C to 70°C.
‡ The listed values are not production tested.

electrical characteristics at specified free-air temperature, V_I = 5 V, I_O = 0 (unless otherwise noted)

PARAMETER	TEST CONDITIONS		T_A†	TLE2426I MIN	TLE2426I TYP	TLE2426I MAX	UNIT
Output voltage	V_I = 4 V		25°C	1.98	2	2.02	V
	V_I = 5 V			2.48	2.5	2.52	
	V_I = 40 V			19.8	20	20.2	
	V_I = 5 V		Full range	2.47		2.53	
Temperature coefficient of output voltage			Full range		25		ppm/°C
Supply current	No load	V_I = 5 V	25°C		170	300	µA
		V_I = 4 to 40 V	Full range			400	
Output voltage regulation (sourcing current)‡	I_O = 0 to −10 mA		25°C		−45	±160	µV
			Full range			±250	
	I_O = 0 to −20 mA		25°C		−150	±450	
Output voltage regulation (sinking current)‡	I_O = 0 to 10 mA		25°C		15	±160	µV
	I_O = 0 to 8 mA		Full range			±250	
	I_O = 0 to 20 mA		25°C		65	±235	
Output impedance			25°C		7.5	22.5	mΩ
Noise-reduction impedance			25°C		110		kΩ
Short-circuit current	Sinking current,	V_O = 5 V	25°C		26		mA
	Sourcing current,	V_O = 0			−47		
Output noise voltage, rms	f = 10 Hz to 10 kHz	C_{NR} = 0	25°C		120		µV
		C_{NR} = 1 µF			30		
Output voltage current step response	V_O to 0.1%, I_O = ±10 mA	C_L = 0	25°C		290		µs
		C_L = 100 pF			275		
	V_O to 0.01%, I_O = ±10 mA	C_L = 0	25°C		400		
		C_L = 100 pF			390		
Step response	V_I = 0 to 5 V, V_O to 0.1%	C_L = 100 pF	25°C		20		µs
	V_I = 0 to 5 V, V_O to 0.01%				160		

† Full range is −40°C to 85°C.
‡ The listed values are not production tested.

electrical characteristics at specified free-air temperature, V_I = 12 V, I_O = 0 (unless otherwise noted)

PARAMETER	TEST CONDITIONS		T_A†	TLE2426I MIN	TLE2426I TYP	TLE2426I MAX	UNIT
Output voltage	V_I = 4 V		25°C	1.98	2	2.02	V
	V_I = 12 V			5.95	6	6.05	
	V_I = 40 V			19.8	20	20.2	
	V_I = 12 V		Full range	5.935		6.065	
Temperature coefficient of output voltage			Full range		35		ppm/°C
Supply current	No load	V_I = 12 V	25°C		195	300	µA
		V_I = 4 to 40 V	Full range			400	
Output voltage regulation (sourcing current)‡	I_O = 0 to −10 mA		25°C		−45	±160	µV
			Full range			±250	
	I_O = 0 to −20 mA		25°C		−150	±450	
Output voltage regulation (sinking current)‡	I_O = 0 to 10 mA		25°C		15	±160	µV
	I_O = 0 to 8 mA		Full range			±250	
	I_O = 0 to 20 mA		25°C		65	±235	
Output impedance			25°C		7.5	22.5	mΩ
Noise-reduction impedance			25°C		110		kΩ
Short-circuit current	Sinking current,	V_O = 12 V	25°C		31		mA
	Sourcing current,	V_O = 0			−70		
Output noise voltage, rms	f = 10 Hz to 10 kHz	C_{NR} = 0	25°C		120		µV
		C_{NR} = 1 µF			30		
Output voltage current step response	V_O to 0.1%, I_O = ±10 mA	C_L = 0	25°C		290		µs
		C_L = 100 pF			275		
	V_O to 0.01%, I_O = ±10 mA	C_L = 0	25°C		400		
		C_L = 100 pF			390		
Step response	V_I = 0 to 12 V, V_O to 0.1%	C_L = 100 pF	25°C		20		µs
	V_I = 0 to 12 V, V_O to 0.01%				120		

† Full range is −40°C to 85°C.
‡ The listed values are not production tested.

electrical characteristics at specified free-air temperature, V_I = 5 V, I_O = 0 (unless otherwise noted)

PARAMETER	TEST CONDITIONS		T_A†	TLE2426M MIN	TLE2426M TYP	TLE2426M MAX	UNIT
Output voltage	V_I = 4 V		25°C	1.98	2	2.02	V
	V_I = 5 V			2.48	2.5	2.52	
	V_I = 40 V			19.8	20	20.2	
	V_I = 5 V		Full range	2.465		2.535	
Temperature coefficient of output voltage			Full range		25		ppm/°C
Supply current	No load	V_I = 5 V	25°C		170	300	µA
		V_I = 4 to 40 V	Full range			400	
Output voltage regulation (sourcing current)‡	I_O = 0 to −10 mA		25°C		−45	±160	µV
			Full range			±250	
	I_O = 0 to −20 mA		25°C		−150	±450	
Output voltage regulation (sinking current)‡	I_O = 0 to 10 mA		25°C		15	±160	µV
	I_O = 0 to 3 mA		Full range			±250	
	I_O = 0 to 20 mA		25°C		65	±235	
Output impedance			25°C		7.5	22.5	mΩ
Noise-reduction impedance			25°C		110		kΩ
Short-circuit current	Sinking current,	V_O = 5 V	25°C		26		mA
	Sourcing current,	V_O = 0			−47		
Output noise voltage, rms	f = 10 Hz to 10 kHz	C_{NR} = 0	25°C		120		µV
		C_{NR} = 1 µF			30		
Output voltage current step response	V_O to 0.1%, I_O = ±10 mA	C_L = 0	25°C		290		µs
		C_L = 100 pF			275		
	V_O to 0.01%, I_O = ±10 mA	C_L = 0	25°C		400		
		C_L = 100 pF			390		
Step response	V_I = 0 to 5 V, V_O to 0.1%	C_L = 100 pF	25°C		20		µs
	V_I = 0 to 5 V, V_O to 0.01%				120		

† Full range is −55°C to 125°C.
‡ The listed values are not production tested.

electrical characteristics at specified free-air temperature, V_I = 12 V, I_O = 0 (unless otherwise noted)

PARAMETER	TEST CONDITIONS		T_A†	TLE2426M MIN	TLE2426M TYP	TLE2426M MAX	UNIT
Output voltage	V_I = 4 V		25°C	1.98	2	2.02	V
	V_I = 12 V			5.95	6	6.05	
	V_I = 40 V			19.8	20	20.2	
	V_I = 12 V		Full range	5.925		6.075	
Temperature coefficient of output voltage			Full range		35		ppm/°C
Supply current	No load	V_I = 12 V	25°C		195	250	µA
		V_I = 4 to 40 V	Full range			350	
Output voltage regulation (sourcing current)‡	I_O = 0 to −10 mA		25°C		−45	±160	µV
			Full range			±250	
	I_O = 0 to −20 mA		25°C		−150	±450	
Output voltage regulation (sinking current)‡	I_O = 0 to 10 mA		25°C		15	±160	µV
	I_O = 0 to 8 mA		Full range			±250	
	I_O = 0 to 20 mA		25°C		65	±235	
Output impedance			25°C		7.5	22.5	mΩ
Noise-reduction impedance			25°C		110		kΩ
Short-circuit current	Sinking current,	V_O = 12 V	25°C		31		mA
	Sourcing current,	V_O = 0			−70		
Output noise voltage, rms	f = 10 Hz to 10 kHz	C_{NR} = 0	25°C		120		µV
		C_{NR} = 1 µF			30		
Output voltage current step response	V_O to 0.1%, I_O = ±10 mA	C_L = 0	25°C		290		µs
		C_L = 100 pF			275		
	V_O to 0.01%, I_O = ±10 mA	C_L = 0	25°C		400		
		C_L = 100 pF			390		
Step response	V_I = 0 to 12 V, V_O to 0.1%	C_L = 100 pF	25°C		12		µs
	V_I = 0 to 12 V, V_O to 0.01%				120		

† Full range is −55°C to 125°C.
‡ The listed values are not production tested.

electrical characteristics at specified free-air temperature, V_I = 5 V, I_O = 0, T_A = 25°C (unless otherwise noted)

PARAMETER	TEST CONDITIONS		TLE2426Y MIN	TLE2426Y TYP	TLE2426Y MAX	UNIT
Output voltage	V_I = 5 V			2.5		V
Supply current	No load			170		µA
Output voltage regulation (sourcing current)†	I_O = 0 to −10 mA			−45		µV
	I_O = 0 to −20 mA			−150		
Output voltage regulation (sinking current)†	I_O = 0 to 10 mA			15		µV
	I_O = 0 to 20 mA			65		
Output impedance				7.5		mΩ
Noise-reduction impedance				110		kΩ
Short-circuit current	Sinking current,	V_O = 5 V		26		mA
	Sourcing current,	V_O = 0		−47		
Output noise voltage, rms	f = 10 Hz to 10 kHz	C_{NR} = 0		120		µV
		C_{NR} = 1 µF		30		
Output voltage current step response	V_O to 0.1%, I_O = ±10 mA	C_L = 0		290		µs
		C_L = 100 pF		275		
	V_O to 0.01%, I_O = ±10 mA	C_L = 0		400		
		C_L = 100 pF		390		
Step response	V_I = 0 to 5 V, V_O to 0.1%	C_L = 100 pF		20		µs
	V_I = 0 to 5 V, V_O to 0.01%			160		

† The listed values are not production tested.

electrical characteristics at specified free-air temperature, V_I = 12 V, I_O = 0, T_A = 25°C (unless otherwise noted)

PARAMETER	TEST CONDITIONS		TLE2426Y MIN	TLE2426Y TYP	TLE2426Y MAX	UNIT
Output voltage	V_I = 12 V			6		V
Supply current	No load			195		µA
Output voltage regulation (sourcing current)†	I_O = 0 to −10 mA			−45		µV
	I_O = 0 to −20 mA			−150		
Output voltage regulation (sinking current)†	I_O = 0 to 3 mA			15		µV
	I_O = 0 to 20 mA			65		
Output impedance				7.5		mΩ
Noise-reduction impedance				110		kΩ
Short-circuit current	Sinking current,	V_O = 12 V		31		mA
	Sourcing current,	V_O = 0		−70		
Output noise voltage, rms	f = 10 Hz to 10 kHZ	C_{NR} = 0		120		µV
		C_{NR} = 1 µF		30		
Output voltage current, step response	V_O to 0.1%, I_O = ±10 mA	C_L = 0		290		µs
		C_L = 100 pF		275		
	V_O to 0.01%, I_O = ±10 mA	C_L = 0		400		
		C_L = 100 pF		390		
Step response	V_I = 0 to 12 V, V_O to 0.1%	C_L = 100 pF		12		µs
	V_I = 0 to 12 V, V_O to 0.01%			120		

† The listed values are not production tested.

TYPICAL CHARACTERISTICS

Table Of Graphs

		FIGURE
Output voltage	Distribution	1,2
Output voltage change	vs Free-air temperature	3
Output voltage error	vs Input voltage	4
Input bias current	vs Input voltage	5
	vs Free-air temperature	6
Output voltage regulation	vs Output current	7
Output impedance	vs Frequency	8
Short-circuit output current	vs Input voltage	9,10
	vs Free-air temperature	11,12
Ripple rejection	vs Frequency	13
Spectral noise voltage density	vs Frequency	14
Output voltage response to output current step	vs Time	15
Output voltage power-up response	vs Time	16
Output current	vs Load capacitance	17

TYPICAL CHARACTERISTICS†

Figure 1

Figure 2

Figure 3

Figure 4

† Data at high and low temperatures are applicable within the rated operating free-air temperature ranges of the various devices.

TYPICAL CHARACTERISTICS†

Figure 5

Figure 6

Figure 7

Figure 8

† Data at high and low temperatures are applicable within the rated operating free-air temperature ranges of the various devices.

TYPICAL CHARACTERISTICS†

SHORT-CIRCUIT OUTPUT CURRENT vs INPUT VOLTAGE

Figure 9

SHORT-CIRCUIT OUTPUT CURRENT vs INPUT VOLTAGE

Figure 10

SHORT-CIRCUIT OUTPUT CURRENT vs FREE-AIR TEMPERATURE

Figure 11

SHORT-CIRCUIT OUTPUT CURRENT vs FREE-AIR TEMPERATURE

Figure 12

† Data at high and low temperatures are applicable within the rated operating free-air temperature ranges of the various devices.

TYPICAL CHARACTERISTICS

RIPPLE REJECTION vs FREQUENCY

Figure 13

SPECTRAL NOISE VOLTAGE DENSITY vs FREQUENCY

Figure 14

OUTPUT VOLTAGE RESPONSE TO OUTPUT CURRENT STEP

Figure 15

OUTPUT VOLTAGE POWER-UP RESPONSE

Figure 16

TYPICAL CHARACTERISTICS

Figure 17

MACROMODEL INFORMATION

```
*   TLE2426 OPERATIONAL AMPLIFIER “MACROMODEL” SUBCIRCUIT
*   CREATED USING PARTS RELEASE 4.03 0N 08/21/90 AT 13:51
*   REV (N/A)     SUPPLY VOLTAGE: 5 V
*   CONNECTIONS:     FILTER
                     |   INPUT
*                    |   |   COMMON
*                    |   |   |   OUTPUT
*                    |   |   |   |
.SUBCKT TLE2426      1   3   4   5
```

```
   C1     11  12  21.66E-12
   C2      6   7  30.00E-12
   C3     87   0  10.64E-9
   CPSR   85  86  15.9E-9
   DCM+   81  82  DX
   DCM-   83  81  DX
   DC      5  53  DX
   DE     54   5  DX
   DLP    90  91  DX
   DLN    92  90  DX
   DP      4   3  DX
   ECMR   84  99  (2,99) 1
   EGND   99   0  POLY(2)   (3,0) (4,0)   0   .5  .5
   EPSR   85   0  POLY(1)   (3,4)  -16.22E-6 3.24E-6
   ENSE   89   2  POLY(1)   (88,0) 120E-6 1
   FB      7  99  POLY(6)   VB  VC  VE  VLP VLN VPSR 0 74.8E6 -10E6  10E6   10E6   -10E6  74E6
   GA      6   0  11  12  320.4E-6
   GCM     0   6  10  99  1.013E-9
   GPSR   85  86  (85,86)   100E-6
   GRC1    4  11  (4,11) 3.204E-4
   GRC2    4  12  (4,12) 3.204E-4
   GRE1   13  10  (13,10)   1.038E-3
   GRE2   14  10  (14,10)   1.038E-3
   HLIM   90   0  VLIM   1K
   HCMR   80   1  POLY(2)   VCM+   VCM-   0   1E2    1E2
   IRP     3   4  146E-6
   IEE     3  10  DC 24.05E-6
   IIO     2   0  .2E-9
   I1     88   0  1E-21
   Q1     11  89  13  QX
   Q2     12  80  14  QX
   R2      6   9  100.0E3
   RCM    84  81  1K
   REE    10  99   8.316E6
   RN1    87   0   2.55E8
   RN2    87  88  11.67E3
   RO1     8   5  63
   RO2     7  99  62
   VCM+   82  99  1.0
   VCM-   83  99  -2.3
   VB      9   0  DC  0
   VC      3  53  DC  1.400
   VE     54   4  DC  1.400
   VLIM    7   8  DC  0
   VLP    91   0  DC  30
   VLN     0  92  DC  30
   VPSR    0  86  DC  0
   RFB     5   2  1K
   RIN1    3   1  220K
   RIN2    1   4  220K
.MODEL DX  D(IS=800.OE-18)
.MODEL QX  PNP(IS=800.OE-18 BF=480)
.ENDS
```

PACKAGING INFORMATION

Orderable Device	Status (1)	Package Type	Package Drawing	Pins	Package Qty	Eco Plan (2)	Lead/Ball Finish (6)	MSL Peak Temp (3)	Op Temp (°C)	Device Marking (4/5)	Samples
5962-9555602Q2A	OBSOLETE	LCCC	FK	20		TBD	Call TI	Call TI	-55 to 125		
5962-9555602QPA	OBSOLETE	CDIP	JG	8		TBD	Call TI	Call TI	-55 to 125		
TLE2426CD	ACTIVE	SOIC	D	8	75	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM		2426C	Samples
TLE2426CDG4	ACTIVE	SOIC	D	8	75	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM		2426C	Samples
TLE2426CDR	ACTIVE	SOIC	D	8	2500	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM		2426C	Samples
TLE2426CDRG4	ACTIVE	SOIC	D	8	2500	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM		2426C	Samples
TLE2426CLP	ACTIVE	TO-92	LP	3	1000	Pb-Free (RoHS)	CU SN	N / A for Pkg Type		2426C	Samples
TLE2426CLPE3	ACTIVE	TO-92	LP	3	1000	Pb-Free (RoHS)	CU SN	N / A for Pkg Type		2426C	Samples
TLE2426CLPR	ACTIVE	TO-92	LP	3	2000	Pb-Free (RoHS)	CU SN	N / A for Pkg Type		2426C	Samples
TLE2426CP	ACTIVE	PDIP	P	8	50	Pb-Free (RoHS)	CU NIPDAU	N / A for Pkg Type		TLE2426CP	Samples
TLE2426ID	ACTIVE	SOIC	D	8	75	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM		2426I	Samples
TLE2426IDG4	ACTIVE	SOIC	D	8	75	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM		2426I	Samples
TLE2426IDR	ACTIVE	SOIC	D	8	2500	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM		2426I	Samples
TLE2426IDRG4	ACTIVE	SOIC	D	8	2500	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM		2426I	Samples
TLE2426ILP	ACTIVE	TO-92	LP	3	1000	Pb-Free (RoHS)	CU SN	N / A for Pkg Type		2426I	Samples
TLE2426ILPR	ACTIVE	TO-92	LP	3	2000	Pb-Free (RoHS)	CU SN	N / A for Pkg Type		2426I	Samples
TLE2426IP	ACTIVE	PDIP	P	8	50	Pb-Free (RoHS)	CU NIPDAU	N / A for Pkg Type		TLE2426IP	Samples
TLE2426IPE4	ACTIVE	PDIP	P	8	50	Pb-Free (RoHS)	CU NIPDAU	N / A for Pkg Type		TLE2426IP	Samples

Orderable Device	Status (1)	Package Type	Package Drawing	Pins	Package Qty	Eco Plan (2)	Lead/Ball Finish (6)	MSL Peak Temp (3)	Op Temp (°C)	Device Marking (4/5)	Samples
TLE2426MD	ACTIVE	SOIC	D	8	75	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM	-55 to 125	2426M	Samples
TLE2426MDG4	ACTIVE	SOIC	D	8	75	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM	-55 to 125	2426M	Samples
TLE2426MFKB	OBSOLETE	LCCC	FK	20		TBD	Call TI	Call TI	-55 to 125		
TLE2426MJGB	OBSOLETE	CDIP	JG	8		TBD	Call TI	Call TI	-55 to 125		
TLE2426MLP	OBSOLETE	TO-92	LP	3		TBD	Call TI	Call TI	-55 to 125		
TLE2426MP	OBSOLETE	PDIP	P	8		TBD	Call TI	Call TI	-55 to 125		

(1) The marketing status values are defined as follows:
ACTIVE: Product device recommended for new designs.
LIFEBUY: TI has announced that the device will be discontinued, and a lifetime-buy period is in effect.
NRND: Not recommended for new designs. Device is in production to support existing customers, but TI does not recommend using this part in a new design.
PREVIEW: Device has been announced but is not in production. Samples may or may not be available.
OBSOLETE: TI has discontinued the production of the device.

(2) Eco Plan - The planned eco-friendly classification: Pb-Free (RoHS), Pb-Free (RoHS Exempt), or Green (RoHS & no Sb/Br) - please check http://www.ti.com/productcontent for the latest availability information and additional product content details.
TBD: The Pb-Free/Green conversion plan has not been defined.
Pb-Free (RoHS): TI's terms "Lead-Free" or "Pb-Free" mean semiconductor products that are compatible with the current RoHS requirements for all 6 substances, including the requirement that lead not exceed 0.1% by weight in homogeneous materials. Where designed to be soldered at high temperatures, TI Pb-Free products are suitable for use in specified lead-free processes.
Pb-Free (RoHS Exempt): This component has a RoHS exemption for either 1) lead-based flip-chip solder bumps used between the die and package, or 2) lead-based die adhesive used between the die and leadframe. The component is otherwise considered Pb-Free (RoHS compatible) as defined above.
Green (RoHS & no Sb/Br): TI defines "Green" to mean Pb-Free (RoHS compatible), and free of Bromine (Br) and Antimony (Sb) based flame retardants (Br or Sb do not exceed 0.1% by weight in homogeneous material)

(3) MSL, Peak Temp. - The Moisture Sensitivity Level rating according to the JEDEC industry standard classifications, and peak solder temperature.

(4) There may be additional marking, which relates to the logo, the lot trace code information, or the environmental category on the device.

(5) Multiple Device Markings will be inside parentheses. Only one Device Marking contained in parentheses and separated by a "~" will appear on a device. If a line is indented then it is a continuation of the previous line and the two combined represent the entire Device Marking for that device.

(6) Lead/Ball Finish - Orderable Devices may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead/Ball Finish values may wrap to two lines if the finish value exceeds the maximum column width.

Important Information and Disclaimer: The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

OTHER QUALIFIED VERSIONS OF TLE2426 :

- Automotive: TLE2426-Q1
- Enhanced Product: TLE2426-EP

NOTE: Qualified Version Definitions:

- Automotive - Q100 devices qualified for high-reliability automotive applications targeting zero defects
- Enhanced Product - Supports Defense, Aerospace and Medical Applications

TAPE AND REEL INFORMATION

REEL DIMENSIONS

TAPE DIMENSIONS

A0	Dimension designed to accommodate the component width
B0	Dimension designed to accommodate the component length
K0	Dimension designed to accommodate the component thickness
W	Overall width of the carrier tape
P1	Pitch between successive cavity centers

QUADRANT ASSIGNMENTS FOR PIN 1 ORIENTATION IN TAPE

*All dimensions are nominal

Device	Package Type	Package Drawing	Pins	SPQ	Reel Diameter (mm)	Reel Width W1 (mm)	A0 (mm)	B0 (mm)	K0 (mm)	P1 (mm)	W (mm)	Pin1 Quadrant
TLE2426CDR	SOIC	D	8	2500	330.0	12.4	6.4	5.2	2.1	8.0	12.0	Q1
TLE2426IDR	SOIC	D	8	2500	330.0	12.4	6.4	5.2	2.1	8.0	12.0	Q1

TAPE AND REEL BOX DIMENSIONS

*All dimensions are nominal

Device	Package Type	Package Drawing	Pins	SPQ	Length (mm)	Width (mm)	Height (mm)
TLE2426CDR	SOIC	D	8	2500	367.0	367.0	35.0
TLE2426IDR	SOIC	D	8	2500	367.0	367.0	35.0

JG (R-GDIP-T8) **CERAMIC DUAL-IN-LINE**

NOTES: A. All linear dimensions are in inches (millimeters).
B. This drawing is subject to change without notice.
C. This package can be hermetically sealed with a ceramic lid using glass frit.
D. Index point is provided on cap for terminal identification.
E. Falls within MIL STD 1835 GDIP1-T8

FK (S–CQCC–N**) LEADLESS CERAMIC CHIP CARRIER

28 TERMINAL SHOWN

NO. OF TERMINALS **	A		B	
	MIN	MAX	MIN	MAX
20	0.342 (8,69)	0.358 (9,09)	0.307 (7,80)	0.358 (9,09)
28	0.442 (11,23)	0.458 (11,63)	0.406 (10,31)	0.458 (11,63)
44	0.640 (16,26)	0.660 (16,76)	0.495 (12,58)	0.560 (14,22)
52	0.740 (18,78)	0.761 (19,32)	0.495 (12,58)	0.560 (14,22)
68	0.938 (23,83)	0.962 (24,43)	0.850 (21,6)	0.858 (21,8)
84	1.141 (28,99)	1.165 (29,59)	1.047 (26,6)	1.063 (27,0)

4040140/D 01/11

NOTES:
A. All linear dimensions are in inches (millimeters).
B. This drawing is subject to change without notice.
C. This package can be hermetically sealed with a metal lid.
D. Falls within JEDEC MS–004

P (R–PDIP–T8) PLASTIC DUAL–IN–LINE PACKAGE

NOTES:
A. All linear dimensions are in inches (millimeters).
B. This drawing is subject to change without notice.
C. Falls within JEDEC MS–001 variation BA.

D (R–PDSO–G8) PLASTIC SMALL OUTLINE

NOTES:
A. All linear dimensions are in inches (millimeters).
B. This drawing is subject to change without notice.
C. Body length does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0.006 (0,15) each side.
D. Body width does not include interlead flash. Interlead flash shall not exceed 0.017 (0,43) each side.
E. Reference JEDEC MS–012 variation AA.

LP (O–PBCY–W3) PLASTIC CYLINDRICAL PACKAGE

NOTES: A. All linear dimensions are in inches (millimeters).
B. This drawing is subject to change without notice.
C. Lead dimensions are not controlled within this area.
D. Falls within JEDEC TO–226 Variation AA (TO–226 replaces TO–92).
E. Shipping Method:
Straight lead option available in bulk pack only.
Formed lead option available in tape & reel or ammo pack.
Specific products can be offered in limited combinations of shipping mediums and lead options.
Consult product folder for more information on available options.

LP (O–PBCY–W3) PLASTIC CYLINDRICAL PACKAGE

TAPE & REEL

4040001–3/E 08/13

NOTES:
A. All linear dimensions are in inches (millimeters).
B. This drawing is subject to change without notice.
C. Tape and Reel information for the Formed Lead Option package.

IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, enhancements, improvements and other changes to its semiconductor products and services per JESD46, latest issue, and to discontinue any product or service per JESD48, latest issue. Buyers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All semiconductor products (also referred to herein as “components”) are sold subject to TI’s terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its components to the specifications applicable at the time of sale, in accordance with the warranty in TI’s terms and conditions of sale of semiconductor products. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by applicable law, testing of all parameters of each component is not necessarily performed.

TI assumes no liability for applications assistance or the design of Buyers’ products. Buyers are responsible for their products and applications using TI components. To minimize the risks associated with Buyers’ products and applications, Buyers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any patent right, copyright, mask work right, or other intellectual property right relating to any combination, machine, or process in which TI components or services are used. Information published by TI regarding third-party products or services does not constitute a license to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of significant portions of TI information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. TI is not responsible or liable for such altered documentation. Information of third parties may be subject to additional restrictions.

Resale of TI components or services with statements different from or beyond the parameters stated by TI for that component or service voids all express and any implied warranties for the associated TI component or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

Buyer acknowledges and agrees that it is solely responsible for compliance with all legal, regulatory and safety-related requirements concerning its products, and any use of TI components in its applications, notwithstanding any applications-related information or support that may be provided by TI. Buyer represents and agrees that it has all the necessary expertise to create and implement safeguards which anticipate dangerous consequences of failures, monitor failures and their consequences, lessen the likelihood of failures that might cause harm and take appropriate remedial actions. Buyer will fully indemnify TI and its representatives against any damages arising out of the use of any TI components in safety-critical applications.

In some cases, TI components may be promoted specifically to facilitate safety-related applications. With such components, TI’s goal is to help enable customers to design and create their own end-product solutions that meet applicable functional safety standards and requirements. Nonetheless, such components are subject to these terms.

No TI components are authorized for use in FDA Class III (or similar life-critical medical equipment) unless authorized officers of the parties have executed a special agreement specifically governing such use.

Only those TI components which TI has specifically designated as military grade or “enhanced plastic” are designed and intended for use in military/aerospace applications or environments. Buyer acknowledges and agrees that any military or aerospace use of TI components which have ***not*** been so designated is solely at the Buyer's risk, and that Buyer is solely responsible for compliance with all legal and regulatory requirements in connection with such use.

TI has specifically designated certain components as meeting ISO/TS16949 requirements, mainly for automotive use. In any case of use of non-designated products, TI will not be responsible for any failure to meet ISO/TS16949.

Products		**Applications**	
Audio	www.ti.com/audio	Automotive and Transportation	www.ti.com/automotive
Amplifiers	amplifier.ti.com	Communications and Telecom	www.ti.com/communications
Data Converters	dataconverter.ti.com	Computers and Peripherals	www.ti.com/computers
DLP® Products	www.dlp.com	Consumer Electronics	www.ti.com/consumer-apps
DSP	dsp.ti.com	Energy and Lighting	www.ti.com/energy
Clocks and Timers	www.ti.com/clocks	Industrial	www.ti.com/industrial
Interface	interface.ti.com	Medical	www.ti.com/medical
Logic	logic.ti.com	Security	www.ti.com/security
Power Mgmt	power.ti.com	Space, Avionics and Defense	www.ti.com/space-avionics-defense
Microcontrollers	microcontroller.ti.com	Video and Imaging	www.ti.com/video
RFID	www.ti-rfid.com		
OMAP Applications Processors	www.ti.com/omap	**TI E2E Community**	e2e.ti.com
Wireless Connectivity	www.ti.com/wirelessconnectivity		

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265
Copyright © 2014, Texas Instruments Incorporated

Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits,General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.

Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)
Факс: 8 (812) 320-02-42
Электронная почта: org@eplast1.ru
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.