



ROBUST PROCESSING POWER & FLEXIBLE LINUX COMPUTING FOR M2M EDGE APPLICATION DEPLOYMENT

The XPort[®] Pro[™] is Lantronix' most powerful, self-contained embedded networking module. Footprint compatible with the popular XPort[®] and running either Linux or Evolution OS[™] operating systems, the XPort Pro eliminates the complexity of designing network connectivity into a product and allows you to deploy advanced applications on the edge device itself.

The thumb-sized XPort Pro provides everything you need in a single embedded solution. It effortlessly handles demanding applications with the power of a high-speed, advanced architecture 32-bit processor. And with ample built-in memory, it allows virtually unlimited flexibility for customization and application enablement.

XPort Pro provides bullet-proof security by offering a variety of robust data encryption and authentication options. What's more, the option to run Linux, with IPv6 built in, enables you to deploy custom applications and take advantage of the large feature-libraries available for Linux developers. Critical agency certification has already been completed by Lantronix, reducing your test time and speeding time-to-market.



XPort[®] Pro[™] Highlights:

- Enable M2M edge computing and effortlessly handle demanding applications with the power of an advanced architecture 32-bit processor
- Run Linux or Lantronix Evolution OS for the ultimate in application development flexibility
- Production-ready hardware and software solution provides simple device set-up, configuration and monitoring, with powerful, industry-standard management tools
- Footprint compatible with the popular XPort, with everything you need in a tiny, integrated RJ45 package that is EMC/EMI/RoHS compliant

Features and Specifications

> High performance 32-bit processor

> On-board memory

- 8MB SDRAM/16MB Flash or 16MB SDRAM/16MB Flash

> Serial Interface

- Software selectable data rates from 300 to 921kbps
- Characters: 7 or 8 data bits
- Parity: Odd, Even, None
- Stop Bits: 1 or 2
- Modem Control Signals: CTS, RTS, DTR/DCD
- Flow Control: XON/XOFF (software), CTS/RTS (hardware)
- Programmable IO: 3 PIO pins (software selectable)

> Network Interface

- 10Base-T and 100Base-TX Link
- Connector: RJ45
- Protocols: TCP/IP, UDP/IP, ARP, ICMP, SNMPv2, TFTP, FTP, Telnet, DHCP, BOOTP, HTTP, SMTP, SSHv2, SSLv3, PPP, AutoIP, RSS, and SYSLOG

> Indicators (LED)

- Link & activity indicator

> Security

- SSLv3 and SSHv2 Client & Server, Selectable 128/256/512/1024 Bit certificates
- Encryption: AES, 3DES and RC4
- Authentication: SHA-1, MD5, Base-64 User Access Lists

> Software

- Windows 98/NT/2000/XP/Vista-Based DeviceInstaller™
- ComPort Redirector™
- Secure ComPort Redirector

> Management

- Internal Web Manager (SSL Option for secure login)
- CLI (over Serial Ports, Telnet or SSH)
- XML Configuration Records via CLI or FTP
- DeviceInstaller software
- Firmware: Upgradeable via FTP, Web, and Serial Port
- Flash wear leveling and erase cycle statistics

> Internal Web Server

- Customizable with CGI
- Web content on local file system and updatable through ftp

> Environmental

- Extended Temp: -40° to 85° C (-40° to 185° F)
- Commercial Temp: 0° to 70° C (32° to 158° F)
- Storage: -40° to 85° C (-40° to 185° F)

> Power

- Input voltage: 3.3 VDC
- IO Max Rating 3.3v

> Dimensions

- Length: 33.9 mm (1.33 in.)
- Width: 16.25 mm (0.64 in.)
- Height: 13.5 mm (0.53 in.)
- Weight: 9.6 g (0.34 oz)

> Regulatory Approvals

- FCC Part 15, Subpart B, Class B
– ICES-003 Issue 4 (2004), Class B
- EN55022:2006 and EN55024:1998 + A1:2001 + A2:2003
- AS/NZS CISPR22:2006
- VCCI V-3/2009.04
- EN 61000-3-2:2006, EN 61000-3-3:1995+A1:2001+A2:2005

> 2-year Limited Warranty

Ordering Information

United States

Call: 800.422.7055

Email: sales@lantronix.com

Buy Online: <http://www.lantronix.com>

NASDAQ: LTRX

Europe

Call: +31 (0) 76.52.3.6.74 4

Email: EMEA@lantronix.com

Asia/Pacific

Call: +852 3428.2338

Email: asiapacific_sales@lantronix.com

> Part Number

XPP1002000-01 R

XPP1003000-01 R

XPP1003000-02 R

XPP1003000-02 RJ

XPP100200S-01 R

XPP100300S-01 R

XPP100300S-02 R

XP10010NMK-01

XPPDK1000-EVO-02

XPPDK1000-LNX-02

> Accessories

930-060-R

> Description

XPort Pro XE (Min. Quantity: 50 units)

XPort Pro RoHS Extended Temperature w/ encryption w/ Evolution OS w/ 8MB SDRAM
XPort Pro RoHS Extended Temperature w/ encryption w/ Linux OS w/ 8MB SDRAM
XPort Pro RoHS Extended Temperature w/ encryption w/ Linux OS w/ 16MB SDRAM
XPort Pro RoHS Extended Temperature w/ encryption w/ Linux OS w/ 16MB SDRAM (Japan only)

XPort Pro SE

XPort Pro RoHS Extended Temperature w/ encryption w/ Evolution OS w/ 8MB SDRAM-Sample
XPort Pro RoHS Extended Temperature w/ encryption w/ Linux OS w/ 8MB SDRAM-Sample
XPort Pro RoHS Extended Temperature w/ encryption w/ Linux OS w/ 16MB SDRAM-Sample

Development Kit & Evaluation Board

Universal Demo Board*
XPort Pro Evolution Development Kit**
XPort Pro Linux Development Kit**

> Description

USB BDM Debug Probe**

* XPort Pro module sold separately

** Debug probe sold separately for development kits PXC2102G2-01



EVOLUTION OS



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.