SMD Power Inductor
0420CDMCC/DS

RoHS

Halogen Free



Dimension - [mm]



Land pattern and Schematics - [mm]



Description
- Metal compound molding type construction.
- Magnetically shielded.
- Low audible core noise.
- Suitable for large current.
- L × W × H: 4.75 × 4.45 × 2.0mm Max.
- Product weight:0.18g (Ref.)
- Moisture Sensitivity Level: 1
- RoHS compliance.
- Halogen Free available.

Environmental Data
- Operating temperature range: -55℃～+125℃ (including coil's self temperature rise)
- Storage temperature range: -55℃～+125℃
- Solder reflow temperature: 260 ℃ peak.

Packaging
- Carrier tape and reel packaging.
- 3000pcs/Reel.

Applications
- Ideally used in notebook, ultrabook, tablet PC, LCD display, Server application.
- HDD,SSD modules application.
- High current, POL converters.
- Low profile, high current power supplies.
- Battery powered devices.
- DC/DC converters in distributed power systems.

Revised: 20-Nov-15

Electrical Characteristics

Part No.	Stamp	Inductance [Within] (μH) ※1	D.C.R (mΩ) Max.(Typ.) at 25℃	Saturation Current (A) Max.(Typ.) (at 25℃) ※2	Temperature rise current (A) (Typ.) ※3
0420CDMCCDS-R10MC	R10	0.10±20%	4.0(3.5)	19(22)	17.0
0420CDMCCDS-R22MC	R22	0.22±20%	6.6(6.0)	15(18)	12.0
0420CDMCCDS-R33MC	R33	0.33±20%	10.5(9.0)	10(12)	10.5
0420CDMCCDS-R47MC	R47	0.47±20%	14(12.5)	9.5(11)	9.0
0420CDMCCDS-R56MC	R56	0.56±20%	16(14)	10(12)	8.1
0420CDMCCDS-R68MC	R68	0.68±20%	18(16)	8.2(9.6)	8.0
0420CDMCCDS-1R0MC	1R0	1.0±20%	27(24)	7.0(8.0)	6.5
0420CDMCCDS-1R2MC	1R2	1.2±20%	27(24)	7.0(8.0)	6.5
0420CDMCCDS-1R5MC	1R5	1.5±20%	46(38)	5.7(6.7)	4.9
0420CDMCCDS-2R2MC	2R2	2.2±20%	58(52)	5.4(6.3)	4.3
0420CDMCCDS-3R3MC	3R3	3.3±20%	87(74)	4.0(4.7)	3.5
0420CDMCCDS-4R7MC	4R7	4.7±20%	105(92)	2.5(3.0)	2.7
0420CDMCCDS-6R8MC	6R8	6.8±20%	175(160)	2.3(2.7)	2.1
0420CDMCCDS-100MC	100	10±20%	282(256)	2.1(2.5)	1.5
0420CDMCCDS-150MC	150	15±20%	352(320)	1.6(1.9)	1.4
0420CDMCCDS-220MC	220	22±20%	363(330)	1.4(1.7)	1.2

※1 Measuring frequency Inductance at 100kHz ,1.0V
※2 Saturation current: The value of DC current when the inductance is over 70% of its initial value. (at 25℃)
※3 Temperature rise current: The actual value of DC current when temperature of coil rise is △T=40℃(Ta=25℃) Board conditions: FR4, Copper=70μm,four-layer PWB, t=1.6mm.

Saturation Current & Temperature Rise Graph

L (20℃) △T

1. 0420CDMCCDS-R10MC



2. 0420CDMCCDS-R22MC



3. 0420CDMCCDS-R33MC



4. 0420CDMCCDS-R47MC



5. 0420CDMCCDS-R56MC



6. 0420CDMCCDS-R68MC



7. 0420CDMCCDS-1R0MC



8. 0420CDMCCDS-1R2MC



9. 0420CDMCCDS-1R5MC



10. 0420CDMCCDS-2R2MC



11. 0420CDMCCDS-3R3MC



12. 0420CDMCCDS-4R7MC



Saturation Current & Temperature Rise Graph

L (20℃) △T

13. 0420CDMCCDS-6R8MC



14. 0420CDMCCDS-100MC



15. 0420CDMCCDS-150MC



16. 0420CDMCCDS-220MC



Solder Reflow Condition





Please refer to the sales offices on our website - http://www.sumida.com

Hong Kong
Tel.+852-2880-6781
FAX.+852-2565-9600
sales@hk.sumida.com

Shanghai
Tel.+86-21-5836-3299
FAX.+86-21-5836-3266
shanghai.sales@cn.sumida.com

Shenzhen
Tel.+86-755-8291-0228
FAX.+86-755-8291-0338
shenzhen.sales@cn.sumida.com

Taipei
Tel.+886-2-8751-2737
FAX.+886-2-8751-2738
sales@tw.sumida.com

Saitama(Japan)
Tel.+81-48-691-7300
FAX.+81-48-691-7340
sales@jp.sumida.com

Seoul
Tel.+82-2-6237-0777
FAX.+82-2-6237-0778
sales@kr.sumida.com

Singapore
Tel.+65-6296-3388
FAX.+65-6841-4426
sales@sg.sumida.com

San Jose
Tel.+1-408-321-9660
FAX.+1-408-321-9308
sales@us.sumida.com

Chicago
Tel.+1-847-545-6700
FAX. +1-847-545-6720
sales@us.sumida.com

Obernzell
Tel.+49-8591-937-0
FAX. +49-8591-937-103
contact@eu.sumida.com

Neumarkt
Tel.+49-9181-4509-110
FAX. +49-9181-4509-310
infocomp@eu.sumida.com

Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits,General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)
Факс: 8 (812) 320-02-42
Электронная почта: org@eplast1.ru
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.