

Description

Magnecraft General Purpose Relays

792 Control Series

DPDT 12 A; 4PDT 6 A and 3 A



UL listed when used with proper Magnecraft sockets



792 Clear Cover



792 Full-Feature Cover

Description

The 792 Plug-in Control relays offer clear or full-feature covers with multiple mounting options and accessories; 4PDT models save valuable space while adding increased functionality.

| Feature | Benefit |
|-------------------------------------|--|
| 12 A / 6 A / 3 A switching current | Ideal for various automation panels and controls |
| Clear or full-feature cover options | Full-feature covers include LED indicator and locking test button to facilitate maintenance and expedite commissioning |
| DPDT and 4PDT contact options | Simultaneously control 2 or 4 separate circuits |
| Socket mount option | Simplifies installation and maintenance while also allowing the use of protection modules, hold-down clips and other accessories |
| Gold-flashed contacts | Reduces contact oxidation and increases shelf life |
| Mechanical flag indicator | Standard feature that displays relay status during testing or operation without having to power the relay |

| Contact Rating | Contact Configuration | Nominal Coil Voltage | Coil Resistance (Ω) | Contacts | Part Number: Clear Cover | Part Number: Clear Cover with LED | Part Number: Full-Feature Cover |
|----------------|-----------------------|----------------------|---------------------|----------------------|--------------------------|-----------------------------------|---------------------------------|
| 3 A | 4PDT | 12 Vac | 44 | Low Level Bifurcated | 792XDX3C-12A | 792XDX3CL-12A | 792XDX3M4L-12A |
| | | 24 Vac | 177 | | 792XDX3C-24A | 792XDX3CL-24A | 792XDX3M4L-24A |
| | | 48 Vac | 708 | | 792XDX3C-48A | 792XDX3CL-48A | 792XDX3M4L-48A |
| | | 120 Vac | 3630 | | 792XDX3C-120A | 792XDX3CL-120A | 792XDX3M4L-120A |
| | | 240 Vac | 17720 | | 792XDX3C-240A | 792XDX3CL-240A | 792XDX3M4L-240A |
| | | 12 Vdc | 160 | | 792XDX3C-12D | 792XDX3CL-12D | 792XDX3M4L-12D |
| | | 24 Vdc | 640 | | 792XDX3C-24D | 792XDX3CL-24D | 792XDX3M4L-24D |
| | | 48 Vdc | 2560 | | 792XDX3C-48D | 792XDX3CL-48D | 792XDX3M4L-48D |
| | | 110 Vdc | 13440 | | 792XDX3C-110D | 792XDX3CL-110D | 792XDX3M4L-110D |
| | | 12 A | DPDT | | 12 Vac | 44 | Standard |
| 24 Vac | 177 | | | 792XBXC-24A | - | 792XBXM4L-24A | |
| 48 Vac | 708 | | | 792XBXC-48A | - | 792XBXM4L-48A | |
| 120 Vac | 3630 | | | 792XBXC-120A | - | 792XBXM4L-120A | |
| 240 Vac | 17720 | | | 792XBXC-240A | - | 792XBXM4L-240A | |
| 12 Vdc | 160 | | | 792XBXC-12D | - | 792XBXM4L-12D | |
| 24 Vdc | 640 | | | 792XBXC-24D | - | 792XBXM4L-24D | |
| 48 Vdc | 2560 | | | 792XBXC-48D | - | 792XBXM4L-48D | |
| 110 Vdc | 13440 | | | 792XBXC-110D | - | 792XBXM4L-110D | |
| 6 A | 4PDT | | | 12 Vac | 44 | Standard | |
| | | 24 Vac | 177 | 792XDXC-24A | 792XDXCCL-24A | | 792DXM4L-24A |
| | | 48 Vac | 708 | 792XDXC-48A | 792XDXCCL-48A | | 792DXM4L-48A |
| | | 120 Vac | 3630 | 792XDXC-120A | 792XDXCCL-120A | | 792DXM4L-120A |
| | | 240 Vac | 17720 | 792XDXC-240A | 792XDXCCL-240A | | 792DXM4L-240A |
| | | 12 Vdc | 160 | 792XDXC-12D | 792XDXCCL-12D | | 792DXM4L-12D |
| | | 24 Vdc | 640 | 792XDXC-24D | 792XDXCCL-24D | | 792DXM4L-24D |
| | | 48 Vdc | 2560 | 792XDXC-48D | 792XDXCCL-48D | | 792DXM4L-48D |
| | | 110 Vdc | 13440 | 792XDXC-110D | 792XDXCCL-110D | | 792DXM4L-110D |

Part Number Explanation



Specifications

| Part Number | 792XBX |
|--|---|
| Contact Characteristics | |
| Terminal Style | Blade |
| Contact Material | Silver Alloy |
| Contact Configuration | DPDT |
| Maximum Switching Current | 12 A |
| Maximum Switching Voltage | IEC: 250 Vac / 28 Vdc UL/CSA: 300 Vac / 30 Vdc |
| Rated Operational Current (Conforming to IEC AC-1 and DC-1) | NO: 12 A at 250 Vac, NC: 6 A at 250 Vac NO: 12 A at 28 Vdc, NC: 6 A at 28 Vdc |
| Rated Operational Current (Conforming to UL) | Resistive: 12 A at 277 Vac, 100k cycles Resistive: 12 A at 120 Vac, 200k cycles Resistive: 12 A at 30 Vdc, 100k cycles Motor: 1/2 HP at 120 Vac, 6k cycles Motor: 1 HP at 277 Vac, 6k cycles B300 PILOT DUTY, 6k cycles |
| Minimum Switching Requirement | 10 mA at 17 Vdc |
| Coil Characteristics | |
| Maximum Operating Voltage | 110% (AC / DC) |
| Maximum Pickup Voltage | 80% (AC); 80% (DC) |
| Drop-out Voltage Threshold | 15% (AC); 10% (DC) |
| Average Consumption | 0.9–1.2 VA (AC); 0.8–1.1 W (DC) |
| General Characteristics | |
| Electrical Life at Rated Load | 200,000 operations (where stated) |
| Mechanical Life (Unpowered) | 10,000,000 operations |
| Operating Time | 25 ms max. at 80% rated coil voltage 20 ms max. at 100% rated coil voltage |
| Release time | 20 ms max. (DC) 35 ms max. (AC) |
| Impulse Withstand Voltage | 4 kV (1.2 / 50 μs) |
| Dielectric Strength - Between Coil and Contact (AC) | 2000 V(rms) |
| Dielectric Strength - Between Poles (AC) | 2000 V(rms) |
| Dielectric Strength - Between Contacts (AC) | 1300 V(rms) |
| Ambient Air Temperature around the Device - Storage | -40 to +85 °C (-40 to +185 °F) |
| Ambient Air Temperature around the Device - Operation | -40 to +55 °C (-40 to +131 °F) |
| Vibration Resistance - In Operation | 3 g-n at 35–150 Hz |
| Vibration Resistance - Not Operating | 5 g-n at 35–150 Hz |
| Shock Resistance - In Operation | 10 g-n |
| Shock Resistance - Not Operating | 30 g-n |
| Degree of Protection (Housing Only) | IP 40 |
| Weight | 37 g (1.31 oz) |
| Agency Approvals | UL with socket, UR (E164862), CE, CSA (225619), RoHS |

Note: Actual product performance may vary depending on application and environmental conditions.

Specifications (continued)

| Part Number | 792XDX | 792XDX3 |
|--|--|--|
| Contact Characteristics | | |
| Terminal Style | Blade | Blade |
| Contact Material | Silver Alloy | Bifurcated |
| Contact Configuration | 4PDT | 4PDT |
| Maximum Switching Current | 6 A | 3 A |
| Load Type | Standard | Low Level |
| Maximum Switching Voltage | 300 V | 300 V |
| Rated Operational Current (Conforming to IEC AC1 and DC1) | NO: 6 A at 250 Vac, NC: 3 A at 250 Vac NO: 6 A at 28 Vdc, NC: 3 A at 28 Vdc | NO: 2 A at 250 Vac, NC: 1 A at 250 Vac NO: 2 A at 28 Vdc, NC: 1 A at 28 Vdc |
| Operational Current (Conforming to UL) | Resistive: 6 A at 277 Vac, 200k cycles Resistive: 8 A at 120 Vac, 200k cycles Resistive: 8 A at 30 Vdc, 200k cycles Motor: 1/3 HP at 120 Vac, 6k cycles Motor: 1/2 HP at 277 Vac, 6k cycles Pilot Duty: B300, 6k cycles | General Purpose: 3 A at 240–277 Vac General Purpose: 3 A at 120 Vac Resistive: 3 A at 30 Vdc Motor: 1/16 HP (2.8 A FLA) at 120 Vac Pilot Duty: 5 A make, 0.5 A break, 3 A continuous at 120 Vac |
| Minimum Switching Requirement | 10 mA at 17 Vdc | 3 mA at 5 Vdc |
| Coil Characteristics | | |
| Maximum Operating Voltage | 110% (AC / DC) | 110% (AC / DC) |
| Maximum Pickup Voltage | 80% (AC); 80% (DC) | 80% (AC); 80% (DC) |
| Drop-out Voltage Threshold | 15% (AC); 10% (DC) | 15% (AC); 10% (DC) |
| Average Consumption | 0.9–1.2 VA (AC); 0.8–1.1 W (DC) | 0.9–1.2 VA (AC); 0.8–1.1 W (DC) |
| General Characteristics | | |
| Electrical Life at Rated Load | 200,000 operations (where stated) | 100,000 (gen. purpose load) operations |
| Mechanical Life (Unpowered) | 10,000,000 operations | 10,000,000 operations |
| Operating Time | 25 ms max. at 80% rated coil voltage 20 ms max. at 100% rated coil voltage | 25 ms max. at 80% rated coil voltage 20 ms max. at 100% rated coil voltage |
| Release time | 20 ms max. (DC) 35 ms max. (AC) | 20 ms max. (DC) 35 ms max. (AC) |
| Impulse Withstand Voltage | 2.5 kV (1.2 / 50 μs) | 2.5 kV (1.2 / 50 μs) |
| Dielectric Strength - Between Coil and Contact (AC) | 2000 V(rms) | 2000 V(rms) |
| Dielectric Strength - Between Poles (AC) | 1600 V(rms) | 1600 V(rms) |
| Dielectric Strength - Between Contacts (AC) | 1300 V(rms) | 1300 V(rms) |
| Ambient Air Temperature around the Device - Storage | -40 to +85 °C (-40 to +185 °F) | -40 to +85 °C (-40 to +185 °F) |
| Ambient Air Temperature around the Device - Operation | -40 to +55 °C (-40 to +131 °F) | -40 to +55 °C (-40 to +131 °F) |
| Vibration Resistance - In Operation | 3 g-n at 35–150 Hz | 3 g-n at 35–150 Hz |
| Vibration Resistance - Not Operating | 5 g-n at 35–150 Hz | 5 g-n at 35–150 Hz |
| Shock Resistance - In Operation | 10 g-n | 10 g-n |
| Shock Resistance - Not Operating | 30 g-n | 30 g-n |
| Degree of Protection (Housing Only) | IP 40 | IP 40 |
| Weight | 37 g (1.31 oz) | 37 g (1.31 oz) |
| Agency Approvals | UL with socket, UR (E164862), CE, CSA (225619), RoHS | |

Note: Actual product performance may vary depending on application and environmental conditions.

Dimensions — inches (millimeters)

Clear Cover Dimension




Full-Feature Cover Dimension




Wiring Diagrams

DPDT




NEMA
IEC

4PDT



NEMA
IEC



Description

Optional sockets offer customizable, Fingersafe™ solutions including protection modules, hold-down clips, and ID tags. Sockets are DIN rail and panel mount compatible.

Relay Accessories



| Description | Function | For Use With Relays | Pkg. Min. | Standard Part Number |
|-------------|--|---------------------|-----------|----------------------|
| Socket 1 | DIN/Panel mount with elevator terminals | 792XBX | 10 | 70-782EL8-1 |
| Socket 2 | DIN/Panel mount with screw terminals and clamping plates | 792XBX / 792XDX | 10 | 70-782D14-1 |
| Socket 3 | DIN/Panel mount with rising elevator box terminals | 792XBX / 792XDX | 10 | 70-782E14-1 |
| Socket 4 | DIN/Panel mount with elevator terminals | 792XBX / 792XDX | 10 | 70-782EL14-1 |
| Socket 5 | DIN/Panel mount with screw terminals and clamping plates | 792XDX | 10 | 70-461-1 |
| Socket 6 | Solder terminals for chassis mount | 792XDX | 10 | 70-378-1 |
| Socket 7 | Printed circuit terminals for PCB mount | 792XDX | 10 | 70-379-1 |
| Adapter 8 | Mount directly to DIN rail | 792XBX / 792XDX | 10 | 16-782C |
| Adapter 9 | Mount directly to panel | 792XBX / 792XDX | 10 | 16-782C1 |

Socket Accessories



| Description | Function | For Use With Sockets | Coil Voltage | Pkg. Min. | Standard Part Number |
|--|--|---|--------------|-----------|----------------------|
| Metal Spring Clip 1 | Secures relay in socket | 70-782D14-1, 70-782E14-1, 70-782EL14-1, 70-782EL8-1 | – | 10 | 16-782SC |
| Plastic Hold-Down Clip 2 | Secures relay in socket or ejects relay off socket | | – | 10 | 16-782PC-1 |
| Write-on tag 3 | Small Write-on tag | – | – | 10 | 16-782FT-1 |
| Write-on tag 4 | Write-on tag for 16-782PC-1 Hold-down Clip | – | – | 10 | 16-700ST-1 |
| Extruded Aluminum DIN Rail, 39.37" (1000 mm) 5 | Quick installation and removal of sockets | 70-782D14-1, 70-782E14-1, 70-782EL8-1, 70-782EL14-1 | – | 10 | 16-700DIN |
| DIN Rail End Clip 5 | Holds sockets firmly in place on DIN rail | – | – | 10 | 16-DCLIP-1 |
| Insulated Coil Bus Jumper System 6 | Wireless socket connection | 70-782EL8-1, 70-782EL14-1 | – | 10 | 16-782CBJ-1 |
| Small Socket Module | Protection Diode (Protects external drive circuitry from inductive voltages) | 70-782D14-1, 70-782E14-1, 70-782EL14-1, 70-782EL8-1 | 6 to 250 Vdc | 10 | 70-BSMD-250 |
| Small Socket Module 7 | LED Indicator (Provides coil status at a glance) | | 24 Vac/Vdc | 10 | 70-BSMLG-24 |
| Small Socket Module | MOV Suppressor (Protects from damaging electrical spikes) | | 120 Vac/Vdc | 10 | 70-BSMM-120 |
| | | | 24 Vac/Vdc | 10 | 70-BSMM-24 |
| | | | 240 Vac/Vdc | 10 | 70-BSMM-240 |

Note: Use of LED socket module may increase coil power draw by up to 10%.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.