

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: [0010101051](#)
Status: **Active**
Overview: [kk](#)
Description: 5.08mm (.200") Pitch KK® PC Board Connector, Right Angle Mount Style A, 1.0µm (40µ") Tin (Sn), 5 Circuits

Documents:
[3D Model](#) [Product Specification PS-99020-0087 \(PDF\)](#)
[Drawing \(PDF\)](#) [RoHS Certificate of Compliance \(PDF\)](#)

Agency Certification

CSA LR19980
UL E29179

General

Product Family PCB Receptacles
Series [3002](#)
Application Board-to-Board
Overview [kk](#)
Product Name KK®

Physical

Circuits (Loaded) 5
Color - Resin Natural
Durability (mating cycles max) 25
Flammability 94V-2
Glow-Wire Compliant No
Material - Metal Phosphor Bronze
Material - Plating Mating Tin
Material - Plating Termination Tin
Material - Resin Nylon
Number of Rows 1
Orientation Right Angle
PC Tail Length (in) 0.169 In
PC Tail Length (mm) 4.30 mm
PCB Locator No
PCB Retention Yes
PCB Thickness Recommended (in) 0.062 In
PCB Thickness Recommended (mm) 1.60 mm
Packaging Type Tray
Pitch - Mating Interface (in) 0.200 In
Pitch - Mating Interface (mm) 5.08 mm
Plating min: Mating (µin) 40.00
Plating min: Mating (µm) 1.000
Plating min: Termination (µin) 40.00
Plating min: Termination (µm) 1.00
Polarized to PCB Yes
Temperature Range - Operating 0°C to +75°C
Termination Interface: Style Through Hole

Electrical

Current - Maximum per Contact 7A
Voltage - Maximum 250V

Solder Process Data

Lead-free Process Capability Wave Capable (TH only)




image - Reference only

EU RoHS

**ELV and RoHS
Compliant**

REACH SVHC

Not Reviewed

Halogen-Free

Status

Halogen-Free

China RoHS



**Need more information on product
environmental compliance?**

Email productcompliance@molex.com
For a multiple part number RoHS Certificate of
Compliance, [click here](#)

Please visit the [Contact Us](#) section for any
non-product compliance questions.

Search Parts in this Series

[3002Series](#)

Mates With

[3003](#) , [2599](#) , [3008](#)

Material Info

Old Part Number300205A


Reference - Drawing Numbers

Product SpecificationPS-99020-0087
Sales DrawingSDAE-3002-NA-*

This document was generated on 05/21/2010

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

CCT	PART No.	ENG No.	DIM A	DIM B
2	10-10-1021	AE-3002-2A	(5.08 ± 0.10) .200 ± .004	(10.16 ± 0.2) .400 ± .008
3	↑ - 1031	↑ - 3A	(10.16 ± 0.10) .400 ± .004	(15.24 ± 0.2) .600 ± .008
4	- 1041	- 4A	(15.24 ± 0.10) .600 ± .004	(20.32 ± 0.2) .800 ± .008
5	- 1051	- 5A	(20.32 ± 0.10) .800 ± .004	(25.40 ± 0.2) 1.000 ± .008
6	- 1061	- 6A	(25.40 ± 0.10) 1.000 ± .004	(30.48 ± 0.2) 1.200 ± .008
7	- 1071	- 7A	(30.48 ± 0.20) 1.200 ± .008	(35.56 ± 0.2) 1.400 ± .008
8	- 1081	- 8A	(35.56 ± 0.20) 1.400 ± .008	(40.64 ± 0.2) 1.600 ± .008
9	- 1091	- 9A	(40.64 ± 0.20) 1.600 ± .008	(45.72 ± 0.2) 1.800 ± .008
10	- 1101	- 10A	(45.72 ± 0.20) 1.800 ± .008	(50.80 ± 0.2) 2.000 ± .008
11	- 1111	- 11A	(50.80 ± 0.20) 2.000 ± .008	(55.88 ± 0.2) 2.200 ± .008
12	- 1121	- 12A	(55.88 ± 0.25) 2.200 ± .010	(60.96 ± 0.30) 2.400 ± .012
13	- 1131	- 13A	(60.96 ± 0.25) 2.400 ± .010	(66.04 ± 0.30) 2.600 ± .012
14	- 1141	- 14A	(66.04 ± 0.25) 2.600 ± .010	(71.12 ± 0.30) 2.800 ± .012
15	- 1151	- 15A	(71.12 ± 0.25) 2.800 ± .010	(76.20 ± 0.30) 3.000 ± .012
16	- 1161	- 16A	(76.20 ± 0.25) 3.000 ± .010	(81.28 ± 0.40) 3.200 ± .016
17	- 1171	- 17A	(81.28 ± 0.30) 3.200 ± .012	(86.36 ± 0.40) 3.400 ± .012
18	- 1181	- 18A	(86.36 ± 0.30) 3.400 ± .012	(91.44 ± 0.40) 3.600 ± .016
19	↓ - 1191	↓ - 19A	(91.44 ± 0.30) 3.600 ± .012	(96.52 ± 0.40) 3.800 ± .012
20	10-10-1201	AE-3002-20A	(96.52 ± 0.30) 3.800 ± .012	(101.60 ± 0.40) 4.000 ± .016



NOTES

1. HOUSING: NYLON, 94V-2, NATURAL
2. HOUSING SUITABLE FOR (1.14 ± 0.15) / .045 ± .006 RD. OR SQ. PINS
3. TERMINAL: PHOS. BR, HOT TIN DIP. (1-2.5UM) / .0000040 - .000100 IN.
4. HOOKS AVAILABLE ON ENDS ONLY

ENG NO. CORRECTION EC NO: E2006-0204 DRWN: DENNEHY 2005/09/09 CHKD: GMSWEENEY 2005/09/09 APPR: DENNEHY 2005/09/22	DESCRIPTION	QUALITY SYMBOLS ▽=0 ▽=0	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM ONLY		SCALE 4:1	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION			
				mm	INCH	DRAWN BY GCH	DATE 1995/06/15	TITLE KONEKTCON AND P.C. TAIL TERMINAL ASSEMBLY (5.08) / .200 PITCH				
			4 PLACES	± ---	± ---	CHECKED BY	DATE					
			3 PLACES	± ---	± ---	GMSWEENEY	2005/08/31					
			2 PLACES	± ---	± ---	APPROVED BY	DATE	MOLEX MOLEX INCORPORATED				
1 PLACE	± ---	± ---	JDENNEHY	2005/08/31								
			ANGULAR ± ---°		MATERIAL NO.		DOCUMENT NO.			SHEET NO.		
			DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		SEE CHART		SDAE-3002-NA-*			1 OF 2		
					SIZE A3		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION					



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.