

# 3M™ CP2 Press-Fit Header

2 mm Type A 110 Signal Contacts

CP2 Series



- 25 mm basic system unit
- 50 mm module
- 2 mm grid spacing allows for high signal density at low cost
- “Eye of the Needle” compliant pin press-fit design reduces manufacturing time and cost
- Three contact mating levels for Early Mate Late Break or “Hot Swap” applications reduces manufacturing time and cost
- Feed through termination available for midplane applications
- Additional grounding rows available for improved ground bounce and EMI immunity
- Mates with 5 row 3M™ HSHM, UHM and CP2 Sockets
- End to end stackable with 5 row 3M™ HSHM, HM, and CP2 Headers
- See the Regulatory Information Appendix (RIA) in the “RoHS compliance” section of [www.3Mconnectors.com](http://www.3Mconnectors.com) for compliance information (RIA E1 & C1 apply)

Date Modified: August 5, 2015

TS-2265-C  
Sheet 1 of 5

---

## Physical

### Insulation:

Material: Glass Filled Polyester (PBT)

Flammability: UL94V-0

### Contact:

Material: Copper Alloy

Plating: See Ordering Information

---

## Mechanical

Mating Force:  $\leq 0.75\text{N/PIN}$

Withdrawl Force:  $\geq 0.15\text{N/PIN}$

Mating and Un-mating Operations: 200 for KR plating

---

## Electrical

Current Rating: 1.0 Amperes at 70°C with all contacts powered

Contact Resistance:  $\leq 20\text{ m}\Omega$

Insulation Resistance:  $\geq 10,000\text{ M}\Omega$

Test Voltage: 750 VAC<sub>RMS</sub>

---

## Environmental

Temperature Ratings: -55°C to +125°C

---

## PCB Data

Recommended PCB Plated Through Hole:  $\text{Ø } 0.6 \pm 0.05\text{ mm}$

Drill Hole Diameter:  $\text{Ø } 0.7 \pm 0.02\text{ mm}$

Hole platings: Cu 25~50  $\mu\text{m}$ , Sn < 10  $\mu\text{m}$

PCB thickness: 2.4 - 5.6 mm for 3.7 mm tails, 1.4 - 5.6 mm for 2.3 mm tails

Press-In Force:  $\leq 204\text{N/pin}$  on nominal hole diameter

Retention Force:  $\geq 13.5\text{N/pin}$  on nominal hole diameter

---

**3M**

Electronics Materials Solutions Division

Interconnect Solutions

<http://www.3Mconnectors.com>


3M is a trademark of 3M Company.  
For technical, sales or ordering information call

**800-225-5373**

# 3M™ CP2 Press-Fit Header

2 mm Type A 110 Signal Contacts

CP2 Series



Recommended PCB Layout

## Ordering Information

### CP2-HA110-XXX-XXXX

#### Loading Configurations

(See diagrams on following pages)

#### Grounding Options:

- G= with ground pins
- Blank= without ground pins
- EMLB Patterns

#### Primary Tail Length

- 1= 3.7 mm
- 2= 2.3 mm
- 4= 15.8 mm

#### Plating Options

- FJ= 10~20 μ" Gold Contact Area  
100~200 μ" Matte Tin  
50~80 μ" Nickel Underplate  
(RIA E1 & C1 apply)
- KR= 30~40 μ" Gold Contact Area  
100~200 μ" Matte Tin  
50~80 μ" Nickel Underplate  
(RIA E1 & C1 apply)
- KV= 30~40 μ" Mate End Gold Contact area  
Gold Flash Tail Contact area  
50~80 μ" Nickel Underplate  
(RIA E1 & C1 apply)  
For Primary Tail Length Option 4 only

- This diagram serves only for Part Number descriptive definitions.
- For standard product configuration please see following pages.

PLEASE CONTACT YOUR LOCAL SALES REPRESENTATIVE FOR CUSTOMER SPECIFIC PRODUCT CONFIGURATIONS.

TS-2265-C  
Sheet 2 of 5

# 3M™ CP2 Press-Fit Header

2 mm Type A 110 Signal Contacts

CP2 Series

CP2-HA110-E1-TG30											Connector Type A22																			
F																														
E	A	A	A	A	A	A	A	A	A	A	A																			
D	A	A	A	A	A	A	A	A	A	A	A																			
C	A	A	A	A	A	A	A	A	A	A	A																			
B	A	A	A	A	A	A	A	A	A	A	A																			
A	A	A	A	A	A	A	A	A	A	A	A																			
Z																														
	1	2	3	4	5	6	7	8	9	10	11																			

CP2-HA110-GE1-TG30											Connector Type A22																			
F	C	C	C	C	C	C	C	C	C	C	C																			
E	A	A	A	A	A	A	A	A	A	A	A																			
D	A	A	A	A	A	A	A	A	A	A	A																			
C	A	A	A	A	A	A	A	A	A	A	A																			
B	A	A	A	A	A	A	A	A	A	A	A																			
A	A	A	A	A	A	A	A	A	A	A	A																			
Z	C	C	C	C	C	C	C	C	C	C	C																			
	1	2	3	4	5	6	7	8	9	10	11																			

CP2-HA110-A1-TG30											Connector Type A22																		
F																													
E	B	B	B	B	B	B	B	B	B	B	B																		
D	B	B	B	B	B	B	B	B	B	B	B																		
C	B	B	B	B	B	B	B	B	B	B	B																		
B	B	B	B	B	B	B	B	B	B	B	B																		
A	B	B	B	B	B	B	B	B	B	B	B																		
Z																													
	1	2	3	4	5	6	7	8	9	10	11																		

CP2-HA110-GA1-TG30											Connector Type A22																		
F	C	C	C	C	C	C	C	C	C	C	C																		
E	B	B	B	B	B	B	B	B	B	B	B																		
D	B	B	B	B	B	B	B	B	B	B	B																		
C	B	B	B	B	B	B	B	B	B	B	B																		
B	B	B	B	B	B	B	B	B	B	B	B																		
A	B	B	B	B	B	B	B	B	B	B	B																		
Z	C	C	C	C	C	C	C	C	C	C	C																		
	1	2	3	4	5	6	7	8	9	10	11																		

# 3M™ CP2 Press-Fit Header

2 mm Type A 110 Signal Contacts

CP2 Series

CP2-HA110-D1-TG30											Connector Type A22																
F																											
E	A	A	A	A	A	A	A	A	A	A							A	A	A	A	A	A	A	A	A		
D	B	B	A	A	A	A	A	A	A	A							A	A	A	A	A	A	A	A	B	B	
C	C	C	A	A	A	A	A	A	A	A							A	A	A	A	A	A	A	A	C	C	
B	B	B	A	A	A	A	A	A	A	A							A	A	A	A	A	A	A	A	B	B	
A	A	A	A	A	A	A	A	A	A	A							A	A	A	A	A	A	A	A	A	A	
Z																											
	1	2	3	4	5	6	7	8	9	10	11						15	16	17	18	19	20	21	22	23	24	25

CP2-HA110-GB1-TG30											Connector Type A22																
F	C	C	C	C	C	C	C	C	C	C							C	C	C	C	C	C	C	C	C	C	
E	B	B	B	B	B	B	B	B	B	B							B	B	B	B	B	B	B	B	B	B	B
D	B	B	B	B	B	B	B	B	B	B	A						B	B	B	B	B	B	B	B	B	B	B
C	B	B	B	B	B	B	B	B	B	C	B						B	B	B	B	B	B	B	B	B	B	B
B	B	B	B	B	B	B	B	B	B	B	B						B	B	B	B	B	B	B	B	B	B	B
A	B	B	B	B	B	B	B	B	B	B	B						B	B	B	B	B	B	B	B	B	B	B
Z	C	C	C	C	C	C	C	C	C	C							C	C	C	C	C	C	C	C	C	C	C
	1	2	3	4	5	6	7	8	9	10	11						15	16	17	18	19	20	21	22	23	24	25

CP2-HA110-GC1-TG30											Connector Type A22																
F	C	C	C	C	C	C	C	C	C	C							C	C	C	C	C	C	C	C	C	C	
E	B	B	B	B	B	B	B	B	B	B							B	B	B	B	B	B	B	B	B	B	B
D	B	B	C	B	B	B	C	B	C	B	A						C	B	C	B	C	B	C	B	C	B	B
C	B	C	B	C	B	B	B	B	B	B	B						B	B	B	B	B	C	B	C	B	B	B
B	B	B	B	B	B	B	B	B	B	B	B						B	B	A	B	B	B	B	B	B	B	B
A	B	B	B	B	B	B	B	B	B	B	B						B	B	B	B	B	B	B	B	B	B	B
Z	C	C	C	C	C	C	C	C	C	C							C	C	C	C	C	C	C	C	C	C	C
	1	2	3	4	5	6	7	8	9	10	11						15	16	17	18	19	20	21	22	23	24	25

CP2-HA110-GA4-GG30											Connector Type A22																
F	T	T	T	T	T	T	T	T	T	T							T	T	T	T	T	T	T	T	T	T	
E	R	R	R	R	R	R	R	R	R	R							R	R	R	R	R	R	R	R	R	R	R
D	R	R	R	R	R	R	R	R	R	R							R	R	R	R	R	R	R	R	R	R	R
C	R	R	R	R	R	R	R	R	R	R							R	R	R	R	R	R	R	R	R	R	R
B	R	R	R	R	R	R	R	R	R	R							R	R	R	R	R	R	R	R	R	R	R
A	R	R	R	R	R	R	R	R	R	R							R	R	R	R	R	R	R	R	R	R	R
Z	T	T	T	T	T	T	T	T	T	T							T	T	T	T	T	T	T	T	T	T	T
	1	2	3	4	5	6	7	8	9	10	11						15	16	17	18	19	20	21	22	23	24	25

Signal Contact Configuration Worksheet											Connector Type A22																
F																											
E																											
D																											
C																											
B																											
A																											
Z																											
	1	2	3	4	5	6	7	8	9	10	11						15	16	17	18	19	20	21	22	23	24	25

# 3M™ CP2 Press-Fit Header

2 mm Type A 110 Signal Contacts

CP2 Series

CP2-HA110-F1-KR

Connector Type A22

F																										
E	A	A	A	A	A	A	A	A	A	A	A					A	A	A	A	A	A	A	A	A		
D	A	A	A	A	A	A	A	A	A	A	A					A	A	A	A	A	A	A	A	A		
C	B	B	B	B	B	B	B	B	B	B	B					B	B	B	B	B	B	B	B	B		
B	A	A	A	A	A	A	A	A	A	A	A					A	A	A	A	A	A	A	A	A		
A	A	A	A	A	A	A	A	A	A	A	A					A	A	A	A	A	A	A	A	A		
Z																										
	1	2	3	4	5	6	7	8	9	10	11					15	16	17	18	19	20	21	22	23	24	25

CP2-HA110-GF1-KR

Connector Type A22

F	C	C	C	C	C	C	C	C	C	C	C					C	C	C	C	C	C	C	C	C	C	
E	A	A	A	A	A	A	A	A	A	A	A					A	A	A	A	A	A	A	A	A	A	
D	A	A	A	A	A	A	A	A	A	A	A					A	A	A	A	A	A	A	A	A	A	
C	B	B	B	B	B	B	B	B	B	B	B					B	B	B	B	B	B	B	B	B	B	
B	A	A	A	A	A	A	A	A	A	A	A					A	A	A	A	A	A	A	A	A	A	
A	A	A	A	A	A	A	A	A	A	A	A					A	A	A	A	A	A	A	A	A	A	
Z	C	C	C	C	C	C	C	C	C	C	C					C	C	C	C	C	C	C	C	C	C	
	1	2	3	4	5	6	7	8	9	10	11					15	16	17	18	19	20	21	22	23	24	25

**3M is a trademark of 3M Company.**

Unless otherwise noted, references to industry specifications are intended to indicate substantial compliance to the material elements of the specification. Such references should not be construed as a guarantee of compliance to all requirements in a given specification.

### **Important Notice**

All statements, technical information, and recommendations related to 3M's products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product which are not contained in 3M's current publications, or any contrary statements contained on your purchase order shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M.

### **Warranty; Limited Remedy; Limited Liability**

This product will be free from defects in material and manufacture for a period of one (1) year from the time of purchase. **3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. **Except where prohibited by law, 3M will not be liable for any direct, indirect, special, incidental or consequential loss or damage arising from this 3M product, regardless of the legal theory asserted.**



#### **Electronics Materials Solutions Division**

6801 River Place Blvd.  
Austin, TX 78726-9000  
U.S.A.  
1-800-225-5373  
[www.3Mconnectors.com](http://www.3Mconnectors.com)

Please recycle. Printed in USA.  
© 3M 2015. All rights reserved.  
RIA-2217A-E



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.