

Features

- High-speed access times
Com'l: 10, 12 and 15 ns
Ind'l: 12 and 15 ns
- Low power operation (typical)
 - PDM41024SA
Active: 450 mW
Standby: 50 mW
 - PDM41024LA
Active: 400 mW
Standby: 25mW
- Single +5V ($\pm 10\%$) power supply
- TTL-compatible inputs and outputs
- Packages
 - Plastic SOJ (300 mil) - TSO
 - Plastic SOJ (400 mil) - SO
 - Plastic TSOP (I)- T


Description

The PDM41024 is a high-performance CMOS static RAM organized as 131,072 x 8 bits. Writing is accomplished when the write enable ($\overline{WE}$) and the chip enable ($\overline{CE1}$) inputs are both LOW and CE2 is HIGH. Reading is accomplished when $\overline{WE}$ and CE2 remain HIGH and $\overline{CE1}$ and $\overline{OE}$ are both LOW.

The PDM41024 operates from a single +5V power supply and all the inputs and outputs are fully TTL-compatible. The PDM41024 comes in two versions: the standard power version (SA) and the low power version (LA). The two versions are functionally the same and differ only in their power consumption.

The PDM41024 is available in a 32-pin plastic TSOP (I), and a 300-mil and 400-mil plastic SOJ.

Functional Block Diagram



Pin Configuration

TSOP (I)

A11	1	32	$\overline{\text{OE}}$
A9	2	31	A10
A8	3	30	CE1
A13	4	29	I/O7
WE	5	28	I/O6
CE2	6	27	I/O5
A15	7	26	I/O4
Vcc	8	25	I/O3
NC	9	24	Vss
A16	10	23	I/O2
A14	11	22	I/O1
A12	12	21	I/O0
A7	13	20	A0
A6	14	19	A1
A5	15	18	A2
A4	16	17	A3

SOJ

NC	1	32	Vcc
A16	2	31	A15
A14	3	30	CE2
A12	4	29	WE
A7	5	28	A13
A6	6	27	A8
A5	7	26	A9
A4	8	25	A11
A3	9	24	$\overline{\text{OE}}$
A2	10	23	A10
A1	11	22	CE1
A0	12	21	I/O7
I/O0	13	20	I/O6
I/O1	14	19	I/O5
I/O2	15	18	I/O4
Vss	16	17	I/O3

Pin Description

Name	Description
A16-A0	Address Inputs
I/O7-I/O0	Data Inputs/Outputs
$\overline{\text{OE}}$	Output Enable Input
WE	Write Enable Input
CE1, CE2	Chip Enable Inputs
NC	No Connect
Vcc	Power (+5V)
Vss	Ground

Truth Table⁽¹⁾

$\overline{\text{OE}}$	WE	CE1	CE2	I/O	MODE
X	X	H	X	Hi-Z	Standby
X	X	X	L	Hi-Z	Standby
L	H	L	H	D _{OUT}	Read
X	L	L	H	D _{IN}	Write
H	H	L	H	Hi-Z	Output Disable

NOTE: 1. H = V_{IH}, L = V_{IL}, X = DON'T CARE

Absolute Maximum Ratings⁽¹⁾

Symbol	Rating	Com'l.	Ind.	Unit
V _{TERM}	Terminal Voltage with Respect to V _{SS}	-0.5 to +7.0	-0.5 to +7.0	V
T _{BIAS}	Temperature Under Bias	-55 to +125	-65 to +135	°C
T _{STG}	Storage Temperature	-55 to +125	-65 to +150	°C
P _T	Power Dissipation	1.0	1.0	W
I _{OUT}	DC Output Current	50	50	mA
T _j	Maximum Junction Temperature ⁽²⁾	125	145	°C

NOTE: 1. Stresses greater than those listed under ABSOLUTE MAXIMUM RATINGS may cause permanent damage to the device. This is a stress rating only and functional operation of the device at these or any other conditions above those indicated in the operational sections of this specification is not implied. Exposure to absolute maximum rating conditions for extended periods may affect reliability.

- Appropriate thermal calculations should be performed in all cases and specifically for those where the chosen package has a large thermal resistance (e.g., TSOP). The calculation should be of the form: $T_j = T_a + P * \theta_{ja}$ where T_a is the ambient temperature, P is average operating power and θ_{ja} the thermal resistance of the package. For this product, use the following θ_{ja} values:

SOJ: 72° C/W

TSOP: 95° C/W

Recommended DC Operating Condition

Symbol	Parameter	Min.	Typ.	Max.	Unit
V _{CC}	Supply Voltage	4.5	5.0	5.5	V
V _{SS}	Supply Voltage	0	0	0	V
Industrial	Ambient Temperature	-40	25	85	°C
Commercial	Ambient Temperature	0	25	70	°C

DC Electrical Characteristics (V_{CC} = 5.0V ± 10%)

Symbol	Parameter	Test Conditions		PDM41024SA		PDM41024LA		Unit
				Min.	Max.	Min.	Max.	
I _{LI}	Input Leakage Current	V _{CC} = MAX., V _{IN} = V _{SS} to V _{CC}	Com'l/ Ind.	-5	5	-1	1	μA
I _{LO}	Output Leakage Current	V _{CC} = MAX., CE1 = V _{IH} and CE2 = V _{IL} , V _{OUT} = V _{SS} to V _{CC}	Com'l/ Ind.	-5	5	-1	1	μA
V _{IL}	Input Low Voltage			-0.5 ⁽¹⁾	0.8	-0.5 ⁽¹⁾	0.8	V
V _{IH}	Input High Voltage			2.2	6.0	2.2	6.0	V
V _{OL}	Output Low Voltage	I _{OL} = 8 mA, V _{CC} = Min. I _{OL} = 10 mA, V _{CC} = Min.		—	0.4 0.5	—	0.4 0.5	V V
V _{OH}	Output High Voltage	I _{OH} = -4 mA, V _{CC} = Min.		2.4	—	2.4	—	V

NOTE: 1. V_{IL}(min) = -3.0V for pulse width less than 20 ns

Power Supply Characteristics

Symbol	Parameter	Power	-10	-12		-15	
			Com'l.	Com'l.	Ind.	Com'l.	Ind.
I _{CC}	Operating Current CE1 = V _{IL} and CE2 = V _{IH}	SA	250	230	240	185	195
	f = f _{MAX} = 1/t _{RC} V _{CC} = Max. I _{OUT} = 0 mA	LA	230	210	220	165	175
I _{SB}	Standby Current CE1 = V _{IH} and CE2 = V _{IL}	SA	80	70	70	55	55
	f = f _{MAX} = 1/t _{RC} V _{CC} = Max.	LA	75	65	65	50	50
I _{SB1}	Full Standby Current CE1 ≥ V _{HC} and CE2 ≤ V _{LC}	SA	20	20	25	10	15
	f = 0 V _{CC} = Max. V _{IN} ≥ V _{CC} - 0.2V or ≤ 0.2V	LA	10	10	10	5	10

SHADED AREAS = PRELIMINARY DATA

NOTES: All values are maximum guaranteed values.

V_{LC} ≤ 0.2V, V_{HC} ≥ V_{CC} - 0.2V

Capacitance⁽¹⁾ ($T_A = +25^\circ\text{C}$, $f = 1.0\text{ MHz}$)

Symbol	Parameter	Max.	Unit
C_{IN}	Input Capacitance	8	pF
C_{OUT}	Output Capacitance	8	pF

NOTE:1. This parameter is determined by device characterization but is not production tested.

AC Test Conditions

Input pulse levels	V_{SS} to 3.0V
Input rise and fall times	3 ns
Input timing reference levels	1.5V
Output reference levels	1.5V
Output load	See Figures 1 and 2




Figure 1. Output Load Equivalent




Figure 2. Output Load Equivalent
(for t_{LZCE} , t_{HZCE} , t_{LZWE} , t_{HZWE} , t_{LZOE} , t_{HZOE})






Figure 3.



Read Cycle No. 1^(4, 5)Read Cycle No. 2^(2, 4, 6)

AC Electrical Characteristics

Description		-10 ⁽⁷⁾		-12 ⁽⁷⁾		-15		
READ Cycle	Sym	Min.	Max.	Min.	Max.	Min.	Max.	Units
READ cycle time	t_{RC}	10		12		15		ns
Address access time	t_{AA}		10		12		15	ns
Chip enable access time	t_{ACE}		10		12		15	ns
Output hold from address change	t_{OH}	3		3		3		ns
Chip enable to output in low Z ^(1,3)	t_{LZCE}	5		5		5		ns
Chip disable to output in high Z ^(1,2,3)	t_{HZCE}		6		6		7	ns
Chip enable to power up time ⁽³⁾	t_{PU}	0		0		0		ns
Chip disable to power down time ⁽³⁾	t_{PD}		10		12		15	ns
Output enable access time	t_{AOE}		6		6		6	ns
Output enable to output in low Z ^(1,3)	t_{LZOE}	0		0		0		ns
Output disable to output in high Z ^(1,3)	t_{HZOE}		6		6		6	ns


SHADED AREA = PRELIMINARY DATA

Notes referenced are after Data Retention Table.

Write Cycle No. 1 (Write Enable Controlled)**Write Cycle No. 2 (Write Enable Controlled)**

NOTE: Output Enable ($\overline{OE}$) is inactive (high)

Write Cycle No. 3 (Chip Enable Controlled)




AC Electrical Characteristics

Description		-10 ⁽⁷⁾		-12 ⁽⁷⁾		-15		
WRITE Cycle	Sym	Min.	Max.	Min.	Max.	Min.	Max.	Units
WRITE cycle time	t_{WC}	10		12		15		ns
Chip enable active time	t_{CW}	10		10		11		ns
Address valid to end of write	t_{AW}	10		10		11		ns
Address setup time	t_{AS}	0		0		0		ns
Address hold from end of write	t_{AH}	0		0		0		ns
Write pulse width	t_{WP1}	8		8		11		ns
Write pulse width	t_{WP2}	8		8		12		ns
Data setup time	t_{DS}	7		7		7		ns
Data hold time	t_{DH}	0		0		0		ns
Write disable to output in low $Z^{(1,3)}$	t_{LZWE}	0		0		0		ns
Write enable to output in high $Z^{(1,3)}$	t_{HZWE}		7		7		7	ns

SHADED AREA = PRELIMINARY DATA

Notes referenced are after Data Retention Table

Low V_{CC} Data Retention Waveform

Data Retention Electrical Characteristics (LA Version Only) for JEDEC Version

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
V_{DR}	V_{CC} for Retention Data		2	—	—	V
I_{CCDR}	Data Retention Current	$\overline{CE1} \geq V_{CC} - 0.2V$ or $\overline{CE2} \leq V_{SS} + 0.2V$ $V_{IN} \geq V_{CC} - 0.2V$ or $\leq 0.2V$	$V_{CC} = 2V$ — $V_{CC} = 3V$ —	—	500 750	μA μA
t_{CDR}	Chip Deselect to Data Retention Time		0	—	—	ns
$t_R^{(3)}$	Operation Recovery Time		t_{RC}	—	—	ns

NOTES: (For three previous Electrical Characteristics tables)

1. The parameter is tested with $C_L = 5$ pF as shown in Figure 2. Transition is measured ± 200 mV from steady state voltage.
2. At any given temperature and voltage condition, t_{HZCE} is less than t_{LZCE} .
3. This parameter is sampled.
4. $\overline{WE}$ is high for a READ cycle.
5. The device is continuously selected. All the Chip Enables are held in their active state.
6. The address is valid prior to or coincident with the latest occurring Chip Enable.
7. $V_{CC} = 5V \pm 5\%$.

Ordering Information

XXXXX	X	XX	X	X	X	
Device Type	Power	Speed	Package Type	Process Temp. Range	Preferred Shipping Container	
						Blank Tubes
						TR Tape & Reel
						TY Tray
						Blank Commercial (0° to +70°C)
						I Industrial (-40° to +85°C)
						A Automotive (-40° to +105°C)
						TSO 32-pin 300-mil Plastic SOJ
						SO 32-pin 400-mil Plastic SOJ
						T 32-pin Plastic TSOP (I)
						10 Commercial Only
						12
						15 (use 15 ns for slower designs)
						SA Standard Power
						LA Low Power
						PDM41024 - 1 Meg (128Kx8) Static RAM



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.