









Defense and Aerospace

KEMET
CHARGED.™

F-3113 5/06

Ceramic High Voltage, High Temperature Capacitors

	KEMET Series	Page
Performance Information		1-4
High Temperature, High Voltage Axial/Radial	HT/HP	5-7
High Temperature, High Voltage Radial	HV	8-9
High Voltage Conformally Coated Radial	HV	10-14
High Voltage MIL-PRF-49467 (Equivalent)	HV	15-17
High Voltage Space Quality	HS	18-22
High Voltage Ceramic Chip	1515/1812/1825/2020/ 2225/2520/3333//3530 4040/4540/5440/5550/6560	23-27
High Voltage L & J Leaded	SM20/SM21/SM22/SM23 SM24/SM25/SM26/SM30/ SM31/SM33/SM34/SM35/SM36	28-32
High Voltage Disc	D30/40/50/75/90/100/120	33-34
High Voltage Disc Multiplie Stacks	D30/40/50/75/90/100/120	35

GENERAL SPECIFICATIONS

Working Voltage:
C0G 50, 100, 200, 500, 1k, 2k, 3k, 4k, 5k, 7.5k, 10k, 15k, 20k
X7R 50, 100, 200, 500, 1k, 2k, 3k, 4k, 5k, 7.5k, 10k, 15k, 20k, 30k, 40k, 50k
X5U 3k, 4k, 5k, 7.5k, 10k, 15k, 20k

Temperature Characteristics:
C0G 0 + 30 PPM / °C from - 55°C to + 125°C (1)
X7R + 15% from - 55°C to + 125°C
X5U + 22%, -56% from -55°C to + 85°C

Capacitance Tolerance:
C0G +0.5pF, +1%, +2%, +5%, +10%
X7R +10%, +20%, +80% / -20%, +100% / -0%
X5U +10%, +20%, +80% / -20%, +100% / -0%

Construction:
Epoxy encapsulated - meets flame test requirements of UL Standard 94V-0.
High-temperature solder - meets EIA RS-198, Method 302, Condition B (260°C for 10 seconds)

Termination Material:
Check individual Series: Part Number and Ordering Information for Termination Materials offered in each series.

Solderability:
MIL-STD 202, Method 208
(Test Method: ANSI/J-STD-002)
Test A for through-hole mount and surface mount leaded.
Test B for surface mount leadless components.

Terminal Strength:
MIL-STD 202, Method 208, Condition A (2.3kg or 5 lbs)

Resistance to Solvents:
MIL-STD 202, Method 215

Resistance to Soldering Heat:
MIL-STD 202, Method 210, Test Condition C

ELECTRICAL

Capacitance @ 25°C:
Within specified tolerance and following test conditions per MIL-STD 202, Method 305.
C0G, X7R & X5U
> 100pF with 1.0 vrms @ 1 kHz with 1.0 vrms
< 100pF with 1.0 vrms @ 1 MHz with 1.0 vrms

Dissipation Factor @ 25°C:
Same test conditions as capacitance.
C0G - 0.15% maximum
X7R - 2.5% maximum
X5U - 2.5% maximum

Insulation Resistance @25°C:
MIL-STD 202, Method 302
C0G & X7R:
100 gigohm or 1 gigohm x uF, whichever is less.
<500V test @ rated voltage, >1kV test @ 500V.

X5U:
10 gigohm or 100 megohm x uF, whichever is less.
<500V test @ rated voltage, >1kV test @ 500V.

Dielectric Withstanding Voltage:
MIL-STD 202, Method 301
<200V test @ 250% of rated voltage
500V to 1250V test @ 150% of rated voltage
>1251V test @ 120% of rated voltage

ENVIRONMENTAL

Vibration:
MIL-STD 202, Method 204, Condition D (20g)

Shock:
MIL-STD 202, Method 213, Condition I (100g)

Life Test:
MIL-STD 202, Method 108

<200V
C0G - 200% rated voltage @ +125°C
X7R - 200% rated voltage @ +125°C

>500V
C0G - rated voltage @ +125°C
X7R - rated voltage @ +125°C
X5U - rated voltage @ +85°C

Post Test Limits @ 25°C are:
Capacitance Change:
C0G (< 200V) - +3% or 0.25pF, whichever is greater.
C0G (> 500V) - +3% or 0.50pF, whichever is greater.
X7R - + 20% of initial value (2)
Dissipation Factor:
C0G - 0.25% maximum
X7R & X5U - 3.0% maximum
Insulation Resistance:
C0G & X7R:
100 gigohm or 1 gigohm x uF, whichever is less.
<500V test @ rated voltage, >1kV test @ 500V.

X5U:
10 gigohm or 100 megohm x uF, whichever is less.
<500V test @ rated voltage, >1kV test @ 500V.

Moisture Resistance:
MIL-STD 202, Method 106
Post Test Limits @ 25°C are:
Capacitance Change:
C0G (< 200V) - +3% or 0.25pF, whichever is greater.
C0G (> 500V) - +3% or 0.50pF, whichever is greater.
X7R - + 20% of initial value (2)
Dissipation Factor:
C0G - 0.25% maximum
X7R & X5U - 3.0% maximum
Insulation Resistance:
C0G & X7R:
100 gigohm or 1 gigohm x uF, whichever is less.
<500V test @ rated voltage, >1kV test @ 500V.

X5U:
10 gigohm or 100 megohm x uF, whichever is less.
<500V test @ rated voltage, >1kV test @ 500V.

Thermal Shock:
MIL-STD 202, Method 107, Condition A
C0G & X7R: -55°C to 125°C
X5U: -55°C to 85°C

(1) +53 PPM -30 PPM/ °C from +25°C to -55°C, + 60 PPM below 10pF.

(2) X7R & X5U dielectrics exhibit aging characteristics; therefore, it is highly recommended that capacitors be deaged for 2 hours at 150°C and stabilized at room temperature for 48 hours before capacitance measurements are made.

© KEMET Electronics Corporation • P.O. Box 5928 • Greenville, SC 29606 (864) 963-6300 • www.kemet.com

KEMET HIGH VOLTAGE TECHNICAL SUMMARY

	HIGH TEMPERATURE	HIGH VOLTAGE
MILITARY & AEROSPACE		
Avionics	X	X
Radar Systems	X	X
Telemetry, Data Tx/Rx		X
Control Systems	X	
MEDICAL		
.5 to 1.5 Tesla MR1 &		X
NM1 Tuning Coils		X
1 to 3 Tesla MR1 Gradient		X
Coils & Magnetic Rings		X
CT-Scanner		X
Medical MRI		X
X-Ray Generator	X	X
SEMICONDUCTOR		
RF Tuning Networks		X
RF Power Supplies		X
Semiconductor Manufacturing	X	
SECURITY		
Handheld Scanners		X
Intruder Detection Systems		X
Luggage Scanners		X
Metal/Explosive Detector		X
OTHER		
LCD Backlight Inverter		X
Electric Ballast for CFL	X	X
Electric Ballast for Fluorescent Lamp	X	X
Measurement Equipment	X	X
Microwave/Convection Ovens	X	X
POWER SUPPLY		
HV Power Supply	X	X
Power Station Equipment		X
Power Supply for Air Conditioner, Washing Machine		X
Inverter Power Supply-AC	X	
TELECOM		
Base Station Power amps		X
Broadcasting Equipment		X
MODEM		
DAA Modem		X
xDSL Modem		X
LAN, Router, HUB, Switches		X
RF Power Amplifiers		X
INDUSTRIAL		
Oil Rigging, Down Hole, Mining	X	X

© KEMET Electronics Corporation • P.O. Box 5928 • Greenville, SC 29606 (864) 963-6300 • www.kemet.com

KEMET HIGH VOLTAGE TECHNICAL SUMMARY


	ELECTRICAL			ENVIRONMENTAL	MECHANICAL
	Voltage Range	Capacitance Range	Dissipation Factor	Operating Temperature Range	Configuration
HIGH VOLTAGE					
Radial Conformally Coated					
Std	C0G/X7R: 500 to 10k VDC	C0G:12 pF - .330µF X7R: 220 pF - 5.6 µF	C0G: 0.15% max X7R: 2.5% max	C0G: -55°C to + 125°C X7R: -55°C to + 125°C	Radial
Mil-PRF-49467 Equivalent	C0G/X7R: 600 to 5k VDC	C0G: 12 pF - .68 µF X7R: 27 pF - .47 µF	C0G: 0.15% max X7R: 2.5% max	C0G/X7R: -55°C to + 125°C	Radial
Space Quality	C0G/X7R: 500 to 10k VDC	C0G/X7R: 560 pF - 2.20µF	C0G: 0.15% max X7R: 2.5% max	C0G/X7R: -55°C to + 125°C	Radial
Ceramic Surface Mount Chip					
Military	C0G/X7R: 500 to 5k VDC	C0G: 12 pF- .10 µF X7R: 270 pF -2.50 µF	C0G: 0.15% max X7R: 2.5% max	C0G/X7R: -55°C to + 125°C	Chip
Leaded Chips J or L lead	C0G/X7R: 500 to 10k VDC	C0G: 12 pF-.330 µF X7R: 220 pF-5.6 uF	C0G: 0.15% max X7R: 2.5% max	C0G/X7R: -55°C to + 125°C	Leaded Chip J or L Lead
Disc	C0G/X5U: 3k to 20k VDC, X7R:3k to 50k VDC	C0G: 1.2 pF-236 pF X7R: 10 p -7400 pF X5U: 80 pF-17300 pF	C0G: 0.15% max X7R: 2.5% max X5U: 2.5% max	C0G/X7R: -55°C to + 125°C X5U: -55°C to + 85°C	Disc
Disc Stack	C0G/X7R/X5U: 5k to 20k VDC	C0G: 1.2 pF-141 pF X7R: 37 pF-4400 pF X5U: 80 pF-10400 pF	C0G: 0.15% max X7R: 2.5% max X5U: 2.5% max	C0G/X7R: -55°C to + 125°C X5U: -55°C to + 85°C	Disc Stack
HIGH TEMPERATURE					
Hi Temp (HT/HP)	100 to 200 VDC	C0G: 22 pF-.100 µF X7R:1000 pF-1.0µF	C0G 0.15% X7R Type 2.0% X7R 2.50%	-55°C to + 200°C	Axial/Radial
Hi Temp Hi Volt (HV)	500 to 4000 VDC	C0G: 390 pF-.015 µF X7R:1400 pF- .270 µF	C0G 0.15% X7R Type 2.0% X7R 2.50%	-55°C to + 200°C	Radial
Ceramic Cased Capacitor					
Std 125°C (SCR/SRR/SCA/SRA)	50 to 200 VDC	C0G: 1.0 pF- .12 µF X7R:100 pF- 6.8 µF	C0G 0.15% X7R 2.50%	-55°C to + 125°C	Axial/Radial
200°C (ACR/ARR/ACA/ARA)	50 to 100 VDC	C0G: 1.0 pF- .12 µF X7R:100 pF- 3.3 µF	C0G 0.15% X7R 2.50%	-55°C to + 200°C	Axial/Radial
260°C (TCR/TRR/TCA/TRA)	50 to 100 VDC	C0G: 1.0 pF- .12 µF X7R:100 pF- 3.3 µF	C0G 0.15% X7R 2.50%	-55°C to + 260°C	Axial/Radial
Hi Temp Hi Volt (VCR/VRR)	500 to 5000 VDC	C0G: 10 pF-.056 µF X7R:330 pF-1.2µF	C0G 0.15% X7R 2.50%	-55°C to + 200°C	Radial

© KEMET Electronics Corporation • P.O. Box 5928 • Greenville, SC 29606 (864) 963-6300 • www.kemet.com

DIELECTRIC COMPARISONS

Features	Ultra Stable	Semi-Stable High Voltage	Semi-Stable Hi-Temp	Temp/Volt Dependent
Dielectric Type	C0G (NPO)	X7R	X7R type	X5U
Temperature Coefficient	0 ±30ppm/ºC	±15%	+15/-40%	+22-56%
Operating Temp. Range	-55 to +200ºC	-55 to +125ºC	-55 to +200ºC	-55 to +125ºC
Dissipation Factor	0.1% max.	2.5% max.	2.0% max.	2.5% max.
Aging Rate	None	-2.0% max/dec. hour	-2.0% max/dec. hour	-2.0% max/dec. hour
Voltage Range	25 to 20k VDC	50 to 50k VDC	25 to 4k VDC	Up to 20K VDC
Standard Tolerance	J, K, M	K, M, P, Z	K, M, P, Z	M, P, Z
Coefficient of Thermal Expansion @ 25ºC	9 X 10-6 IN/IN ºC	11 X 10-6 IN/IN ºC	11 X 10-6 IN/IN ºC	11 X 10-6 IN/IN ºC

TYPICAL INSULATION RESISTANCE VS. TEMP (C°) FOR C0G, NPO & X7R DIELECTRICS



© KEMET Electronics Corporation • P.O. Box 5928 • Greenville, SC 29606 (864) 963-6300 • www.kemet.com

HIGH TEMPERATURE (+200ºC) AXIAL/RADIAL CERAMIC CAPACITORS HT/HP SERIES

FEATURES


The HT/HP Series is used in robust applications

- Down Hole
- Industrial
- Harsh Environments

Where a Radial/Axial coated capacitor can withstand high temperatures (200°C).

NOTE:
Other tolerances, higher capacitance values, voltages, or special package configurations are available upon request.

CAPACITOR OUTLINE DRAWING



DIMENSIONS

Molded (HT) and Conformal Coated (HP), Radial Lead Types

Style	Sizes in Inches (mm) max			Lead Spacing ±0.030 (S)
	Length (L)	Height (H)	Thickness (W)	
HT05	.200 (5.08)	.200 (5.08)	.100 (2.54)	.100 (2.54)
HT55	.200 (5.08)	.200 (5.08)	.100 (2.54)	.200 (5.08)
HT06	.300 (7.62)	.300 (7.62)	.150 (3.81)	.200 (5.08)
HT08	.500 (12.70)	.500 (12.70)	.250 (6.35)	.400 (10.16)
HT09	.700 (17.78)	.400 (10.16)	.200 (5.08)	.500 (12.70)

Tubular Case, Axial Lead Types

Style	Sizes in Inches (mm) max	
	Length (L)	Diameter (D)
HT11	.170 (4.32)	.100 (2.54)
HT13	.260 (6.60)	.135 (3.43)
HT14	.400 (10.16)	.155 (3.94)
HT15	.500 (12.70)	.200 (5.08)
HT16	.750 (19.05)	.375 (9.52)

PART NUMBER AND ORDERING INFORMATION

HT06 A W 472 K C

STYLE
HT=Molded
HP= Conformal Coated

VOLTAGE
A=25V
B=50V
C=100V
D=200V

DIELECTRIC MATERIAL
B, W=X7R type
N=C0G (NP0)

CAPACITANCE VALUE
First two digits are significant, last digit is number of zeros, i.e., 472=4700pF

TOLERANCE
J=±5%
K=±10%
M=±20%
Other tolerance available upon request

OPTIONAL COPPER LEAD
Solder coated. Add to part number only if required

MARKING
(HT05, HT55, HT11)
472K
KEC

(All other sizes)
HT06AW472K
KEC
Date Code

For CONFORMAL COATED types, change style number to HPXX. HP dimensions will be reduced slightly.

© KEMET Electronics Corporation • P.O. Box 5928 • Greenville, SC 29606 (864) 963-6300 • www.kemet.com

COG & X7R DIELECTRIC

Radial	C0G															
Series	HT/HP05			HT/HP55			HT/HP06			HT/HP08			HT/HP09			
W max	.200 (5.08)			.200 (5.08)			.300 (7.62)			.500 (12.70)			.700 (17.78)			
H max	.200 (5.08)			.200 (5.08)			.300 (7.62)			.500 (12.70)			.400 (10.16)			
T max	.100 (2.54)			.100 (2.54)			.150 (3.81)			.250 (6.35)			.200 (5.08)			
S ±.030	.100 (2.54)			.200 (5.08)			.200 (5.08)			.400 (10.16)			500 (12.70)			
Lead Dia.	.025 (.635)			.025 (.635)			.025 (.635)			.025 (.635)			.025 (.635)			
Cap	Cap Code	WVDC			WVDC			WVDC			WVDC			WVDC		
		50	100	200	50	100	200	50	100	200	50	100	200	50	100	200
1.0pF	109				■	■	■									
1.2	129				■	■	■									
1.5	159				■	■	■									
1.8	189				■	■	■									
2.2	229				■	■	■									
2.7	279				■	■	■									
3.3	339				■	■	■									
3.9	399				■	■	■									
4.7	479				■	■	■									
5.6	569				■	■	■									
6.8	689				■	■	■									
8.2	829				■	■	■									
10	100				■	■	■									
12	120				■	■	■									
15	150				■	■	■									
18	180				■	■	■									
22	220	■	■	■	■	■	■									
27	270	■	■	■	■	■	■									
33	330	■	■	■	■	■	■									
39	390	■	■	■	■	■	■									
47	470	■	■	■	■	■	■									
56	560	■	■	■	■	■	■									
68	680	■	■	■	■	■	■									
82	820	■	■	■	■	■	■									
100	101	■	■	■	■	■	■									
120	121	■	■	■	■	■	■									
150	151	■	■	■	■	■	■									
180	181	■	■	■	■	■	■									
220	221	■	■	■	■	■	■	■	■	■						
270	271	■	■	■	■	■	■	■	■	■						
330	331	■	■	■	■	■	■	■	■	■						
390	391	■	■	■	■	■	■	■	■	■						
470	471	■	■	■	■	■	■	■	■	■						
560	561	■	■	■	■	■	■	■	■	■						
680	681	■	■	■	■	■	■	■	■	■	■	■	■			
820	821	■	■	■	■	■	■	■	■	■	■	■	■			
1000	102	■	■	■	■	■	■	■	■	■	■	■	■			
1200	122	■	■	■	■	■	■	■	■	■	■	■	■			
1500	152	■	■	■	■	■	■	■	■	■	■	■	■			
1800	182	■	■	■	■	■	■	■	■	■	■	■	■			
2200	222	■	■	■	■	■	■	■	■	■	■	■	■			
2700	272	■	■	■	■	■	■	■	■	■	■	■	■			
3300	332	■	■	■	■	■	■	■	■	■	■	■	■			
3900	392	■	■	■	■	■	■	■	■	■	■	■	■			
4700	472	■	■	■	■	■	■	■	■	■	■	■	■			
5600	562	■	■	■	■	■	■	■	■	■	■	■	■			
6800	682	■	■	■	■	■	■	■	■	■	■	■	■			
8200	822	■	■	■	■	■	■	■	■	■	■	■	■			
.010uF	103	■	■		■	■		■	■	■	■	■	■	■	■	■
.012	123							■	■	■	■	■	■	■	■	■
.015	153							■	■	■	■	■	■	■	■	■
.018	183							■	■	■	■	■	■	■	■	■
.022	223							■	■	■	■	■	■	■	■	■
.027	273							■	■	■	■	■	■	■	■	■
.033	333							■	■		■	■	■	■	■	■
.039	393										■	■	■	■	■	■
.047	473										■	■	■	■	■	■
.056	563										■	■	■	■	■	■
.068	683										■	■	■	■	■	■
.082	823										■	■	■	■	■	■
.10	104										■	■		■	■	■
.12	124										■	■		■	■	■
.15	154													■	■	■

Radial	X7R															
Series	HT/HP05			HT/HP55			HT/HP06			HT/HP08			HT/HP09			
W max	.200 (5.08)			.200 (5.08)			.300 (7.62)			.500 (12.70)			.700 (17.78)			
H max	.200 (5.08)			.200 (5.08)			.300 (7.62)			.500 (12.70)			.400 (10.16)			
T max	.100 (2.54)			.100 (2.54)			.150 (3.81)			.250 (6.35)			.200 (5.08)			
S ±.030	.100 (2.54)			.200 (5.08)			.200 (5.08)			.400 (10.16)			500 (12.70)			
Lead Dia.	.025 (.635)			.025 (.635)			.025 (.635)			.025 (.635)			.025 (.635)			
Cap	Cap Code	WVDC			WVDC			WVDC			WVDC			WVDC		
		50	100	200	50	100	200	50	100	200	50	100	200	50	100	200
100pF	101				■	■	■									
120	121				■	■	■									
150	151				■	■	■									
180	181				■	■	■									
220	221				■	■	■									
270	271				■	■	■	■	■	■						
330	331				■	■	■	■	■	■						
390	391				■	■	■	■	■	■						
470	471				■	■	■	■	■	■						
560	561				■	■	■	■	■	■						
680	681				■	■	■	■	■	■	■	■	■			
820	821				■	■	■	■	■	■	■	■	■			
1000	102	■	■	■	■	■	■	■	■	■	■	■	■			
1200	122	■	■	■	■	■	■	■	■	■	■	■	■			
1500	152	■	■	■	■	■	■	■	■	■	■	■	■			
1800	182	■	■	■	■	■	■	■	■	■	■	■	■			
2200	222	■	■	■	■	■	■	■	■	■	■	■	■			
2700	272	■	■	■	■	■	■	■	■	■	■	■	■			
3300	332	■	■	■	■	■	■	■	■	■	■	■	■			
3900	392	■	■	■	■	■	■	■	■	■	■	■	■			
4700	472	■	■	■	■	■	■	■	■	■	■	■	■			
5600	562	■	■	■	■	■	■	■	■	■	■	■	■			
6800	682	■	■	■	■	■	■	■	■	■	■	■	■			
8200	822	■	■	■	■	■	■	■	■	■	■	■	■			
.010uF	103	■	■	■	■	■	■	■	■	■	■	■	■			
.012	123	■	■	■	■	■	■	■	■	■	■	■	■			
.015	153	■	■	■	■	■	■	■	■	■	■	■	■			
.018	183	■	■	■	■	■	■	■	■	■	■	■	■			
.022	223	■	■		■	■	■	■	■	■	■	■	■			
.027	273				■	■	■	■	■	■	■	■	■			
.033	333				■	■	■	■	■	■	■	■	■			
.039	393				■	■	■	■	■	■	■	■	■			
.047	473				■	■	■	■	■	■	■	■	■			
.056	563							■	■	■	■	■	■			
.068	683							■	■		■	■	■			
.082	823							■	■		■	■	■			
.10	104							■	■		■	■	■	■	■	■
.12	124							■	■		■	■	■	■	■	■
.15	154							■	■		■	■	■	■	■	■
.18	184							■	■		■	■	■	■	■	■
.22	224							■	■		■	■	■	■	■	■
.27	274							■	■		■	■	■	■	■	■
.33	334							■	■		■	■	■	■	■	■
.39	394							■	■		■	■	■	■	■	■
.47	474							■	■		■	■	■	■	■	■
.56	564							■	■		■	■	■	■	■	■
.68	684							■	■		■	■	■	■	■	■
.82	824							■	■		■	■	■	■	■	
1.0	105							■	■		■	■	■	■	■	
1.2	125										■	■	■			
1.5	155										■	■	■			
1.8	185										■	■	■			
2.2	225										■	■				
2.7	275										■	■				
3.3	335										■	■				
3.9	395										■	■				
4.7	475										■	■				

© KEMET Electronics Corporation • P.O. Box 5928 • Greenville, SC 29606 (864) 963-6300 • www.kemet.com

COG & X7R DIELECTRIC

Radial		C0G															
Series		HT/HP05			HT/HP55			HT/HP06			HT/HP08			HT/HP09			
	W max	.200 (5.08)			.200 (5.08)			.300 (7.62)			.500 (12.70)			.700 (17.78)			
	H max	.200 (5.08)			.200 (5.08)			.300 (7.62)			.500 (12.70)			.400 (10.16)			
	T max	.100 (2.54)			.100 (2.54)			.150 (3.81)			.250 (6.35)			.200 (5.08)			
	S ±.030	.100 (2.54)			.200 (5.08)			.200 (5.08)			.400 (10.16)			500 (12.70)			
	Lead Dia.	.025 (.635)			.025 (.635)			.025 (.635)			.025 (.635)			.025 (.635)			
Cap	Cap Code	WVDC			WVDC			WVDC			WVDC			WVDC			
		50	100	200	50	100	200	50	100	200	50	100	200	50	100	200	
1.0pF	109				■	■	■										
1.2	129				■	■	■										
1.5	159				■	■	■										
1.8	189				■	■	■										
2.2	229				■	■	■										
2.7	279				■	■	■										
3.3	339				■	■	■										
3.9	399				■	■	■										
4.7	479				■	■	■										
5.6	569				■	■	■										
6.8	689				■	■	■										
8.2	829				■	■	■										
10	100				■	■	■										
12	120				■	■	■										
15	150				■	■	■										
18	180				■	■	■										
22	220	■	■	■	■	■	■										
27	270	■	■	■	■	■	■										
33	330	■	■	■	■	■	■										
39	390	■	■	■	■	■	■										
47	470	■	■	■	■	■	■										
56	560	■	■	■	■	■	■										
68	680	■	■	■	■	■	■										
82	820	■	■	■	■	■	■										
100	101	■	■	■	■	■	■										
120	121	■	■	■	■	■	■										
150	151	■	■	■	■	■	■										
180	181	■	■	■	■	■	■										
220	221	■	■	■	■	■	■	■	■	■							
270	271	■	■	■	■	■	■	■	■	■							
330	331	■	■	■	■	■	■	■	■	■							
390	391	■	■	■	■	■	■	■	■	■							
470	471	■	■	■	■	■	■	■	■	■							
560	561	■	■	■	■	■	■	■	■	■							
680	681	■	■	■	■	■	■	■	■	■	■	■	■				
820	821	■	■	■	■	■	■	■	■	■	■	■	■				
1000	102	■	■	■	■	■	■	■	■	■	■	■	■				
1200	122	■	■	■	■	■	■	■	■	■	■	■	■				
1500	152	■	■	■	■	■	■	■	■	■	■	■	■				
1800	182	■	■	■	■	■	■	■	■	■	■	■	■				
2200	222	■	■	■	■	■	■	■	■	■	■	■	■				
2700	272	■	■	■	■	■	■	■	■	■	■	■	■				
3300	332	■	■	■	■	■	■	■	■	■	■	■	■				
3900	392	■	■	■	■	■	■	■	■	■	■	■	■				
4700	472	■	■	■	■	■	■	■	■	■	■	■	■				
5600	562	■	■	■	■	■	■	■	■	■	■	■	■				
6800	682	■	■	■	■	■	■	■	■	■	■	■	■				
8200	822	■	■	■	■	■	■	■	■	■	■	■	■				
.010uF	103	■	■		■	■		■	■	■	■	■	■	■	■	■	
.012	123							■	■	■	■	■	■	■	■	■	
.015	153							■	■	■	■	■	■	■	■	■	
.018	183							■	■	■	■	■	■	■	■	■	
.022	223							■	■	■	■	■	■	■	■	■	
.027	273							■	■		■	■	■	■	■	■	
.033	333										■	■	■	■	■	■	
.039	393										■	■	■	■	■	■	
.047	473										■	■	■	■	■	■	
.056	563										■	■	■	■	■	■	
.068	683										■	■	■	■	■	■	
.082	823										■	■	■	■	■	■	
.10	104										■	■		■	■	■	
.12	124										■	■		■	■	■	
.15	154													■	■	■	

Radial		X7R															
Series		HT/HP05			HT/HP55			HT/HP06			HT/HP08			HT/HP09			
	W max	.200 (5.08)			.200 (5.08)			.300 (7.62)			.500 (12.70)			.700 (17.78)			
	H max	.200 (5.08)			.200 (5.08)			.300 (7.62)			.500 (12.70)			.400 (10.16)			
	T max	.100 (2.54)			.100 (2.54)			.150 (3.81)			.250 (6.35)			.200 (5.08)			
	S ±.030	.100 (2.54)			.200 (5.08)			.200 (5.08)			.400 (10.16)			500 (12.70)			
	Lead Dia.	.025 (.635)			.025 (.635)			.025 (.635)			.025 (.635)			.025 (.635)			
Cap	Cap Code	WVDC			WVDC			WVDC			WVDC			WVDC			
		50	100	200	50	100	200	50	100	200	50	100	200	50	100	200	
100pF	101				■	■	■										
120	121				■	■	■										
150	151				■	■	■										
180	181				■	■	■										
220	221				■	■	■										
270	271				■	■	■	■	■	■							
330	331				■	■	■	■	■	■							
390	391				■	■	■	■	■	■							
470	471				■	■	■	■	■	■							
560	561				■	■	■	■	■	■							
680	681				■	■	■	■	■	■	■	■	■				
820	821				■	■	■	■	■	■	■	■	■				
1000	102	■	■	■	■	■	■	■	■	■	■	■	■				
1200	122	■	■	■	■	■	■	■	■	■	■	■	■				
1500	152	■	■	■	■	■	■	■	■	■	■	■	■				
1800	182	■	■	■	■	■	■	■	■	■	■	■	■				
2200	222	■	■	■	■	■	■	■	■	■	■	■	■				
2700	272	■	■	■	■	■	■	■	■	■	■	■	■				
3300	332	■	■	■	■	■	■	■	■	■	■	■	■				
3900	392	■	■	■	■	■	■	■	■	■	■	■	■				
4700	472	■	■	■	■	■	■	■	■	■	■	■	■				
5600	562	■	■	■	■	■	■	■	■	■	■	■	■				
6800	682	■	■	■	■	■	■	■	■	■	■	■	■				
8200	822	■	■	■	■	■	■	■	■	■	■	■	■				
.010uF	103	■	■	■	■	■	■	■	■	■	■	■	■				
.012	123	■	■	■	■	■	■	■	■	■	■	■	■				
.015	153	■	■	■	■	■	■	■	■	■	■	■	■				
.018	183	■	■	■	■	■	■	■	■	■	■	■	■				
.022	223	■	■		■	■	■	■	■	■	■	■	■				
.027	273				■	■	■	■	■	■	■	■	■				
.033	333				■	■	■	■	■	■	■	■	■				
.039	393				■	■	■	■	■	■	■	■	■				
.047	473				■	■	■	■	■	■	■	■	■				
.056	563							■	■	■	■	■	■				
.068	683							■	■		■	■	■				
.082	823							■	■		■	■	■	■	■		
.10	104							■	■		■	■	■	■	■	■	
.12	124							■	■		■	■	■	■	■	■	
.15	154							■	■		■	■	■	■	■	■	
.18	184							■	■		■	■	■	■	■	■	
.22	224							■	■		■	■	■	■	■	■	
.27	274							■	■		■	■	■	■	■	■	
.33	334							■	■		■	■	■	■	■	■	
.39	394							■	■		■	■	■	■	■	■	
.47	474							■	■		■	■	■	■	■	■	
.56	564							■	■		■	■	■	■	■	■	
.68	684							■	■		■	■	■	■	■	■	
.82	824							■	■		■	■	■	■	■		
1.0	105							■	■		■	■	■	■	■		
1.2	125										■	■	■				
1.5	155										■	■	■				
1.8	185										■	■	■				
2.2	225										■	■					
2.7	275										■	■					
3.3	335										■	■					
3.9	395										■	■					
4.7	475										■	■					

© KEMET Electronics Corporation • P.O. Box 5928 • Greenville, SC 29606 (864) 963-6300 • www.kemet.com

HIGH TEMPERATURE (+200ºC), HIGH VOLTAGE RADIAL CERAMIC CAPACITORS HV SERIES

FEATURES


The HV series not only withstands high temperatures (200°C) , but also offers high voltage (500-4000 VDC)

To be used in robust applications

- Down Hole
- Industrial
- Harsh Environments

NOTE:
Other tolerances, higher capacitance values, voltages, or special package configurations are available upon request.

CAPACITOR OUTLINE DRAWING



DIMENSIONS

Style	Sizes in Inches (mm) max.			Lead Spacing ±0.030 (S)
	Length (L)	Height (H)	Thickness (T)	
HV10	.250 (6.35)	.220 (5.59)	.150 (3.81)	.170 (4.32)
HV11	.320 (8.13)	.300 (7.62)	.250 (6.35)	.200 (5.08)
HV12	.420 (10.67)	.400 (10.16)	.250 (6.35)	.300 (7.62)
HV13	.520 (13.21)	.500 (12.70)	.300 (7.62)	.400 (10.16)
HV14	.620 (15.75)	.500 (12.70)	.300 (7.62)	.500 (12.70)
HV15	.720 (18.29)	.700 (17.78)	.300 (7.62)	.600 (15.24)
HV16	.820 (20.83)	.700 (17.78)	.350 (8.89)	.700 (17.78)

PART NUMBER AND ORDERING INFORMATION

10 HV12 B 472 K C M

VOLTAGE
05=500V
10=1000V
20=2000V
30=3000V
40=4000V

STYLE
HV12, etc

TEMPERATURE COEFFICIENT
B, W=X7R type
N=C0G (NP0)

CAPACITANCE VALUE
First two digits are significant, last digit is number of zeros, i.e., 472=4700pF

TOLERANCE
J=±5%
K=±10%
M=±20%
Other tolerances available upon request

OPTIONAL COPPER LEAD
Solder coated. Add to part number only if required

GROUP A SCREENING*
Add to part number if required
*MIL-PRF-49467 (Subgroup 1) except Corona

MARKING

(HV10, HV11)
472M
KEC
Date Code

(All other sizes)
HV12B472M
1kV
KEC
Date Code


© KEMET Electronics Corporation • P.O. Box 5928 • Greenville, SC 29606 (864) 963-6300 • www.kemet.com

COG DIELECTRIC

STYLE COG		HV10			HV11				HV12				HV13				HV14					HV15					HV16				
	L max	.250 (6.35)			.320 (8.13)				.420 (10.67)				.520 (13.21)				.620 (15.75)					.720 (18.29)					.820 (20.83)				
	H max	.220 (5.59)			.300 (7.62)				.400 (10.16)				.500 (12.70				.500 (12.70					.700 (17.78)					.700 (17.78)				
	W max	.150 (3.81)			.250 (6.35)				.250 (6.35)				.300 (7.62)				.300 (7.62)					.300 (7.62)					.350 (8.89)				
	S ± .030	.170 (4.32			.200 (5.08)				.300 (7.62)				.400 (10.16)				.500 (12.70					.600 (15.24)					.700 (17.78)				
	Lead Dia. +.004/-.002	.025 (.635)			.025 (.635)				.025 (.635)				.025 (.635)				.025 (.635)					.025 (.635)					.025 (.635)				
	Cap Code	WVDC			WVDC				WVDC				WVDC				WVDC					WVDC					WVDC				
Cap	pF	500	1k	2k	500	1k	2k	3k	500	1k	2k	3k	500	1k	2k	3k	500	1k	2k	3k	4k	500	1k	2k	3k	4k	500	1k	2k	3k	4k
12pF	120			■																											
15	150			■																											
18	180			■																	■										
22	220			■			■	■													■										
27	270	■	■	■			■	■			■	■									■					■					
33	330	■	■	■			■	■			■	■									■					■					
39	390	■	■	■	■	■	■	■			■	■									■					■					
47	470	■	■	■	■	■	■	■	■	■	■	■			■	■					■					■					■
56	560	■	■	■	■	■	■	■	■	■	■	■			■	■					■					■					■
68	680	■	■	■	■	■	■	■	■	■	■	■			■	■					■					■					■
82	820	■	■	■	■	■	■	■	■	■	■	■			■	■					■					■					■
100	101	■	■	■	■	■	■	■	■	■	■	■			■	■			■	■	■					■					■
120	121	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■			■	■	■					■					■
150	151	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■			■	■	■			■	■	■					■
180	181	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■			■	■	■			■	■	■					■
220	221	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■			■	■	■					■
270	271	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■			■	■	■			■	■	■
330	331	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■			■	■	■			■	■	■
390	391	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■			■	■	■
470	471	■	■		■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
560	561	■	■		■	■	■		■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
680	681	■	■		■	■	■		■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
820	821	■	■		■	■	■		■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
1000	102	■	■		■	■	■		■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
1200	122	■			■	■			■	■	■		■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
1500	152	■			■	■			■	■	■		■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
1800	182				■	■			■	■			■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
2200	222				■				■	■			■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
2700	272								■	■			■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
3300	332								■				■	■	■		■	■	■	■		■	■	■	■		■	■	■	■	■
3900	392												■	■			■	■	■			■	■	■	■		■	■	■	■	■
4700	472												■	■			■	■				■	■	■			■	■	■	■	■
5600	562												■				■	■				■	■				■	■	■	■	■
6800	682																■	■				■	■				■	■	■	■	
8200	822																■					■	■				■	■	■	■	
.010uF	103																					■	■				■	■	■		
.012	123																										■	■	■		
.015	153																										■	■			

© KEMET Electronics Corporation • P.O. Box 5928 • Greenville, SC 29606 (864) 963-6300 • www.kemet.com

CAPACITOR OUTLINE DRAWING



DIMENSIONS

Style	Sizes in Inches (mm) max.			Lead Spacing ±0.030 (S)
	Length (L)	Height (H)	Thickness (T)	
HV20	.250 (6.35)	.220 (5.59)	.200 (5.08)	.170 (4.32)
HV21	.320 (8.13)	.280 (7.11)	.250 (6.35)	.220 (5.59)
HV22	.370 (9.40)	.300 (7.62)	.250 (6.35)	.275 (6.98)
HV23	.470 (11.94)	.400 (10.16)	.270 (6.89)	.375 (9.52)
HV24	.570 (14.48)	.500 (12.70)	.270 (6.89)	.475 (12.06)
HV25	.670 (17.02)	.600 (15.24)	.270 (6.89)	.575 (14.60)
HV26	.770 (19.56)	.720 (18.29)	.270 (6.89)	.675 (17.14)
HV30	.450 (11.43)	.220 (5.59)	.200 (5.08)	.300 (7.62)
HV31	.550 (13.97)	.280 (7.11)	.250 (6.35)	.400 (10.16)
HV33	.850 (21.59)	.400 (10.16)	.270 (6.89)	.700 (17.78)
HV34	1.050 (26.67)	.500 (12.70)	.270 (6.89)	.975 (24.76)
HV35	1.250 (31.75)	.600 (15.24)	.270 (6.89)	1.175 (29.84)
HV36	1.450 (36.83)	.720 (18.29)	.270 (6.89)	1.375 (34.92)

PART NUMBER AND ORDERING INFORMATION

10 HV23 N 102 K M

VOLTAGE
05 = 500V
10 = 1000V
20 = 2000V
30 = 3000V
40 = 4000V
50 = 5000V
75 = 7500V
100 = 10000V

STYLE
HV23, etc.

DIELECTRIC MATERIAL
N = COG (NPO)
B = X7R

GROUP A SCREENING
Add to part number only if required MIL-PRF-49467 (subgroup1) except Corona

TOLERANCE
COG
J=±5%
K=±10%
M=±20%
X7R
K=±10%
M=±20%
P=0/+100%
Z= -20/+80%
Other tolerances available upon request

CAPACITANCE VALUE
First two digits are significant, last digit is number of zeros, i.e., 102=1000pF

MARKING

(HV20, HV21)	(All Other Sizes)
103K	HV24A103K
1 kV	1 kV
KEC	KEC
Date Code	Date Code

© KEMET Electronics Corporation • P.O. Box 5928 • Greenville, SC 29606 (864) 963-6300 • www.kemet.com

COG DIELECTRIC

STYLE COG		HV20				HV21				HV22				HV23					HV24						HV25						HV26					
	W max	.250 (6.35)				.320 (8.13)				.370(9.40)				.470 (11.94)					.570 (14.48)						.670 (17.02)						.770 (19.56)					
	L max	.220 (5.59)				.280 (7.11)				.300 (7.62)				.400 (10.16)					.500 (12.70)						.600 (15.24)						.720 (18.29)					
	T max	.200 (5.08)				.250 (6.35)				.250 (6.35)				.270 (6.86)					.270 (6.86)						.270 (6.86)						.270 (6.86)					
	S ±.030	.170 (4.32)				.220 (5.59)				.275 (6.98)				.375 (9.52)					.475 (12.06)						.575 (14.60)						.675 (17.14)					
	Lead Dia. +.004/-.002	.025 (..635)				.025 (..635)				.025 (..635)				.025 (.635)					.025 (.635)						.025 (.635)						.025 (.635)					
Cap	Cap Code	WVDC				WVDC				WVDC				WVDC					WVDC						WVDC						WVDC					
	pF	500	1k	2k	3k	500	1k	2k	3k	500	1k	2k	3k	500	1k	2k	3k	4k	500	1k	2k	3k	4k	5k	500	1k	2k	3k	4k	5k	500	1k	2k	3k	4k	5k
12pF	120			■	■																															
15	150			■	■																															
18	180			■	■																		■	■												
22	220			■	■			■	■														■	■												
27	270	■	■	■	■			■	■			■	■					■					■	■					■	■						
33	330	■	■	■	■			■	■			■	■					■					■	■					■	■						
39	390	■	■	■	■	■	■	■	■			■	■					■					■	■					■	■						
47	470	■	■	■	■	■	■	■	■	■	■	■	■			■	■	■					■	■					■	■				■	■	
56	560	■	■	■	■	■	■	■	■	■	■	■	■			■	■	■					■	■					■	■				■	■	
68	680	■	■	■	■	■	■	■	■	■	■	■	■			■	■	■					■	■					■	■				■	■	
82	820	■	■	■	■	■	■	■	■	■	■	■	■			■	■	■					■	■					■	■				■	■	
100	101	■	■	■	■	■	■	■	■	■	■	■	■			■	■	■			■	■	■	■					■	■				■	■	
120	121	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■			■	■	■	■					■	■				■	■	
150	151	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■			■	■	■	■			■	■	■	■				■	■	
180	181	■	■	■		■	■	■	■	■	■	■	■	■	■	■	■	■			■	■	■	■			■	■	■	■				■	■	
220	221	■	■	■		■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■			■	■	■	■				■	■	
270	271	■	■	■		■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■			■	■	■	■			■	■	■	■
330	331	■	■	■		■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■			■	■	■	■			■	■	■	■
390	391	■	■	■		■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■			■	■	■	■
470	471	■	■	■		■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
560	561	■	■	■		■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
680	681	■	■	■		■	■	■		■	■	■		■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
820	821	■	■			■	■	■		■	■	■		■	■	■	■		■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
1000	102	■	■			■	■			■	■	■		■	■	■	■		■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
1200	122	■	■			■	■			■	■	■		■	■	■	■		■	■	■	■	■		■	■	■	■	■	■	■	■	■	■	■	■
1500	152	■	■			■	■			■	■			■	■	■	■		■	■	■	■	■		■	■	■	■	■	■	■	■	■	■	■	■
1800	182	■				■	■			■	■			■	■	■			■	■	■	■			■	■	■	■	■	■	■	■	■	■	■	■
2200	222	■				■	■			■	■			■	■	■			■	■	■	■			■	■	■	■	■	■	■	■	■	■	■	■
2700	272	■				■	■			■	■			■	■	■			■	■	■	■			■	■	■	■	■	■	■	■	■	■	■	■
3300	332	■				■	■			■	■			■	■	■			■	■	■	■			■	■	■				■	■	■	■	■	
3900	392	■				■	■			■	■			■	■				■	■	■	■			■	■	■				■	■	■	■	■	
4700	472	■				■				■	■			■	■				■	■	■				■	■	■				■	■	■	■		
5600	562					■				■	■			■	■				■	■	■				■	■	■				■	■	■	■		
6800	682					■				■	■			■	■				■	■	■				■	■	■				■	■	■	■		
8200	822					■				■				■	■				■	■					■	■	■				■	■	■	■		
.010uF	103									■				■	■				■	■					■	■	■				■	■	■			
.012	123													■	■				■	■					■	■					■	■	■			
.015	153													■	■				■	■					■	■					■	■	■			
.018	183													■	■				■	■					■	■					■	■	■			
.022	223													■					■	■					■	■					■	■	■			
.027	273																		■	■					■	■					■	■				
.033	333																		■	■					■	■					■	■				
.039	393																		■						■	■					■	■				
.047	473																		■						■	■					■	■				
.056	563																		■						■						■	■				
.068	683																								■						■	■				
.082	823																								■						■					
.10	104																														■					

© KEMET Electronics Corporation • P.O. Box 5928 • Greenville, SC 29606 (864) 963-6300 • www.kemet.com

COG DIELECTRIC

STYLE COG		HV30					HV31						HV33							HV34								HV35								HV36							
	W max	.450 (11.43)					.550 (13.97)						.850 (21.59)							1.050 (26.67)								1.250 (31.75)								1.450 (36.83)							
	L max	.220 (5.59)					.280 (7.11)						.400 (10.16)							.500 (12.70)								.600 (15.24)								.720 (18.29)							
	T max	.200 (5.08)					.250 (6.35)						.270 (6.89)							.270 (6.89)								.270 (6.89)								.270 (6.89)							
	S ±.030	.300 (7.62)					.400 (10.16)						.700 (17.78)							.975 (24.76)								1.175 (29.84)								1.375 (34.92)							
	Lead Dia. +.004/-.002	.025 (.635)					.025 (.635)						.025 (.635)							.025 (.635)								.025 (.635)								.025 (.635)							
	Cap Code	WVDC					WVDC						WVDC							WVDC								WVDC								WVDC							
Cap	pF	500	1k	2k	3k	4k	500	1k	2k	3k	4k	5k	500	1k	2k	3k	4k	5k	7k	500	1k	2k	3k	4k	5k	7k	10k	500	1k	2k	3k	4k	5k	7k	10k	500	1k	2k	3k	4k	5k	7k	10k
10pF	100					■					■	■							■																								
12	120					■					■	■							■																								
15	150			■	■	■					■	■							■																								
18	180			■	■	■					■	■							■						■	■																	
22	220			■	■	■					■	■							■						■	■																	
27	270			■	■	■			■	■	■	■					■	■	■						■	■																	
33	330			■	■	■			■	■	■	■					■	■	■						■	■									■	■							
39	390			■	■	■			■	■	■	■					■	■	■						■	■									■	■							
47	470			■	■	■			■	■	■	■					■	■	■					■	■	■									■	■							
56	560			■	■	■			■	■	■	■					■	■	■					■	■	■									■	■					■	■
68	680	■	■	■	■	■			■	■	■	■			■	■	■	■	■					■	■	■									■	■					■	■
82	820	■	■	■	■	■	■	■	■	■	■	■			■	■	■	■	■					■	■	■							■	■	■	■					■	■
100	101	■	■	■	■	■	■	■	■	■	■	■			■	■	■	■	■					■	■	■							■	■	■	■					■	■
120	121	■	■	■	■	■	■	■	■	■	■	■			■	■	■	■	■			■	■	■	■	■							■	■	■	■					■	■
150	151	■	■	■	■	■	■	■	■	■	■	■			■	■	■	■	■			■	■	■	■	■							■	■	■	■					■	■
180	181	■	■	■	■	■	■	■	■	■	■	■			■	■	■	■	■			■	■	■	■	■							■	■	■	■					■	■
220	221	■	■	■	■	■	■	■	■	■	■	■			■	■	■	■	■			■	■	■	■	■						■	■	■	■	■				■	■
270	271	■	■	■	■		■	■	■	■	■	■			■	■	■	■	■			■	■	■	■	■						■	■	■	■	■				■	■
330	331	■	■	■	■		■	■	■	■	■	■	■	■	■	■	■	■	■			■	■	■	■	■						■	■	■	■	■				■	■
390	391	■	■	■			■	■	■	■	■		■	■	■	■	■	■	■			■	■	■	■	■						■	■	■	■	■				■	■
470	471	■	■	■			■	■	■	■	■		■	■	■	■	■	■	■	■	■	■	■	■	■	■						■	■	■	■	■				■	■
560	561	■	■	■			■	■	■	■	■		■	■	■	■	■	■		■	■	■	■	■	■	■						■	■	■	■	■				■	■
680	681	■	■	■			■	■	■	■			■	■	■	■	■	■		■	■	■	■	■	■	■		■	■	■	■	■	■	■	■			■	■	■	■	■
820	821	■	■	■			■	■	■	■			■	■	■	■	■	■		■	■	■	■	■	■	■		■	■	■	■	■	■	■	■			■	■	■	■	■
1000	102	■	■	■			■	■	■	■			■	■	■	■	■	■		■	■	■	■	■	■			■	■	■	■	■	■	■	■	■	■	■	■	■	■
1200	122	■	■				■	■	■	■			■	■	■	■	■			■	■	■	■	■	■			■	■	■	■	■	■	■	■	■	■	■	■	■	■
1500	152	■	■				■	■	■	■			■	■	■	■	■			■	■	■	■	■	■			■	■	■	■	■	■	■		■	■	■	■	■	■	■
1800	182	■	■				■	■	■	■			■	■	■	■				■	■	■	■	■	■			■	■	■	■	■	■			■	■	■	■	■	■	■
2200	222	■	■				■	■	■	■			■	■	■	■				■	■	■	■	■	■			■	■	■	■	■	■			■	■	■	■	■	■	■
2700	272	■	■				■	■					■	■	■	■				■	■	■	■	■				■	■	■	■	■	■			■	■	■	■	■	■	
3300	332	■	■				■	■					■	■	■	■				■	■	■	■	■				■	■	■	■	■	■			■	■	■	■	■	■	
3900	392	■	■				■	■					■	■	■	■				■	■	■	■					■	■	■	■	■	■			■	■	■	■	■	■	
4700	472	■	■				■	■					■	■	■	■				■	■	■	■					■	■	■	■	■				■	■	■	■	■	■	
5600	562	■					■	■					■	■	■					■	■	■	■					■	■	■	■	■				■	■	■	■	■	■	
6800	682	■					■	■					■	■	■					■	■	■						■	■	■	■					■	■	■	■	■		
8200	822	■					■	■					■	■	■					■	■	■						■	■	■	■					■	■	■	■	■		
.010uF	103	■					■	■					■	■	■					■	■	■						■	■	■	■					■	■	■	■			
.012	123	■					■						■	■						■	■	■						■	■	■	■					■	■	■	■			
.015	153	■					■						■	■						■	■	■						■	■	■	■					■	■	■	■			
.018	183						■						■	■						■	■							■	■	■						■	■	■	■			
.022	223						■						■	■						■	■							■	■	■						■	■	■				
.027	273						■						■	■						■	■							■	■							■	■	■				
.033	333												■	■						■	■							■	■							■	■					
.039	393												■	■						■	■							■	■							■	■	■				
.047	473												■	■						■	■							■	■							■	■					
.056	563												■	■						■	■							■	■							■	■					
.068	683												■	■						■								■	■							■	■					
.082	823												■							■								■	■							■	■					
.10	104												■							■								■	■							■	■					
.12	124												■							■								■								■	■					
.15	154																			■								■								■	■					
.18	184																			■								■								■						
.22	224																			■								■								■						
.27	274																																			■						
.33	334																																			■						

© KEMET Electronics Corporation • P.O. Box 5928 • Greenville, SC 29606 (864) 963-6300 • www.kemet.com

X7R DIELECTRIC

STYLE X7R		HV20			HV21				HV22				HV23					HV24						HV25						HV26					
	W max	.250 (6.35)			.320 (8.13)				.370.(9.40)				.470 (11.94)					.570 (14.48)						.670 (17.02)						.770 (19.56)					
	L max	.220 (5.59)			.280 (7.11)				.300 (7.62)				.400 (10.16)					.500 (12.70)						.600 (15.24)						.720 (18.29)					
	T max	.200 (5.08)			.250 (6.35)				.250 (6.35)				.270 (6.86)					.270 (6.86)						.270 (6.86)						.270 (6.86)					
	S ±.030	.170 (4.32)			.220 (5.59)				.275 (6.98)				.375 (9.52)					.475 (12.06)						.575 (14.60)						.675 (17.14)					
	Lead Dia. +.004/-.002	.025 (.635)			.025 (.635)				.025 (.635)				.025 (.635)					.025 (.635)						.025 (.635)						.025 (.635)					
	Cap Code	WVDC			WVDC				WVDC				WVDC					WVDC						WVDC						WVDC					
Cap	pF	500	1k	2k	500	1k	2k	3k	500	1k	2k	3k	500	1k	2k	3k	4k	500	1k	2k	3k	4k	5k	500	1k	2k	3k	4k	5k	500	1k	2k	3k	4k	5k
270pF	271			■													■																		
330	331			■													■																		
390	391			■													■																		
470	471			■													■					■	■												
560	561			■			■	■									■					■	■												
680	681	■	■	■			■	■			■	■					■					■	■					■	■						
820	821	■	■	■			■	■			■	■					■					■	■					■	■						
1000	102	■	■	■			■	■			■	■					■					■	■					■	■						
1200	122	■	■	■	■	■	■	■	■	■	■	■			■	■	■					■	■					■	■				■	■	
1500	152	■	■	■	■	■	■	■	■	■	■	■			■	■	■					■	■					■	■				■	■	
1800	182	■	■	■	■	■	■	■	■	■	■	■			■	■	■					■	■					■	■				■	■	
2200	222	■	■	■	■	■	■	■	■	■	■	■			■	■	■					■	■					■	■				■	■	
2700	272	■	■	■	■	■	■	■	■	■	■	■			■	■	■			■	■	■	■					■	■				■	■	
3300	332	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■			■	■	■	■					■	■				■	■	
3900	392	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■			■	■	■	■			■	■	■	■				■	■	
4700	472	■	■		■	■	■		■	■	■	■	■	■	■	■	■			■	■	■	■			■	■	■	■				■	■	
5600	562	■	■		■	■	■		■	■	■		■	■	■	■	■			■	■	■	■			■	■	■	■				■	■	
6800	682	■	■		■	■	■		■	■	■		■	■	■	■	■	■	■	■	■	■	■			■	■	■	■			■	■	■	
8200	822	■	■		■	■	■		■	■	■		■	■	■	■		■	■	■	■	■				■	■	■	■			■	■	■	
.010uF	103	■	■		■	■	■		■	■	■		■	■	■	■		■	■	■	■	■		■	■	■	■	■	■			■	■	■	
.012	123	■	■		■	■	■		■	■	■		■	■	■	■		■	■	■	■			■	■	■	■	■				■	■	■	
.015	153	■	■		■	■			■	■	■		■	■	■	■		■	■	■	■			■	■	■	■	■		■	■	■	■	■	■
.018	183	■	■		■	■			■	■	■		■	■	■			■	■	■	■			■	■	■	■			■	■	■	■	■	
.022	223	■	■		■	■			■	■			■	■	■			■	■	■	■			■	■	■	■			■	■	■	■	■	
.027	273	■			■	■			■	■			■	■	■			■	■	■	■			■	■	■	■			■	■	■	■	■	
.033	333	■			■	■			■	■			■	■	■			■	■	■	■			■	■	■	■			■	■	■	■		
.039	393	■			■	■			■	■			■	■				■	■	■				■	■	■	■			■	■	■	■		
.047	473	■			■	■			■	■			■	■				■	■	■				■	■	■				■	■	■	■		
.056	563	■			■	■			■	■			■	■				■	■	■				■	■	■				■	■	■	■		
.068	683	■			■	■			■	■			■	■				■	■	■				■	■	■				■	■	■	■		
.082	823	■			■				■	■			■	■				■	■					■	■	■				■	■	■	■		
.10	104				■				■				■	■				■	■					■	■	■				■	■	■			
.12	124				■				■				■	■				■	■					■	■					■	■	■			
.15	154				■				■				■	■				■	■					■	■					■	■	■			
.18	184				■				■				■	■				■	■					■	■					■	■	■			
.22	224								■				■	■				■	■					■	■					■	■				
.27	274												■	■				■	■					■	■					■	■				
.33	334												■					■	■					■	■					■	■				
.39	394												■					■	■					■	■					■	■				
.47	474												■					■	■					■	■					■	■				
.56	564												■					■						■	■					■	■				
.68	684																	■						■	■					■	■				
.82	824																	■						■						■	■				
1.0	105																	■						■						■	■				
1.2	125																	■						■						■					
1.5	155																							■						■					
1.8	185																							■						■					
2.2	225																													■					

© KEMET Electronics Corporation • P.O. Box 5928 • Greenville, SC 29606 (864) 963-6300 • www.kemet.com

X7R DIELECTRIC


STYLE X7R		HV30					HV31						HV33							HV34								HV35								HV36							
	W max	.450 (11.43)					.550 (13.97)						.850 (21.59)							1.050 (26.67)								1.250 (31.75)								1.450 (36.83)							
	L max	.220 (5.59)					.280 (7.11)						.400 (10.16)							.500 (12.70)								.600 (15.24)								.720 (18.29)							
	T max	.200 (5.08)					.250 (6.35)						.270 (6.89)							.270 (6.89)								.270 (6.89)								.270 (6.89)							
	S ±.030	.300 (7.62)					.400 (10.16)						.700 (17.78)							.975 (24.76)								1.175 (29.84)								1.375 (34.92)							
	Lead Dia. +.004/-.002	.025 (.635)					.025 (.635)						.025 (.635)							.025 (.635)								.025 (.635)								.025 (.635)							
	Cap Code	WVDC					WVDC						WVDC							WVDC								WVDC								WVDC							
Cap	pF	50	1k	2k	3k	4k	500	1k	2k	3k	4k	5k	500	1k	2k	3k	4k	5k	7k	500	1k	2k	3k	4k	5k	7k	10k	500	1k	2k	3k	4k	5k	7k	10k	500	1k	2k	3k	4k	5k	7.5k	10k
150pF	151					■													■							■	■							■	■							
180	181					■													■							■	■							■	■							
220	221					■													■							■	■							■	■							
270	271					■					■	■							■							■	■							■	■							
330	331					■					■	■							■							■	■							■	■							
390	391			■	■	■					■	■							■							■	■							■	■							
470	471			■	■	■					■	■							■						■	■	■							■	■							
560	561			■	■	■					■	■							■						■	■	■							■	■							
680	681			■	■	■			■	■	■	■				■	■		■						■	■	■							■	■							
820	821			■	■	■			■	■	■	■				■	■		■						■	■	■						■	■	■	■							
1000	102			■	■	■			■	■	■	■				■	■		■						■	■	■						■	■	■	■							
1200	122			■	■	■			■	■	■	■				■	■		■					■	■	■	■						■	■	■	■					■	■	
1500	152			■	■				■	■	■	■				■	■		■					■	■	■	■						■	■	■	■					■	■	
1800	182	■	■	■	■				■	■	■	■			■	■	■		■				■	■	■	■	■					■	■	■	■					■	■	
2200	222	■	■	■	■				■	■	■	■			■	■	■		■				■	■	■	■	■				■	■	■	■	■					■	■	
2700	272	■	■	■			■	■	■	■	■	■			■	■	■		■				■	■	■	■	■				■	■	■	■	■					■	■	
3300	332	■	■	■			■	■	■	■	■				■	■	■		■			■	■	■	■	■	■			■	■	■	■	■	■				■	■	■	
3900	392	■	■	■			■	■	■	■	■				■	■	■		■			■	■	■	■	■	■			■	■	■	■	■	■				■	■	■	
4700	472	■	■	■			■	■	■	■	■				■	■	■		■			■	■	■	■	■				■	■	■	■	■	■				■	■	■	
5600	562	■	■	■			■	■	■	■					■	■	■		■			■	■	■	■	■					■	■	■	■	■				■	■	■	
6800	682	■	■	■			■	■	■	■					■	■	■		■			■	■	■	■	■					■	■	■	■					■	■	■	
8200	822	■	■	■			■	■	■	■					■	■	■		■			■	■	■	■						■	■	■	■					■	■	■	
.010uF	103	■	■				■	■	■				■	■	■	■	■					■	■	■	■						■	■	■	■					■	■	■	
.012	123	■	■				■	■	■				■	■	■	■	■			■	■	■	■	■	■						■	■	■						■	■	■	
.015	153	■	■				■	■	■				■	■	■	■				■	■	■	■	■	■						■	■	■						■	■	■	
.018	183	■	■				■	■	■				■	■	■	■				■	■	■	■	■	■				■	■	■	■	■						■	■	■	
.022	223	■	■				■	■	■				■	■	■	■				■	■	■	■	■	■				■	■	■	■	■						■	■		
.027	273	■	■				■	■					■	■	■	■				■	■	■	■	■					■	■	■	■	■				■	■	■	■	■	
.033	333	■	■				■	■					■	■	■					■	■	■	■	■					■	■	■	■	■				■	■	■	■	■	
.039	393	■	■				■	■					■	■	■					■	■	■	■	■					■	■	■	■	■				■	■	■	■	■	
.047	473	■	■				■	■					■	■	■					■	■	■	■	■					■	■	■	■	■				■	■	■	■		
.056	563	■	■				■	■					■	■	■					■	■	■	■	■					■	■	■	■					■	■	■	■		
.068	683	■					■	■					■	■	■					■	■	■							■	■	■	■					■	■	■	■		
.082	823	■					■	■					■	■	■					■	■	■							■	■	■	■					■	■	■	■		
.10	104	■					■	■					■	■						■	■	■							■	■	■						■	■	■	■		
.12	124	■					■	■					■	■						■	■	■							■	■	■						■	■	■	■		
.15	154	■					■	■					■	■						■	■	■							■	■	■						■	■	■			
.18	184	■					■						■	■						■	■								■	■	■						■	■	■			
.22	224	■					■						■	■						■	■								■	■	■						■	■	■			
.27	274						■						■	■						■	■								■	■	■						■	■	■			
.33	334						■						■	■						■	■								■	■							■	■	■			
.39	394						■						■	■						■	■								■	■							■	■	■			
.47	474												■	■						■	■								■	■							■	■				
.56	564												■	■						■	■								■	■							■	■				
.68	684												■	■						■	■								■	■							■	■				
.82	824												■							■	■								■	■							■	■				
1.0	105												■							■	■								■	■							■	■				
1.2	125												■							■									■	■							■	■				
1.5	155												■							■									■	■							■	■				
1.8	185																			■									■								■	■				
2.2	225																			■									■								■	■				
2.7	275																												■								■					
3.3	335																												■								■					
3.9	395																												■								■					
4.7	475																																				■					
5.6	565																																				■					

© KEMET Electronics Corporation • P.O. Box 5928 • Greenville, SC 29606 (864) 963-6300 • www.kemet.com

FEATURES

1. Electrical characteristics and environmental information on these parts may be obtained by referring to MIL-PRF-49467.
2. All parts are conformal coated multilayer ceramic.
3. Designed to provide excellent long-term reliability.
4. Parts are Group A screened per MIL-PRF-49467 which includes 100% Corona testing and meet all other specification requirements.
5. Designed for surface, sea and airborne military and commercial high-reliability applications.
6. No IR degradation over life.
7. BR (X7R) V/TC is -40% at rated voltage and BZ (X7R) V/TC is -40% at 60% rated voltage.
8. BX characteristic (-25%) on BR parts is approximately 52% rated voltage.
9. 100% Non-destructive test by means of CSAM inspection available. SLAM available by special order.

CAPACITOR OUTLINE DRAWING



DIMENSIONS

Style	Sizes in Inches (mm) max.			Lead Spacing ±0.030 (S)
	Length (L)	Height (H)	Thickness (W)	
HV60	.250 (6.35)	.220 (5.59)	.200 (5.08)	.170 (4.32)
HV61	.320 (8.13)	.280 (7.11)	.250 (6.35)	.220 (5.59)
HV62	.370 (9.40)	.300 (7.62)	.250 (6.35)	.275 (6.98)
HV63	.470 (11.94)	.400 (10.16)	.270 (6.86)	.375 (9.52)
HV64	.570 (14.48)	.500 (12.70)	.270 (6.86)	.475 (12.06)
HV65	.670 (17.02)	.600 (15.24)	.270 (6.86)	.575 (14.60)
HV66	.770 (19.56)	.720 (18.29)	.270 (6.86)	.675 (17.14)
HV68	1.300 (33.02)	.600 (15.24)	.270 (6.86)	1.175 (29.84)
HV69	1.500 (38.10)	.720 (18.29)	.270 (6.86)	1.375 (34.92)

PART NUMBER AND ORDERING INFORMATION

10 HV60 R 102 K C

Voltage
06 = 600V
10 = 1000V
20 = 2000V
30 = 3000V
40 = 4000V
50 = 5000V

Style
HV60, etc.

Dielectric
P = BP C0G (NP0)
R = BR (X7R)
Z = BZ (X7R)

Capacitance Value
First two digits are significant, last digit is number of zeros, i.e., 102=1000pF

Tolerance
(C0G only) J=±5%
K=±10%
M=±20%

C=CSAM
S= SLAM
Add to part number if required.

MARKING

(HV60, HV61)	(All Other Sizes)
102K	HV63R102K
1 kV	1 kV
KEC	KEC
Date Code	Date Code

© KEMET Electronics Corporation • P.O. Box 5928 • Greenville, SC 29606 (864) 963-6300 • www.kemet.com

COG DIELECTRIC

STYLE COG		HV60			HV61				HV62				HV63					HV64						HV65					HV66				
	W max	.250 (6.35)			.320 (8.13)				.370.(9.40)				.470 (11.94)					.570 (14.48)						.670 (17.02)					.770 (19.56)				
	L max	.220 (5.59)			.280 (7.11)				.300 (7.62)				.400 (10.16)					.500 (12.70)						.600 (15.24)					.720 (18.29)				
	T max	.200 (5.08)			.250 (6.35)				.250 (6.35)				.270 (6.86)					.270 (6.86)						.270 (6.86)					.270 (6.86)				
	S ±.030	.170 (4.32)			.220 (5.59)				.275 (6.98)				.375 (9.52)					.475 (12.06)						.575 (14.60)					.675 (17.14)				
	Lead Dia. +.004/-.002	.025 (.635)			.025 (.635)				.025 (.635)				.025 (.635)					.025 (.635)						.025 (.635)					.025 (.635)				
	Cap Code	WVDC			WVDC				WVDC				WVDC					WVDC						WVDC					WVDC				
Cap	pF	600	1k	2k	600	1k	2k	3k	600	1k	2k	3k	600	1k	2k	3k	4k	600	1k	2k	3k	4k	5k	1k	2k	3k	4k	5k	1k	2k	3k	4k	5k
12pF	120			■																													
15	150			■																													
18	180			■																													
22	220			■			■	■																									
27	270	■	■	■			■	■			■	■																					
33	330	■	■	■			■	■			■	■																					
39	390	■	■	■	■	■	■	■			■	■																					
47	470	■	■	■	■	■	■	■	■	■	■	■			■	■	■																
56	560	■	■	■	■	■	■	■	■	■	■	■			■	■	■																
68	680	■	■	■	■	■	■	■	■	■	■	■			■	■	■																
82	820	■	■	■	■	■	■	■	■	■	■	■			■	■	■																
100	101	■	■	■	■	■	■	■	■	■	■	■			■	■	■			■	■	■	■										
120	121	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■			■	■	■	■										
150	151	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■			■	■	■	■		■	■	■	■					
180	181	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■			■	■	■	■		■	■	■	■					
220	221	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■		■	■	■	■					
270	271	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■		■	■	■	■		■	■	■	■
330	331	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■		■	■	■	■		■	■	■	■
390	391	■	■		■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■		■	■	■	■
470	471	■	■		■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
560	561	■	■		■	■	■		■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
680	681	■	■		■	■	■		■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
820	821	■			■	■	■		■	■	■		■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
1000	102	■			■	■			■	■	■		■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
1200	122	■			■	■			■	■	■		■	■	■	■		■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
1500	152	■			■	■			■	■			■	■	■	■		■	■	■	■	■		■	■	■	■	■	■	■	■	■	■
1800	182	■			■	■			■	■			■	■	■			■	■	■	■	■		■	■	■	■	■	■	■	■	■	■
2200	222	■			■				■	■			■	■	■			■	■	■	■			■	■	■	■	■	■	■	■	■	■
2700	272	■			■				■	■			■	■				■	■	■	■			■	■	■	■		■	■	■	■	■
3300	332	■			■				■				■	■				■	■	■	■			■	■	■	■		■	■	■	■	■
3900	392	■			■				■				■	■				■	■	■				■	■	■			■	■	■	■	
4700	472	■			■				■				■	■				■	■	■				■	■	■			■	■	■	■	
5600	562	■			■				■				■					■	■					■	■				■	■	■		
6800	682				■				■				■					■	■					■	■				■	■	■		
8200	822				■				■				■					■	■					■					■	■			
.010uF	103				■				■				■					■	■					■					■	■			
.012	123				■				■				■					■						■					■				
.015	153								■				■					■						■					■				
.018	183												■					■											■				
.022	223												■					■											■				
.027	273												■					■											■				
.033	333												■					■															
.039	393												■					■															
.047	473																	■															
.056	563																	■															
.068	683																	■															

© KEMET Electronics Corporation • P.O. Box 5928 • Greenville, SC 29606 (864) 963-6300 • www.kemet.com

X7R DIELECTRIC

STYLE X7R		HV60			HV61				HV62				HV63					HV64						HV65					HV66					HV68			HV69		
	W max	.250 (6.35)			.320 (8.13)				.370.(9.40)				.470 (11.94)					.570 (14.48)						.670 (17.02)					.770 (19.56)					1.300 (33.02)			1.500 (38.10)		
	L max	.220 (5.59)			.280 (7.11)				.300 (7.62)				.400 (10.16)					.500 (12.70)						.600 (15.24)					.720 (18.29)					.600 (15.24)			.720 (18.29)		
	T max	.200 (5.08)			.250 (6.35)				.250 (6.35)				.270 (6.86)					.270 (6.86)						.270 (6.86)					.270 (6.86)					.270 (6.86)			.270 (6.86)		
	S ± .030	.170 (4.32)			.220 (5.59)				.275 (6.98)				.375 (9.52)					.475 (12.06)						.575 (14.60)					.675 (17.14)					1.175 (29.84)			1.375 (34.92)		
	Lead Dia. +.004/-.002	.025 (.635)			.025 (.635)				.025 (.635)				.025 (.635)					.025 (.635)						.025 (.635)					.025 (.635)					.025 (.635)			.025 (.635)		
	Cap Code	WVDC			WVDC				WVDC				WVDC					WVDC						WVDC					WVDC					WVDC			WVDC		
Cap	pF	600	1k	2k	600	1k	2k	3k	600	1k	2k	3k	600	1k	2k	3k	4k	600	1k	2k	3k	4k	5k	1k	2k	3k	4k	5k	1k	2k	3k	4k	5k	3k	4k	5k	3k	4k	5k
270pF	271			■													■																							
330	331			■													■																							
390	391			■													■																							
470	471			■													■					■	■																	
560	561			■			■	■									■					■	■																	
680	681	■	■	■			■	■			■	■					■					■	■				■	■												
820	821	■	■	■			■	■			■	■					■					■	■				■	■												
1000	102	■	■	■			■	■			■	■					■					■	■				■	■												
1200	122	■	■	■	■	■	■	■	■	■	■	■			■	■	■					■	■				■	■				■	■						
1500	152	■	■	■	■	■	■	■	■	■	■	■			■	■	■					■	■				■	■				■	■						
1800	182	■	■	■	■	■	■	■	■	■	■	■			■	■	■					■	■				■	■				■	■						
2200	222	■	■	■	■	■	■	■	■	■	■	■			■	■	■					■	■				■	■				■	■		■	■			
2700	272	■	■	■	■	■	■	■	■	■	■	■			■	■	■			■	■	■	■				■	■				■	■		■	■			
3300	332	■	■	■	■	■	■		■	■	■	■	■	■	■	■	■			■	■	■	■				■	■				■	■		■	■		■	■
3900	392	■	■		■	■	■		■	■	■	■	■	■	■	■	■			■	■	■	■		■	■	■	■	■				■	■		■	■		■	■
4700	472	■	■		■	■	■		■	■	■		■	■	■	■	■			■	■	■	■		■	■	■	■	■				■	■		■	■		■	■
5600	562	■	■		■	■	■		■	■	■		■	■	■	■	■			■	■	■	■		■	■	■	■	■				■	■	■	■	■		■	■
6800	682	■	■		■	■	■		■	■	■		■	■	■	■	■	■	■	■	■	■	■		■	■	■	■	■		■	■	■	■	■	■		■	■
8200	822	■	■		■	■			■	■	■		■	■	■	■		■	■	■	■	■			■	■	■	■	■		■	■	■	■	■	■	■	■	■
.010uF	103	■	■		■	■			■	■	■		■	■	■	■		■	■	■	■	■		■	■	■	■	■		■	■	■	■	■	■	■	■	■
.012	123	■			■	■			■	■			■	■	■	■		■	■	■	■			■	■	■	■			■	■	■	■	■	■	■	■	■
.015	153	■			■	■			■	■			■	■	■			■	■	■	■			■	■	■	■		■	■	■	■	■	■	■	■	■	■	■
.018	183	■			■				■	■			■	■	■			■	■	■	■			■	■	■			■	■	■	■		■	■	■	■	■	■
.022	223	■			■				■	■			■	■	■			■	■	■	■			■	■	■			■	■	■	■		■	■	■	■	■	■
.027	273	■			■				■				■	■	■			■	■	■				■	■	■			■	■	■	■		■	■		■	■	■
.033	333				■				■				■	■				■	■	■				■	■	■			■	■	■			■	■		■	■	■
.039	393				■				■				■	■				■	■	■				■	■				■	■	■			■	■		■	■	■
.047	473				■				■				■	■				■	■	■				■	■				■	■	■			■			■	■	■
.056	563				■				■				■	■				■	■	■				■	■				■	■	■			■			■	■	■
.068	683				■				■				■					■	■					■	■				■	■				■			■		
.082	823				■				■				■					■	■					■	■				■	■							■		
.10	104								■				■					■	■					■					■	■							■		
.12	124												■					■	■					■					■	■									
.15	154												■					■						■					■	■									
.18	184												■					■						■															
.22	224												■					■											■											
.27	274												■					■											■											
.33	334																	■											■											
.39	394																	■											■											
.47	474																	■											■											

© KEMET Electronics Corporation • P.O. Box 5928 • Greenville, SC 29606 (864) 963-6300 • www.kemet.com


HIGH VOLTAGE SPACE QUALITY MLC (-55° TO +125°C)

HS SERIES

FEATURES

1. Similar to NASA Spec. SSQ 21113 (1, 2 & 5kV).
2. Conforms to MIL-PRF-49467. (Group A Screening, Subgroup 1)
3. 100% Corona tested.
4. No IR degradation over life.
5. High density, low DF ceramic.
6. Conservative and proven design is recommended for non-repairable applications such as spacecraft.
7. CSAM inspections are available and is recommended for space applications. SLAM available by special order.
8. Burn-in in a non-contaminating inert fluid available.

CAPACITOR OUTLINE DRAWING



DIMENSIONS

Style	Sizes in Inches (mm) max.			Lead Spacing ±0.030 (S)
	Length (L)	Height (H)	Thickness (W)	
HS20	.250 (6.35)	.220 (5.59)	.200 (5.08)	.170 (4.32)
HS21	.320 (8.13)	.280 (7.11)	.250 (6.35)	.220 (5.59)
HS22	.370 (9.40)	.300 (7.62)	.250 (6.35)	.275 (6.98)
HS30	.450 (11.43)	.220 (5.59)	.200 (5.08)	.300 (7.62)
HS23	.470 (11.94)	.400 (10.16)	.270 (6.89)	.375 (9.52)
HS31	.550 (13.97)	.280 (7.11)	.250 (6.35)	.400 (10.16)
HS24	.570 (14.48)	.500 (12.70)	.270 (6.89)	.475 (12.06)
HS25	.670 (17.02)	.600 (15.24)	.270 (6.89)	.575 (14.60)
HS26	.770 (19.56)	.720 (18.29)	.270 (6.89)	.675 (17.14)
HS33	.850 (21.59)	.400 (10.16)	.270 (6.89)	.700 (17.78)
HS34	1.050 (26.67)	.500 (12.70)	.270 (6.89)	.975 (24.76)
HS35	1.250 (31.75)	.600 (15.24)	.270 (6.89)	1.175 (29.84)
HS36	1.450 (36.83)	.720 (18.29)	.270 (6.89)	1.375 (34.92)

PART NUMBER AND ORDERING INFORMATION

10 HS24 B 103 K C F

VOLTAGE
05 = 500V
10 = 1000V
20 = 2000V
30 = 3000V
40 = 4000V
50 = 5000V
75 = 7500V
100 = 10,000V

STYLE
HS24, etc.

DIELECTRIC
B = X7R
N = BP C0G (NP0)

CAPACITANCE VALUE
First two digits are significant, last digit is number of zeros, i.e., 103=10000pF

INERT LIQUID (BURN-IN)
Std. for ≥2kV;
Add "F" if required for 500V or 1kV parts

C=CSAM
S=SLAM
Add to part number if required.

TOLERANCE
J = ±5% (C0G only)
K = ±10%
M = ±20%
P = 0/+100%
Z = -20%/+80%

MARKING

(HS20, HV21)	(All Other Sizes)
103K	HS24B103K
1 kV	1 kV
KEC	KEC
Date Code	Date Code

© KEMET Electronics Corporation • P.O. Box 5928 • Greenville, SC 29606 (864) 963-6300 • www.kemet.com

COG DIELECTRIC

STYLE COG		HS20			HS21			HS22			HS23				HS24						HS25						HS26					
	W max	.250 (6.35)			.320 (8.13)			.370(9.40)			.470 (11.94)				.570 (14.48)						.670 (17.02)						.770 (19.56)					
	L max	.220 (5.59)			.280 (7.11)			.300 (7.62)			.400 (10.16)				.500 (12.70)						.600 (15.24)						.720 (18.29)					
	T max	.200 (5.08)			.250 (6.35)			.250 (6.35)			.270 (6.86)				.270 (6.86)						.270 (6.86)						.270 (6.86)					
	S ± .030	.170 (4.32)			.220 (5.59)			.275 (6.98)			.375 (9.52)				.475 (12.06)						.575 (14.60)						.675 (17.14)					
	Lead Dia. +.004/-.002	.025 (.635)			.025 (.635)			.025 (.635)			.025 (.635)				.025 (.635)						.025 (.635)						.025 (.635)					
	Cap Code	WVDC			WVDC			WVDC			WVDC				WVDC						WVDC						WVDC					
Cap	pF	500	1k	2k	500	1k	2k	500	1k	2k	500	1k	2k	3k	500	1k	2k	3k	4k	5k	500	1k	2k	3k	4k	5k	500	1k	2k	3k	4k	5k
10pF	100																															
12	120			■																												
15	150			■																												
18	180			■															■	■												
22	220			■			■												■	■												
27	270	■	■	■			■			■									■	■					■	■						
33	330	■	■	■			■			■									■	■					■	■						
39	390	■	■	■	■	■	■			■									■	■					■	■						
47	470	■	■	■	■	■	■	■	■	■			■	■					■	■					■	■					■	■
56	560	■	■	■	■	■	■	■	■	■			■	■					■	■					■	■					■	■
68	680	■	■	■	■	■	■	■	■	■			■	■					■	■					■	■					■	■
82	820	■	■	■	■	■	■	■	■	■			■	■					■	■					■	■					■	■
100	101	■	■	■	■	■	■	■	■	■			■	■			■	■	■	■					■	■					■	■
120	121	■	■	■	■	■	■	■	■	■	■	■	■	■			■	■	■	■					■	■					■	■
150	151	■	■	■	■	■	■	■	■	■	■	■	■	■			■	■	■	■			■	■	■	■					■	■
180	181	■	■	■	■	■	■	■	■	■	■	■	■	■			■	■	■	■			■	■	■	■					■	■
220	221	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■			■	■	■	■					■	■
270	271	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■			■	■	■	■			■	■	■	■
330	331	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■			■	■	■	■			■	■	■	■
390	391	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■			■	■	■	■
470	471	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
560	561	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
680	681	■	■		■	■	■	■	■	■	■	■	■	■	■	■	■	■	■		■	■	■	■	■	■	■	■	■	■	■	■
820	821	■	■		■	■	■	■	■	■	■	■	■	■	■	■	■	■	■		■	■	■	■	■	■	■	■	■	■	■	■
1000	102	■	■		■	■	■	■	■	■	■	■	■	■	■	■	■	■	■		■	■	■	■	■	■	■	■	■	■	■	■
1200	122	■	■		■	■	■	■	■	■	■	■	■	■	■	■	■	■			■	■	■	■	■	■	■	■	■	■	■	■
1500	152	■	■		■	■		■	■	■	■	■	■	■	■	■	■	■			■	■	■	■	■	■	■	■	■	■	■	■
1800	182	■	■		■	■		■	■		■	■	■	■	■	■	■	■			■	■	■	■	■		■	■	■	■	■	■
2200	222	■	■		■	■		■	■		■	■	■		■	■	■	■			■	■	■	■			■	■	■	■	■	■
2700	272	■	■		■	■		■	■		■	■	■		■	■	■	■			■	■	■	■			■	■	■	■	■	
3300	332	■			■	■		■	■		■	■			■	■	■	■			■	■	■	■			■	■	■	■		
3900	392	■			■	■		■	■		■	■			■	■	■	■			■	■	■	■			■	■	■	■		
4700	472	■			■	■		■	■		■	■			■	■	■				■	■	■	■			■	■	■	■		
5600	562				■	■		■	■		■	■			■	■	■				■	■	■	■			■	■	■	■		
6800	682				■			■			■	■			■	■					■	■	■	■			■	■	■	■		
8200	822				■			■			■	■			■	■					■	■	■				■	■	■	■		
.010uF	103				■			■			■	■			■	■					■	■	■				■	■	■	■		
.012	123				■			■			■	■			■	■					■	■					■	■	■			
.015	153										■	■			■	■					■	■					■	■	■			
.018	183										■	■			■	■					■	■					■	■				
.022	223										■				■	■					■	■					■	■				
.027	273										■				■	■					■	■					■	■				
.033	333										■				■	■					■	■					■	■				
.039	393														■						■	■					■	■				
.047	473														■						■	■					■	■				
.056	563														■						■						■	■				
.068	683																				■						■	■				
.082	823																				■						■					
.10	104																				■						■					
.12	124																										■					
.15	154																										■					

© KEMET Electronics Corporation • P.O. Box 5928 • Greenville, SC 29606 (864) 963-6300 • www.kemet.com

COG DIELECTRIC

STYLE COG		HS30				HS31						HS33						HS34							HS35								HS36							
	L max	.450 (11.43)				.550 (13.97)						.850 (21.59)						1.050 (26.67)							1.250 (31.75)								1.450 (36.83)							
	W max	.220 (5.08)				.280 (7.11)						.400 (10.16)						.500 (12.70)							.600 (15.24)								.720 (18.29)							
	T max	.200 (6.86)				.250 (6.35)						.270 (6.89)						.270 (6.89)							.270 (6.89)								.270 (6.89)							
	S ±.030	.300 (7.62)				.400 (10.16)						.700 (17.78)						.975 (24.76)							1.175 (29.84)								1.375 (34.92)							
	Lead Dia. +.004/-.002	.025 (.635)				.025 (.635)						.025 (.635)						.025 (.635)							.025 (.635)								.025 (.635)							
	Cap Code	WVDC				WVDC						WVDC						WVDC							WVDC								WVDC							
Cap	pF	500	1k	2k	3k	500	1k	2k	3k	4k	5k	500	1k	2k	3k	4k	5k	500	1k	2k	3k	4k	5k	7.5k	500	1k	2k	3k	4k	5k	7.5k	10k	500	1k	2k	3k	4k	5k	7.5k	10k
10pF	100																																								
12	120																																								
15	150																																								
18	180																																								
22	220																																								
27	270																																								
33	330																																								
39	390																																								
47	470																																								
56	560																																								
68	680																																								
82	820																																								
100	101																																								
120	121																																								
150	151																																								
180	181																																								
220	221																																								
270	271																																								
330	331																																								
390	391																																								
470	471																																								
560	561																																								
680	681																																								
820	821																																								
1000	102																																								
1200	122																																								
1500	152																																								
1800	182																																								
2200	222																																								
2700	272																																								
3300	332																																								
3900	392																																								
4700	472																																								
5600	562																																								
6800	682																																								
8200	822																																								
.010uF	103																																								
.012	123																																								
.015	153																																								
.018	183																																								
.022	223																																								
.027	273																																								
.033	333																																								
.039	393																																								
.047	473																																								
.056	563																																								
.068	683																																								
.082	823																																								
.10	104																																								
.12	124																																								
.15	154																																								
.18	184																																								

© KEMET Electronics Corporation • P.O. Box 5928 • Greenville, SC 29606 (864) 963-6300 • www.kemet.com

X7R DIELECTRIC

STYLE X7R		HS20			HS21			HS22			HS23				HS24					HS25						HS26					
	W max	.250 (6.35)			.320 (8.13)			.370(9.40)			.470 (11.94)				.570 (14.48)					.670 (17.02)						.770 (19.56)					
	L max	.220 (5.59)			.280 (7.11)			.300 (7.62)			.400 (10.16)				.500 (12.70)					.600 (15.24)						.720 (18.29)					
	T max	.200 (5.08)			.250 (6.35)			.250 (6.35)			.270 (6.86)				.270 (6.86)					.270 (6.86)						.270 (6.86)					
	S ±.030	.170 (4.32)			.220 (5.59)			.275 (6.98)			.375 (9.52)				.475 (12.06)					.575 (14.60)						.675 (17.14)					
	Lead Dia. +.004/-.002	.025 (.635)			.025 (.635)			.025 (.635)			.025 (.635)				.025 (.635)					.025 (.635)						.025 (.635)					
	Cap Code	WVDC			WVDC			WVDC			WVDC				WVDC					WVDC						WVDC					
Cap	pF	500	1k	2k	500	1k	2k	500	1k	2k	500	1k	2k	3k	500	1k	2k	3k	4k	500	1k	2k	3k	4k	5k	500	1k	2k	3k	4k	5k
270pF	271			■															■												
330	331			■															■												
390	391			■															■												
470	471			■															■												
560	561			■			■												■												
680	681	■	■	■			■			■									■					■	■						
820	821	■	■	■			■			■									■					■	■						
1000	102	■	■	■			■			■									■					■	■						
1200	122	■	■	■	■	■	■	■	■	■			■	■					■					■	■					■	■
1500	152	■	■		■	■	■	■	■	■			■	■					■					■	■					■	■
1800	182	■	■		■	■	■	■	■	■			■	■					■					■	■					■	■
2200	222	■	■		■	■	■	■	■	■			■	■					■					■	■					■	■
2700	272	■	■		■	■	■	■	■	■			■	■			■	■	■					■	■					■	■
3300	332	■	■		■	■	■	■	■	■	■	■	■	■			■	■	■					■	■					■	■
3900	392	■	■		■	■	■	■	■	■	■	■	■	■			■	■	■			■	■	■	■					■	■
4700	472	■	■		■	■	■	■	■	■	■	■	■	■			■	■	■			■	■	■	■					■	■
5600	562	■	■		■	■		■	■	■	■	■	■	■			■	■				■	■	■						■	■
6800	682	■	■		■	■		■	■	■	■	■	■		■	■	■	■				■	■	■					■	■	■
8200	822	■			■	■		■	■		■	■	■		■	■	■	■				■	■	■					■	■	■
.010uF	103	■			■	■		■	■		■	■	■		■	■	■	■		■	■	■	■						■	■	
.012	123	■			■	■		■	■		■	■	■		■	■	■	■		■	■	■	■						■	■	■
.015	153	■			■	■		■	■		■	■	■		■	■	■			■	■	■	■			■	■	■	■		
.018	183	■			■	■		■	■		■	■			■	■	■			■	■	■	■			■	■	■	■		
.022	223	■			■	■		■	■		■	■			■	■	■			■	■	■	■			■	■	■	■		
.027	273	■			■			■	■		■	■			■	■	■			■	■	■				■	■	■	■		
.033	333				■			■			■	■			■	■				■	■	■				■	■	■	■		
.039	393				■			■			■	■			■	■				■	■	■				■	■	■			
.047	473				■			■			■	■			■	■				■	■	■				■	■	■			
.056	563				■			■			■	■			■	■				■	■					■	■	■			
.068	683				■			■			■	■			■	■				■	■					■	■	■			
.082	823				■			■			■	■			■	■				■	■					■	■				
.10	104							■			■				■	■				■	■					■	■				
.12	124										■				■	■				■	■					■	■				
.15	154										■				■	■				■	■					■	■				
.18	184										■				■					■	■					■	■				
.22	224										■				■					■	■					■	■				
.27	274										■				■					■						■	■				
.33	334														■					■						■	■				
.39	394														■					■						■					
.47	474														■					■						■					
.56	564																			■						■					
.68	684																			■						■					
.82	824																									■					
1.0	105																									■					

© KEMET Electronics Corporation • P.O. Box 5928 • Greenville, SC 29606 (864) 963-6300 • www.kemet.com

X7R DIELECTRIC


STYLE X7R		HS30				HS31					HS33							HS34							HS35							HS36							
	L max	.450 (11.43)				.550 (13.97)					.850 (21.59)							1.050 (26.67)							1.250 (31.75)							1.450 (36.83)							
	W max	.220 (5.08)				.280 (7.11)					.400 (10.16)							.500 (12.70)							.600 (15.24)							.720 (18.29)							
	T max	.200 (6.86)				.250 (6.35)					.270 (6.89)							.270 (6.89)							.270 (6.89)							.270 (6.89)							
	S ±.030	.300 (7.62)				.400 (10.16)					.700 (17.78)							.975 (24.76)							1.175 (29.84)							1.375 (34.92)							
	Lead Dia. +.004/-.002	.025 (.635)				.025 (.635)					.025 (.635)							.025 (.635)							.025 (.635)							.025 (.635)							
	Cap Code	WVDC				WVDC					WVDC							WVDC							WVDC							WVDC							
Cap	pF	500	1k	2k	3k	500	1k	2k	3k	4k	500	1k	2k	3k	4k	5k	7.5	500	1k	2k	3k	4k	5k	7.5k	500	1k	2k	3k	4k	5k	7.5k	10k	500	1k	2k	3k	4k	5k	7.5k	10k
220pF	221																																							
270	271																																							
330	331																																							
390	391																																							
470	471																																							
560	561																																							
680	681																																							
820	821																																							
1000	102																																							
1200	122																																							
1500	152																																							
1800	182																																							
2200	222																																							
2700	272																																							
3300	332																																							
3900	392																																							
4700	472																																							
5600	562																																							
6800	682																																							
8200	822																																							
.010uF	103																																							
.012	123																																							
.015	153																																							
.018	183																																							
.022	223																																							
.027	273																																							
.033	333																																							
.039	393																																							
.047	473																																							
.056	563																																							
.068	683																																							
.082	823																																							
.10	104																																							
.12	124																																							
.15	154																																							
.18	184																																							
.22	224																																							
.27	274																																							
.33	334																																							
.39	394																																							
.47	474																																							
.56	564																																							
.68	684																																							
.82	824																																							
1.0	105																																							
1.2	125																																							
1.5	155																																							
1.8	185																																							
2.2	225																																							

© KEMET Electronics Corporation • P.O. Box 5928 • Greenville, SC 29606 (864) 963-6300 • www.kemet.com

FEATURES

1. The ceramic chip capacitors described in this section are the types used in our other high voltage ceramic multilayer product lines.
2. Types BP, BR and BZ available as described in MIL-PRF-49467.
3. Group A and B screening per MIL-PRF-49467 available.
4. Ceramic chip capacitors are extremely sensitive to thermal shock damage during installation. Wherever possible, processes involving infrared or vapor phase soldering systems should be utilized.
5. Higher voltages available upon request
6. Where nickel barrier termination is required, end band length dimensions may exceed the standard dimension listed.

CERAMIC CHIP OUTLINE DRAWING




DIMENSIONS

Style	Length (L) Inches (mm)	Width (W) Inches (mm)	Thickness (T) max Inches (mm)	Bandwidth (BW) Inches
1515	.150 ±.015 (3.81 ±.38)	.150 ±.015 (3.81 ±.38)	.140 (3.55)	.010 - .030"
1812	.180 ±.020 (4.57 ±.51)	.120 ±.015 (3.05 ±.38)	.100 (2.54)	.010 - .040"
1825	.180 ±.020 (4.57 ±.51)	.250 ±.020 (6.35 ±.51)	.160 (4.07)	.010 - .040"
2020	.200 ±.020 (5.08 ±.51)	.200 ±.020 (5.08 ±.51)	.180 (3.55)	.010 - .040"
2225	.220 ±.020 (5.59 ±.51)	.250 ±.020 (6.35 ±.51)	.200 (5.08)	.010 - .040"
2520	.250 ±.020 (6.35 ±.51)	.200 ±.020 (5.08 ±.51)	.180 (4.57)	.030 - .060"
3333	.330 ±.030 (8.38 ±.76)	.330 ±.030 (8.38 ±.76)	.220 (5.59)	.030 - .060"
3530	.350 ±.030 (8.89 ±.76)	.300 ±.030 (7.62 ±.76)	.220 (5.59)	.030 - .060"
4040	.400 ±.030 (10.2 ±.76)	.400 ±.030 (10.2 ±.76)	.220 (5.59)	.030 - .060"
4540	.450 ±.030 (11.43 ±.76)	.400 ±.030 (10.2 ±.76)	.220 (5.59)	.030 - .060"
5440	.540 ±.030 (13.7 ±.76)	.400 ±.030 (10.2 ±.76)	.220 (5.59)	.030 - .060"
5550	.550 ±.030 (14.0 ±.76)	.500 ±.030 (12.7 ±.76)	.220 (5.59)	.030 - .060"
6560	.650 ±.030 (16.5 ±.76)	.600 ±.030 (15.2 ±.76)	.220 (5.59)	.030 - .060"

RECOMMENDED SOLDER PAD PATTERN DIMENSIONS

Chip Size	T (Total Length)		S (Separation)		W (Pad Width)		L (Pad Length)	
	mm	in.	mm	in.	mm	in.	mm	in.
1515	5.20	0.205	1.90	0.075	4.34	0.171	1.65	0.065
1812	5.90	0.232	2.30	0.091	3.70	0.146	1.80	0.071
1825	5.90	0.232	2.30	0.091	6.90	0.272	1.80	0.071
2020	6.50	0.256	2.80	0.110	5.62	0.221	1.85	0.073
2225	7.00	0.276	3.30	0.130	6.80	0.268	1.85	0.073
2520	8.68	0.342	4.98	0.196	5.62	0.221	1.85	0.073
3333	10.91	0.430	7.11	0.280	9.27	0.365	1.90	0.075
3530	11.51	0.453	7.61	0.300	8.51	0.335	1.95	0.077
4040	12.88	0.507	8.88	0.350	11.05	0.435	2.00	0.079
4540	14.21	0.559	10.15	0.400	11.05	0.435	2.03	0.080
5440	16.51	0.650	10.41	0.410	11.05	0.435	3.05	0.120
5550	18.92	0.745	12.82	0.505	13.59	0.535	3.05	0.120
6560	19.80	0.780	13.20	0.520	16.13	0.635	3.30	0.130



PART NUMBER AND ORDERING INFORMATION

4540 B 472 M 202 P M

Style
1515, 2020, etc.

Dielectric
B or R = X7R
N = C0G (NP0)

Capacitance Value
First two digits are significant, last digit is number of zeros, i.e., 472=4700pF

Tolerance
J = ±5% C0G (NP0)
K = ±10%
M = ±20%
P = 0/+100%
Z = -20%/+80%

MARKING
Not applicable
As required by customer only.

Voltage
First two digits are significant, last digit is number of zeros, i.e., 202=2000V

Terminal Material
P = PdAg
S = Ag
E = Ag/Ni/SnPb Plate
C = Ag/Ni/Sn Plate

Group A Screening*
Add to part number if required
*MIL-PRF-49467
(subgroup 1)
except Corona

© KEMET Electronics Corporation • P.O. Box 5928 • Greenville, SC 29606 (864) 963-6300 • www.kemet.com

HIGH VOLTAGE CERAMIC CHIP (+125ºC)

Military Equivalent

C0G DIELECTRIC

STYLE COG		1515				1812				1825				2020				2225				2520				3333					3530			
	L	.150 ±.015 (3.81 ±.38)				.180 ±.020(4.57 ±.51)				.180 ±.020(4.57 ±.51)				.200 ±.020(5.08 ±.51)				.220 ±.020(5.59±.51)				.250 ±.020(6.35±.51)				.330 ±.030(8.38±.76)					.350 ±.030(8.89±.76)			
	W	.150 ±.015 (3.81 ±.38)				.120 ±.015 (3.05±.38)				.250 ±.020(6.35±.51)				.200 ±.020(5.08 ±.51)				.250 ±.020(6.35±.51)				.200 ±.020(5.08 ±.51)				.330 ±.030(8.38±.76)					.300 ±.030(7.62±.76)			
	T max	.140 (3.55)				.100 (2.54)				.160 (4.07)				.180 (3.55)				.200 (5.08)				.180 (3.55)				.220 (5.59)					.220 (5.59)			
	Band Width	.010 - .030"				.010 - .040"				.010 - .040"				.010 - .040"				.010 - .040"				.030 - .060"				.030 - .060"					.030 - .060"			
Cap	Cap pF	WVDC				WVDC				WVDC				WVDC				WVDC				WVDC				WVDC					WVDC			
		500	1k	2k	3k	500	1k	2k	3k	500	1k	2k	3k	500	1k	2k	3k	500	1k	2k	3k	500	1k	2k	3k	500	1k	2k	3k	4k	500	1k	2k	3k	4k
10pF	100																																		
12	120			■	■			■	■																										
15	150			■	■			■	■																										
18	180			■	■			■	■																										
22	220			■	■			■	■			■	■			■	■																		
27	270	■	■	■	■	■	■	■	■			■	■			■	■			■	■			■	■				■						■
33	330	■	■	■	■	■	■	■	■			■	■			■	■			■	■			■	■				■						■
39	390	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■			■	■			■	■				■						■
47	470	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■			■	■	■			■	■	■
56	560	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■			■	■	■			■	■	■
68	680	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■			■	■	■			■	■	■
82	820	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■			■	■	■			■	■	■
100	101	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■			■	■	■			■	■	■
120	121	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
150	151	■	■	■	■	■	■	■		■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
180	181	■	■	■		■	■	■		■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
220	221	■	■	■		■	■	■		■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
270	271	■	■	■		■	■	■		■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
330	331	■	■	■		■	■	■		■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
390	391	■	■	■		■	■	■		■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
470	471	■	■	■		■	■	■		■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
560	561	■	■	■		■	■			■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
680	681	■	■	■		■	■			■	■	■		■	■	■		■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
820	821	■	■			■	■			■	■	■		■	■	■		■	■	■		■	■	■		■	■	■	■		■	■	■	■	
1000	102	■	■			■	■			■	■			■	■			■	■	■		■	■	■		■	■	■	■		■	■	■	■	
1200	122	■	■			■	■			■	■			■	■			■	■	■		■	■	■		■	■	■	■		■	■	■	■	
1500	152	■	■			■				■	■			■	■			■	■			■	■			■	■	■	■		■	■	■	■	
1800	182	■				■				■	■			■	■			■	■			■	■			■	■	■			■	■	■		
2200	222	■				■				■	■			■	■			■	■			■	■			■	■	■			■	■	■		
2700	272	■				■				■	■			■	■			■	■			■	■			■	■	■			■	■	■		
3300	332	■								■	■			■	■			■	■			■	■			■	■				■	■	■		
3900	392	■								■	■			■	■			■	■			■	■			■	■				■	■			
4700	472	■								■				■				■	■			■	■			■	■				■	■			
5600	562									■				■				■	■			■	■			■	■				■	■			
6800	682									■				■				■	■			■				■	■				■	■			
8200	822									■				■				■	■			■				■	■				■	■			
.010uF	103																	■				■				■	■				■	■			
.012	123																	■								■	■				■	■			
.015	153																									■					■	■			
.018	183																														■	■			
.022	223																														■				
.027	273																																		
.033	333																																		
.039	393																																		
.047	473																																		
.056	563																																		
.068	683																																		
.082	823																																		
.10	104																																		

© KEMET Electronics Corporation • P.O. Box 5928 • Greenville, SC 29606 (864) 963-6300 • www.kemet.com

C0G DIELECTRIC

STYLE COG		4040					4540						5440					5550						6560					
	L	.400 ±.030(10.20±.76)					.450 ±.030(11.43±.76)						.540 ±.030(13.70±.76)					.550 ±.030(14.00±.76)						.650 ±.030(16.50±.76)					
	W	.400 ±.030(10.20±.76)					.400 ±.030(10.20±.76)						.400 ±.030(10.20±.76)					.500 ±.030(10.20±.76)						.600 ±.030(15.20±.76)					
	T max	.220 (5.59)					.220 (5.59)						.220 (5.59)					.220 (5.59)						.220 (5.59)					
	Band Width	.030 - .060"					.030 - .060"						.030 - .060"					.030 - .060"						.030 - .060"					
Cap	Cap Code pF	WVDC					WVDC						WVDC					WVDC						WVDC					
		500	1k	2k	3k	4k	500	1k	2k	3k	4k	5k	500	1k	2k	3K	4k	500	1k	2k	3k	4k	5k	500	1k	2k	3k	4k	5k
10pF	100																												
12	120																												
15	150																												
18	180					■					■	■																	
22	220					■					■	■																	
27	270					■					■	■					■					■	■						
33	330					■					■	■					■					■	■						
39	390					■					■	■					■					■	■						
47	470					■					■	■					■					■	■					■	■
56	560					■					■	■					■					■	■					■	■
68	680					■					■	■					■					■	■					■	■
82	820					■					■	■					■					■	■					■	■
100	101			■	■	■			■	■	■	■					■					■	■					■	■
120	121			■	■	■			■	■	■	■					■					■	■					■	■
150	151			■	■	■			■	■	■	■			■	■	■			■	■	■	■					■	■
180	181			■	■	■			■	■	■	■			■	■	■			■	■	■	■					■	■
220	221	■	■	■	■	■	■	■	■	■	■	■			■	■	■			■	■	■	■					■	■
270	271	■	■	■	■	■	■	■	■	■	■	■			■	■	■			■	■	■	■			■	■	■	■
330	331	■	■	■	■	■	■	■	■	■	■	■			■	■	■			■	■	■	■			■	■	■	■
390	391	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■			■	■	■	■
470	471	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
560	561	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
680	681	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
820	821	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
1000	102	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
1200	122	■	■	■	■	■	■	■	■	■	■		■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
1500	152	■	■	■	■		■	■	■	■	■		■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
1800	182	■	■	■	■		■	■	■	■			■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
2200	222	■	■	■	■		■	■	■	■			■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
2700	272	■	■	■			■	■	■	■			■	■	■	■		■	■	■	■			■	■	■	■	■	■
3300	332	■	■	■			■	■	■	■			■	■	■	■		■	■	■	■			■	■	■	■	■	
3900	392	■	■	■			■	■	■	■			■	■	■			■	■	■	■			■	■	■	■	■	
4700	472	■	■	■			■	■	■				■	■	■			■	■	■	■			■	■	■	■		
5600	562	■	■	■			■	■	■				■	■	■			■	■	■	■			■	■	■	■		
6800	682	■	■				■	■	■				■	■	■			■	■	■	■			■	■	■	■		
8200	822	■	■				■	■					■	■	■			■	■	■				■	■	■	■		
.010uF	103	■	■				■	■					■	■				■	■	■				■	■	■			
.012	123	■	■				■	■					■	■				■	■					■	■	■			
.015	153	■	■				■	■					■	■				■	■					■	■	■			
.018	183	■	■				■	■					■	■				■	■					■	■	■			
.022	223	■	■				■	■					■	■				■	■					■	■	■			
.027	273	■					■	■					■	■				■	■					■	■				
.033	333	■					■	■					■	■				■	■					■	■				
.039	393	■					■						■					■	■					■	■				
.047	473						■						■					■	■					■	■				
.056	563						■						■					■						■	■				
.068	683												■					■						■	■				
.082	823												■											■					
.10	104																							■					

© KEMET Electronics Corporation • P.O. Box 5928 • Greenville, SC 29606 (864) 963-6300 • www.kemet.com

X7R DIELECTRIC

STYLE X7R		1515			1812			1825				2020				2225				2520				3333				3530				
	L	.150+.015 (3.81 ± .38)			.180 ±.020(4.57 ±.51)			.180 ±.020(4.57 ±.51)				.200 ±.020(5.08 ±.51)				.220 ±.020(5.59±.51)				.250 ±.020(6.35±.51)				.330 ±.030(8.38±.76)				.350 ±.030(8.89±.76)				
	W	.150+.015 (3.81 ± .38)			.120 ± .015 (3.05 ±.38)			.250 ±.020(6.35±.51)				.200 ±.020(5.08 ±.51)				.250 ±.020(6.35±.51)				.200 ±.020(5.08 ±.51)				.330 ±.030(8.38±.76)				.300 ±.030(7.62±.76)				
	T max	.140 (3.55)			.100 (2.54)			.160 (4.07)				.180 (3.55)				.200 (5.08)				.180 (3.55)				.220 (5.59)				.220 (5.59)				
	Band Width	.010 - .030"			.010 - .040"			.010 - .040"				.010 - .040"				.010 - .040"				.030 - .060"				.030 - .060"				.030 - .060"				
Cap	Cap Code pF	WVDC			WVDC			WVDC				WVDC				WVDC				WVDC				WVDC				WVDC				
		500	1k	2k	500	1k	2k	500	1k	2k	3k	500	1k	2k	3k	500	1k	2k	3k	500	1k	2k	3k	500	1k	2k	3k	500	1k	2k	3k	4k
220pF	221																															
270	271			■			■																									■
330	331			■			■																									■
390	391			■			■																									■
470	471			■			■																									■
560	561			■			■			■	■			■	■																	■
680	681	■	■	■	■	■	■			■	■			■	■			■	■			■	■									■
820	821	■	■	■	■	■	■			■	■			■	■			■	■			■	■									■
1000	102	■	■	■	■	■	■			■	■			■	■			■	■			■	■									■
1200	122	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■			■	■			■	■	■
1500	152	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■			■	■			■	■	■
1800	182	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■			■	■			■	■	■
2200	222	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■			■	■			■	■	■
2700	272	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■			■	■			■	■	■
3300	332	■	■	■	■	■		■	■	■		■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
3900	392	■	■	■	■	■		■	■	■		■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
4700	472	■	■		■	■		■	■	■		■	■	■		■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
5600	562	■	■		■	■		■	■	■		■	■	■		■	■	■		■	■	■	■	■	■	■	■	■	■	■	■	■
6800	682	■	■		■	■		■	■	■		■	■	■		■	■			■	■			■	■	■	■	■	■	■	■	■
8200	822	■	■		■	■		■	■	■		■	■	■		■	■			■	■			■	■	■	■	■	■	■	■	
.010uF	103	■	■		■	■		■	■			■	■			■	■			■	■			■	■	■	■	■	■	■	■	
.012	123	■	■		■	■		■	■			■	■			■	■			■	■			■	■	■	■	■	■	■	■	
.015	153	■	■		■	■		■	■			■	■			■	■	■		■	■	■		■	■	■		■	■	■	■	
.018	183	■	■		■	■		■	■			■	■			■	■			■	■	■		■	■	■		■	■	■		
.022	223	■	■		■			■	■			■	■			■	■			■	■			■	■	■		■	■	■		
.027	273	■			■			■	■			■	■			■	■			■	■			■	■	■		■	■	■		
.033	333	■			■			■	■			■	■			■	■			■	■			■	■			■	■	■		
.039	393	■			■			■	■			■	■			■	■			■	■			■	■			■	■			
.047	473	■			■			■	■			■	■			■	■			■	■			■	■			■	■			
.056	563	■			■			■				■	■			■	■			■	■			■	■			■	■			
.068	683	■						■				■	■			■	■			■	■			■	■			■	■			
.082	823							■				■				■				■	■			■	■			■	■			
.10	104							■				■				■				■				■	■			■	■			
.12	124							■				■				■				■				■	■			■	■			
.15	154							■				■				■				■				■	■			■	■			
.18	184							■				■				■				■				■	■			■	■			
.22	224															■				■				■	■			■	■			
.27	274																							■				■	■			
.33	334																							■				■				
.39	394																							■				■				
.47	474																							■				■				
.56	564																											■				
.68	684																															
.82	824																															
1.0	105																															
1.2	125																															
1.5	155																															
1.8	185																															
2.2	225																															

© KEMET Electronics Corporation • P.O. Box 5928 • Greenville, SC 29606 (864) 963-6300 • www.kemet.com

X7R DIELECTRIC

STYLE X7R		4040					4540						5440					5550						6560					
	L	.400 ±.030(10.20±.76)					.450 ±.030(11.43±.76)						.540 ±.030(13.70±.76)					.550 ±.030(14.00±.76)						.650 ±.030(16.50±.76)					
	W	.400 ±.030(10.20±.76)					.400 ±.030(10.20±.76)						.400 ±.030(10.20±.76)					.500 ±.030(10.20±.76)						.600 ±.030(15.20±.76)					
	T max	.220 (5.59)					.220 (5.59)						.220 (5.59)					.220 (5.59)						.220 (5.59)					
	Band Width	.030 - .060"					.030 - .060"						.030 - .060"					.030 - .060"						.030 - .060"					
Cap	Cap Code pF	WVDC					WVDC						WVDC					WVDC						WVDC					
		500	1k	2k	3k	4k	500	1k	2k	3k	4k	5k	500	1k	2k	3k	4k	500	1k	2k	3k	4k	5k	500	1k	2k	3k	4k	5k
220pF	221																												
270	271																												
330	331																												
390	391																												
470	471					■					■	■																	
560	561					■					■	■																	
680	681					■					■	■					■					■	■						
820	821					■					■	■					■					■	■						
1000	102					■					■	■					■					■	■						
1200	122					■					■	■					■					■	■					■	■
1500	152					■					■	■					■					■	■					■	■
1800	182					■					■	■					■					■	■					■	■
2200	222					■					■	■					■					■	■					■	■
2700	272			■	■	■			■	■	■	■					■					■	■					■	■
3300	332			■	■	■			■	■	■	■					■					■	■					■	■
3900	392			■	■	■			■	■	■	■			■	■	■			■	■	■	■					■	■
4700	472			■	■	■			■	■	■	■			■	■	■			■	■	■	■					■	■
5600	562			■	■	■			■	■	■	■			■	■	■			■	■	■	■			■	■	■	■
6800	682	■	■	■	■	■	■	■	■	■	■	■			■	■	■			■	■	■	■			■	■	■	■
8200	822	■	■	■	■	■	■	■	■	■	■				■	■	■			■	■	■	■			■	■	■	■
.010uF	103	■	■	■	■		■	■	■	■	■		■	■	■	■	■	■	■	■	■	■	■			■	■	■	■
.012	123	■	■	■	■		■	■	■	■			■	■	■	■		■	■	■	■	■				■	■	■	■
.015	153	■	■	■	■		■	■	■	■			■	■	■			■	■	■	■	■			■	■	■	■	■
.018	183	■	■	■	■		■	■	■	■			■	■	■			■	■	■	■				■	■	■	■	
.022	223	■	■	■			■	■	■	■			■	■	■			■	■	■	■				■	■	■	■	
.027	273	■	■	■			■	■	■	■			■	■	■			■	■	■	■				■	■	■	■	
.033	333	■	■	■			■	■	■	■			■	■	■			■	■	■	■				■	■	■		
.039	393	■	■	■			■	■	■				■	■	■			■	■	■	■				■	■	■		
.047	473	■	■	■			■	■	■				■	■	■			■	■	■					■	■	■		
.056	563	■	■				■	■	■				■	■	■			■	■	■					■	■	■		
.068	683	■	■				■	■	■				■	■				■	■	■					■	■	■		
.082	823	■	■				■	■					■	■				■	■	■					■	■	■		
.10	104	■	■				■	■					■	■				■	■	■					■	■	■		
.12	124	■	■				■	■					■	■				■	■	■					■	■	■		
.15	154	■	■				■	■					■	■				■	■						■	■	■		
.18	184	■	■				■	■					■	■				■	■						■	■	■		
.22	224	■	■				■	■					■	■				■	■						■	■			
.27	274	■	■				■	■					■	■				■	■						■	■			
.33	334	■	■				■	■					■	■				■	■						■	■			
.39	394	■	■				■	■					■	■				■	■						■	■			
.47	474	■					■	■					■	■				■	■						■	■			
.56	564	■					■						■	■				■	■						■	■			
.68	684	■					■						■	■				■	■						■	■			
.82	824	■					■						■					■	■						■	■			
1.0	105						■						■					■							■	■			
1.2	125						■						■					■							■				
1.5	155												■					■							■				
1.8	185																	■							■				
2.2	225																								■				

© KEMET Electronics Corporation • P.O. Box 5928 • Greenville, SC 29606 (864) 963-6300 • www.kemet.com


HIGH VOLTAGE L & J LEADED CERAMIC CAPACITOR
SM SERIES

FEATURES

1. Silver plated copper alloy terminal for easy soldering.
2. Mounting tabs are designed to minimize the effect of thermal stress introduced by the differences in coefficient of thermal expansion between the capacitor and the mounting surface.
3. Low ESR.
4. High current discharge capability.
5. Group A and B screening per MIL-PRF-49467 available .
6. Standard lead configuration is 'B'.(J) If lead configuration is left out of part number the lead style is assumed to be 'B'.

CAPACITOR OUTLINE DRAWING

STANDARD



DIMENSIONS

Style	Length (L) Inches (mm)	Width (W) Inches (mm)	Thickness (T) max Inches (mm)	Tab (A) max Inches (mm)
SM20	.150 ±.015 (3.81 ±.38)	.150 ±.015 (3.81 ± .38)	.130 (3.30)	.100 (2.54)
SM21	.200 ±.020 (5.08 ±.51)	.200 ±.020 (5.08 ± .51)	.180 (4.57)	.100 (2.54)
SM22	.250 ±.020 (6.35 ±.51)	.200 ±.020 (5.08 ± .51)	.180 (4.57)	.100 (2.54)
SM23	.350 ±.030 (8.89 ±.76)	.300 ±.030 (7.62 ± .76)	.220 (5.59)	.200 (5.08)
SM24	.450 ±.030 (11.43 ±.76)	.400 ±.030 (10.20 ± .76)	.220 (5.59)	.300 (7.62)
SM25	.550 ±.030 (14.00 ±.76)	.500 ±.030 (12.70 ± .76)	.220 (5.59)	.400 (10.2)
SM26	.650 ±.030 (16.50 ±.76)	.600 ±.030 (15.20 ± .76)	.220 (5.59)	.500 (12.7)
SM30	.300 ±.030 (7.62 ±.76)	.150 ±.015 (3.81 ± .38)	.140 (3.55)	.100 (2.54)
SM31	.400 ±.030 (10.20 ±.76)	.200 ±.020 (5.08 ± .51)	.130 (3.30)	.100 (2.54)
SM33	.700 ±.030 (17.08 ±.76)	.300 ±.030 (7.62 ± .76)	.180 (4.57)	.200 (5.08)
SM34	.900 ±.030 (22.90 ±.76)	.400 ±.030 (10.20 ±. 76)	.220 (5.59)	.300 (7.62)
SM35	1.100 ±.030 (27.90 ±.76)	.500 ±.030 (12.70 ±. 76)	.220 (5.59)	.400 (10.2)
SM36	1.350 ±.030 (33.00 ±.76)	.600 ±.030 (15.20 ±. 76)	.220 (5.59)	.500 (12.7)

PART NUMBER AND ORDERING INFORMATION

SM24 B 472 M 202 A M

Style
SM24, etc.

Dielectric
B = X7R
N = C0G (NP0)

Capacitance Value
First two digits are significant, last digit is number of zeros, i.e., 472=4700pF

Tolerance
J = ±5% C0G (NP0)
K = ±10%
M = ±20%
P = 0/+100%
Z = -20%/+80%

MARKING
Not applicable
As required by customer only.

Voltage
First two digits are significant, last digit is number of zeros, i.e., 202=2000V

Configuration
A=Config (L)
B=Config (J)

Group A Screening*
Add to part number if required
*MIL-PRF-49467 (subgroup 1) except Corona

© KEMET Electronics Corporation • P.O. Box 5928 • Greenville, SC 29606 (864) 963-6300 • www.kemet.com

C0G DIELECTRIC

STYLE COG		SM20				SM21				SM22				SM23					SM24						SM25						SM26					
	L	.150±.015(3.31 ±.38)				.200±.020(5.08 ±.51)				.250 ± .020 (6.35 ± .51)				.350 ±.030 (8.89 ±.76)					.450 ±.030 (11.43 ±.76)						.550 ±.030 (14.00 ±.76)						.650 ±.030 (16.50 ±.76)					
	W	.150±.015(3.31 ±.38)				.200±.020(5.08 ±.51)				.200±.020(5.08 ±.51)				.300 ±.030 (7.62 ±.76)					.400 ±.030 (10.20 ±.76)						.500 ±.030 (12.70 ±.76)						.600 ±.030 (15.20 ±.76)					
	T max	.130 (3.30)				.180 (4.57)				.180 (4.57)				.220 (5.59)					.220 (5.59)						.220 (5.59)						.220 (5.59)					
	Tab A max	.100 (2.54)				.100 (2.54)				.100 (2.54)				.200 (5.08)					.300 (7.62)						.400 (10.20)						.500 (12.70)					
	Cap Code	WVDC				WVDC				WVDC				WVDC					WVDC						WVDC						WVDC					
Cap	pF	500	1k	2k	3k	500	1k	2k	3k	500	1k	2k	3k	500	1k	2k	3k	4k	500	1k	2k	3k	4k	5k	500	1k	2k	3k	4k	5k	500	1k	2k	3k	4k	5k
12pF	120			■	■																															
15	150			■	■																															
18	180			■	■																		■	■												
22	220			■	■			■	■														■	■												
27	270	■	■	■	■			■	■			■	■					■					■	■					■	■						
33	330	■	■	■	■			■	■			■	■					■					■	■					■	■						
39	390	■	■	■	■	■	■	■	■			■	■					■					■	■					■	■						
47	470	■	■	■	■	■	■	■	■	■	■	■	■			■	■	■					■	■					■	■				■	■	
56	560	■	■	■	■	■	■	■	■	■	■	■	■			■	■	■					■	■					■	■				■	■	
68	680	■	■	■	■	■	■	■	■	■	■	■	■			■	■	■					■	■					■	■				■	■	
82	820	■	■	■	■	■	■	■	■	■	■	■	■			■	■	■					■	■					■	■				■	■	
100	101	■	■	■	■	■	■	■	■	■	■	■	■			■	■	■			■	■	■	■					■	■				■	■	
120	121	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■			■	■	■	■					■	■				■	■	
150	151	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■			■	■	■	■			■	■	■	■				■	■	
180	181	■	■	■		■	■	■	■	■	■	■	■	■	■	■	■	■			■	■	■	■			■	■	■	■				■	■	
220	221	■	■	■		■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■			■	■	■	■				■	■	
270	271	■	■	■		■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■			■	■	■	■			■	■	■	■
330	331	■	■	■		■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■			■	■	■	■			■	■	■	■
390	391	■	■	■		■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■			■	■	■	■
470	471	■	■	■		■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
560	561	■	■	■		■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
680	681	■	■	■		■	■	■		■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
820	821	■	■			■	■	■		■	■	■		■	■	■	■		■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
1000	102	■	■			■	■			■	■	■		■	■	■	■		■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
1200	122	■	■			■	■			■	■	■		■	■	■	■		■	■	■	■	■		■	■	■	■	■	■	■	■	■	■	■	■
1500	152	■	■			■	■			■	■			■	■	■	■		■	■	■	■	■		■	■	■	■	■	■	■	■	■	■	■	■
1800	182	■				■	■			■	■			■	■	■			■	■	■	■			■	■	■	■	■	■	■	■	■	■	■	■
2200	222	■				■	■			■	■			■	■	■			■	■	■	■			■	■	■	■	■	■	■	■	■	■	■	■
2700	272	■				■	■			■	■			■	■	■			■	■	■	■			■	■	■	■			■	■	■	■	■	■
3300	332	■				■	■			■	■			■	■	■			■	■	■	■			■	■	■	■			■	■	■	■	■	
3900	392	■				■	■			■	■			■	■				■	■	■	■			■	■	■	■			■	■	■	■	■	
4700	472	■				■				■	■			■	■				■	■	■				■	■	■	■			■	■	■	■		
5600	562					■				■	■			■	■				■	■	■				■	■	■	■			■	■	■	■		
6800	682					■				■	■			■	■				■	■	■				■	■	■	■			■	■	■	■		
8200	822					■				■				■	■				■	■					■	■	■				■	■	■	■		
.010uF	103									■				■	■				■	■					■	■	■				■	■	■			
.012	123													■	■				■	■					■	■					■	■				
.015	153													■	■				■	■					■	■					■	■				
.018	183													■	■				■	■					■	■					■	■				
.022	223													■					■	■					■	■					■	■				
.027	273																		■	■					■	■					■	■				
.033	333																		■	■					■	■					■	■				
.039	393																		■						■	■					■	■				
.047	473																		■						■	■					■	■				
.056	563																		■						■						■	■				
.068	683																								■						■	■				
.082	823																								■						■					
.10	104																														■					

© KEMET Electronics Corporation • P.O. Box 5928 • Greenville, SC 29606 (864) 963-6300 • www.kemet.com

HIGH VOLTAGE L & J LEADED CERAMIC CAPACITOR
SM SERIES

C0G DIELECTRIC

STYLE COG		SM30					SM31					SM33						SM34							SM35							SM36							
	L	.300 ±.030 (7.62±.76)					.400 ±.030(10.20 ±.76)					.700 ±.030 (17.08 ±.76)						.900 ±.030 (22.90 ±.76)							1.100 ±.030 (27.90 ±.76)							1.350 ±.030 (33.00 ±.76)							
	W	.150 ±.015 (3.31 ±.38)					.200 ±.020(5.08 ±.51)					.300 ±.030(7.62 ±.76)						.400 ±.030(10.20 ±.76)							.500 ±.030(12.70 ±.76)							.600 ±.030(15.20 ±.76)							
	T max	.140 (3.55)					.130 (3.30)					.180 (4.57)						.220 (5.59)_							.220 (5.59)_							.220 (5.59)_							
	Tab A max	.100 (2.54)					.100 (2.54)					.200 (5.08)						.300 (7.62)							.400 (10.20)							.500 (12.70)							
	Cap Code	WVDC					WVDC					WVDC						WVDC							WVDC							WVDC							
Cap	pF	500	1k	2k	3k	4k	50	1k	2k	3k	4k	5k	500	1k	2k	3k	4k	5k	7k	500	1k	2k	3k	4k	5k	7k	10k	500	1k	2k	3k	4k	5k	7k	10k	50	1k	2k	3k	4k	5k	7k	10
10pF	100					■				■	■	■							■																								
12	120					■				■	■	■							■																								
15	150				■	■				■	■	■							■																								
18	180				■	■				■	■	■							■						■	■																	
22	220				■	■				■	■	■							■						■	■																	
27	270				■	■			■	■	■	■					■	■	■						■	■																	
33	330				■	■			■	■	■	■					■	■	■						■	■										■	■						
39	390				■	■			■	■	■	■					■	■	■						■	■										■	■						
47	470				■	■			■	■	■	■					■	■	■				■	■	■	■										■	■						
56	560				■	■			■	■	■	■					■	■	■				■	■	■	■										■	■				■	■	
68	680	■	■	■	■	■			■	■	■	■			■	■	■	■	■				■	■	■	■										■	■				■	■	
82	820	■	■	■	■	■	■	■	■	■	■	■			■	■	■	■	■				■	■	■	■						■	■	■	■						■	■	
100	101	■	■	■	■	■	■	■	■	■	■	■			■	■	■	■	■				■	■	■	■						■	■	■	■						■	■	
120	121	■	■	■	■	■	■	■	■	■	■	■			■	■	■	■	■			■	■	■	■	■						■	■	■	■						■	■	
150	151	■	■	■	■	■	■	■	■	■	■	■			■	■	■	■	■			■	■	■	■	■						■	■	■	■						■	■	
180	181	■	■	■	■	■	■	■	■	■	■	■			■	■	■	■	■			■	■	■	■	■						■	■	■	■						■	■	
220	221	■	■	■	■		■	■	■	■	■	■			■	■	■	■	■			■	■	■	■	■						■	■	■	■						■	■	
270	271	■	■	■	■		■	■	■	■	■	■			■	■	■	■	■			■	■	■	■	■						■	■	■	■						■	■	
330	331	■	■	■	■		■	■	■	■	■	■	■	■	■	■	■	■	■			■	■	■	■	■						■	■	■	■						■	■	
390	391	■	■	■	■		■	■	■	■	■	■	■	■	■	■	■	■	■			■	■	■	■	■						■	■	■	■						■	■	
470	471	■	■	■			■	■	■	■	■		■	■	■	■	■	■	■	■	■	■	■	■	■	■						■	■	■	■						■	■	
560	561	■	■	■			■	■	■	■	■		■	■	■	■	■	■		■	■	■	■	■	■	■						■	■	■	■						■	■	
680	681	■	■	■			■	■	■	■			■	■	■	■	■	■		■	■	■	■	■	■	■		■	■	■	■	■	■	■	■						■	■	
820	821	■	■	■			■	■	■	■			■	■	■	■	■	■		■	■	■	■	■	■	■		■	■	■	■	■	■	■	■						■	■	
1000	102	■	■	■			■	■	■				■	■	■	■	■	■		■	■	■	■	■	■	■		■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
1200	122	■	■				■	■	■				■	■	■	■	■	■		■	■	■	■	■	■	■		■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
1500	152	■	■				■	■	■				■	■	■	■	■	■		■	■	■	■	■	■	■		■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
1800	182	■	■				■	■	■				■	■	■	■	■	■		■	■	■	■	■	■	■		■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
2200	222	■	■				■	■	■				■	■	■	■	■	■		■	■	■	■	■	■	■		■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
2700	272	■	■				■	■					■	■	■	■	■	■		■	■	■	■	■	■	■		■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
3300	332	■	■				■	■					■	■	■	■	■	■		■	■	■	■	■	■	■		■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
3900	392	■	■				■	■					■	■	■	■	■	■		■	■	■	■	■	■	■		■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
4700	472	■	■				■	■					■	■	■	■	■	■		■	■	■	■	■	■	■		■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
5600	562	■					■	■					■	■	■	■	■	■		■	■	■	■	■	■	■		■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
6800	682	■					■	■					■	■	■	■	■	■		■	■	■	■	■	■	■		■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
8200	822	■					■	■					■	■	■	■	■	■		■	■	■	■	■	■	■		■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
.010uF	103	■					■	■					■	■	■	■	■	■		■	■	■	■	■	■	■		■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
.012	123	■					■						■	■	■	■	■	■		■	■	■	■	■	■	■		■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
.015	153	■					■						■	■	■	■	■	■		■	■	■	■	■	■	■		■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
.018	183						■						■	■	■	■	■	■		■	■	■	■	■	■	■		■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
.022	223						■						■	■	■	■	■	■		■	■	■	■	■	■	■		■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
.027	273						■						■	■	■	■	■	■		■	■	■	■	■	■	■		■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
.033	333												■	■	■	■	■	■		■	■	■	■	■	■	■		■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
.039	393												■	■	■	■	■	■		■	■	■	■	■	■	■		■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
.047	473												■	■	■	■	■	■		■	■	■	■	■	■	■		■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
.056	563												■	■	■	■	■	■		■	■	■	■	■	■	■		■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
.068	683												■	■	■	■	■	■		■	■	■	■	■	■	■		■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
.082	823												■							■	■	■	■	■	■	■		■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
.10	104												■							■	■	■	■	■	■	■		■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
.12	124												■							■	■	■	■	■	■	■		■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
.15	154												■							■	■	■	■	■	■	■		■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
.18	184																			■	■	■	■	■	■	■		■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
.22	224																			■	■	■	■	■	■	■		■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
.27	274																											■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
.33	334																											■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	

© KEMET Electronics Corporation • P.O. Box 5928 • Greenville, SC 29606 (864) 963-6300 • www.kemet.com

X7R DIELECTRIC

STYLE X7R		SM20			SM21				SM22				SM23					SM24						SM25						SM26					
	L	.150±.015 (3.81±.38)			.200±.020(5.08 ±.51)				.250 ±.020 (6.35 ±.51)				.350 ±.030 (8.89 ±.76)					.450 ±.030 (11.43 ±.76)						.550 ±.030 (14.00 ±.76)						.650 ±.030 (16.50 ±.76)					
	W	.150±.015 (3.81±.38)			.200±.020(5.08 ±.51)				.200 ±.020(5.08 ±.51)				.300 ±.030 (7.62 ±.76)					.400 ±.030 (10.20 ±.76)						.500 ±.030 (12.70 ±.76)						.600 ±.030 (15.20 ±.76)					
	T max	.130 (3.30)			.180 (4.57)				.180 (4.57)				.220 (5.59)					.220 (5.59)						.220 (5.59)						.220 (5.59)					
	Tab A max	.100 (2.54)			.100 (2.54)				.100 (2.54)				.200 (5.08)					.300 (7.62)						.400 (10.20)						.500 (12.70)					
	Cap Code	WVDC			WVDC				WVDC				WVDC					WVDC						WVDC						WVDC					
Cap	pF	500	1k	2k	500	1k	2k	3k	500	1k	2k	3k	500	1k	2k	3k	4k	500	1k	2k	3k	4k	5k	500	1k	2k	3k	4k	5k	500	1k	2k	3k	4k	5k
270pF	271			■													■																		
330	331			■													■																		
390	391			■													■																		
470	471			■													■					■	■												
560	561			■			■	■									■					■	■												
680	681	■	■	■			■	■			■	■					■					■	■					■	■						
820	821	■	■	■			■	■			■	■					■					■	■					■	■						
1000	102	■	■	■			■	■			■	■					■					■	■					■	■						
1200	122	■	■	■	■	■	■	■	■	■	■	■			■	■	■					■	■					■	■				■	■	
1500	152	■	■	■	■	■	■	■	■	■	■	■			■	■	■					■	■					■	■				■	■	
1800	182	■	■	■	■	■	■	■	■	■	■	■			■	■	■					■	■					■	■				■	■	
2200	222	■	■	■	■	■	■	■	■	■	■	■			■	■	■					■	■					■	■				■	■	
2700	272	■	■	■	■	■	■	■	■	■	■	■			■	■	■			■	■	■	■					■	■				■	■	
3300	332	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■			■	■	■	■					■	■				■	■	
3900	392	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■			■	■	■	■			■	■	■	■				■	■	
4700	472	■	■		■	■	■		■	■	■	■	■	■	■	■	■			■	■	■	■			■	■	■	■				■	■	
5600	562	■	■		■	■	■		■	■	■	■	■	■	■	■	■			■	■	■	■			■	■	■	■				■	■	
6800	682	■	■		■	■	■		■	■	■		■	■	■	■	■	■	■	■	■	■	■			■	■	■	■			■	■	■	■
8200	822	■	■		■	■	■		■	■	■		■	■	■	■		■	■	■	■	■				■	■	■	■			■	■	■	■
.010uF	103	■	■		■	■			■	■	■		■	■	■	■		■	■	■	■	■		■	■	■	■	■	■			■	■	■	■
.012	123	■	■		■	■			■	■	■		■	■	■	■		■	■	■	■			■	■	■	■	■				■	■	■	■
.015	153	■	■		■	■			■	■	■		■	■	■	■		■	■	■	■			■	■	■	■	■			■	■	■	■	■
.018	183	■	■		■	■			■	■	■		■	■	■			■	■	■	■			■	■	■	■	■			■	■	■	■	
.022	223	■	■		■	■			■	■			■	■	■			■	■	■	■			■	■	■	■	■			■	■	■	■	
.027	273	■			■	■			■	■			■	■	■			■	■	■	■			■	■	■	■	■			■	■	■	■	
.033	333	■			■	■			■	■			■	■	■			■	■	■				■	■	■	■				■	■	■		
.039	393	■			■	■			■	■			■	■				■	■	■				■	■	■	■				■	■	■		
.047	473	■			■	■			■	■			■	■				■	■	■				■	■	■					■	■	■		
.056	563	■			■	■			■	■			■	■				■	■	■				■	■	■					■	■	■		
.068	683	■			■	■			■	■			■	■				■	■	■				■	■	■					■	■	■		
.082	823	■			■				■	■			■	■				■	■					■	■	■					■	■	■		
.10	104				■				■				■	■				■	■					■	■	■					■	■			
.12	124				■				■				■	■				■	■					■	■	■					■	■			
.15	154				■				■				■	■				■	■					■	■						■	■			
.18	184				■				■				■	■				■	■					■	■						■	■			
.22	224								■				■	■				■	■					■	■						■				
.27	274												■	■				■	■					■	■						■				
.33	334												■					■	■					■	■						■				
.39	394												■					■	■					■	■						■				
.47	474												■					■	■					■	■						■				
.56	564												■					■						■	■						■				
.68	684																	■						■	■						■				
.82	824																	■						■	■						■				
1.0	105																	■						■							■				
1.2	125																	■						■							■				
1.5	155																							■							■				
1.8	185																							■							■				
2.2	225																														■				
2.7	275																														■				

© KEMET Electronics Corporation • P.O. Box 5928 • Greenville, SC 29606 (864) 963-6300 • www.kemet.com

X7R DIELECTRIC


STYLE X7R		SM30					SM31						SM33							SM34								SM35								SM36							
	L	.300 ±.030 (7.62±.76)					.400 ±.030(10.20 ±.76)						.700 ±.030 (17.08 ±.76)							.900 ±.030 (22.90 ±.76)								1.100 ±.030 (27.90 ±.76)								1.350 ±.030 (33.00 ±.76)							
	W	.150 ±.015 (3.31 ±.38)					.200 ±.020(5.08 ±.51)						.300 ±.030(7.62 ±.76)							.400 ±.030(10.20 ±.76)								.500 ±.030(12.70 ±.76)								.600 ±.030(15.20 ±.76)							
	T max	.140 (3.55)					.130 (3.30)						.180 (4.57)							.220 (5.59)								.220 (5.59)								.220 (5.59)							
	Tab A max	.100 (2.54)					.100 (2.54)						.200 (5.08)							.300 (7.62)								.400 (10.20)								.500 (12.70)							
	Cap Code	WVDC					WVDC						WVDC							WVDC								WVDC								WVDC							
Cap	pF	500	1k	2k	3k	4k	500	1k	2k	3k	4k	5k	500	1k	2k	3k	4k	5k	7k	500	1k	2k	3k	4k	5k	7k	10k	500	1k	2k	3k	4k	5k	7k	10k	500	1k	2k	3k	4k	5k	7.5k	10k
150p	151					■													■																								
180	181					■													■																								
220	221					■													■																								
270	271					■					■	■							■																								
330	331					■					■	■							■																								
390	391			■	■	■					■	■							■																								
470	471			■	■	■					■	■							■						■	■																
560	561			■	■	■					■	■							■						■	■																
680	681			■	■	■			■	■	■	■				■	■	■	■						■	■																
820	821			■	■	■			■	■	■	■				■	■	■	■						■	■										■	■					
1000	102			■	■	■			■	■	■	■				■	■	■	■						■	■										■	■					
1200	122			■	■				■	■	■	■				■	■	■	■					■	■	■										■	■				■	■
1500	152			■	■				■	■	■	■				■	■	■	■					■	■	■										■	■				■	■
1800	182	■	■	■	■				■	■	■				■	■	■	■	■					■	■	■										■	■				■	■
2200	222	■	■	■	■				■	■	■				■	■	■	■	■					■	■	■								■	■	■	■				■	■
2700	272	■	■	■			■	■	■	■					■	■	■	■	■					■	■	■								■	■	■	■				■	■
3300	332	■	■	■			■	■	■	■					■	■	■	■	■			■	■	■	■	■							■	■	■	■				■	■
3900	392	■	■	■			■	■	■	■					■	■	■	■				■	■	■	■	■							■	■	■	■				■	■
4700	472	■	■	■			■	■	■						■	■	■	■				■	■	■	■	■							■	■	■	■				■	■
5600	562	■	■	■			■	■	■						■	■	■	■				■	■	■	■	■					■	■	■	■	■	■				■	■
6800	682	■	■				■	■	■						■	■	■	■				■	■	■	■	■					■	■	■	■	■	■				■	■
8200	822	■	■				■	■	■						■	■	■					■	■	■	■	■					■	■	■	■	■	■			■	■	■
.010u	103	■	■				■	■	■				■	■	■	■	■					■	■	■	■	■					■	■	■	■	■	■			■	■	■
.012	123	■	■				■	■	■				■	■	■	■	■			■	■	■	■	■	■					■	■	■	■	■	■			■	■	■	
.015	153	■	■				■	■	■				■	■	■	■				■	■	■	■	■	■					■	■	■	■	■	■			■	■	■	
.018	183	■	■				■	■	■				■	■	■	■				■	■	■	■	■	■			■	■	■	■	■	■	■			■	■	■	■	
.022	223	■	■				■	■	■				■	■	■	■				■	■	■	■	■	■			■	■	■	■	■	■	■				■	■	■	
.027	273	■	■				■	■					■	■	■	■				■	■	■	■	■				■	■	■	■	■	■	■		■	■	■	■	■	■	
.033	333	■	■				■	■					■	■	■					■	■	■	■					■	■	■	■	■				■	■	■	■	■	■	
.039	393	■	■				■	■					■	■	■					■	■	■	■					■	■	■	■	■				■	■	■	■	■	■	
.047	473	■	■				■	■					■	■	■					■	■	■	■					■	■	■	■					■	■	■	■	■		
.056	563	■	■				■	■					■	■	■					■	■	■						■	■	■	■					■	■	■	■	■		
.068	683	■					■	■					■	■	■					■	■	■						■	■	■	■					■	■	■	■			
.082	823	■					■	■					■	■	■					■	■	■						■	■	■	■					■	■	■	■			
.10	104	■					■	■					■	■						■	■	■						■	■	■						■	■	■	■			
.12	124	■					■	■					■	■						■	■	■						■	■	■						■	■	■	■			
.15	154	■					■	■					■	■						■	■	■						■	■	■						■	■	■				
.18	184	■					■						■	■						■	■							■	■	■						■	■	■				
.22	224	■					■						■	■						■	■							■	■	■						■	■	■				
.27	274						■						■	■						■	■							■	■							■	■	■				
.33	334						■						■	■						■	■							■	■							■	■	■				
.39	394						■						■	■						■	■							■	■							■	■	■				
.47	474												■	■						■	■							■	■							■	■					
.56	564												■	■						■	■							■	■							■	■					
.68	684												■							■	■							■	■							■	■					
.82	824												■							■	■							■	■							■	■					
1.0	105												■							■								■	■							■	■					
1.2	125												■							■								■	■							■	■					
1.5	155												■							■								■								■	■					
1.8	185																			■								■								■	■					
2.2	225																			■								■								■						
2.7	275																											■								■						
3.3	335																											■								■						
3.9	395																											■								■						
4.7	475																																			■						
5.6	565																																			■						

© KEMET Electronics Corporation • P.O. Box 5928 • Greenville, SC 29606 (864) 963-6300 • www.kemet.com

FEATURES

Disc ceramic capacitors made under strict quality control procedures are a reliable component. Special attention is given to the ceramic pressing operation to assure high and uniform ceramic density.
These parts are manufactured for the quality conscious customer. Parts are available screened to MIL-PRF-49467 established reliability specification.

CAPACITOR OUTLINE DRAWING



INSTALLATION

Higher-voltage parts may require further encapsulation to prevent surface breakdown. Parts should be cleaned and oven dried at 85°C before further encapsulation. Silicone rubbers or an epoxy may be used. De-airing of encapsulants is recommended. We recommend that a heat sink be attached to the lead between the soldering iron and the capacitor during installation soldering. Testing of higher-voltage parts before encapsulation may be done in a suitable dielectric fluid such as Freon.

DIELECTRIC COMPARISON

CERAMIC TYPE	C0G (NP0)	X7R	X5U
Dissipation Factor	0.1%	2.5%	2.5%
Temperature Coefficient	±30ppm/ºC	±15%	+22% -56%
Voltage Coefficient	0	-20%	N/A
Dielectric Withstanding Voltage Test	3 to 15kV at 1.5x rated, 20 to 50kV at rated +10kV	3 to 15kV at 1.5x rated, 20 to 50kV at rated +10kV	3 to 15kV at 1.5x rated, 20 to 50kV at rated +10kV
Insulation Resistance (25ºC)	100k megohms or 1k megohms-µF, whichever is less	100k megohms or 1k megohms-µF, whichever is less	10k megohms or 100 megohms-µF, whichever is less
Operating Temperature Range (rated voltage)	-55ºC to +125ºC	-55ºC to +125ºC	-55ºC to +85ºC

Thickness: Inches (mm) max.
3kV = 0.15 (3.81)
5kV = 0.20 (5.08)
7.5kV = 0.28 (7.11)
10kV = 0.35 (8.89)
15kV = 0.45 (11.43)
20kV = 0.55 (13.97)
30kV = 0.95 (24.13)
40kV = 1.20 (30.48)
50kV = 1.50 (38.10)

Lead Type: Solder plated, copper-clad steel (CCFE)-
D30, D40: 0.025" (22GA)
D50 & Larger: 0.032" (20GA)

PART NUMBER AND ORDERING INFORMATION

30 D50 W 122 M M Q

Voltage
30 =3000V
100 =10,000V
etc.

Style
D50, etc.

Dielectric
N = C0G (NP0)
W = X7R
Y = X5U

MARKING

(D30)	(All Other Sizes)
301M	D50W122M
3kV	3kV
KEC	KEC
Date Code	Date Code

Capacitance Value
First two digits are significant, last digit is number of zeroes, i.e., 472=4700pF

Tolerance
J = ±5% C0G (NP0)
K = ±10%
M = ±20%
P = 0/+100%
Z = -20%/+80%

Group A Screening*
Add to part number if required
*MIL-PRF-49467 (subgroup 1) except Corona

No Leads
Add to part number if required

© KEMET Electronics Corporation • P.O. Box 5928 • Greenville, SC 29606 (864) 963-6300 • www.kemet.com

3K VDC

Disc Style	D Max.	S ±.030	C0G (NP0)		X7R		X5U	
			Min.	Max.	Min.	Max.	Min.	Max.
D30	.30	.250	7.8pF	9.6pF	250pF	300pF	520pF	700pF
D40	.40	.250	20pF	25pF	630pF	770pF	1300pF	1800pF
D50	.50	.375	36pF	44pF	1100pF	1400pF	2400pF	3200pF
D75	.75	.375	80pF	98pF	2500pF	3100pF	5300pF	7200pF
D90	.90	.500	123pF	150pF	3800pF	4700pF	8200pF	11000pF
D100	1.00	.500	145pF	178pF	4600pF	5600pF	9700pF	13000pF
D120	1.20	.500	193pF	236pF	6000pF	7400pF	12900pF	17300pF

5K VDC

D30	.30	.250	4.7pF	5.7pF	150pF	180pF	310pF	420pF
D40	.40	.250	12pF	15pF	380pF	460pF	810pF	1100pF
D50	.50	.375	21pF	26pF	670pF	820pF	1400pF	1900pF
D75	.75	.375	48pF	59pF	1500pF	1800pF	3200pF	4300pF
D90	.90	.500	74pF	90pF	2300pF	2800pF	4900pF	6600pF
D100	1.00	.500	87pF	107pF	2700pF	3300pF	5800pF	7800pF
D120	1.20	.500	116pF	141pF	3600pF	4400pF	7700pF	10400pF

7.5K VDC

D30	.30	.250	3.1pF	3.8pF	100pF	120pF	210pF	280pF
D40	.40	.250	8.1pF	9.9pF	250pF	310pF	540pF	720pF
D50	.50	.375	14pF	17pF	450pF	550pF	950pF	1300pF
D75	.75	.375	32pF	39pF	1000pF	1200pF	2100pF	2900pF
D90	.90	.500	49pF	60pF	1500pF	1900pF	3300pF	4400pF
D100	1.00	.500	58pF	71pF	1800pF	2200pF	3900pF	5200pF
D120	1.20	.500	77pF	94pF	2400pF	3000pF	5100pF	6900pF

10K VDC

D30	.30	.250	2.4pF	2.9pF	70pF	90pF	160pF	210pF
D40	.40	.250	6.1pF	7.4pF	190pF	230pF	400pF	540pF
D50	.50	.375	10.7pF	13.1pF	330pF	410pF	710pF	960pF
D75	.75	.375	24pF	29pF	750pF	920pF	1600pF	2200pF
D90	.90	.500	37pF	45pF	1200pF	1400pF	2500pF	3300pF
D100	1.00	.500	44pF	53pF	1400pF	1700pF	2900pF	3900pF
D120	1.20	.500	58pF	71pF	1800pF	2200pF	3900pF	5200pF

15K VDC

D30	.30	.250	1.6pF	1.9pF	50pF	60pF	100pF	140pF
D40	.40	.250	4.0pF	4.9pF	130pF	150pF	270pF	360pF
D50	.50	.375	7.1pF	8.7pF	220pF	270pF	480pF	640pF
D75	.75	.375	16pF	20pF	500pF	610pF	1100pF	1400pF
D90	.90	.500	25pF	30pF	770pF	940pF	1600pF	2200pF
D100	1.00	.500	29pF	36pF	910pF	1100pF	1900pF	2600pF
D120	1.20	.500	39pF	47pF	1200pF	1500pF	2600pF	3500pF

20K VDC

D30	.30	.250	1.2pF	1.4pF	37pF	45pF	80pF	110pF
D40	.40	.250	3.0pF	3.7pF	100pF	120pF	200pF	270pF
D50	.50	.375	5.3pF	6.5pF	170pF	200pF	360pF	480pF
D75	.75	.375	12pF	15pF	380pF	460pF	800pF	1100pF
D90	.90	.500	18pF	22pF	580pF	700pF	1200pF	1600pF
D100	1.00	.500	22pF	27pF	680pF	830pF	1500pF	2000pF
D120	1.20	.500	29pF	35pF	910pF	1100pF	1900pF	2600pF

30K, 40K & 50K VDC

Disc Style	D Max.	S ±.030	30kVDC X7R		40kDVC X7R		50kVDC X7R	
			Min.	Max.	Min.	Max.	Min.	Max.
D30	.30	.250	20pF	30pF	18pF	22pF	10pF	20pF
D40	.40	.250	60pF	80pF	50pF	60pF	40pF	50pF
D50	.50	.375	110pF	140pF	80pF	100pF	70pF	80pF
D75	.75	.375	250pF	310pF	190pF	230pF	150pF	180pF
D90	.90	.500	380pF	470pF	290pF	350pF	230pF	280pF
D100	1.00	.500	460pF	560pF	340pF	420pF	270pF	330pF
D120	1.20	.500	600pF	740pF	450pF	550pF	360pF	440pF


© KEMET Electronics Corporation • P.O. Box 5928 • Greenville, SC 29606 (864) 963-6300 • www.kemet.com

FEATURES

1. Special lead configurations available.
2. Custom designs are available upon request.

D dimension - See previous page for capacitance/voltage desired and resulting diameter.

CAPACITOR OUTLINE DRAWING



L DIMENSION
INCHES (MM) MAX.

Number of Selections	Voltage per Section				
	5k VDC	7.5k VDC	10k VDC	15k VDC	20k VDC
2	.40 (10.16)	.50 (12.70)	.60 (15.24)	.90 (22.86)	1.00 (25.40)
3	.55 (13.97)	.70 (17.78)	.85 (21.59)	1.15 (29.21)	1.55 (39.07)
4	.70 (17.78)	.85 (21.59)	1.10 (27.94)	1.45 (36.83)	1.90 (48.26)
5	.80 (20.32)	1.10 (27.94)	1.30 (33.02)	1.80 (45.72)	2.30 (58.42)
6	.95 (24.13)	1.30 (33.02)	1.55 (39.07)	2.15 (54.61)	2.75 (69.85)
S ±0.030 (±.76)	.13 (3.30)	.18 (4.57)	.23 (5.84)	.33 (8.35)	.43 (10.92)

PART NUMBER AND ORDERING INFORMATION

4X **100** **D90** **W** **102** **K**

Number of Sections

Voltage
30 = 3000V
50 = 5000 V
75 = 7500 V
100 =10,000V
150 = 15,000 V
200 =20,000 V

Style
D50, etc.

Dielectric
N = C0G (NP0)
W = X7R
Y = X5U

Tolerance
J = ±5% C0G (NP0)
K = ±10%
M = ±20%
P = 0/+100%
Z = -20%/+80%

Capacitance Value
First two digits are significant, last digit is number of zeros, i.e., 102=1000pF

MARKING

(D30)	(All Other Sizes)
301M	4XD50W122M
3kV	3kV
KEC	KEC
Date Code	Date Code

© KEMET Electronics Corporation • P.O. Box 5928 • Greenville, SC 29606 (864) 963-6300 • www.kemet.com


Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits,General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)
Факс: 8 (812) 320-02-42
Электронная почта: org@eplast1.ru
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.