

4

3

2

1

NOTES:

1. ALL DIMENSIONS ARE IN INCHES / LBS [MILLIMETERS] [GRAMS]

2. DIMENSIONS APPEARING IN TABLE ARE AS FOLLOWS:

- a AS SUPPLIED
b AFTER UNRESTRICTED RECOVERY

COATING (ADHESIVE) IS OPTIONAL. AS SUPPLIED DIMENSIONS APPEARING IN TABLE ARE FOR UNCOATED PARTS. WHEN COATING IS ADDED, ENTRY DIAMETERS WILL BE REDUCED BY .06 MAX.

MOLDING PORTS ARE OPTIONAL. WHEN -00 MODIFICATION NUMBER IS SPECIFIED MOLDING PORTS WILL BE LOCATED AS SHOWN.


ON SIZES 222A111 AND 222A121 THE 0.18 INCH DIAMETER MOLDING PORT AT "T" WILL BE ELIMINATED. THE 0.12" DIA MOLDING PORT WILL BE ENLARGED TO 0.18 INCHES

5. WEIGHT SHOWN IN TABLE OF DIMENSIONS IS BASED ON POLYOLEFIN PART


6. ORDERING INFORMATION 222A1XX -XX -XX /XXX /0

- BASE PART NUMBER
MATERIAL DASH NUMBER
-3 POLYOLEFIN, SEMI RIGID (RT-301)
-4 POLYOLEFIN, FLEXIBLE (RT-1304)
-5 ELASTOMER, FLEXIBLE (RT-501)
-6 SILICONE (RT-602)
-12 FLUORO ELASTOMER, FLEXIBLE (RT-1312)
-25 ELASTOMER, FLUID RESISTANT (RW-2070)
-100 POLYOLEFIN, SEMI-FLEXIBLE ZEROHAL (RT-1323)

MODIFICATION NUMBER
ADHESIVE SLASH NUMBER
SEE COMPATIBILITY CHART BELOW
COLOR DESIGNATOR



AS SUPPLIED



AFTER UNRESTRICTED RECOVERY

Table with 3 columns: LTR, DESCRIPTION, DATE. Row 1: V, REVISED PER ECO-15-010088, 07/01/15

TABLE OF DIMENSIONS

Table with columns: PART DESCRIPTION, H (MIN, MAX), J (MIN, MAX), P, R, S, T, U, JO, W, C*, WEIGHT REF. Lists parts 222A111 through 222A196 with their respective dimensions.

IF THIS DOCUMENT IS PRINTED IT BECOMES UNCONTROLLED. CHECK FOR THE LATEST REVISION.

COMPATIBILITY CHART

Table with 3 columns: MATERIAL DASH NO., ADHESIVE (COATING) SLASH NO., ADHESIVE (COATING) S NO. Lists compatibility for various dash numbers.

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE INCHES. METRIC DIMENSIONS ARE IN BRACKETS. DECIMAL TOLERANCES: .XXX ± 0.005 [0.13 mm], .XX ± 0.01 [0.25 mm], .X ± 0.1 [0.50 mm]. ANGLE TOLERANCE: .X ± 1 DEG.

DRAWN: YUNGUYEN
APPROVED: DHURRELL
THIRD ANGLE PROJECTION symbol

CUSTOMER DRAWING

TE Connectivity logo and address: Raychem Molded Parts, 305 Constitution Dr, Menlo Park, CA 94025. Title: BOOT, 90 DEGREE, THIN WALL. Size: B, Code Ident. No.: 06090, Dwg. No.: 222A111thru196.

DO NOT SCALE THIS DRAWING SHEET 1 OF 1



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.