



For more
Information
please call

1-800-Belden1



General Description:

FiberExpress Single Jacket-All Dielectric Cable, 12-Fiber, OS2 OFNR, Loose Tube, Indoor & Outdoor Rated with UV Resistant Black Jacket, No grounding required, Suited for aerial lashing and underground conduit.

Physical Characteristics (Overall)

Fiber Type:	SM, (OS2)
Number of Fibers:	12
Mode Field Diameter @ 1310nm:	9.2
Clad Diameter:	125
Primary Coating Diameter:	245
Buffer Tube Material:	Thermoplastic

Outer Jacket

Outer Jacket Material:	
Outer Jacket Material:	PVC - Polyvinyl Chloride
Outer Jacket Color:	Black

Strength Member

Strength Member Material:	Aramid Yarn, Fiberglass Epoxy Rod
---------------------------	-----------------------------------

Overall Cable

Overall Nominal Diameter:	0.510 in.
---------------------------	-----------

Mechanical Characteristics (Overall)

Storage Temperature Range:	-40°C To +75°C
Installation Temperature Range:	-30°C To + 70°C
Operating Temperature Range:	-40°C To +70°C
Bulk Cable Weight:	108 lbs/1000 ft.
Min. Bend Radius/Minor Axis:	10,200 in.
Min. Bend Radius for Long Term Application:	5,100 in.
Max. Load for Installation:	600 lbs.
Max. Load for Long Term Application:	200 lbs.

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

NEC(UL) Specification:	OFNR
CEC(C/UL) Specification:	OFN
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	08/22/2008
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

Flame Test

UL Flame Test:	UL1666 Riser
C(UL) Flame Test:	FT4
CSA Flame Test:	FT4

B9W811 Fiber - All Dielectric Cable - In/Outdoor Riser

Suitability

Suitability - Indoor:	Yes
Suitability - Outdoor:	Yes
Suitability - Aerial:	Yes - When supported by messenger wire
Suitability - Burial:	Yes
Sunlight Resistance:	Yes
Plenum/Non-Plenum	
Plenum (Y/N):	No

Optical Characteristics (Overall)

Maximum Attenuation @ 1310nm:	.35 dB/km
Maximum Attenuation @ 1550nm:	.25 dB/km
Maximum Gigabit Ethernet Length @ 1300nm:	5000 meters

Fiber Coding MLT EMEA:

Fiber/Tube No.	Color
1	Blue
2	Orange
3	Green
4	Brown
5	Slate
6	White
7	Red
8	Black
9	Yellow
10	Violet
11	Rose
12	Aqua

Related Documents:

[Loose Tube Single Jacket All Dielectric.pdf](#) - Loose Tube Single Jacket All Dielectric technical information.

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
B9W811	1 FT	0.080 LB	BLACK		REPLACED BY FDSL012RF

Revision Number: 2 Revision Date: 07-23-2014

© 2017 Belden, Inc.
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.