

## AQ24CANFD 200W TVS Diode Array




### Description

The AQ24CANFD is designed to protect automotive Controller Area Network (CAN) lines from damage due to electrostatic discharge (ESD), electrical fast transient (EFT), and other overvoltage transients.

The AQ24CANFD can absorb repetitive ESD strikes above the maximum level specified in the IEC 61000-4-2 international standard without performance degradation and can safely withstand 3A surge (8/20 waveshape as defined in IEC 61000-4-5 2<sup>nd</sup> edition) at a very low clamping voltage.

### Pinout and Functional Block Diagram




### Features

- ESD, IEC 61000-4-2,  $\pm 21\text{kV}$  contact,  $\pm 21\text{kV}$  air
- EFT, IEC 61000-4-4, 50A (5/50ns)
- Lightning, 3A (8/20 $\mu\text{s}$  as defined in IEC 61000-4-5 2<sup>nd</sup> edition)
- PPAP capable
- ESD, ISO 10605, 330pF 330 $\Omega$ ,  $\pm 21\text{kV}$  contact,  $\pm 21\text{kV}$  air
- Low clamping voltage
- Low leakage current
- AEC-Q101 qualified
- Moisture Sensitivity Level (MSL -1)
- Halogen free, lead free and RoHS compliant

### Applications

- CAN Bus Protection
- Automotive Applications
- Electronic Control Units
- Body Control Units
- ADAS Control Units
- PowerTrain Control Units
- Factory Automation
- Lightning Control (DALI)

### Application Example



Life Support Note:

**Not Intended for Use in Life Support or Life Saving Applications**

The products shown herein are not designed for use in life sustaining or life saving applications unless otherwise expressly indicated.

## Absolute Maximum Ratings

| Symbol     | Parameter                              | Value      | Units |
|------------|----------------------------------------|------------|-------|
| $P_{PK}$   | Peak Pulse Power ( $t_p=8/20\mu s$ )   | 200        | W     |
| $I_{PP}$   | Peak Pulse Current ( $t_p=8/20\mu s$ ) | 3.0        | A     |
| $T_{OP}$   | Operating Temperature                  | -40 to 150 | °C    |
| $T_{STOR}$ | Storage Temperature                    | -55 to 150 | °C    |

Notes:

CAUTION: Stresses above those listed in "Absolute Maximum Ratings" may cause permanent damage to the component. This is a stress only rating and operation of the component at these or any other conditions above those indicated in the operational sections of this specification is not implied.

## Electrical Characteristics ( $T_{OP}=25^{\circ}C$ )


| Parameter                          | Symbol        | Test Conditions                                         | Min  | Typ  | Max      | Units    |
|------------------------------------|---------------|---------------------------------------------------------|------|------|----------|----------|
| Reverse Standoff Voltage           | $V_{RWM}$     | $I_R=1\mu A$ , Pin1 or Pin2 to Pin3                     |      |      | 24.0     | V        |
| Breakdown Voltage                  | $V_{BR}$      | $I_R=1mA$ , Pin1 or Pin2 to Pin3                        | 26.7 | 28.0 |          | V        |
| Reverse Leakage Current            | $I_{LEAK}$    | $V_R=24V$                                               |      | 0.02 | 0.5      | $\mu A$  |
| Clamp Voltage <sup>1</sup>         | $V_C$         | $I_{PP}=1A$ , $t_p=8/20\mu s$ , Pin 1 or Pin 2 to Pin 3 |      | 32.7 | 40.0     | V        |
|                                    |               | $I_{PP}=3A$ , $t_p=8/20\mu s$ , Pin 1 or Pin 2 to Pin 3 |      | 41.2 | 50.0     | V        |
| Dynamic Resistance <sup>2</sup>    | $R_{DYN}$     | TLP, $t_p=100ns$ , I/O to GND                           |      | 0.5  |          | $\Omega$ |
| ESD Withstand Voltage <sup>1</sup> | $V_{ESD}$     | IEC 61000-4-2 (Contact Discharge)                       |      |      | $\pm 21$ | kV       |
|                                    |               | IEC 61000-4-2 (Air Discharge)                           |      |      | $\pm 21$ | kV       |
| Diode Capacitance <sup>1</sup>     | $C_{I/O-GND}$ | Reverse Bias=0V, $f=1MHz$ ;<br>Pin 1 or Pin2 to Pin 3   |      | 11.5 | 14.0     | pF       |

Note:


1 Parameter is guaranteed by design and/or component characterization.

2 Transmission Line Pulse (TLP) with 100ns width, 2ns rise time, and average window  $t_1=70ns$  to  $t_2=90ns$


## 8/20 $\mu s$ Pulse Waveform




## Clamping Voltage vs $I_{PP}$




**Capacitance vs. Reverse Bias**




**Transmission Line Pulsing (TLP) Plot**



**IEC 61000 -4-2 +8 kV Contact ESD Clamping Voltage**




**IEC 61000 -4-2 -8 kV Contact ESD Clamping Voltage**



**ISO10605 +8 kV Contact ESD Clamping Voltage**




**ISO10605 -8 kV Contact ESD Clamping Voltage**




### Soldering Parameters

|                                                        |                                    |                         |
|--------------------------------------------------------|------------------------------------|-------------------------|
| Reflow Condition                                       |                                    | Pb – Free assembly      |
| Pre Heat                                               | - Temperature Min ( $T_{s(min)}$ ) | 150°C                   |
|                                                        | - Temperature Max ( $T_{s(max)}$ ) | 200°C                   |
|                                                        | - Time (min to max) ( $t_s$ )      | 60 – 180 secs           |
| Average ramp up rate (Liquidus) Temp ( $T_L$ ) to peak |                                    | 3°C/second max          |
| $T_{s(max)}$ to $T_L$ - Ramp-up Rate                   |                                    | 3°C/second max          |
| Reflow                                                 | - Temperature ( $T_L$ ) (Liquidus) | 217°C                   |
|                                                        | - Temperature ( $t_L$ )            | 60 – 150 seconds        |
| Peak Temperature ( $T_p$ )                             |                                    | 260 <sup>+0/-5</sup> °C |
| Time within 5°C of actual peak Temperature ( $t_p$ )   |                                    | 20 – 40 seconds         |
| Ramp-down Rate                                         |                                    | 6°C/second max          |
| Time 25°C to peak Temperature ( $T_p$ )                |                                    | 8 minutes Max.          |
| Do not exceed                                          |                                    | 260°C                   |




### Part Marking System



AB : Part code  
V : Assembly code  
D : Date code

### Part Numbering System




### Ordering Information

| Part Number     | Package | Min. Order Qty. |
|-----------------|---------|-----------------|
| AQ24CANFD-02HTG | SOT23-3 | 3000            |

### Product Characteristics

|                           |                                                        |
|---------------------------|--------------------------------------------------------|
| <b>Lead Plating</b>       | Matte Tin                                              |
| <b>Lead Material</b>      | Copper Alloy                                           |
| <b>Lead Coplanarity</b>   | 0.004 inches(0.102mm)                                  |
| <b>Substrate material</b> | Silicon                                                |
| <b>Body Material</b>      | Molded Compound                                        |
| <b>Flammability</b>       | UL Recognized compound meeting flammability rating V-0 |


### Package Dimensions — SOT23-3



Recommended soldering pad layout (unit :mm)

| Symbol    | Millimeters |      |      | Inches    |       |       |
|-----------|-------------|------|------|-----------|-------|-------|
|           | Min         | Nom  | Max  | Min       | Nom   | Max   |
| <b>A</b>  | 0.89        | -    | 1.17 | 0.035     | -     | 0.046 |
| <b>A1</b> | 0.01        | -    | 0.15 | 0.000     | -     | 0.006 |
| <b>A2</b> | 0.88        | 0.95 | 1.02 | 0.035     | 0.037 | 0.040 |
| <b>b</b>  | 0.30        | -    | 0.50 | 0.012     | -     | 0.020 |
| <b>b1</b> | 0.30        | 0.40 | 0.45 | 0.012     | 0.016 | 0.018 |
| <b>c</b>  | 0.08        | -    | 0.20 | 0.003     | -     | 0.008 |
| <b>c1</b> | 0.08        | 0.10 | 0.16 | 0.003     | 0.004 | 0.006 |
| <b>D</b>  | 2.80        | 2.90 | 3.04 | 0.110     | 0.114 | 0.120 |
| <b>E</b>  | 2.10        | 2.35 | 2.60 | 0.083     | 0.093 | 0.102 |
| <b>E1</b> | 1.20        | 1.30 | 1.40 | 0.047     | 0.051 | 0.055 |
| <b>e</b>  | 0.95 BSC    |      |      | 0.037BSC  |       |       |
| <b>e1</b> | 1.90 BSC    |      |      | 0.075BSC  |       |       |
| <b>L</b>  | 0.28        | 0.44 | 0.60 | 0.011     | 0.017 | 0.024 |
| <b>L1</b> | 0.54 REF    |      |      | 0.021 REF |       |       |
| <b>L2</b> | 0.25 BSC    |      |      | 0.010 BSC |       |       |
| <b>θ</b>  | 0°          | -    | 8°   | 0°        | -     | 8°    |

### Embossed Carrier Tape & Reel Specification — SOT23-3



| Symbol    | Millimetres |      | Inches |       |
|-----------|-------------|------|--------|-------|
|           | Min         | Max  | Min    | Max   |
| <b>E</b>  | 1.65        | 1.85 | 0.065  | 0.073 |
| <b>F</b>  | 3.40        | 3.60 | 0.134  | 0.142 |
| <b>P2</b> | 1.90        | 2.10 | 0.075  | 0.083 |
| <b>D</b>  | 1.40        | 1.60 | 0.055  | 0.063 |
| <b>P0</b> | 3.90        | 4.10 | 0.154  | 0.161 |
| <b>W</b>  | 7.70        | 8.30 | 0.303  | 0.327 |
| <b>P</b>  | 3.90        | 4.10 | 0.154  | 0.161 |
| <b>A0</b> | 3.05        | 3.25 | 0.120  | 0.128 |
| <b>B0</b> | 2.67        | 2.87 | 0.105  | 0.113 |
| <b>K0</b> | 1.12        | 1.32 | 0.044  | 0.052 |
| <b>t</b>  | 0.22        | 0.24 | 0.009  | 0.009 |

**Disclaimer Notice** - Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice at <http://www.littelfuse.com/disclaimer-electronics>.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.