Grove - Luminance Sensor User Manual

Release date： 2015/9/22

Version： 1.0

Wiki: http://www.seeedstudio.com/wiki/Grove_-_Luminance_Sensor

Bazaar: http://www.seeedstudio.com/depot/Grove-Luminance-Sensor-p-1941.html?cPath=25_128

Document Revision History

Revision	Date	Author	Description
1.0	Sep 22, 2015	Loovee	Create file

Contents

Document Revision History ····· 2
1. Introduction ····· 2
2. Specification ····· 3
3. Hookup Grove Luminance sensor with Seeduino Lotus ····· 4
4. Resource ····· 7

Disclaimer

For physical injuries and possessions loss caused by those reasons which are not related to product quality, such as operating without following manual guide, natural disasters or force majeure, we take no responsibility for that.

Under the supervision of Seeed Technology Inc., this manual has been compiled and published which covered the latest product description and specification. The content of this manual is subject to change without notice.

Copyright

The design of this product (including software) and its accessories is under tutelage of laws. Any action to violate relevant right of our product will be penalized through law. Please consciously observe relevant local laws in the use of this product.

1. Introduction

Grove - Luminance Sensor detects the intensity of the ambient light on a surface area. It uses **APDS-9002** analog output ambient light photo sensor. This has responsivity closer to human eye.

This Luminance Sensor can be used in application which requires automatic light adjustment in residential or commercial lighting.




2. Specification

- Input Voltage: 3.3/5V
- Linear Output Range: 0~2.3V
- Luminance measurement range: 0~1000 Lux

3. Hookup Grove Luminance sensor with Seeduino Lotus

- Plug the Grove-Luminance sensor to the A0 port of Seeeduino Lotus with a Grove connector.



- Copy the following code in an arduino sketch.

```
float VoutArray[] =  { 0.0011498,  0.0033908,  0.011498, 0.041803, 0.15199,  0.53367,  1.3689,
1.9068,  2.3};
float  LuxArray[] =  { 1.0108,  3.1201,  9.8051,  27.43,  69.545,  232.67,  645.11,
73.52,  1000};



void setup() {
    // put your setup code here, to run once:
    Serial.begin(9600);

}

void loop() {
    // put your main code here, to run repeatedly:

    Serial.print("Vout =");
    Serial.print(readAPDS9002Vout(A0));
    Serial.print(" V,Luminance =");
    Serial.print(readLuminance(A0));
    Serial.println("Lux");
    delay(500);

}

float readAPDS9002Vout(uint8_t analogpin)
```

```
{
    // MeasuredVout = ADC Value * (Vcc / 1023) * (3 / Vcc)
    // Vout samples are with reference to 3V Vcc
    // The above expression is simplified by cancelling out Vcc
    float MeasuredVout = analogRead(A0) * (3.0 / 1023.0);
    //Above 2.3V , the sensor value is saturated

    return MeasuredVout;

}

float readLuminance(uint8_t analogpin)
{

    // MeasuredVout = ADC Value * (Vcc / 1023) * (3 / Vcc)
    // Vout samples are with reference to 3V Vcc
    // The above expression is simplified by cancelling out Vcc
    float MeasuredVout = analogRead(A0) * (3.0 / 1023.0);
    float Luminance = FmultiMap(MeasuredVout, VoutArray, LuxArray, 9);

    /*************************************************************************

    The Luminance in Lux is calculated based on APDS9002 datasheet -- > Graph 1
    ( Output voltage vs. luminance at different load resistor)
    The load resistor is 1k in this board. Vout is referenced to 3V Vcc.

    The data from the graph is extracted using WebPlotDigitizer
    http://arohatgi.info/WebPlotDigitizer/app/

    VoutArray[] and LuxArray[] are these extracted data. Using MultiMap, the data
    is interpolated to get the Luminance in Lux.

    This implementation uses floating point arithmetic and hence will consume
    more flash, RAM and time.

    The Luminance in Lux is an approximation and depends on the accuracy of
    Graph 1 used.

    *************************************************************************/

    return Luminance;
}
```

```
//This code uses MultiMap implementation from http://playground.arduino.cc/Main/MultiMap


float FmultiMap(float val, float * _in, float * _out, uint8_t size)
{
    // take care the value is within range
    // val = constrain(val, _in[0], _in[size-1]);
    if (val <= _in[0]) return _out[0];
    if (val >= _in[size-1]) return _out[size-1];

    // search right interval
    uint8_t pos = 1;  // _in[0] allready tested
    while(val > _in[pos]) pos++;

    // this will handle all exact "points" in the _in array
    if (val == _in[pos]) return _out[pos];

    // interpolate in the right segment for the rest
    return (val - _in[pos-1]) * (_out[pos] - _out[pos-1]) / (_in[pos] - _in[pos-1]) + _out[pos-1];
}
```

- Upload the code to seeeduino lotus.
- Hold the Grove Luminance sensor under a light source or in a place where lux has to be detected.
- Open the serial monitor.



- The Vout and Lux is displayed in the serial monitor.

4. Resource

- Grove-Luminance Sensor Demo code
- Grove-Luminance Sensor eagle file
- Grove-Luminance Sensor PDF
- Datasheet


Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits,General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)
Факс: 8 (812) 320-02-42
Электронная почта: org@eplast1.ru
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.