



RAYCHEM MATCHED IMPEDANCE SPLICES

FAST, EASY REPAIRS THAT MAINTAIN THE COAXIAL CABLE'S
ELECTRICAL CHARACTERISTICS

MATCHED IMPEDANCE

- Maintains cable's electrical properties
- Meets MIL-PRF-32517 performance requirements
- Matches cable's impedance +10%/-3%

TIME AND COST SAVING

- Repairs made in situ
- No need to remove or replace cable

SEALED

- Heat-shrinkable outer layer plus thermoplastic adhesive for sealing and strain relief

ROBUST

- Withstands high vibration
- Corrosion resistant
- Wide temperature range
- Excellent fluid resistance
- Suitable for high EMI environments

APPLICATIONS

- Military Aerospace
- Commercial Aerospace

With the matched impedance splice, TE Connectivity (TE) solves the problem of costly removal and replacement of damaged coaxial cable. Not only does the new splice allow fast, easy repair of the cable in situ, it maintains the characteristic impedance and other electrical properties. System performance is not affected by the repair.

SAVE TIME AND MONEY

Removing and replacing a damaged coaxial cable can be time consuming and expensive. The matched impedance splice's ability to be applied without removing the cable can significantly speed the repair, saving time and cost.

SIMPLE AND EFFECTIVE

The splice contains three components: a hexagonal crimp barrel for the center conductors, a dielectric shell that helps maintain cable geometry for impedance control, and a SolderShield splice that both terminates the cable's shield and provides sealing to protect the splice environmentally.

The SolderShield splice uses a flux-coated, solder-impregnated copper shield inside an adhesive-lined, heat-shrinkable sleeve. The completed assembly provides an environmentally sealed termination and strain relief.

TE Components . . . TE Technology . . . TE Know-how . . .

AMP | Agastat | CII | Hartman | Kilovac | Microdot | Nanonics | Polamco | Raychem | Rochester | DEUTSCH
SEACON Phoenix | L.L. Rowe | Phoenix Optix | AFP | SEACON

Get your product to market faster with a smarter, better solution.

Raychem Matched Impedance Splices

Fast, Easy Cable Repair

SPECIFICATIONS

Electrical

Impedance:	MIL-PRF-32517
Insertion Loss:	MIL-PRF-32517
Return Loss:	MIL-PRF-32517
Insulation Resistance:	5000 M Ω

Environmental/Mechanical

Altitude Immersion:	75,000 ft
Heat Aging:	750 hr. at +165°C
Temperature Range:	-55° C to 150°C

Cable Compatibility


Cable Types:	RG-393
---------------------	--------

TE Specifications

Application Specification:	D-6204
Product Specification:	D-6204
Qualification Test Reports:	HT4203 (for D-150-Z393)
Installation Instructions:	RPIP-1108

PART NUMBERS

Cable Type	Part Number
RG-393	D-150-Z393



te.com/matched-impedance-splice

© 2016 TE Connectivity Ltd. family of companies. All Rights Reserved.

1-1773880-4 05/16

Raychem, SolderShield, TE, TE Connectivity and the TE connectivity (logo) are trademarks of the TE Connectivity Ltd. family of companies.

Other product or company names mentioned herein may be trademarks of their respective owners.

While TE has made every reasonable effort to ensure the accuracy of the information herein, nothing herein constitutes any guarantee that such information is error-free, or any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. The TE entity issuing this publication reserves the right to make any adjustments to the information contained herein at any time without notice. All implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose are expressly disclaimed. The dimensions herein are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice.

Consult TE for the latest dimensions and design specifications.

North America +1 800 522 6752 • Asia Pacific +86 400 820 6015 • France +33 1 34 20 86 86 • Germany +49 6251 133 1999 • United Kingdom +44 800 267 666
Visit te.com for additional country contacts.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.