SRP-EEM351

Factory Energy Management Solution



Features

- Highly stable and reliable centralized monitoring and management system for key energy consumption equipment
- Intact data guaranteed by store and forward when communication fails
- Easy to understand data indicators via intuitive graphical display
- Smart alarm notification through SMS, e-mail
- Complete energy consumption statistics and analysis tool to capture energy waste and reduce energy costs
- Easy maintenance of backend via simple management
- Unified and flexible central management system for integrating existing systems
- Cross browser and platform support powered by the WebAccess Dashboard

Introduction

Advantech factory energy management solution aims to save energy costs, reduce maintenance, and increase production. It provides the hardware and software needed to establish an efficient energy management system. This solution adopts an acquisition gateway which supports multi-protocols and multi-network communications to accurately target high energy consuming devices and factory facilities. With the help of Advantech's WebAccess/EMS software and high-performance industrial computer it can perform remote real-time monitoring, smart alarms, report statistics and intelligent analysis, to help managers find abnormal energy consumption and identify areas that need improving. It will optimize the energy use of equipment, improve production scheduling, and make energy savings all round.

System Diagram



Major System Functions

Graphical Dashboard for Clear Energy Indicators

- The whole factory energy data integrated in one screen
- Real-time energy performance indictors
- Flexible filter to display the real-time information of selected item
- [My favorite] personal exclusive page



Data Diagnosis to Save Energy

- Connects MES/ERP system, compares work orders, finds abnormal power consumption and adjusts peak electricity
- · Amortizes public facilities' electricity expenses with actual usage
- Electricity calibration, balances energy management fees and accounting statements



SCADA for Centralized/Decentralized Control

- WebAccess/SCADA graphical control software platform, with complete SCADA graphical control expansion functions
- Single interface integrates all plant environmental control messages and offers unified warnings



Displays Electricity Usage for Analysis

- · Peak/off-peak/semi-peak separation analysis
- Long-term record of electricity consumption to calculate the best contract capacity
- Group, timeline comparison analysis tool
- Establish energy performance indicators and energy consumption baseline



Easy Maintenance of Backend System

- Easy expansion
- System data can be exported to Excel
- Electricity amortization can be flexibly set due to organizational changes



Mobile Devices Support for Monitoring Anywhere/Anytime

- Based on HTLM5 platform, supports cross-browser & cross-platform viewing
- · Real-time exception alerts via APP push notifications, improving reaction rates



EMS Software Specifications

General

- Database
- Office
- Report Export Format
- Display Resolution
- Cross Browser and Platform
- Language

Browser

Office 2016 Excel 1920 x 1080 (Optimal) Yes Simplified Chinese/Traditional Chinese/ English Internet Explorer: IE 11 Chrome: Version 50 or above Safari: Version 7 or above

Microsoft SQL Server Express 2012

Data Refresh and Response Time

Items	Refresh	Response
Device Communication Status	5 s	< 5s (Affected by the network channel delay and controlled equipment)
Real-time Data	5 s	< 5s (Affected by the network channel delay and controlled equipment)
Weather Information	1 min	< 5s (Affected by the network channel delay and controlled equipment)
Demand Data	1 min	< 5s (Affected by the network channel delay and controlled equipment)
Energy Consumption Data	15 min	< 5s (Affected by the network channel delay and controlled equipment)
Electricity Cost Data	1 day	< 5s (Affected by the network channel delay and controlled equipment)
Energy Consumption Data for per Unit Capacity	1 day	< 5s (Affected by the network channel delay and controlled equipment)

50

Capacity

- Maximum Number of I/O Tags 5000 50
- Maximum Number of Meters Maximum Number of Energy
- **Consumption Items**
- Maximum Number of Building 1
- Maximum Number of 100
- **Building floors** Maximum Number of Areas 100
- Maximum Number of Meters 10
- for Each Area Maximum Number of 100
- Virtual Meters Maximum Number of Groups for 100 Each Organization
- Maximum Number of 20 Organizations
- Maximum Data Retention Period 20 years

Platform Specifications

8GB

IIS 6.1

CE, FCC, UL, CCC, BSMI

Windows 7 Embedded Pro.

.Net Framework 4.0

CE. FCC. BSMI

TI Cortex A8, 800MHz

another one for data storage

2 x 10/100 Base-T RJ-45 ports

Intel Haswell Core i7 4650U dual-core

1 x 2.5" HDD 500GB, 1 x 2.5" HDD 1TB

4 x 10/100/1000 1000Base-T RJ45 ports

EMS Server

- Certification
- CPU
- Memory •
- Storage
- Ethernet Port •
- **Operating System** •
- Framework .
 - Web Server

Data Gateway

- Certification
- CPU
- Storage
- Ethernet Port
- Wireless (Optional)
- Configuration Tool
- Advantech TagLink Studio Protocol Support Modbus, IEC-60870-104(slave)

Ordering Information

- SRP-EEM351-TOA
- 1 x ECU-1251 with Advantech TagLink and 1GB Micro-SD card, 1 x UNO-2483G-474AE with Intel i7-4650U, 8G RAM, 500G HDD, 1TB HDD, WES7P, Office 2016, WebAccess/SCADA 8.2 Pro. 5000 tags, WebAccess/EMS, SQL Server Express 2012

2 x 1GB Micro-SD card, one for system storage and

Interface: 1 x Mini-PCIe (Full-size, signal: USB)

Extension Solution

Gateway

ECU-1251TL-R10AAE TI Cortex A8 Industrial Communication Gateway with 2 x LAN, 4 x COM, 1 x Mini-PCle

Wi-Fi Solution for ECU-1251

- 9656EWMG00E Half to full-size Mini PCIe bracket pack
- EWM-W150H02E Half-size mini card, supports 802.1 1bgn
- 1750006043 SMA (M) cable, 15cm
- 1750000318 2dBi antenna for testing, 11cm

Storage Solution for ECU-1251

96FMMSDI-1G-ET-AT1 ATP 1G MICRO SD CARD I-GRD SLC (G)

Wireless AP

EKI-6332GN IEEE802.11 b/g/n Wi-Fi AP/Client

Smart Meter

- WISE-M502-125C060E 1P2W/5Loop&100A/33.3mA input power meter
- WISE-M502-332C060E 3P3W/2Loop&60A/20mA input power meter



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный) **Факс:** 8 (812) 320-02-42 **Электронная почта:** <u>org@eplast1.ru</u> **Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.