

Technical Data Sheet

RRC-SMB-UBC-M RRC Medical SMBUS Universal Battery Charger



65 Watt Medical SMBUS Desktop Universal Battery Charger for Smart Batteries

Features:

- Single bay fast charger
- For the standard battery form factors RRC2020, 2024, 2040, 2040-2, 2054, 2054-2, 2057 or smart batteries with a similar footprint (e.g. 202x range, 204x range, 205x range, DR36, etc.)
- Optimized charging process for RRC batteries:
 - Longer cycle life
 - Faster charging
- Simple operation – Plug and Play
- Automatic recognition and calibration of smart battery learned capacity
- External power supply for worldwide use
- Country specific AC input cables available

Applications:

- Standard charging station for mobile devices used in medical, industrial and consumer markets

Specification RRC-SMB-UBC

Input	
Voltage range	19 - 26VDC
Current	3400mA max.
Power	65W

Output	
Voltage range	0 - 17.4VDC
Current range	0 - 4.8A
Voltage tolerance ⁽¹⁾	±1% max.
Current tolerance ⁽¹⁾	±10% max. @1A, ±3% max. @4A
Protection	Short circuit Over temperature shutdown Input-/output over current

Environmental	
Cooling	convection cooled
Temperature	Operating: 0°C to 40°C Non-operating -10°C to 70°C
Pressure & Altitude	Operating: 1060hPa to 795hPa -382m to 2000m Non-operating: 1060hPa to 572hPa -382m to 4570m
Humidity	5% to 95% r.H., non-condensing

General	
Efficiency ⁽²⁾	~95% at 100% load
Indicator	Multi-color LED (green, red, orange)
Battery types	Standard battery form factors RRC2020, 2024, 2040, 2040-2, 2054, 2054-2, 2057 or smart batteries with a similar footprint (e.g. 202x range, 204x range, 205x range, DR36, etc.)
Green procurement	RoHS 2011/65/EU WEEE 2012/19/EU Chinese RoHS

LED Indications	
One time Red/Orange/Green	Selftest: Charger is ready for use.
Red/Green blinking	Battery recognition and initialization.
Orange blinking	The battery is currently being calibrated.
Orange light	The inserted battery is of the correct type and is currently being charged.
Green light	The battery is charged and can be removed for use.
Red blinking	The battery is too hot or too cold to be charged without damage. If the battery is too cold it will be charged as soon as it has warmed up sufficiently. If the battery is too hot it should be removed to cool down.
Red light	The battery is damaged or it is a conventional battery which cannot be recharged.

Notes:

1. Total regulation tolerance includes initial set accuracy, line and load regulation
2. Power losses of input and output cables are not considered here.

Technical Data Sheet

RRC-SMB-UBC-M RRC Medical SMBUS Universal Battery Charger



Charger Mechanical Details	
Housing dimensions (LxWxH)	151 x 90 x 43mm
Weight	198g (excluding power supply)

Safety & EMC	In combination with specified external AC/DC power supply	
Regulatory approvals	Europe	CE
Electromagnetic Emissions	Europe USA	EN55011, EN55032, level B FCC15 class B
Electromagnetic Immunity	ESD immunity	EN/IEC61000-4-2
	Electromagnetic field immunity	EN/IEC61000-4-3
	EFT / Burst	EN/IEC61000-4-4
	Surge	EN/IEC61000-4-5
	Conducted Immunity	EN/IEC61000-4-6
	Magnetic Fields	EN/IEC61000-4-8
	Voltage dips, short instrumentations & voltage variations	EN/IEC61000-4-11
	Immunity characteristics	EN55024

Specification external AC/DC medical power supply

Input	
Voltage range	100 - 240VAC
Current	1.6A max.
Stand by power	No load < 0.21W @ 230 VAC

Output	
Voltage	19VDC \pm 5%
Power	65W max.
Current range	0 - 3.43A
Protection	Over voltage, over current, Short circuit

Environmental	
Temperature	Operating: 0°C to 40°C Non-operating -20°C to 80°C

General	
Efficiency	DoE VI, ErP (Stage 2), GEMS, NRCAN, CEC, EPA
Ripple & Noise	190mV (p-p)

Power Supply Mechanical Details	
Standard output connector	DC barrel jack (\varnothing 5.5 x \varnothing 2.5 x 9.5mm)
Housing dimensions (LxWxH)	119 x 60 x 36mm
Weight	310g

Safety & EMC		
Safety	ITE Medical	CB, PSE cULus, T-mark, EN/IEC60601-1
EMI	Europe USA / Canada	CE FCC15 class B

Germany/Headquarters	USA	Hong Kong	China
RRC power solutions GmbH Technologiepark 1 D-66424 Homburg / Saar	RRC power solutions Inc. 18340 Yorba Linda Blvd., Suite 107-437 Yorba Linda, CA 92886-4104	RRC power solutions Ltd. S-V,6/F, Valiant Industrial Centre 2-12 Au Pui Wan Street Fo Tan, N.T., Hong Kong	RRC power solutions Ltd. Room 520, Yuanlin Building, Aiguo Road No. 3066, Luohu District, Shenzhen 518021
Tel.: +49 6841 98090 Fax: +49 6841 9809280 Email: sales@rrc-ps.de Web: www.rrc-ps.de	Tel.: +1 714 777 3604 Fax: +1 714 777 3658 Email: usa@rrc-ps.com Web: www.rrc-ps.com	Tel.: +852 2376 0106 Fax: +852 2375 0107 Email: hkrrc@rrc-ps.cn Web: www.rrc-ps.com	Tel.: +86 755 8374 1908 Fax: +86 755 8374 1861 Email: hkrrc@rrc-ps.cn Web: www.rrc-ps.com



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.