19-2403; Rev 0; 8/95

MAXIM

±15kV ESD-Protected, Quad, Low-Power RS-232 Line Driver

General Description

The MAX1488E quad, low-power line driver is designed for EIA/TIA-232, EIA/TIA-562, and CCITT V.28 communications in harsh environments. Each transmitter output is protected against ±15kV electrostatic discharge (ESD) shocks. The inputs are TTL and CMOS compatible with minimal loading. The outputs feature internally controlled slew-rate limiting and current limiting. This device has a guaranteed 120kbps data rate. Power-supply current is less than 180µA over a ±4.5V to ±13.2V supply voltage range.

The MAX1488E is pin compatible with the MC1488, MC14C88, SN75188, SN75C188, DS1488, and DS14C88. It is available in 14-pin plastic DIP and SO packages.

Features

- **ESD Protection:**
  ±15kV—Human Body Model
  ±6kV—IEC801-2, Contact Discharge
  ±15kV—IEC801-2, Air-Gap Discharge
- **Latchup Free, Even During an ESD Event**
- **Low 85µA Supply Current from I_{EE} or I_{CC}**
- **Guaranteed 120kbps Data Rate**
- **No External Capacitors Required for Slew-Rate Limiting**
- **Pin Compatible with MC1488, MC14C88, SN75188, SN75C188, DS1488, and DS14C88**

Applications

PC Motherboards

Modems

Interface Data Terminal Equipment (DTE) with Data Circuit-Terminating Equipment (DCE)

Equipment Meeting IEC1000-4-2 (formerly IEC801-2) or ±15kV ESD Protection

Ordering Information

PART	TEMP. RANGE	PIN-PACKAGE
MAX1488ECPD	0°C to +70°C	14 Plastic DIP
MAX1488ECSD	0°C to +70°C	14 SO
MAX1488EC/D	0°C to +70°C	Dice*
MAX1488EEPD	-40°C to +85°C	14 Plastic DIP
MAX1488EESD	-40°C to +85°C	14 SO

** Dice are specified at T_A = +25°C.*

Typical Operating Circuit



Pin Configuration



DIP/SO

Call toll free 1-800-998-8800 for free samples or literature.

±15kV ESD-Protected, Quad, Low-Power RS-232 Line Driver

ABSOLUTE MAXIMUM RATINGS

Positive Supply Voltage (V_{CC}) .....+14V
Negative Supply Voltage (V_{EE}) .....-14V
Input Voltage (V_{IN}) .....-0.3V to +15V
Driver Output Voltage .....±15V
Continuous Power Dissipation (T_A = +70°C)
Plastic DIP (derate 10.00mW/°C above +70°C) 800mW
SO (derate 8.7mW/°C above +70°C) 695mW

Operating Temperature Ranges
MAX1488EC_D .....0°C to +70°C
MAX1488EE_D .....-40°C to +85°C
Storage Temperature Range .....-65°C to +160°C
Lead Temperature (soldering, 10sec) .....+300°C

Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

ELECTRICAL CHARACTERISTICS

(V_{CC} = 4.5V to 13.2V, V_{EE} = -4.5V to -13.2V, T_A = T_{MIN} to T_{MAX}, unless otherwise noted. Typical values are at T_A = +25°C.)

PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNITS
DC CHARACTERISTICS						
Output Voltage High	V_{OH}	V_{CC} = -V_{EE} = 5.0V, R_L = 3kΩ	3.7	4.0		V
		V_{CC} = -V_{EE} = 6.5V, R_L = 3kΩ	5	5.4		
		V_{CC} = -V_{EE} = 12.0V, R_L = 3kΩ	10	10.5		
		V_{CC} = -V_{EE} = 13.2V, R_L = open			13.2	
Output Voltage Low	V_{OL}	V_{CC} = -V_{EE} = 5.0V, R_L = 3kΩ		-4.5	-3.7	V
		V_{CC} = -V_{EE} = 6.5V, R_L = 3kΩ		-5.8	-5	
		V_{CC} = -V_{EE} = 12.0V, R_L = 3kΩ		-10.8	-10	
		V_{CC} = -V_{EE} = 13.2V, R_L = open	-13.2			
Operating Voltage Range	V_{CC}		4.5		13.2	V
	V_{EE}		-13.2		-4.5	
Positive Supply Current	I_{CC}	No load		85	180	µA
Negative Supply Current	I_{EE}	No load	-180	-85		µA
Output Short-Circuit Current	I_{OS}	Output shorted to ground (Note 1)	±4	±20	±45	mA
Input High Voltage	V_{IH}		2.0			V
Input Low Voltage	V_{IL}				0.8	V
Input Current	I_{IN1}			0	±2	µA
Output Resistance	R_O	V_{CC} = V_{EE} = 0V $\lvert V_O \rvert \le$ 2.0V		300		Ω
TIMING CHARACTERISTICS (see Figure 1)						
Output Propagation Delay, Low to High	t_{PLH}	V_{CC} = 4.5V, V_{EE} = -4.5V, C_L = 50pF		2.4	3.5	µs
		V_{CC} = 9.0V, V_{EE} = -9.0V, C_L = 50pF		2.8	3.9	
		V_{CC} = 12.0V, V_{EE} = -12.0V, C_L = 50pF		3.1	4.2	
Output Propagation Delay, High to Low	t_{PHL}	V_{CC} = 4.5V, V_{EE} = -4.5V, C_L = 50pF		2.1	4.5	µs
		V_{CC} = 9.0V, V_{EE} = -9.0V, C_L = 50pF		2.4	5.1	
		V_{CC} = 12.0V, V_{EE} = -12.0V, C_L = 50pF		2.6	5.4	
Propagation Delay Skew, $\lvert t_{PLH} - t_{PHL} \rvert$	t_{SK}	V_{CC} = 4.5V, V_{EE} = -4.5V, C_L = 50pF		0.25		µs
		V_{CC} = 9.0V, V_{EE} = -9.0V, C_L = 50pF		0.42		
		V_{CC} = 12.0V, V_{EE} = -12.0V, C_L = 50pF		0.42		
ESD CHARACTERISTICS						
ESD Protection		Human Body Model		±15		kV
		IEC-1000-4-2 (Contact Discharge)		±6		
		IEC-1000-4-2 (Air-Gap Discharge)		±15		

ELECTRICAL CHARACTERISTICS (continued)

(V_{CC} = 4.5V to 13.2V, V_{EE} = -4.5V to -13.2V, T_A = T_{MIN} to T_{MAX}, unless otherwise noted. Typical values are at T_A = +25°C.)

PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNITS
Output Rise Time	t_{R1}	C_L = 1500pF, R_L = 5kΩ, $V_{OUTPUT_}$ from -3.3V to 3.3V		850		ns
	t_{R2}	C_L = 1500pF, R_L = 5kΩ, $V_{OUTPUT_}$ from -3.0V to 3.0V		740		
Output Fall Time	t_{F1}	C_L = 1500pF, R_L = 5kΩ, $V_{OUTPUT_}$ from -3.3V to 3.3V		860		ns
	t_{F2}	C_L = 1500pF, R_L = 5kΩ, $V_{OUTPUT_}$ from -3.0V to 3.0V		765		
Output Slew Rate	SR	C_L = 15pF to 2500pF, R_L = 3kΩ to 7kΩ, V_{CC} = 12V, V_{EE} = -12V, T_A = +25°C, $V_{OUTPUT_}$ from -3.0V to 3.0V	4		30	V/µs
Guaranteed Data Rate		C_L = 15pF to 2500pF, R_L = 3kΩ to 7kΩ, V_{CC} = 12V, V_{EE} = -12V, T_A = +25°C	120			kbps

Note 1: The I_{OS} value is for one output at a time. If more than one output is shorted simultaneously, damage may occur.

Typical Operating Characteristics

(V_{CC} = 12V, V_{EE} = -12V, T_A = +25°C, unless otherwise noted.)

OUTPUT VOLTAGE vs. SUPPLY VOLTAGE



SLEW RATE vs. LOAD CAPACITANCE



OUTPUT VOLTAGE vs. TEMPERATURE



±15kV ESD-Protected, Quad, Low-Power RS-232 Line Driver

Pin Description

PIN	NAME	FUNCTION
1	V_{EE}	-4.5V to -13.2V Supply Voltage Input
2, 4, 5, 9, 10, 12, 13	INPUT_	Driver Inputs
3, 6, 8, 11	OUTPUT_	Driver Outputs
7	GND	Ground
14	V_{CC}	+4.5V to +13.2V Supply Voltage Input

Detailed Description

The MAX1488E provides ±15kV of ESD protection when operating or when powered down. After an ESD event, the MAX1488E will not latch up. Internal slew-rate-limiting circuitry eliminates the need for external capacitors. The MAX1488E has a guaranteed 120kbps data rate.

Outputs

Tables 1 and 2 describe the output states. The output voltage level is affected by both the load current and supply voltage, and is stable over temperature. Refer to the *Typical Operating Characteristics* to see how the output voltage varies with supply voltage, load capacitance, and temperature.

Table 1. Driver A Functions

INPUT A	OUTPUTA
H	L
L	H

Table 2. Driver B–D Functions

INPUT_1	INPUT_2	OUTPUT_
H	H	L
L	X	H
X	L	H

Inputs

The driver inputs determine the driver output states (Tables 1 and 2). Driver inputs B, C, and D have two inputs. **Connect unused inputs to ground or V_{CC}.**

±15kV ESD Protection

As with all Maxim devices, ESD-protection structures are incorporated on all pins to protect against electrostatic discharges encountered during handling and assembly. The MAX1488E driver outputs have extra protection against static electricity found in normal operation. Maxim's engineers developed state-of-the-art structures to protect these pins against ESD of ±15kV, without damage. After an ESD event, the MAX1488E keeps working without latchup.



Figure 1. Slew-Rate Test Circuit and Timing Diagram

ESD protection can be tested in various ways; the transmitter outputs are characterized for protection to the following:

1) ±15kV using the Human Body Model
2) ±6kV using the Contact-Discharge Method specified in IEC1000-4-2 (formerly IEC801-2)
3) ±15kV using the Air-Gap Method specified in IEC1000-4-2 (formerly IEC801-2).

ESD Test Conditions

ESD performance depends on a number of conditions. Contact Maxim for a reliability report that documents test setup, methodology, and results.

Human Body Model

Figure 2a shows the Human Body Model, and Figure 2b shows the current waveform it generates when discharged into a low impedance. This model consists of a 100pF capacitor charged to the ESD voltage of interest, which is then discharged into the test device through a 1.5kΩ resistor.



Figure 2a. Human Body ESD Test Model



Figure 3a. IEC1000-4-2 ESD Test Model



Figure 2b. Human Body Model Current Waveform



Figure 3b. IEC1000-4-2 ESD Generator Current Waveform

IEC1000-4-2

The IEC1000-4-2 standard covers ESD testing and performance of finished equipment; it does not specifically refer to integrated circuits. The MAX1488E helps you design equipment that meets Level 4 (the highest level) of IEC1000-4-2, without additional ESD-protection components.

The major difference between tests done using the Human Body Model and IEC1000-4-2 is higher peak current in IEC1000-4-2. Because series resistance is lower in the IEC1000-4-2 ESD test model (Figure 3a), the ESD withstand voltage measured to this standard is generally lower than that measured using the Human Body Model. Figure 3b shows the current waveform for the ±6kV IEC1000-4-2 Level 4 ESD Contact-Discharge test.

The Air-Gap test involves approaching the device with a charged probe. The Contact-Discharge method connects the probe to the device before the probe is energized.

Machine Model

The Machine Model for ESD testing uses a 200pF storage capacitor and zero-discharge resistance. Its objective is to mimic the stress caused by contact that occurs with handling and assembly during manufacturing. Of course, all pins (not just RS-232 inputs and outputs) require this protection during manufacturing. Therefore, the Machine Model is less relevant to the I/O ports than the Human Body Model and IEC1000-4-2.

Applications Information

Use proper layout to ensure other devices on your board are not damaged in an ESD strike. Currents as high as 60A can instantaneously pass into the ground, so it is important to minimize the ground-lead return path to the power supply. A separate return path to the power supply is recommended. Trace widths should be greater than 40 mils. V_{CC} and V_{EE} must be bypassed with 0.1µF capacitors as close to the part as possible to ensure maximum ESD protection.

±15kV ESD-Protected, Quad, Low-Power RS-232 Line Driver

Chip Topography



TRANSISTOR COUNT: 95

SUBSTRATE CONNECTED TO GND

Package Information





DIM	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	0.053	0.069	1.35	1.75
A1	0.004	0.010	0.10	0.25
B	0.014	0.019	0.35	0.49
C	0.007	0.010	0.19	0.25
E	0.150	0.157	3.80	4.00
e	0.050		1.27	
H	0.228	0.244	5.80	6.20
L	0.016	0.050	0.40	1.27



Narrow SO SMALL-OUTLINE PACKAGE (0.150 in.)

DIM	PINS	INCHES		MILLIMETERS	
		MIN	MAX	MIN	MAX
D	8	0.189	0.197	4.80	5.00
D	14	0.337	0.344	8.55	8.75
D	16	0.386	0.394	9.80	10.00

21-0041A

±15kV ESD-Protected, Quad, Low-Power RS-232 Line Driver

Package Information (continued)



Plastic DIP PLASTIC DUAL-IN-LINE PACKAGE (0.300 in.)

DIM	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	–	0.200	–	5.08
A1	0.015	–	0.38	–
A2	0.125	0.175	3.18	4.45
A3	0.055	0.080	1.40	2.03
B	0.016	0.022	0.41	0.56
B1	0.045	0.065	1.14	1.65
C	0.008	0.012	0.20	0.30
D1	0.005	0.080	0.13	2.03
E	0.300	0.325	7.62	8.26
E1	0.240	0.310	6.10	7.87
e	0.100	–	2.54	–
eA	0.300	–	7.62	–
eB	–	0.400	–	10.16
L	0.115	0.150	2.92	3.81

PKG.	DIM	PINS	INCHES		MILLIMETERS	
			MIN	MAX	MIN	MAX
P	D	8	0.348	0.390	8.84	9.91
P	D	14	0.735	0.765	18.67	19.43
P	D	16	0.745	0.765	18.92	19.43
P	D	18	0.885	0.915	22.48	23.24
P	D	20	1.015	1.045	25.78	26.54
N	D	24	1.14	1.265	28.96	32.13

21-0043A

Maxim cannot assume responsibility for use of any circuitry other than circuitry entirely embodied in a Maxim product. No circuit patent licenses are implied. Maxim reserves the right to change the circuitry and specifications without notice at any time.

© 1995 Maxim Integrated Products Printed USA MAXIM is a registered trademark of Maxim Integrated Products.

Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits,General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)
Факс: 8 (812) 320-02-42
Электронная почта: org@eplast1.ru
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.