

# DIN Style Type D and Neozed

## Low Voltage Industrial Fuses

D, NZ

### TYPE 'D' Fuse




Figure 1

Figure 2

Figure 3

Figure 4

500Vac 2 to 100A, 100k AIR

'D' type fuses complying with DIN 49360 Part 2 and DIN 49515, operating class gL.

| Figure Number | Catalog Number | Dimensional Data (mm) |   |    | Ampere Rating | Color Code | Carton Quantity |
|---------------|----------------|-----------------------|---|----|---------------|------------|-----------------|
|               |                | A                     | B | D  |               |            |                 |
| 1             | 2D16           | —                     | — | 6  | 2             | Pink       | 5               |
|               | 4D16           | —                     | — | 6  | 4             | Brown      |                 |
|               | 6D16           | —                     | — | 6  | 6             | Green      |                 |
|               | 10D16          | —                     | — | 8  | 10            | Red        |                 |
|               | 16D16          | —                     | — | 10 | 16            | Grey       |                 |
|               | 20D16          | —                     | — | 12 | 20            | Blue       |                 |
|               | 25D16          | —                     | — | 14 | 25            | Yellow     |                 |
| 2             | 2D27           | —                     | — | 6  | 2             | Pink       | 5               |
|               | 4D27           | —                     | — | 6  | 4             | Brown      |                 |
|               | 6D27           | —                     | — | 6  | 6             | Green      |                 |
|               | 10D27          | —                     | — | 8  | 10            | Red        |                 |
|               | 16D27          | —                     | — | 10 | 16            | Grey       |                 |
|               | 20D27          | —                     | — | 12 | 20            | Blue       |                 |
|               | 25D27          | —                     | — | 14 | 25            | Yellow     |                 |
| 3             | 35D33          | —                     | — | 16 | 35            | Black      | 5               |
|               | 50D33          | —                     | — | 18 | 50            | White      |                 |
|               | 63D33          | —                     | — | 20 | 63            | Copper     |                 |
| 4             | 80D125         | —                     | — | 5  | 80            | Silver     | 10              |
|               | 100D125        | —                     | — | 7  | 100           | Red        |                 |

**Additional Fuselinks:** Quick acting fuselinks in body sizes D16, D27, D33 and D125 rated 2-100A.

Reference number suffixed Q, i.e. 10D27Q. Voltage rating 500Vac. Notes: (a) Gauge rings and keys can also be supplied.

### NEOZED FUSE




Figure 5

400Vac 2 to 63A, 100k AIR

(Also suitable for use on 250Vdc systems.)

| Figure Number | Catalog Number | Dimensional Data (mm) |    |   | Ampere Rating | Color Code | Carton Quantity |
|---------------|----------------|-----------------------|----|---|---------------|------------|-----------------|
|               |                | A                     | B  | D |               |            |                 |
| 5             | 2NZ01          | —                     | 11 | — | 2             | Pink       | 10              |
|               | 4NZ01          | —                     | 11 | — | 4             | Brown      |                 |
|               | 6NZ01          | —                     | 11 | — | 6             | Green      |                 |
|               | 10NZ01         | —                     | 11 | — | 10            | Red        |                 |
|               | 16NZ01         | —                     | 11 | — | 16            | Grey       |                 |
|               | 20NZ02         | —                     | 15 | — | 20            | Blue       |                 |
|               | 25NZ02         | —                     | 15 | — | 25            | Yellow     |                 |
|               | 35NZ02         | —                     | 15 | — | 35            | Black      |                 |
|               | 50NZ02         | —                     | 15 | — | 50            | White      |                 |
|               | 63NZ02         | —                     | 15 | — | 63            | Copper     |                 |

The only controlled copy of this Data Sheet is the electronic read-only version located on the Bussmann Network Drive. All other copies of this Data Sheet are by definition uncontrolled. This bulletin is intended to clearly present comprehensive product data and provide technical information that will help the end user with design applications. Bussmann reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Bussmann also reserves the right to change or update, without notice, any technical information contained in this bulletin. Once a product has been selected, it should be tested by the user in all possible applications.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.