National Semiconductor

July 2004

FPD87208AXA
+2.5V Low EMI, Low Dynamic Power XGA/WXGA TFT-LCD Timing Controller with Reduced Swing Differential Signaling RSDS™ Outputs

General Description

The FPD87208AXA is a timing controller that combines an LVDS single pixel input interface with National Reduced Swing Differential Signaling (RSDS™) output driver interface for XGA and Wide XGA resolutions. It resides on the TFT-LCD panel and provides the data buffering and control signal generation for XGA, and Wide XGA graphic modes. The RSDS path to the column driver contributes toward lowering radiated EMI and reducing system dynamic power consumption.

This single RSDS bus conveys the 6-bit color data for XGA, and three different WXGA resolutions.

Features

- Reduced Swing Differential Signaling (RSDS) digital bus reduces dynamic power, EMI and bus-width from the timing controller
- LVDS single pixel input interface system
- Input clock range from 25 MHz to 85 MHz
- Drives RSDS column drivers at 170 Mb/s with an 85 MHz clock (Max)
- BIST Function
- CMOS circuitry operates from a 2.25V–2.75V; 0˚C–70˚C
- 64 TQFP package with body size 10 mm x 10 mm x 1.0 mm

System Diagram




FIGURE 1. Block Diagram of the LCD Module

RSDS™ is a trademark of National Semiconductor Corporation.

© 2004 National Semiconductor Corporation

Absolute Maximum Ratings (Note 1)

If Military/Aerospace specified devices are required, please contact the National Semiconductor Sales Office/ Distributors for availability and specifications.

Supply Voltage (V_{DD})	−0.3V to +3.0V
DC TTL Input Voltage (V_{IN})	−0.3V to (V_{DD} + 0.3V)
DC LVDS Input Voltage (V_{IN})	−0.3V to (V_{DD} + 0.3V)
DC Output Voltage (V_{OUT})	−0.3V to (V_{DD} + 0.3V)
Junction Temperature	+150˚C
Storage Temperature Range (T_{STG})	−65˚C to +150˚C
Lead Temperature (T_L) (Soldering 10 sec.)	260˚C

ESD Rating:

HBM:	2 kV
MM:	200V

(R_{ZAP} = 1.5 kΩ, C_{ZAP} = 100 pF, MM: R_{ZAP} = 0Ω, C_{ZAP} = 200 pF)

Operating Conditions

	Min	Max	Units
Supply Voltage (V_{DD})	2.25	2.75	V
Operating Temp. Range (T_A)	0	70	˚C
Supply Noise Voltage		200	mV_{PP}

Note 1: "Absolute Maximum Ratings" are those values beyond which the safety of the device cannot be guaranteed. They are not meant to imply that the devices should be operated at these limits. The table of "Electrical Characteristics" specifies conditions of device operation.

DC Electrical Characteristics

V_{DD} = 2.5V ±0.25V, T_A = 0˚C to 70˚C, I_{PI} = 100 µA (Unless otherwise specified)

TTL DC Electrical Characteristics

Symbol	Parameter	Conditions	Min	Typ	Max	Units
V_{DD}	Supply Voltage		2.25	2.5	2.75	
V_{IH}	Minimum Input High Voltage		1.8			V
V_{IL}	Maximum Input Low Voltage				0.7	V
V_{OH}	Output High Voltage	I_{OH} = −8 mA	0.8 x V_{DD}			
V_{OL}	Output Low Voltage	I_{OL} = 8 mA			0.4	
I_{IN}	Input Current	V_{IN} = V_{DD}			10	µA
		V_{IN} = GND			10	µA
I_{DD}	Average Supply Current	CLK = 85 MHz, RPI = 12.3k $C_{L(TTL)}$ = 50 pF, $R_{L(RSDS)}$ = 100Ω and $C_{L(RSDS)}$ = 5 pF (jig & test fixture capacitance), See *Figure 3* for input conditions		80 I_P = 100 µA V_{DD} = 2.5V	120 I_P = 100 µA V_{DD} = 2.75V	mA

FPD-Link (LVDS) Receiver Input (RxCLKP/N; RxIN[y]P/N, y = 0,1,2)

Symbol	Parameter	Conditions	Min	Typ	Max	Units
LVDS RECEIVER DC SPECIFICATIONS **Note: LVDS Receiver DC parameters are measured under Static and Steady state conditions which may not be reflective of its performance in the end application.** **This device is compatible with TIA644 SPEC. V0 and V2.4.**						
$V_{TH_{LVDS}}$	Differential Input **H**igh **T**hreshold **V**oltage	V_{CM} = 1.2V			+100	mV
$V_{TL_{LVDS}}$	Differential Input **L**ow **T**hreshold **V**oltage		−100			mV
I_{IN}	**IN**put Current	V_{IN} = V_{DD} −0.4V, V_{DD} = 2.75V			±10	µA
		V_{IN} = 0V, V_{DD} = 2.75V			±10	µA
V_{IN}	**IN**put **V**oltage Range		0		V_{DD} −0.4	V
$\|V_{ID}\|$	**D**ifferential **I**nput **V**oltage		0.100		0.600	V
V_{CM}	**C**ommon **M**ode **V**oltage Offset		0 + $\|V_{ID}\|/2$		(V_{DD} −0.4) − $\|V_{ID}\|/2$	V

DC Electrical Characteristics V_{DD} = 2.5V ±0.25V, T_A = 0˚C to 70˚C, I_{PI} = 100 µA (Unless otherwise specified) (Continued)




FIGURE 2. LVDS V_{ID} and V_{CM} Allowable Operating Range

FPD-Link Receiver Input Pattern Used to Measure I_{DD}




FIGURE 3. FPD-Link Receiver I_{DD} Pattern

DC Electrical Characteristics V_{DD} = 2.5V ±0.25V, T_A = 0˚C to 70˚C, I_{PI} = 100 µA (Unless otherwise specified) (Continued)

RSDS Output

(CLKP/N, xyP/N; x = R, G, B; y = 0, 1, 2), V_{DD} = 2.25V to 2.75V (Unless otherwise specified)

Symbol	Parameter	Conditions	Min	Typ	Max	Units
$\lvert V_{OD_{RSDS}} \rvert$	Differential Output Voltage Typ.	R_L = 100Ω		200 (*Figure 4*)		mV
$V_{OS_{RSDS}}$	Offset Voltage	I_{PI} = 100 µA		1.2		V




FIGURE 4. RSDS Output Waveforms: Single Ended vs Differential




FIGURE 5. Typical RSDS V_{OD} vs R_{PI} Response Curve

DC Electrical Characteristics V_{DD} = 2.5V ±0.25V, T_A = 0˚C to 70˚C, I_{PI} = 100 µA (Unless otherwise specified) (Continued)

Schmitt Trigger

Symbol	Parameter	Conditions	Min	Typ	Max	Units
V_H	Hysteresis Voltage	$V_{T+} - V_{T-}$		0.4		V
V_{T-}	Hysteresis Low Threshold Voltage			1.2		V
V_{T+}	Hysteresis High Threshold Voltage			1.6		V
I_{INHYS}	Input Current	$V_{IN} = V_{DD}$			20	µA
		$V_{IN} = V_{SS}$	–20	0		µA




FIGURE 6. Hysteresis Definition


AC Electrical Characteristics

T_A = 0˚C to 70˚C, V_{DD} = 2.5V ±0.25V, I_{PI} = 100 µA (Unless otherwise specified)

LVDS Data Input

Symbol	Parameter	Conditions	Min	Max	Units
F_{RXCLK}	RxCLK Frequency (LVDS)		25	85	MHz
RPLLS	FPD-Link Receiver Phase Lock Loop Wake-Up Time			10	ms
RMS	RxIN Strobe Margin (Note 2) and (*Figure 7*)	F = 85 MHz	400		ps

Note 2: Receiver Strobe Margin is defined as the valid data sampling region at the receiver inputs.



Acronyms:
RSM **R**eceiver **S**trobe **M**argin
RSPOS **R**eceiver **S**trobe **Pos**ition
SW **S**trobe **W**idth

Definitions:
SW Setup and Hold Time (Internal data sampling window)

20101407


FIGURE 7. FPD-Link Receiver Input Skew Margin

AC Electrical Characteristics

T_A = 0˚C to 70˚C, V_{DD} = 2.5V ±0.25V, I_{PI} = 100 µA (Unless otherwise specified) (Continued)

Ring Oscillator Characteristics

Symbol	Parameter	Conditions	Min	Typ	Max	Units
RESOSC	Ring Oscillator Clock Frequency	R = 14.5KΩ; V_{DD}= 2.5V		40		MHz



20101416

FIGURE 8. Application diagram of Ring Oscillator

AC Electrical Characteristics

T_A = 0˚C to 70˚C, V_{DD} = 2.5V ±0.25V, I_{PI} = 100 µA (Unless otherwise specified) (Continued)





FIGURE 9. FPD-Link Receiver Phase Lock Loop Wake-Up Time



Note: R/G/B[7]s are MSBs and R/G/B[0]s are LSBs

FIGURE 10. FPD-Link Receiver Input Data Mapping

AC Electrical Characteristics

T_A = 0˚C to 70˚C, V_{DD} = 2.5V ±0.25V, I_{PI} = 100 µA (Unless otherwise specified) (Continued)

Output Timing

R_T = 100Ω, I_{PI} = 100 µA, f = 85 MHz (Unless otherwise specified)

Symbol	Parameter	Conditions	Min	Typ	Max	Units
RCHP	RSDS Clock (RSCK) High Period	$C_{L(RSDS)}$ = 5 pF		5.8		ns
RCLP	RSDS Clock (RSCK) Low Period	$C_{L(RSDS)}$ = 5 pF		5.8		ns
SPSTU	STH Rising to RSCK Falling	$C_{L(TTL)}$ = 15 pF	4.0			ns
SPHLD	STH Falling to RSCK Falling		4.0			ns
RSTU (Note 3)	RSDS Setup to Falling or Rising Edge of RSCK	$C_{L(RSDS)}$ = 5 pF RSDS[2:0]=[011]		3.3		ns
RHLD (Note 3)	RSDS Hold from Falling or Rising Edge of RSCK			2.1		ns

Note 3: Refer to the table "RSDS Setup and Hold Time with Data Skew Control Values" for each skew control.

RSDS Setup and Hold Time with Data Skew Control Values—Reference Only

(RxCLKP/N = 85 MHz, R_T = 100Ω, I_{PI} = 100 µA, V_{DD} = 2.5V; Duty Clock = 50%/50%, ±2%; 25˚C)
Note: Typical values on this table are measured under Static and Steady state conditions which may not be reflective of its performance in the end application.

RSDS[2:0]	Setup Time (RSTU, nS)			Hold Time (RHLD, nS)			Units
	Min	Typ	Max	Min	Typ	Max	
000		1.83			3.61		ns
001		2.33			3.09		
010		2.83			2.61		
011		3.31			2.10		
100		3.85			1.55		
101		4.34			1.03		
110		4.81			0.53		
111		5.33			0.01		

RSDS and TTL Output Tr/Tf

Symbol	Parameter	Conditions	Min	Typ	Max	Units
RSTr/RSTf	RSDS Output Rising/Falling Time (All RSDS Outputs)	$C_{L(RSDS)}$ = 5 pF		1.5		ns
TTL Tr/Tf	TTL Output Rising and Falling Time	C_L = 15 pF (20%–80%)		2.0		ns

AC Electrical Characteristics

T_A = 0˚C to 70˚C, V_{DD} = 2.5V ±0.25V, I_{PI} = 100 µA (Unless otherwise specified) (Continued)





FIGURE 11. RSDS and TTL Output Timing Diagram

AC Electrical Characteristics

T_A = 0˚C to 70˚C, V_{DD} = 2.5V ±0.25V, I_{PI} = 100 µA (Unless otherwise specified) (Continued)



Note: RSCKP/N, RSR[2:0]P/N, RSG[2:0]P/N and RSB[2:0]P/N are differential outputs, STH is a single ended TTL output.

20101411

FIGURE 12. RSDS Output Data Mapping

AC Electrical Characteristics

T_A = 0˚C to 70˚C, V_{DD} = 2.5V ±0.25V, I_{PI} = 100 µA (Unless otherwise specified) (Continued)

Input Signal Timing—Reference Only

Signal	Item	Symbol		XGA (1024 x 768)	WXGA1 (1280 x 768)	WXGA2 (1280 x 800)	WXGA3 (1280 x 854)	Unit
Clock Frequency	1/Tclk	F	Typ	65	82	68	69	MHz
Vertical Timing	Total	Tv	Min	774	774	806	860	Th
			Typ	806	806	816	880	
			Max	1024	1024	1024	1024	
	Active	Tvact	Min	-	-	-	-	
			Typ	768	768	800	854	
			Max	-	-	-	-	
Horizontal Timing	Total	Th	Min	1078	1334	1334	1334	Tclk
			Typ	1344	1688	1408	1408	
			Max	2047	2047	2047	2047	
	Active	Thact	Min	100	100	100	100	
			Typ	1024	1280	1280	1280	
			Max	-	-	-	-	

Output Timing—TTL

Display Resolution Selection Control

DTM1	DTM0	Display Mode	Resolution
0	0	WXGA1	1280 x 768
0	1	WXGA2	1280 x 800
1	0	XGA	1024 x 768
1	1	WXGA3	1280 x 854

TTL Timing Selection Control: RO[2:0]

	XGA								
RO[2:0]	**000**	**001**	**010**	**011**	**100**	**101**	**110**	**111**	**Unit**
T1	2	2	2	2	2	2	2	TEST MODE	T_{CLK}
T2	1	1	1	1	1	1	1		T_{CLK}
T3	1030	1030	1030	1030	1030	1030	1030		T_{CLK}
T4	16	24	16	24	32	48	42		T_{CLK}
T5	912	960	960	912	842	912	802		T_{CLK}
T5'	782	830	830	782	712	782	672		T_{CLK}
T6	200	160	160	130	220	220	260		T_{CLK}
T6'	130	130	130	130	130	130	130		T_{CLK}
T7	1038	1056	1056	976	874	976	834		T_{CLK}
T8	650	650	650	650	680	680	725		T_{CLK}
T9	348	348	348	348	348	348	348		T_{CLK}
T10	1	1	1	1	1	1	1		HLINE
T11	348	348	348	348	348	348	348		T_{CLK}
T12	1	1	1	1	1	1	1		HLINE
T13*	567	567	567	567	567	567	567		T_{CLK}
T14*	2	2	2	2	2	2	2		HLINE

*Timing based on first occurrence of STH.

Output Timing—TTL (Continued)

WXGA									
RO[2:0]	**000**	**001**	**010**	**011**	**100**	**101**	**110**	**111**	**Unit**
T1	2	2	2	2	2	2	2	TEST MODE	T_{CLK}
T2	1	1	1	1	1	1	1		T_{CLK}
T3	1286	1286	1286	1286	1286	1286	1286		T_{CLK}
T4	16	24	16	24	32	48	42		T_{CLK}
T5	1168	1216	1216	1168	1098	1168	1058		T_{CLK}
T5'	1038	1086	1086	1038	968	1038	928		T_{CLK}
T6	200	160	160	130	220	220	260		T_{CLK}
T6'	130	130	130	130	130	130	130		T_{CLK}
T7	1294	1312	1312	1232	1130	1232	1090		T_{CLK}
T8	650	650	650	650	680	680	725		T_{CLK}
T9	348	348	348	348	348	348	348		T_{CLK}
T10	1	1	1	1	1	1	1		HLINE
T11	348	348	348	348	348	348	348		T_{CLK}
T12	1	1	1	1	1	1	1		HLINE
T13*	567	567	567	567	567	567	567		T_{CLK}
T14*	2	2	2	2	2	2	2		HLINE

*Timing based on first occurrence of STH.

Output Timing—TTL (Continued)





FIGURE 13. TTL Output Timing Diagram

Output Timing—TTL (Continued)



* Timing based on first occurrence of STH signal to the left of the measured output.

20101413

FIGURE 14. TTL Output Timing Diagram (Continued)

Output Timing—Power-Up Sequence (reference only)




FIGURE 15. Power-Up Sequence

Connection Diagram




FIGURE 16. Pinout Assignment

Pin Descriptions

LVDS Rx Inputs

Symbol	Pin Count	Type	Function
RxIN[0]N/P	2	LVDSI	LVDS Rx Data Differential Input Pairs
RxIN[1]N/P	2	LVDSI	LVDS Rx Data Differential Input Pairs
RxIN[2]N/P	2	LVDSI	LVDS Rx Data Differential Input Pairs
RxCLKN/P	2	LVDSI	LVDS Rx Clock Differential Input Pairs
Sub-Total Pin Count	8		

Pin Descriptions (Continued)

RSDS Tx Outputs

Symbol	Pin Count	Type	Function
R [2:0]P/N	6	RSO	Red Reduced Swing Differential Outputs to Column Drivers
G [2:0]P/N	6	RSO	Green Reduced Swing Differential Outputs to Column Drivers
B [2:0]P/N	6	RSO	Blue Reduced Swing Differential Outputs to Column Drivers
CLKP/N	2	RSO	Clock Reduced Swing Differential Outputs to Column Drivers
Sub-Total Pin Count	20		

RSDS Tx Bias Reference Input

Symbol	Pin Count	Type	Function
PI	1		Current Reference for RSDS Tx Output (1.23V)
Sub-Total Pin Count	1		

CMOS Input (2.75V Maximum)

Symbol	Pin Count	Type	Function
RSDS[2:0]	3	I	RSDS Skew/Timing Control
RO[2:0]	3	I	Display Timing Selection
POLSET	1	I	0: Two Line Inversion; 1: One Line Inversion
DTM[1:0]	2	I	Display Mode Selection (XGA, WXGA1, WXGA2, WXGA3)
RESOSC	1	AI	RC oscillator reference for BIST function. 14.5 kΩ = ~40 MHz
IDREV	1	PU	IDREV = HIGH (default, pull high): Output data is 3F during vertical blanking. IDREV = LOW: Output data is 00 during vertical blanking.
BIST	1	I	BIST Control Function (Active High), tied to ground for norm mode
RESETZ	1	Schmitt I	TCON Reset (Active Low)
Sub-Total Pin Count	13		

CMOS Outputs (2.75V Maximum)

Symbol	Pin Count	Type	Function
STV	1	TO	Row Driver Start Pulse
CPV	1	TO	Row Driver Shift Clock
TP	1	TO	Line Latch Signal Output to Column Drivers
STH	1	TO	Horizontal Start Signal Output to Column Drivers
REV	1	TO	Alternative Signal Output for each 1 or 2 Horizontal Line to Column Drivers
OE1	1	TO	Control TFT Gate Pulse Width to Row Drivers
OE2	1	TO	Control TFT Gate Pulse Width to Row Drivers
Sub-Total Pin Count	7		

Pin Descriptions (Continued)


Power Supply

Symbol	Pin Count	Type	Function
V_{DD}	1	P	Digital Power for Logic Core
V_{SS}	1	G	Digital Ground for Logic Core
V_{DDIO}	4	P	Digital I/O and RSDS Power
V_{SSIO}	4	G	Digital I/O and RSDS Ground
V_{DDA}	1	P	FPD Receiver—Power for Analog
V_{DDD}	1	P	FPD Receiver—Power for Digital
V_{SSD}	1	G	FPD Receiver—Ground for Digital
V_{SSP}	1	G	FPD Receiver—Ground for PLL
V_{SSA}	1	G	FPD Receiver—Ground for Analog
Sub-Total Pin Count	15		
Total Pin Count	64		System Interface = 8 RSDS Tx Out = 20 RSDS Tx Bias Reference Input = 1 CMOS Input (control) = 13 CMOS Output = 7 Power Supply = 15

Pin Types

AI	-Analog Input	P	-Power
I	-Input (LVTTL)	G	-Ground
TO	-TTL Output (LVTTL)	PD	-Pull Down
LVDSI	-Low Voltage Differential Signal Input	PU	-Pull Up
RSO	-Reduced Swing Differential Output	Schmitt I	-Schmitt Triggered Input

Physical Dimensions inches (millimeters) unless otherwise noted



64-Lead TQFP Package, JEDEC
Dimension in millimeters only
Order Number FPD87208AXAVS
NS Package Number VEC64A

LIFE SUPPORT POLICY

NATIONAL'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT AND GENERAL COUNSEL OF NATIONAL SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

BANNED SUBSTANCE COMPLIANCE

National Semiconductor certifies that the products and packing materials meet the provisions of the Customer Products Stewardship Specification (CSP-9-111C2) and the Banned Substances and Materials of Interest Specification (CSP-9-111S2) and contain no "Banned Substances" as defined in CSP-9-111S2.

National Semiconductor
Americas Customer
Support Center
Email: new.feedback@nsc.com
Tel: 1-800-272-9959

www.national.com

National Semiconductor
Europe Customer Support Center
Fax: +49 (0) 180-530 85 86
Email: europe.support@nsc.com
Deutsch Tel: +49 (0) 69 9508 6208
English Tel: +44 (0) 870 24 0 2171
Français Tel: +33 (0) 1 41 91 8790

National Semiconductor
Asia Pacific Customer
Support Center
Email: ap.support@nsc.com

National Semiconductor
Japan Customer Support Center
Fax: 81-3-5639-7507
Email: jpn.feedback@nsc.com
Tel: 81-3-5639-7560

National does not assume any responsibility for use of any circuitry described, no circuit patent licenses are implied and National reserves the right at any time without notice to change said circuitry and specifications.


Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits,General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)
Факс: 8 (812) 320-02-42
Электронная почта: org@eplast1.ru
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.