



New Product

SUD50N03-06AP

Vishay Siliconix

N-Channel 30-V (D-S) MOSFET

| PRODUCT SUMMARY | | | |
|-----------------|---------------------------|---------------------------|-------------|
| V_{DS} (V) | $r_{DS(on)}$ (Ω) | I_D (A) ^{a, e} | Q_g (Typ) |
| 30 | 0.0057 @ $V_{GS} = 10$ V | 90 | 30 |
| | 0.0078 @ $V_{GS} = 4.5$ V | 77 | |



FEATURES

- TrenchFET® Power MOSFET
- Optimized for Low-Side Synchronous Rectifier Operation
- 100% R_g Tested



APPLICATIONS

- DC/DC Converters
- Synchronous Rectifiers



Ordering Information: SUD50N03-06AP—E3 (Lead (Pb)-free)

N-Channel MOSFET

| ABSOLUTE MAXIMUM RATINGS ($T_A = 25^\circ\text{C}$ UNLESS OTHERWISE NOTED) | | | | |
|---|--------------------------|----------------|---------------------|------------------|
| Parameter | | Symbol | Limit | Unit |
| Drain-Source Voltage | | V_{DS} | 30 | V |
| Gate-Source Voltage | | V_{GS} | ± 20 | |
| Continuous Drain Current ($T_J = 175^\circ\text{C}$) | $T_C = 25^\circ\text{C}$ | I_D | 90 ^{a, e} | A |
| | $T_C = 70^\circ\text{C}$ | | 75 ^{a, e} | |
| | $T_A = 25^\circ\text{C}$ | | 30 ^{b, c} | |
| | $T_A = 70^\circ\text{C}$ | | 25 ^{b, c} | |
| Pulsed Drain Current | | I_{DM} | 100 | |
| Continuous Source-Drain Diode Current | $T_C = 25^\circ\text{C}$ | I_S | 55 ^{a, e} | |
| | $T_A = 25^\circ\text{C}$ | | 6.7 ^{b, c} | |
| Avalanche Current Pulse | | I_{AS} | 45 | mJ |
| Single Pulse Avalanche Energy | | | E_{AS} | |
| Maximum Power Dissipation | $T_C = 25^\circ\text{C}$ | P_D | 83 | W |
| | $T_C = 70^\circ\text{C}$ | | 58 | |
| | $T_A = 25^\circ\text{C}$ | | 10 ^{b, c} | |
| | $T_A = 70^\circ\text{C}$ | | 7 ^{b, c} | |
| Operating Junction and Storage Temperature Range | | T_J, T_{stg} | -55 to 175 | $^\circ\text{C}$ |

| THERMAL RESISTANCE RATINGS | | | | | |
|---|-----------------|------------|---------|---------|--------------------|
| Parameter | | Symbol | Typical | Maximum | Unit |
| Maximum Junction-to-Ambient ^{b, d} | $t \leq 10$ sec | R_{thJA} | 12 | 15 | $^\circ\text{C/W}$ |
| Maximum Junction-to-Case | Steady State | R_{thJC} | 1.5 | 1.8 | |

Notes:

- Based on $T_C = 25^\circ\text{C}$.
- Surface mounted on 1" x 1" FR4 board.
- $t = 10$ sec
- Maximum under steady state conditions is 50°C/W .
- Calculated based on maximum junction temperature. Package limitation current is 50 A.

| SPECIFICATIONS (T _J = 25 °C UNLESS OTHERWISE NOTED) | | | | | | |
|--|--------------------------------------|---|-----------|--------|--------|-------|
| Parameter | Symbol | Test Condition | Min | Typ | Max | Unit |
| Static | | | | | | |
| Drain-Source Breakdown Voltage | V _{DS} | V _{GS} = 0 V, I _D = 250 μA | 30 | | | V |
| V _{DS} Temperature Coefficient | ΔV _{DS} /T _J | I _D = 250 μA | | 25 | | mV/°C |
| V _{GS(th)} Temperature Coefficient | ΔV _{GS(th)} /T _J | | | -6.3 | | |
| Gate-Source Threshold Voltage | V _{GS(th)} | V _{DS} = V _{GS} , I _D = 250 μA | 1.2 | | 2.4 | V |
| Gate-Source Leakage | I _{GSS} | V _{DS} = 0 V, V _{GS} = ±20 V | | | ±100 | nA |
| Zero Gate Voltage Drain Current | I _{DSS} | V _{DS} = 30 V, V _{GS} = 0 V | | | 1 | μA |
| | | V _{DS} = 30 V, V _{GS} = 0 V, T _J = 55°C | | | 10 | |
| On-State Drain Current ^a | I _{D(on)} | V _{DS} ≥ 5 V, V _{GS} = 10 V | 50 | | | A |
| Drain-Source On-State Resistance ^a | r _{DS(on)} | V _{GS} = 10 V, I _D = 20 A | | 0.0046 | 0.0057 | Ω |
| | | V _{GS} = 4.5 V, I _D = 20 A | | 0.0062 | 0.0078 | |
| Forward Transconductance ^a | g _{fs} | V _{DS} = 15 V, I _D = 30 A | | 70 | | S |
| Dynamic^b | | | | | | |
| Input Capacitance | C _{iss} | V _{DS} = 15 V, V _{GS} = 0 V, f = 1 MHz | | 3800 | | pF |
| Output Capacitance | C _{oss} | | | 615 | | |
| Reverse Transfer Capacitance | C _{rss} | | | 305 | | |
| Total Gate Charge | Q _g | V _{DS} = 15 V, V _{GS} = 10 V, I _D = 30 A | | 62 | 95 | nC |
| | | V _{DS} = 15 V, V _{GS} = 4.5 V, I _D = 25 A | | 30 | 45 | |
| Gate-Source Charge | Q _{gs} | V _{DS} = 15 V, V _{GS} = 4.5 V, I _D = 25 A | | 11 | | nC |
| Gate-Drain Charge | Q _{gd} | | | 9 | | |
| Gate Resistance | R _g | | f = 1 MHz | | 0.9 | |
| Turn-On Delay Time | t _{d(on)} | V _{DD} = 15 V, R _L = 0.5 Ω I _D ≅ 30 A, V _{GEN} = 10 V, R _g = 1 Ω | | 12 | 18 | ns |
| Rise Time | t _r | | | 10 | 15 | |
| Turn-Off Delay Time | t _{d(off)} | | | 30 | 45 | |
| Fall Time | t _f | | | 8 | 12 | |
| Turn-On Delay Time | t _{d(on)} | V _{DD} = 15 V, R _L = 0.6 Ω I _D ≅ 25 A, V _{GEN} = 4.5 V, R _g = 1 Ω | | 26 | 40 | ns |
| Rise Time | t _r | | | 230 | 345 | |
| Turn-Off Delay Time | t _{d(off)} | | | 25 | 40 | |
| Fall Time | t _f | | | 9 | 14 | |
| Drain-Source Body Diode Characteristics | | | | | | |
| Continuous Source-Drain Diode Current | I _S | T _C = 25°C | | | 55° | A |
| Pulse Diode Forward Current ^a | I _{SM} | | | | 100 | |
| Body Diode Voltage | V _{SD} | I _S = 6.7 A | | 0.9 | 1.5 | V |
| Body Diode Reverse Recovery Time | t _{rr} | I _F = 6.7 A, di/dt = 100 A/μs, T _J = 25°C | | 65 | 100 | ns |
| Body Diode Reverse Recovery Charge | Q _{rr} | | | 38 | 60 | nC |
| Reverse Recovery Fall Time | t _a | | | 50 | | ns |
| Reverse Recovery Rise Time | t _b | | | 15 | | |

Notes


- Pulse test; pulse width ≤ 300 μs, duty cycle ≤ 2%.
- Guaranteed by design, not subject to production testing.
- Calculated based on maximum junction temperature. Package limitation current is 50 A.

Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.




TYPICAL CHARACTERISTICS (25°C UNLESS NOTED)


Output Characteristics




Transfer Characteristics




On-Resistance vs. Drain Current




Capacitance



Gate Charge








On-Resistance vs. Junction Temperature






TYPICAL CHARACTERISTICS (25 °C UNLESS NOTED)






TYPICAL CHARACTERISTICS (25°C UNLESS NOTED)

Current De-Rating





Power De-Rating





TYPICAL CHARACTERISTICS (25°C UNLESS NOTED)



Vishay Siliconix maintains worldwide manufacturing capability. Products may be manufactured at one of several qualified locations. Reliability data for Silicon Technology and Package Reliability represent a composite of all qualified locations. For related documents such as package/tape drawings, part marking, and reliability data, see <http://www.vishay.com/ppg?73540>.



Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.