AMPHENOL PCD SHENZHEN

EXCEL | MATE MSD

Manual Service Disconnect

www.amphenolpcd.com.cn

INDUSTRIAL@AMPHENOL TRUSTED GLOBALLY

CONTENTS

EXCEL|MATE MSD 2

EXCEL|MATE MSD - TECHNICAL CHARACTERISTICS 3

PRODUCT DIMENSIONS 4

HOW TO ORDER | EXCEL|MATE MSD 6

EXCEL|MATE MSD V - TECHNICAL CHARACTERISTICS 7

HOW TO ORDER | EXCEL|MATE MSD V 8

EXCEL|MATE MSD XL - TECHNICAL CHARACTERISTICS 9

PRODUCT DIMENSIONS 10

HOW TO ORDER | EXCEL|MATE MSD XL 13

EXCEL|MATE MINI MSD 14

EXCEL|MATE MINI MSD - TECHNICAL CHARACTERISTICS 15

PRODUCT DIMENSIONS 16

HOW TO ORDER | EXCEL|MATE MINI MSD 18

Amphenol PCD Manual Service Disconnect

Excel | Mate MSD is a safe and a reliable solution for HEV servicing.

Equipped with a two-stage lever to open the HVIL circuit prior to the separation of HV contacts, it is a tool-free solution for disconnecting the internal high voltage battery pack and protecting it from short circuit. All HV conductive contact surfaces on the receptacle assembly are finger-touch safe.

Available in a scalable design with a variety of fuse ratings.

KEY FEATURES

A two-stage lever provides an HVIL time delay

2 x integrated internal HVIL

Unique cooling structure

Dual-channel design lowers temperature rise

No tools required to unmate

Various fuse ratings

Receptacle can be front or rear mounted

APPLICATION	
It is a tool-free solution for disconnecting the internal high voltage battery pack and protecting it from short circuit.	
MECHANICAL	
Mating cycles	≥ 50 cycles
ELECTRICAL	
Fuse specification	up to 630A
With fuse:	
Rated current	Current is approximately 1/3 the fuse rating (230A Max)
Rated voltage	600V DC
With shunt:	
Rated current	230A Max
Rated voltage	1000V DC Max
ENVIRONMENTAL	
Protection degree	IP67, IP6K9K (mated)
Ambient temperature	-40°C to 70°C
Storage temperature	-40°C to 85°C
Operating temperature	-40°C to 125°C
STANDARDS	
USCAR-2	
USCAR-37	
LV-215	
RoHS	

PRODUCT DIMENSIONS





FRONT MOUNTED



REAR MOUNTED



DUST CAP AVAILABLE
P/N: C270006810

HOW TO ORDER - EXCEL|MATE MSD

MSD	M	350	2	F
Shell type: **M:** Plug **F:** Receptacle				
Fuse rating current: **XXX:** 200, 250, 315, 350, 400, 450, 500, 550, 630 (Unit: AMP) **000:** No fuse needed, can directly use the terminal				
Fuse brand (this applies to plugs) : **1:** Ferraz **2:** Bussmann				
Flange mounted type (this applies to sockets) : **F:** Front mounted **R:** Rear mounted				

MSD V is an upgraded version of the standard MSD.

It provides a rated voltage of 800V and a plug with integrated fuse.The other parameters remain unchanged.

KEY FEATURES

A two-stage lever provides an HVIL time delay

2 x integrated internal HVIL

Unique cooling structure

Dual-channel design lowers temperature rise

No tools required to unmate

Various fuse ratings

Receptacle can be front or rear mounted

APPLICATION	
It is a tool-free solution for disconnecting the internal high voltage battery pack and protecting it from short circuit.	
MECHANICAL	
Mating cycles	≥ 50 cycles
ELECTRICAL	
Fuse specification	up to 630A
With fuse:	
Rated current	Current is approximately 1/3 the fuse rating (230A Max)
Rated voltage	800V DC
With shunt:	
Rated current	230A Max
Rated voltage	1000V DC Max
ENVIRONMENTAL	
Protection degree	IP67, IP6K9K (mated)
Ambient temperature	-40°C to 70°C
Storage temperature	-40°C to 85°C
Operating temperature	-40°C to 125°C
STANDARDS	
USCAR-2	
USCAR-37	
LV-215	
RoHS	

HOW TO ORDER - EXCEL|MATE MSD V

MSD V	M	350	/
Shell type: **M:** Plug			
Fuse rating current: **XXX:** 200, 250, 315, 350, 400, 450, 500, 550, 630 (Unit: AMP) **000:** No fuse needed, can directly use the terminal			
Fuse brand (this applies to plugs): **/ :** Bussmann (by default) For other brands, please contact us			

KEY FEATURES

1 x integrated internal HVIL

Unique cooling structure

High current contacts with Amphenol Radsok technology

No tools required to unmate

Various fuse ratings

Receptacle can be front or rear mounted

APPLICATION	
It is a tool-free solution for disconnecting the internal high voltage battery pack and protecting it from short circuit.	
MECHANICAL	
Mating cycles	≥ 500 cycles
ELECTRICAL	
Fuse specification	up to 630A
With fuse:	
Rated current	300A Max
Rated voltage	1000V DC
With shunt:	
Rated current	300A
Rated voltage	1500V DC Max
ENVIRONMENTAL	
Protection degree	IP67, IP6K9K (mated)
Ambient temperature	-40°C to 70°C
Storage temperature	-40°C to 85°C
Operating temperature	-40°C to 125°C
STANDARDS	
USCAR-2	
USCAR-37	
LV-215	
RoHS	

PRODUCT DIMENSIONS



FRONT MOUNTED





REAR MOUNTED









REAR MOUNTING OPENING SIZE

HOW TO ORDER - EXCEL|MATE MSD XL

MSD XL	M	350	/	F

Shell type:
M: Plug
F: Receptacle

Fuse rating current:
XXX: 160, 200, 250, 315, 350, 400, 450, 500, 550, 630
(Unit: AMP)
000: No fuse needed, can directly use the terminal

Fuse brand (this applies to plugs):
/ : Bussmann (by default)
For other brands, please contact us

Flange mounted type (this applies to sockets) **:**
F: Front mounted
R: Rear mounted

Amphenol PCD MINI Manual Service Disconnect

Mini MSD has been developped from the standard MSD.Smaller in size and lower in cost, it offers a more compact solution.

Available in a scalable design with a variety of fuse ratings.

KEY FEATURES

A two-stage lever provides an HVIL time delay

1 x integrated internal HVIL

Unique cooling structure

Dual-channel design lowers temperature rise

No tools required to unmate

Various fuse ratings

Receptacle can be front or rear mounted

APPLICATION	
It is a tool-free solution for disconnecting the internal high voltage battery pack and protecting it from short circuit.	
MECHANICAL	
Mating cycles	≥ 50 cycles
ELECTRICAL	
Fuse specification	up to 400A
With fuse:	
Rated current	Current is approximately 1/3 the fuse rating (170A Max)
Rated voltage	600V to 700V DC
With shunt:	
Rated current	170A Max
Rated voltage	1500V DC Max
ENVIRONMENTAL	
Protection degree	IP67, IP6K9K (mated)
Ambient temperature	-40°C to 70°C
Storage temperature	-40°C to 85°C
Operating temperature	-40°C to 125°C
STANDARDS	
USCAR-2	
USCAR-37	
LV-215	
RoHS	

PRODUCT DIMENSIONS









FRONT MOUNTED



REAR MOUNTED



DUST CAP AVAILABLE:
P/N: C270006809

HOW TO ORDER - EXCEL|MATE MINI MSD

MINI MSD	M	350	/	F

Shell type:
M: Plug
F: Receptacle

Fuse rating current:
XXX: 080, 100, 125, 160, 200, 250, 315, 350, 400
(Unit: AMP)
000: No fuse needed, can directly use the terminal

Fuse brand (this applies to plugs) :
/ : Bussmann (by default)
1: Other brands (TBD)

Flange mounted type (this applies to sockets):
F: Front mounted
R: Rear mounted

Amphenol PCD Shenzhen

Building 21
1st Liao Keng Industrial Zone
Shi Yan Street, Bao An District Shenzhen 518108
China

Tel.: +86 755-8173-8000
Fax: +86 755-8173-8180
Email: inquiry@amphenolpcd.com.cn

www.amphenolpcd.com.cn

Notes:

Amphenol PCD Shenzhen has made every effort to ensure that the information contained in this catalog is accurate at the time of publication. Specifications or information stated in this publication are subject to change without notice.

Amphenol PCD Shenzhen reserves the right to clarify this catalog.

Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits,General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)
Факс: 8 (812) 320-02-42
Электронная почта: org@eplast1.ru
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.