

HT23-601C

NEMA 23 Step Motor with 10 Foot Shielded Cable



Product Features

- 2-phase hybrid step motor
- High torque design
- Standard NEMA 23 dimensions
- Optimized for 24 – 48 VDC bus voltage
- Please call for pricing regarding encoder and encoder with cover options



Description

Product Description:

The HT23-601C two-phase stepper motor is designed for use with the ST5 and STR4 stepper drives and is suitable for a wide range of motion control applications. The motor is optimized for use with DC powered drives and comes with an integral 10 ft shielded cable.

Single and double shaft versions are available. The HT23-601DC-ZAC includes an optical encoder with 10 foot cable and rugged metal cover.












The motor is terminated with 8 motor leads plus a ground lead.

Specifications

Part Number:	HT23-601C
Frame Size:	NEMA 23
Motor Type:	High torque
Part Number w/Double Shaft:	HT23-601DC
Part Number w/Encoder:	HT23-601DC-ZAA
Part Number w/Encoder & Cover:	HT23-601DC-ZAC
Motor Length:	3.20 inches
Number of Lead Wires:	8
Lead Wire Configuration:	shielded cable, no connector
Lead Wire/Cable Length:	10 feet inches
Lead Wire Gauge:	22 AWG
Unipolar Holding Torque:	191 oz-in
Bipolar Holding Torque:	269 oz-in
Step Angle:	1.8 deg
Bipolar Series Current:	2.12 A/phase
Bipolar Series Resistance:	2.2 Ohms/phase
Bipolar Series Inductance:	6.8 mH/phase
Bipolar Parallel Current:	4.24 A/phase
Bipolar Parallel Resistance:	0.7 Ohms/phase
Bipolar Parallel Inductance:	1.7 mH/phase
Unipolar Current:	3.00 A/phase
Unipolar Resistance:	1.1 Ohms/phase
Unipolar Inductance:	1.7 mH/phase
Rotor Inertia:	0.0064 oz-in-sec ²
Integral Gearhead:	No
Weight:	2.2 lbs

Weight:	2.2 lbs
Storage Temperature:	-30 +70 °C
Operating Temperature:	-20 +50 °C
Insulation Class:	B
Shaft Run Out:	0.002 inch T.I.R. max
Radial Play:	0.001 inch max w/ 1.1 lb load
End Play:	0.003 inch max w/ 1.1 lb load
Perpendicularity:	0.004 inches
Concentricity:	0.002 inches

Downloads

Datasheet:	http://s3.amazonaws.com/applied-motion-pdf/HT23-601C.pdf
2D Drawing:	 HT23-601C_RevC.pdf  HT23-601DC_RevC.pdf  HT23-601DC-ZAA_RevA.pdf  HT23-601DC-ZAC_RevA.pdf
3D Drawing:	 HT23-601C.igs  HT23-601DC.igs  HT23-601DC-ZAA.igs  HT23-601DC-ZAC.igs
Speed-Torque Curves:	 ST_speed-torque.pdf  STR_speed-torque.pdf  STR2_speed-torque.pdf

Products in the Series *Cabled Step Motors*

Part Number	Frame Size	Length	Holding Torque	Series Current	Parallel Current	Rotor Inertia
HT23-552	NEMA 23	1.71	84.4	0.71	1.41	1.70E-03
HT23-553	NEMA 23	2.17	167	0.71	1.41	4.25E-03
HT23-554	NEMA 23	3.05	255	0.71	1.41	6.80E-03
HT23-598C	NEMA 23	2.35	158	2.12	4.24	0.0036
HT23-601C	NEMA 23	3.20	269	2.12	4.24	0.0064
HT34-495	NEMA 34	3.11	555	2.15	4.30	2.27E-02
HT34-496	NEMA 34	4.63	1110	2.05	4.10	4.53E-02
HT34-497	NEMA 34	6.14	1694	2.55	5.10	6.80E-02
HT34-506C	NEMA 34	4.94	1260	2.8	5.6	0.0387
HT34-696	NEMA 34	4.59	1110	2.05	4.1	3.87E-02
HW23-598	NEMA 23	2.34	158	2.12	4.24	3.68E-03
HW23-601	NEMA 23	3.21	269	2.12	4.24	6.51E-03
HW23-753	NEMA 23	2.19	153	0.71	1.41	3.12E-03
HW23-754	NEMA 23	3.23	227	0.71	1.41	6.51E-03
HW24-108	NEMA 24	3.72	354	NA	4.0	1.27E-02
HW34-506	NEMA 34	5.0	1260	2.8	5.6	3.87E-02
HW34-696	NEMA 34	4.59	1062	2.03	4.06	3.87E-02



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.