

NLP65 Series

Single, dual,
and triple output

Total Power: 65 - 75W
Input Voltage: 85 - 264 Vac
120 - 370 Vdc*
of Outputs: Single, dual,
triple



Special Features

- Universal Input
- 3" x 5" footprint
- Low profile fits 1U applications
- EN61000-3-2 compliance option (HCC)
- Overvoltage and short circuit protection
- 65 W with free air convection cooling
- EN55022, EN55011 conducted emissions level B
- EN61000-4-2, -3, -4, -5, -6 immunity compliant
- RoHS compliant
- LPX80 enclosure kit available
- 2 year warranty

Safety

VDE0805/EN60950/IEC950
File No. 1040100-3336-0096
Licence No. 114404

UL1950 File No. E136005

CSA C22.2 No. 950
File No. LR41062C

China Compulsory
Certification 60950

*NLP65-76xx version only

Electrical Specifications

Input

| | | |
|----------------------------------|----------------------------------|--------------------------------------|
| Input voltage range | Universal input, (See Note 2) | 85-264 Vac |
| | NLP65-76xx version only | 120-370 Vdc |
| Input frequency range | | 47-63 Hz |
| Input current (cold start) | 120 Vac | 17 A max. |
| | 230 Vac | 32 A max. |
| Safety ground leakage current | 120 Vac, 60 Hz | 0.7 mA |
| | 230 Vac, 50 Hz | 1.4 mA |
| Input current | 120 Vac, with PFC | 1.05 A rms |
| | 230 Vac, with PFC | 0.51 A rms |
| | 120 Vac, without PFC | 1.40 A rms |
| | 230 Vac, without PFC | 0.80 A rms |
| Input fuse | UL/IEC127 | S3.15 A, 250 Vac In live and neutral |

Output

| | | |
|-------------------------------------|-------------------------|---------------------------------------|
| Total regulation (line and load) | Main output | ±2.0% |
| | Auxiliary outputs | ±5.0% |
| Rise time | At turn-on | 1.0 s, max |
| Transient response | Main output | 5.0% or 250 mV |
| | 25% step at 0.1 A/μs | max. dev., 1ms max. recovery to 1% |
| Temperature coefficient | | ±0.02%/°C |
| Overvoltage protection | Main outputs | 125%, ±10% |
| Short circuit protection | Cyclic operation | Continuous |
| Minimum output current | Single and multiple | (See Note 6) |

All specifications are typical at nominal input, full load at 25° C unless otherwise stated.

Rev.06.02.08
NLP65 Series
2 of 4

EMC Characteristics ^(11, 12)

| | | |
|---------------------|----------------------|------------------|
| Conducted emissions | EN55022, FCC part 15 | Level B |
| Radiated emissions | EN55022, FCC part 15 | Level A |
| ESD air | EN61000-4-2, level 3 | Perf. criteria 1 |
| ESD contact | EN61000-4-2, level 4 | Perf. criteria 1 |
| Surge | EN61000-4-2, level 3 | Perf. criteria 1 |
| Fast transients | EN61000-4-4, level 3 | Perf. criteria 1 |
| Radiated immunity | EN61000-4-3, level 3 | Perf. criteria 2 |
| Conducted immunity | EN61000-4-6, level 3 | Perf. criteria 2 |

General Specifications

| | | |
|--|--------------------------|-------------------|
| Hold-up time | 120 Vac, 60 Hz | 16 ms @ 65 W |
| | 230 Vac, 50 Hz | 78 ms @ 65 W |
| Efficiency | 120 Vac, 65 W | 72% typical |
| Isolation voltage | Input/output | 3000 Vac |
| | Input/chassis | 1500 Vac |
| Switching frequency | Fixed | 100 kHz, ±5 kHz |
| Approvals and standards (see Notes 9, 13) | EN60950, VDE0805 | |
| | IEC950, UL1950, CCC60950 | |
| | CSA C22.2 No. 950 | |
| Weight | 283 g (10 oz) | |
| MTBF demonstrated | MIL-HDBK-217F | 150,000 hours min |

Environmental Specifications

| | | |
|---|---|-----------------------|
| Thermal performance (see Notes 1, 3, 10) | Operating ambient, | 0 °C to +70 °C |
| | (See derating curve) | |
| | Non-operating | -40 °C to +85 °C |
| | 50 °C to 70 °C ambient, convection cooled | Derate to 50% load |
| | 0 °C to 50 °C, ambient, convection cooled | 65 W |
| | 0 °C to 50 °C ambient, 20 CFM forced air (See Note 10) | 75 W |
| | Peak (0 °C to +50 °C, 60 s) | See table |
| Relative humidity | Non-condensing | 5% to 95% RH |
| Altitude | Operating | 10,000 feet max |
| | Non-operating | 30,000 feet max |
| Vibration (see Note 5) | 5-500 Hz | 2.4 G rms peak |
| Shock | per MIL-STD-810E | 516.4 Part IV |



| Output Voltage | Output Current | | | | Total Regulation (6) | Non-harmonic Corrected | Harmonic Corrected | Ground Pin (12, 14, 17) |
|----------------|----------------|----------|----------|------------|----------------------|------------------------|--------------------|-------------------------|
| | Max (1) | Peak (3) | Fan (10) | Ripple (4) | | | | |
| +5 V (IA) | 7.5 A | 9.1 A | 8 A | 50 mV | ±2.0% | NLP65-7608J | NLP65-9608J | NLP65-X608GJ |
| +12 V (IB) | 2.5 A | 3.3 A | 3 A | 150 mV | ±5.0% | | | |
| -12 V | 0.65 A | 0.81 A | 0.8 A | 120 mV | ±5.0% | | | |
| +5 V (IA) | 7.5 A | 9.1 A | 8 A | 50 mV | ±2.0% | NLP65-7610J | NLP65-9610J | NLP65-X610GJ |
| +15 V (IB) | 2.2 A | 2.9 A | 2.5 A | 150 mV | ±5.0% | | | |
| -15 V | 0.65 A | 0.85 A | 0.8 A | 150 mV | ±5.0% | | | |
| +5 V | 7.0 A | 9.1 A | 8.0 A | 50 mV | ±2.0% | NLP65-3322J | | |
| +24 V | 1.5 A | 2.6 A | 2.0 A | 240 mV | ±5.0% | | | |
| +12 V | 0.7 A | 1.0 A | 1.0 A | 120 mV | ±5.0% | | | |
| +5 V (IA) | 7 A | 9.1 A | 8 A | 50 mV | ±2.0% | NLP65-7620J | NLP65-9620J | NLP65-X620GJ |
| +24 V (IB) | 2 A | 2.6 A | 2 A | 240 mV | ±5.0% | | | |
| +5 V (IA) | 7 A | 9.1 A | 8 A | 50 mV | ±2.0% | NLP65-7629J | NLP65-9629J | NLP65-X629GJ |
| +12 V (IB) | 2.5 A | 3.3 A | 3 A | 150 mV | ±5.0% | | | |
| +5 V | 10 A | 13 A | 12 A | 50 mV | ±2.0% | NLP65-7605J | NLP65-9605J | NLP65-X605GJ |
| +12 V | 5.4 A | 7 A | 6.5 A | 120 mV | ±2.0% | NLP65-7612J | NLP65-9612J | NLP65-X612GJ |
| +15 V | 4.4 A | 5.7 A | 5.3 A | 150 mV | ±2.0% | NLP65-7615J | NLP65-9615J | NLP65-X615GJ |
| +24 V | 2.7 A | 3.5 A | 3.5 A | 240 mV | ±2.0% | NLP65-7624J | NLP65-9624J | NLP65-X624GJ |

Notes

- Natural convection cooling. Models NLP65-X629J, NLP65-X608J, NLP65-X610J must not exceed 62.5 Watts continuous output power with natural convection. Model NLP65-X620J not to exceed 65 Watts continuous output power with natural convection. Model NLP65-3322J must not exceed 60 Watts continuous output power with natural convection.
- When the input voltage is less than 90 Vac the operating temperature range is 0 °C to +40 °C. The ripple and regulation specifications may not be met.
- Peak output current lasting less than 60 seconds with duty cycle less than 5%. During peak loading, output voltage may exceed total regulation limits.
- Figure is peak-to-peak for convection power rating. Output noise measurements are made across a 20 MHz bandwidth using a 6 inch twisted pair, terminated with a 10 µF electrolytic capacitor and a 0.1 µF ceramic capacitor.
- Three orthogonal axes, random vibration 10 minutes for each axes, 2.4 G rms 5 Hz to 500 Hz.
- A minimum load on the main output is required for proper start up. For multiple outputs and single +5V output, the minimum load on the +5 V is 0.2 A. For single outputs greater than +5 V the minimum load is 0.1 A. To maintain stated regulation then:
for single output units
 $I \geq 0.2 \text{ A}$
for multiple output units
 $0.25 \leq I(A)/I(B) \leq 5$, for $I(A) \geq 0.2 \text{ A}$.
- For optimum reliability, no part of the heatsink should exceed 120 °C, and no semiconductor case temperature should exceed 130 °C.
- CAUTION: Allow a minimum of 1 second after disconnecting line power when making thermal measurements.
- This product is only for inclusion by professional installers within other equipment and must not be operated as a stand alone product.
- Maximum continuous output power for all multiple output models must not exceed 75 Watts (70 watts for NLP65-3322J) with 20 CFM forced air cooling.
- Conducted and radiated emissions testing were performed using the standard EN55022 set-up with a stand alone NLP65 unit placed on a grounded metal plate with a line choke on the AC input and ground wires (i.e. the wires are looped through an EMI suppression toroid). For system compliance it is usually necessary to install an 'off-the-shelf' AC inlet with an integral line filter in the system chassis or to install a line choke on the input wires as close as possible to AC entry point of the system chassis. Please contact the applications group at Artesyn for assistance with EMI compliance.
- The NLP65 units with the suffix 'G' is the ground pin and ground choke option. J2, L6 and JP10 are included. J2 is a safety agency approved grounding pin, L6 is a ground choke and JP10 is a jumper. This option is intended for use in non-metallic chassis applications where grounding is not possible via the mounting screws. The ground choke is provided to assist system EMC compliance. When performing conducted emissions testing on stand alone units, the 'G' option is required to meet level B. To order simply add the suffix 'G' to the standard model number, e.g. NLP65-7608GJ, NLP65-9608GJ. This option is available for both the PFC and non-PFC versions.
- All models require a minimum mounting stand-off of 0.25 inches (6.35 mm) in the end use product.
- The NLP65-9608J is available with an enclosure. To order an enclosed version, see model numbering options below.
- No PFC version, EN61000-3-2 is not applicable to this model.
- The 'J' suffix indicates that these parts are Pb-free (RoHS 6/6) compliant. TSE RoHS 5/6 (non Pb-free) compliant versions may be available on special request, please contact your local sales representative for details.
- NOTICE: Some models do not support all options. Please contact your local Emerson Network Power representative or use the on-line model number search tool at <http://www.powerversion.com>.

Model Numbering Options

- The enclosure version includes: IEC connector, on/off switch, wire harness output connector and fitted cover. To order, please add the suffix 'E' the model number, e.g. NLP65-9608EJ. See NLP65 enclosure for details.
- A Safety earth ground pin and ground choke are available as an option. To order, please add the suffix 'G' the model number, e.g. NLP65-X608GJ.
- To order an enclosure kit (unfitted), order the part number LPX80.

Mechanical Drawing



ALL DIMENSIONS IN INCHES (mm)

Americas

5810 Van Allen Way
Carlsbad, CA 92008
USA
Telephone: +1 (760) 930 4600
Facsimile: +1 (760) 930 0698

Europe (UK)

Waterfront Business Park
Merry Hill, Dudley
West Midlands, DY5 1LX
United Kingdom
Telephone: +44 (0) 1384 842 211
Facsimile: +44 (0) 1384 843 355

Asia (HK)

14/F, Lu Plaza
2 Wing Yip Street
Kwun Tong, Kowloon
Hong Kong
Telephone: +852 2176 3333
Facsimile: +852 2176 3888

For global contact, visit:

www.powerconversion.com
technicalsupport@powerconversion.com

While every precaution has been taken to ensure accuracy and completeness in this literature, Emerson Network Power assumes no responsibility, and disclaims all liability for damages resulting from use of this information or for any errors or omissions.

Emerson Network Power.

The global leader in enabling business-critical continuity.

- AC Power
- Connectivity
- DC Power
- Embedded Computing
- Embedded Power
- Monitoring
- Outside Plant
- Power Switching & Controls
- Precision Cooling
- Racks & Integrated Cabinets
- Services
- Surge Protection

EmersonNetworkPower.com

Emerson Network Power and the Emerson Network Power logo are trademarks and service marks of Emerson Electric Co. ©2008 Emerson Electric Co.

| INPUT | |
|-------------------------|---------------|
| PIN CONNECTIONS | |
| J1 | |
| Pin 1 | AC Line |
| Pin 2 | No Pin |
| Pin 3 | AC Neutral |
| J2 (ON 'G' SUFFIX ONLY) | |
| Pin 1 | Safety Ground |

Input and output connectors

AC (J1) connector type
Molex 26-60-4030 type.

DC (J3) connector type
Molex 26-60-4060 type.

Note: The input and output connectors are the same as those used on NFS40, NFN40, NAL40, NAN40 and NLP40.

Mating connectors

AC (J1) mating connector type
Molex 09-50-3031 or equivalent with Molex 08-50-0105 or equivalent crimp terminals.

DC (J3) mating connector type
Molex 09-50-3061 with Molex 2478 phosphor bronze crimp terminals or equivalent.

| OUTPUT PIN CONNECTIONS | | | | |
|------------------------|--------|--------|--------|--|
| J3 | SINGLE | DUAL | TRIPLE | |
| Pin 1 | V (A) | V (B) | V (B) | |
| Pin 2 | V (A) | V (A) | V (A) | |
| Pin 3 | V (A) | V (A) | V (A) | |
| Pin 4 | Return | Return | Return | |
| Pin 5 | Return | Return | Return | |
| Pin 6 | Return | N/C | V (C) | |



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.