





LOC	DIST	REVISIONS					
		P	LTR	DESCRIPTION	DATE	DWN	APVD
AD	00		L1	REV PER ECO-06-026066	05DEC2006	BC	AS
			L2	REVISED PER ECO-09-021510	12SEP09	KK	AEG



SECTION T-T



RECOMMENDED P.C. BOARD LAYOUT

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN R. K. SEIFRIED CHK F. KIBLER APVD —	04/09/90 8-17-92 —	Tyco Electronics Tyco Electronics Corporation Harrisburg, PA 17105-3608	
DIMENSIONS: mm [INCHES]	TOLERANCES UNLESS OTHERWISE SPECIFIED:	NAME		PRODUCT SPEC	
	0 PLC ± —	APPLICATION SPEC		SIZE	
	1 PLC ± —	—		CAGE CODE	
	2 PLC ± —	—		DRAWING NO	
	3 PLC ± 0.13 [.005]	—		RESTRICTED TO	
MATERIAL	FINISH	WEIGHT		A1 00779 C=533270	
CUSTOMER DRAWING		SCALE		4:1	
		SHEET		1 OF 2	
		REV		L2	

LOC	DIST	REVISIONS				
AD	00	P	LTR	DESCRIPTION	DATE	OWN
		—	—	SEE SHEET 1	—	—

- 1

HOUSING MATERIAL: THERMOPLASTIC, COLOR—BLACK.
- 2

CONTACT MATERIAL: PHOSPHOR BRONZE.
- 3

CONTACT FINISH: .00127—.00254 [.000050—.000100] NICKEL UNDERPLATE ALL OVER; .00076 [.000030] GOLD PLATE IN CONTACT AREA AND FOR 5.08 [.200] FROM TIP OF WIRE—WRAP POST; GOLD FLASH ON REMAINDER OF POST.
- 4

ACTION PIN POSTS REQUIRE 2.36 [.093] MIN THICK P.C. BOARD. RECOMMENDED P.C. BOARD HOLES ARE 1.151 [.0453] DIA PLATED THRU WITH 0.025—0.076 [.001—.003] COPPER, WITH 0.0076 [.0003] MIN TIN—LEAD PLATING; FINISHED HOLE AFTER PLATING 0.94—1.09 [.037—0.43] DIA.
- 5

HOUSINGS WITH CENTER MOUNTING IS RECOMMENDED FOR ASSEMBLIES HAVING 75 CONTACTS PER ROW OR MORE.
- 6

OBSOLETE.
- 7

OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

△	5	251.46 [9.900]	—99—	255.27 [10.050]	265.43 [10.450]	273.05 [10.750]	—400—	1—533270—6
	5	226.06 [8.900]	—89—	229.87 [9.050]	240.03 [9.450]	247.65 [9.750]	—360—	1—533270—5
	5	213.36 [8.400]	—84—	217.17 [8.550]	227.33 [8.950]	234.95 [9.250]	—340—	1—533270—4
	5	200.66 [7.900]	—79—	204.47 [8.050]	214.63 [8.450]	222.25 [8.750]	—320—	1—533270—3
△ OBSOLETE		187.96 [7.400]	74	191.77 [7.550]	201.93 [7.950]	209.55 [8.250]	300	—1—533270—2—
	6	175.26 [6.900]	69	179.07 [7.050]	189.23 [7.450]	196.85 [7.750]	280	1—533270—1
	6	162.56 [6.400]	64	166.37 [6.550]	176.53 [6.950]	184.15 [7.250]	260	1—533270—0
	6	149.86 [5.900]	59	153.67 [6.050]	163.83 [6.450]	171.45 [6.750]	240	533270—9
		137.16 [5.400]	54	140.97 [5.550]	151.13 [5.950]	158.75 [6.250]	220	533270—8
		124.46 [4.900]	49	128.27 [5.050]	138.43 [5.450]	146.05 [5.750]	200	533270—7
	6	111.76 [4.400]	44	115.57 [4.550]	125.73 [4.950]	133.35 [5.250]	180	533270—6
		99.06 [3.900]	39	102.87 [4.050]	113.03 [4.450]	120.65 [4.750]	160	533270—5
	6	86.36 [3.400]	34	90.17 [3.550]	100.33 [3.950]	107.95 [4.250]	140	533270—4
	6	78.74 [3.100]	31	82.55 [3.250]	92.71 [3.650]	100.33 [3.950]	128	533270—3
	6	73.66 [2.900]	29	77.47 [3.050]	87.63 [3.450]	95.25 [3.750]	120	533270—2
	△ OBSOLETE		60.96 [2.400]	24	64.77 [2.550]	74.93 [2.950]	82.55 [3.250]	100
		E	D	C	B	A	POSN	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.				DWN R. K. SEIFRIED CHK F. KIBLER APVD —	04/09/90 8-17-92 —	Tyco Electronics Tyco Electronics Corporation Harrisburg, PA 17105-3608			
DIMENSIONS: mm [INCHES]		TOLERANCES UNLESS OTHERWISE SPECIFIED:		PRODUCT SPEC —		NAME HDI, 4 ROW, PIN ASSEMBLY, 13.54 [.533] LONG ACTION PINS, ALL GOLD PLATED POSTS			
		0 PLC ± — 1 PLC ± — 2 PLC ± — 3 PLC ± 0.13 [.005] 4 PLC ± — ANGLES ± —		APPLICATION SPEC —					
MATERIAL 1 2		FINISH 3		WEIGHT —		SIZE A1	CAGE CODE 00779	DRAWING NO 533270	RESTRICTED TO —
CUSTOMER DRAWING						SCALE 4:1	SHEET 2	OF 2	REV L2



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.