

Very High Speed, High Output Current, Voltage Feedback Amplifier

General Description

The LM7171 is a high speed voltage feedback amplifier that has the slewing characteristic of a current feedback amplifier; yet it can be used in all traditional voltage feedback amplifier configurations. The LM7171 is stable for gains as low as +2 or -1. It provides a very high slew rate at 4100V/µs and a wide unity-gain bandwidth of 200 MHz while consuming only 6.5 mA of supply current. It is ideal for video and high speed signal processing applications such as HDSL and pulse amplifiers. With 100 mA output current, the LM7171 can be used for video distribution, as a transformer driver or as a laser diode driver.

Operation on $\pm 15V$ power supplies allows for large signal swings and provides greater dynamic range and signal-tonoise ratio. The LM7171 offers low SFDR and THD, ideal for ADC/DAC systems. In addition, the LM7171 is specified for $\pm 5V$ operation for portable applications.

The LM7171 is built on National's advanced VIP[®] III (Vertically integrated PNP) complementary bipolar process.

Features

(Typical Unless Otherwise Noted)

- Easy-To-Use Voltage Feedback Topology
- Very High Slew Rate: 2400V/µs
- Wide Unity-Gain Bandwidth: 200 MHz
- -3 dB Frequency @ A_V = +2: 220 MHz
- Low Supply Current: 6.5 mA
- High Open Loop Gain: 85 dB
- High Output Current: 100 mA
- Specified for ±15V and ±5V Operation
- Available with radiation guarantee
 _____ Total lonizing Dose
 - ELDRS Free

- HDSL and ADSL Drivers
- Multimedia Broadcast Systems
- Professional Video Cameras
- Video Amplifiers

Applications

- Copiers/Scanners/Fax
- HDTV Amplifiers
- Pulse Amplifiers and Peak Detectors
- CATV/Fiber Optics Signal Processing

NS Part Number	SMD Part Number	NS Package Number	Package Description
LM7171AMJ-QML	5962-9553601QPA	J08A	8LD Ceramic Dip
LM7171AMJFQMLV HIGH DOSE RATE (<i>Note 5</i>)	5962F9553601VPA 300 krad(Si)	J08A	8LD Ceramic Dip
LM7171AMWFQMLV HIGH DOSE RATE (<i>Note 5</i>)	5962F9553601VHA 300 krad(Si)	W10A	10LD Ceramic Flatpack
LM7171AMWFLQMLV ELDRS FREE (<i>Note 14</i>)	5962F9553602VHA 300 krad(Si)	W10A	10LD Ceramic Flatpack
LM7171AMWG-QML	5962-9553601QXA	WG10A	10LD Ceramic SOIC
LM7171AMWGFQMLV HIGH DOSE RATE (<i>Note 5</i>)	5962F9553601QXA 300 krad(Si)	WG10A	10LD Ceramic SOIC
LM7171AMWGFLQV ELDRS FREE (<i>Note 14</i>)	5962F9553602VXA 300 krad(Si)	WG10A	10LD Ceramic SOIC

Ordering Information

M7171QML Very High Speed, High Output Current, Voltage Feedback Amplifier

300 krad(Si)

300 krad(Si)

VIP® is a registered trademark of National Semiconductor Corporation

Connection Diagrams





Simplified Schematic Diagram



Note: M1 and M2 are current mirrors.



Absolute Maximum Ratings (Note 1)

Supply Voltage (V+–V–) Differential Input Voltage (<i>Note 10</i>) Maximum Power Dissipation (<i>Note 2</i>) Output Short Circuit to Ground (<i>Note 6</i>) Storage Temperature Range Thermal Resistance (<i>Note 13</i>)	$36V$ $\pm 10V$ $730mW$ Continuous $-65^{\circ}C \leq T_{A} \leq +150^{\circ}C$
θ _{JA} 8LD Ceramic Dip (Still Air) 8LD Ceramic Dip (500LF/Min Air flow) 10LD Ceramic Flatpack (Still Air) 10LD Ceramic Flatpack (500LF/Min Air flow) 10LD Ceramic SOIC (Still Air) 10LD Ceramic SOIC (500LF/Min Air flow)	106°C/W 53°C/W 182°C/W 105°C/W 182°C/W 105°C/W
θ _{JC} 8LD Ceramic Dip 10LD Ceramic Flatpack 10LD Ceramic SOIC (<i>Note 3</i>) Package Weight (Typical)	3°C/W 5°C/W 5°C/W
8LD Ceramic Dip 10LD Ceramic Flatpack 10LD Ceramic SOIC Maximum Junction Temperature (<i>Note 2</i>) ESD Tolerance (<i>Note 4</i>)	965mg 235mg 230mg 150°C 3000V

Recommended Operating Conditions (Note 1)

Supply Voltage	$5.5V \le V_S \le 36V$
Operating Temperature Range	–55°C ≤ T _A ≤ +125°C

Quality Conformance Inspection

-		
Mil-Std-883	Method 5005	- Group A

Subgroup	Description	Temp °C
1	Static tests at	25
2	Static tests at	125
3	Static tests at	-55
4	Dynamic tests at	25
5	Dynamic tests at	125
6	Dynamic tests at	-55
7	Functional tests at	25
8A	Functional tests at	125
8B	Functional tests at	-55
9	Switching tests at	25
10	Switching tests at	125
11	Switching tests at	-55
12	Settling time at	25
13	Settling time at	125
14	Settling time at	-55

LM7171 (±15) Electrical Characteristics

DC Parameters (Note 5)

The following conditions apply, unless otherwise specified. DC: $T_{.1} = 25^{\circ}C$, V⁺ = +15V, V⁻ = -15V, V_{CM} = 0V, and R_L > 1M Ω

Symbol	Parameter	Conditions	Notes	Min	Max	Units	Sub- groups
V _{IO}	Input Offset Voltage			-1.0	1.0	mV	1
				-7.0	7.0	mV	2, 3
+l _{IB}	Input Bias Current				10	μA	1
					12	μA	2, 3
-I _{IB}	Input Bias Current				10	μA	1
					12	μA	2, 3
I _{IO}	Input Offset Current			-4.0	4.0	μA	1
				-6.0	6.0	μA	2, 3
CMRR	Common Mode Rejection Ratio	$V_{CM} = \pm 10V$		85		dB	1
				70		dB	2, 3
PSRR	Power Supply Rejection Ratio	$V_{\rm S} = \pm 15$ V to ± 5 V		85		dB	1
				80		dB	2, 3
A _V	Large Signal Voltage Gain	$R_L = 1K\Omega, V_O = \pm 5V$	(Note 7)	80		dB	1
			(Note 7)	75		dB	2, 3
		R _L = 100Ω, V _O = ±5V	(Note 7)	75		dB	1
			(Note 7)	70		dB	2, 3
Vo	Output Swing	$R_L = 1K\Omega$		13	-13	V	1
				12.7	-12.7	V	2, 3
		R _L = 100Ω		10.5	-9.5	V	1
				9.5	-9.0	V	2, 3
	Output Current (Open Loop)	Sourcing	(<i>Note 8</i>)	105		mA	1
		R _L = 100Ω	(<i>Note 8</i>)	95		mA	2, 3
		Sinking	(<i>Note 8</i>)		-95	mA	1
		R _L = 100Ω	(<i>Note 8</i>)		-90	mA	2, 3
I _S	Supply Current				8.5	mA	1
					9.5	mA	2, 3

AC Parameters (Note 5)

The following conditions apply, unless otherwise specified.

AC: $T_J = 25^{\circ}C$, $V^+ = +15V$, $V^- = -15V$, $V_{CM} = 0V$, and $R_L > 1M\Omega$

Symbol	Parameter	Conditions	Notes	Min	Max	Units	Sub- groups
SR	Slew Rate	$A_V = 2, V_I = \pm 2.5V$	(<i>Note 11</i>),	2000		V/µS	4
		3nS Rise & Fall time	(<i>Note 9</i>)				
GBW	Unity-Gain Bandwidth		(Note 12)	170		MHz	4

DC Drift Parameters (Note 5)

The following conditions apply, unless otherwise specified.

DC: $T_J = 25^{\circ}C$, V⁺ = +15V, V⁻ = -15V, V_{CM} = 0V, and R_L > 1M Ω

Delta calculations performed on QMLV devices at group B, subgroup 5.

Symbol	Parameter	Conditions	Notes	Min	Max	Units	Sub- groups
V _{IO}	Input Offset Voltage			-250	250	μV	1
+I _{Bias}	Input Bias Current			-500	500	nA	1
-I _{Bias}	Input Bias Current			-500	500	nA	1

LM7171 (±5) Electrical Characteristics

DC Parameters (Note 5)

The following conditions apply, unless otherwise specified.

DC: $T_J = 25^{\circ}C$, $V^+ = +5V$, $V^- = -5V$, $V_{CM} = 0V$, and $R_L > 1M\Omega$

Symbol	Parameter	Conditions	Notes	Min	Max	Units	Sub- groups
V _{IO}	Input Offset Voltage			-1.5	1.5	mV	1
				-7.0	7.0	mV	2, 3
+I _{IB}	Input Bias Current				10	μA	1
					12	μA	2, 3
-I _{IB}	Input Bias Current				10	μA	1
					12	μA	2, 3
I _{IO}	Input Offset Current			-4.0	4.0	μA	1
				-6.0	6.0	μA	2, 3
CMRR	Common Mode Rejection Ratio	$V_{CM} = \pm 2.5 V$		80		dB	1
				70		dB	2, 3
A _V	Large Signal Voltage Gain	$R_L = 1K\Omega, V_O = \pm 1V$	(Note 7)	75		dB	1
			(<i>Note 7</i>)	70		dB	2, 3
		$R_{L} = 100\Omega, V_{O} = \pm 1V$	(<i>Note 7</i>)	72		dB	1
			(Note 7)	67		dB	2, 3
Vo	Output Swing	$R_L = 1K\Omega$		3.2	-3.2	V	1
				3.0	-3.0	V	2, 3
		R _L = 100Ω		2.9	-2.9	V	1
				2.8	-2.75	V	2, 3
	Output Current (Open Loop)	Sourcing	(<i>Note 8</i>)	29		mA	1
		R _L = 100Ω	(<i>Note 8</i>)	28		mA	2, 3
		Sinking	(<i>Note 8</i>)		-29	mA	1
		R _L = 100Ω	(<i>Note 8</i>)		-27.5	mA	2, 3
I _S	Supply Current				8.0	mA	1
					9.0	mA	2, 3

DC Drift Parameters (Note 5)

The following conditions apply, unless otherwise specified.

DC: $T_J = 25^{\circ}C, V^+ = +5V, V^- = -5V, V_{CM} = 0V, and R_L > 1M\Omega$

Delta calculations performed on QMLV devices at group ${\sf B}$, subgroup 5.

Symbol	Parameter	Conditions	Notes	Min	Max	Units	Sub- groups
V _{IO}	Input Offset Voltage			-250	250	μV	1
+I _{Bias}	Input Bias Current			-500	500	nA	1
-I _{Bias}	Input Bias Current			-500	500	nA	1

Note 1: Absolute Maximum Ratings indicate limits beyond which damage to the device may occur. Operating Ratings indicate conditions for which the device is functional, but do not guarantee specific performance limits. For guaranteed specifications and test conditions, see the Electrical Characteristics. The guaranteed specifications apply only for the test conditions listed. Some performance characteristics may degrade when the device is not operated under the listed test conditions.

Note 2: The maximum power dissipation must be derated at elevated temperatures and is dictated by T_{Jmax} (maximum junction temperature), θ_{JA} (package junction to ambient thermal resistance), and T_A (ambient temperature). The maximum allowable power dissipation at any temperature is $P_{Dmax} = (T_{Jmax} - T_A)/\theta_{JA}$ or the number given in the Absolute Maximum Ratings, whichever is lower.

Note 3: The package material for these devices allows much improved heat transfer over our standard ceramic packages. In order to take full advantage of this improved heat transfer, heat sinking must be provided between the package base (directly beneath the die), and either metal traces on, or thermal vias through, the printed circuit board. Without this additional heat sinking, device power dissipation must be calculated using θ_{JA} , rather than θ_{JC} , thermal resistance. It must not be assumed that the device leads will provide substantial heat transfer out the package, since the thermal resistance of the leadframe material is very poor, relative to the material of the package base. The stated θ_{JC} thermal resistance is for the package material only, and does not account for the additional thermal resistance between the package, to calculate the total allowed power dissipation for the device.

Note 4: Human body model, $1.5 \text{ k}\Omega$ in series with 100 pF.

Note 5: Pre and post irradiation limits are identical to those listed under AC and DC electrical characteristics except as listed in the Post Radiation Limits Table. These parts may be dose rate sensitive in a space environment and demonstrate enhanced low dose rate effect. Radiation end point limits for the noted parameters are guaranteed only for the conditions as specified in MIL-STD-883, per Test Method 1019, Condition A.

Note 6: Applies to both single-supply and split-supply operation. Continuous short circuit operation at elevated ambient temperature can result in exceeding the maximum allowed junction temperature of 150°C.

Note 7: Large signal voltage gain is the total output swing divided by the input signal required to produce that swing. For $V_S = \pm 15V$, $V_{OUT} = \pm 5V$. For $V_S = \pm 5V$, $V_{OUT} = \pm 1V$.

Note 8: The open loop output current is guaranteed, by the measurement of the open loop output voltage swing, using 100Ω output load.

Note 9: Slew Rate measured between ±4V.

Note 10: Differential input voltage is applied at $V_S = \pm 15V$.

Note 11: See AN00001 for SR test circuit.

Note 12: See AN00002 for GBW test circuit.

Note 13: All numbers apply for packages soldered directly into a PC board.

Note 14: Pre and post irradiation limits are identical to those listed under AC and DC electrical characteristics except as listed in the Post Radiation Limits Table. Low dose rate testing has been performed on a wafer-by-wafer basis, per Test Method 1019, Condition D of MIL-STD-883, with no enhanced low dose rate sensitivity (ELDRS).

Typical Performance Characteristics unless otherwise noted, $T_A = 25^{\circ}C$







20159568

TEMPERATURE (°C)















Large Signal Voltage Gain vs Load



20159555

Input Voltage Noise vs Frequency



20159557

















300M











20159574





Note 15: The THD measurement at low frequency is limited by the test instrument.



Harmonic Distortion vs Frequency



20159575

Application Notes

LM7171 Performance Discussion

The LM7171 is a very high speed, voltage feedback amplifier. It consumes only 6.5 mA supply current while providing a unity-gain bandwidth of 200 MHz and a slew rate of $4100V/\mu$ s. It also has other great features such as low differential gain and phase and high output current.

The LM7171 is a true voltage feedback amplifier. Unlike current feedback amplifiers (CFAs) with a low inverting input impedance and a high non-inverting input impedance, both inputs of voltage feedback amplifiers (VFAs) have high impedance nodes. The low impedance inverting input in CFAs and a feedback capacitor create an additional pole that will lead to instability. As a result, CFAs cannot be used in traditional op amp circuits such as photodiode amplifiers, I-to-V converters and integrators where a feedback capacitor is required.

LM7171 Circuit Operation

The class AB input stage in the LM7171 is fully symmetrical and has a similar slewing characteristic to the current feedback amplifiers. In the LM7171 Simplified Schematic, Q1 through Q4 form the equivalent of the current feedback input buffer, R_E the equivalent of the feedback resistor, and stage A buffers the inverting input. The triple-buffered output stage isolates the gain stage from the load to provide low output impedance.

LM7171 Slew Rate Characteristic

The slew rate of the LM7171 is determined by the current available to charge and discharge an internal high impedance node capacitor. This current is the differential input voltage divided by the total degeneration resistor R_E . Therefore, the slew rate is proportional to the input voltage level, and the higher slew rates are achievable in the lower gain configurations. A curve of slew rate versus input voltage level is provided in the "Typical Performance Characteristics".

When a very fast large signal pulse is applied to the input of an amplifier, some overshoot or undershoot occurs. By placing an external resistor such as 1 k Ω in series with the input of the LM7171, the bandwidth is reduced to help lower the overshoot.

Slew Rate Limitation

If the amplifier's input signal has too large of an amplitude at too high of a frequency, the amplifier is said to be slew rate limited; this can cause ringing in time domain and peaking in frequency domain at the output of the amplifier.

In the "Typical Performance Characteristics" section, there are several curves of $A_V = +2$ and $A_V = +4$ versus input signal levels. For the $A_V = +4$ curves, no peaking is present and the LM7171 responds identically to the different input signal levels of 30 mV, 100 mV and 300 mV.

For the $A_V = +2$ curves, slight peaking occurs. This peaking at high frequency (>100 MHz) is caused by a large input signal at high enough frequency that exceeds the amplifier's slew rate. The peaking in frequency response does not limit the pulse response in time domain, and the LM7171 is stable with noise gain of ≥+2.

Layout Consideration

PRINTED CIRCUIT BOARDS AND HIGH SPEED OP AMPS

There are many things to consider when designing PC boards for high speed op amps. Without proper caution, it is very easy to have excessive ringing, oscillation and other degraded AC performance in high speed circuits. As a rule, the signal traces should be short and wide to provide low inductance and low impedance paths. Any unused board space needs to be grounded to reduce stray signal pickup. Critical components should also be grounded at a common point to eliminate voltage drop. Sockets add capacitance to the board and can affect high frequency performance. It is better to solder the amplifier directly into the PC board without using any socket.

USING PROBES

Active (FET) probes are ideal for taking high frequency measurements because they have wide bandwidth, high input impedance and low input capacitance. However, the probe ground leads provide a long ground loop that will produce errors in measurement. Instead, the probes can be grounded directly by removing the ground leads and probe jackets and using scope probe jacks.

COMPONENT SELECTION AND FEEDBACK RESISTOR

It is important in high speed applications to keep all component leads short. For discrete components, choose carbon composition-type resistors and mica-type capacitors. Surface mount components are preferred over discrete components for minimum inductive effect.

Large values of feedback resistors can couple with parasitic capacitance and cause undesirable effects such as ringing or oscillation in high speed amplifiers. For the LM7171, a feedback resistor of 510Ω gives optimal performance.

Compensation for Input Capacitance

The combination of an amplifier's input capacitance with the gain setting resistors, adds a pole that can cause peaking or oscillation. To solve this problem, a feedback capacitor with a value

$$C_F > (R_G \times C_{IN})/R_F$$

can be used to cancel that pole. For the LM7171, a feedback capacitor of 2 pF is recommended. *Figure 1* illustrates the compensation circuit.





Power Supply Bypassing

Bypassing the power supply is necessary to maintain low power supply impedance across frequency. Both positive and negative power supplies should be bypassed individually by placing 0.01 μ F ceramic capacitors directly to power supply pins and 2.2 μ F tantalum capacitors close to the power supply pins.



FIGURE 2. Power Supply Bypassing

Termination

In high frequency applications, reflections occur if signals are not properly terminated. *Figure 3* shows a properly terminated signal while *Figure 4* shows an improperly terminated signal.









FIGURE 4. Improperly Terminated Signal

To minimize reflection, coaxial cable with matching characteristic impedance to the signal source should be used. The other end of the cable should be terminated with the same value terminator or resistor. For the commonly used cables, RG59 has 75 Ω characteristic impedance, and RG58 has 50 Ω characteristic impedance.

Driving Capacitive Loads

Amplifiers driving capacitive loads can oscillate or have ringing at the output. To eliminate oscillation or reduce ringing, an isolation resistor can be placed as shown below in *Figure 5*. The combination of the isolation resistor and the load capacitor forms a pole to increase stability by adding more phase margin to the overall system. The desired performance depends on the value of the isolation resistor; the bigger the isolation resistor, the more damped the pulse response becomes. For LM7171, a 50 Ω isolation resistor is recommended for initial evaluation. *Figure 6* shows the LM7171 driving a 150 pF load with the 50 Ω isolation resistor.



FIGURE 5. Isolation Resistor Used to Drive Capacitive Load



FIGURE 6. The LM7171 Driving a 150 pF Load with a 50Ω Isolation Resistor

Power Dissipation

The maximum power allowed to dissipate in a device is defined as:

$$\mathsf{P}_{\mathsf{D}} = (\mathsf{T}_{\mathsf{J}(\mathsf{max})} - \mathsf{T}_{\mathsf{A}})/\theta_{\mathsf{J}\mathsf{A}}$$

Where

PD	is the power dissipation in a device
T _{J(max)}	is the maximum junction temperature
TA	is the ambient temperature
θιλ	is the thermal resistance of a particular package

For example, for the LM7171 in a Ceramic SOIC package, the maximum power dissipation at 25°C ambient temperature is 680 mW.

Thermal resistance, θ_{JA} , depends on parameters such as die size, package size and package material. The smaller the die size and package, the higher θ_{JA} becomes. The 8-pin DIP package has a lower thermal resistance (106°C/W) than that of the Ceramic SOIC (182°C/W). Therefore, for higher dissipation capability, use an 8-pin DIP package.

The total power dissipated in a device can be calculated as:

$$\mathsf{P}_{\mathsf{D}} = \mathsf{P}_{\mathsf{Q}} + \mathsf{P}_{\mathsf{L}}$$

 P_Q is the quiescent power dissipated in a device with no load connected at the output. P_L is the power dissipated in the device with a load connected at the output; it is not the power dissipated by the load.

Furthermore,

- P_Q : = supply current × total supply voltage with no load
- P_L: = output current × (voltage difference between supply voltage and output voltage of the same side of supply voltage)

For example, the total power dissipated by the LM7171 with V_S = ±15V and output voltage of 10V into 1 k Ω is

$$P_D = P_Q + P_L$$

- $= (6.5 \text{ mA}) \times (30 \text{V}) + (10 \text{ mA}) \times (15 \text{V} 10 \text{V})$
- = 195 mW + 50 mW
- = 245 mW

Application Circuit

Fast Instrumentation Amplifier









20159581





Released	Revision	Section	Changes
02/04/09	A	New Release, Corporate format	1 MDS data sheet converted into one Corp. data sheet format. Added ELDRS NSID's to Ordering Information Table. MNLM7171AM-X-RH Rev 0Co will be archived.

←0.270 MAX→ 0.080 0.055 0.050 ± 0.005 - 0.005 MIN TYP ТҮР 0.035 0.026 10 6 ТҮР 0.370 0.250 0.270 MAX 0.260 GLASS 0.238 0.012 0.008 DETAIL A DETAIL A 0.370 0.250 PIN #1 W10A (REV E) IDENT 5 0.006 0.004 0.019 0.045 MAX TYP ТҮР 0.015 TYP 10-Lead Ceramic Flatpack NS Package Number W10A .270 MAX [6.86] .005 MIN [0.12] TYP 10 (.370) [9.4] .410±.010 [10.41±0.25] .241⁺.020 [6.12^{+0.50} [6.12^{+0.50}] SUPPLIER'S-OPTION (10X .090 LEAD 1 ID (10X .027 [0.69] (8X .050) [1.27] RECOMMENDED LAND PATTERN .010±.002 [0.25±0.05] 10X .017±.002 [0.43±0.05] 8X .050±.002 [1.27±0.05] .070⁺:010 [1.78⁺⁰:25] (R.015 TYP [0.38] .004 [0.1] 045 MAX [1.14] TYP .008±.004 [0.2±0.1] 0° - 4° T Y F .040±.003 [1.02±0.07] TYP .006±.002 TYP [0.15±0.05] SEATING PLANE CONTROLLING DIMENSION IS INCH VALUES IN [] ARE MILLIMETERS DIMENSIONS IN () FOR REFERENCE ONLY MIL-PRF-38535 CONFIGURATION CONTROL WG10A (Rev F) 10-Lead Ceramic SOIC NS Package Number WG10A

Physical Dimensions inches (millimeters) unless otherwise noted



Notes

For more National Semiconductor product information and proven design tools, visit the following Web sites at: www.national.com

Products		Design Support	
Amplifiers	www.national.com/amplifiers	WEBENCH® Tools	www.national.com/webench
Audio	www.national.com/audio	App Notes	www.national.com/appnotes
Clock and Timing	www.national.com/timing	Reference Designs	www.national.com/refdesigns
Data Converters	www.national.com/adc	Samples	www.national.com/samples
Interface	www.national.com/interface	Eval Boards	www.national.com/evalboards
LVDS	www.national.com/lvds	Packaging	www.national.com/packaging
Power Management	www.national.com/power	Green Compliance	www.national.com/quality/green
Switching Regulators	www.national.com/switchers	Distributors	www.national.com/contacts
LDOs	www.national.com/ldo	Quality and Reliability	www.national.com/quality
LED Lighting	www.national.com/led	Feedback/Support	www.national.com/feedback
Voltage References	www.national.com/vref	Design Made Easy	www.national.com/easy
PowerWise® Solutions	www.national.com/powerwise	Applications & Markets	www.national.com/solutions
Serial Digital Interface (SDI)	www.national.com/sdi	Mil/Aero	www.national.com/milaero
Temperature Sensors	www.national.com/tempsensors	SolarMagic™	www.national.com/solarmagic
PLL/VCO	www.national.com/wireless	PowerWise® Design University	www.national.com/training

THE CONTENTS OF THIS DOCUMENT ARE PROVIDED IN CONNECTION WITH NATIONAL SEMICONDUCTOR CORPORATION ("NATIONAL") PRODUCTS. NATIONAL MAKES NO REPRESENTATIONS OR WARRANTIES WITH RESPECT TO THE ACCURACY OR COMPLETENESS OF THE CONTENTS OF THIS PUBLICATION AND RESERVES THE RIGHT TO MAKE CHANGES TO SPECIFICATIONS AND PRODUCT DESCRIPTIONS AT ANY TIME WITHOUT NOTICE. NO LICENSE, WHETHER EXPRESS, IMPLIED, ARISING BY ESTOPPEL OR OTHERWISE, TO ANY INTELLECTUAL PROPERTY RIGHTS IS GRANTED BY THIS DOCUMENT.

TESTING AND OTHER QUALITY CONTROLS ARE USED TO THE EXTENT NATIONAL DEEMS NECESSARY TO SUPPORT NATIONAL'S PRODUCT WARRANTY. EXCEPT WHERE MANDATED BY GOVERNMENT REQUIREMENTS, TESTING OF ALL PARAMETERS OF EACH PRODUCT IS NOT NECESSARILY PERFORMED. NATIONAL ASSUMES NO LIABILITY FOR APPLICATIONS ASSISTANCE OR BUYER PRODUCT DESIGN. BUYERS ARE RESPONSIBLE FOR THEIR PRODUCTS AND APPLICATIONS USING NATIONAL COMPONENTS. PRIOR TO USING OR DISTRIBUTING ANY PRODUCTS THAT INCLUDE NATIONAL COMPONENTS, BUYERS SHOULD PROVIDE ADEQUATE DESIGN, TESTING AND OPERATING SAFEGUARDS.

EXCEPT AS PROVIDED IN NATIONAL'S TERMS AND CONDITIONS OF SALE FOR SUCH PRODUCTS, NATIONAL ASSUMES NO LIABILITY WHATSOEVER, AND NATIONAL DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY RELATING TO THE SALE AND/OR USE OF NATIONAL PRODUCTS INCLUDING LIABILITY OR WARRANTIES RELATING TO FITNESS FOR A PARTICULAR PURPOSE, MERCHANTABILITY, OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT.

LIFE SUPPORT POLICY

NATIONAL'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS PRIOR WRITTEN APPROVAL OF THE CHIEF EXECUTIVE OFFICER AND GENERAL COUNSEL OF NATIONAL SEMICONDUCTOR CORPORATION. As used herein:

Life support devices or systems are devices which (a) are intended for surgical implant into the body, or (b) support or sustain life and whose failure to perform when properly used in accordance with instructions for use provided in the labeling can be reasonably expected to result in a significant injury to the user. A critical component is any component in a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system or to affect its safety or effectiveness.

National Semiconductor and the National Semiconductor logo are registered trademarks of National Semiconductor Corporation. All other brand or product names may be trademarks or registered trademarks of their respective holders.

Copyright© 2010 National Semiconductor Corporation

For the most current product information visit us at www.national.com



National Semiconductor Americas Technical Support Center Email: support@nsc.com Tel: 1-800-272-9959

National Semiconductor Europe Technical Support Center Email: europe.support@nsc.com National Semiconductor Asia Pacific Technical Support Center Email: ap.support@nsc.com National Semiconductor Japan Technical Support Center Email: jpn.feedback@nsc.com



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный) Факс: 8 (812) 320-02-42 **Электронная почта:** <u>org@eplast1.ru</u> **Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.