


## Bolt connection terminal block - RBO 6 - 3075896

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Bolt connection terminal block, Connection method: Bolt connection, Cross section: 2.5 mm<sup>2</sup> - 35 mm<sup>2</sup>, AWG: 12 - 2, Width: 17 mm, Height: 48.6 mm, Color: gray, Mounting type: NS 35/7,5, NS 35/15

### Product Features

- Compact connection with ring and fork-type cable lugs
- Mounting on standard DIN rails or directly in control boxes
- Isolator bridge bar for switchable cross connections
- Bridge shaft for potential distribution using standard screw bridges



### Key commercial data

|                                      |          |
|--------------------------------------|----------|
| Packing unit                         | 1 1      |
| Weight per Piece (excluding packing) | 37.5 GRM |
| Custom tariff number                 | 85369010 |
| Country of origin                    | India    |

### Technical data

#### General

|   |   |
|---|---|
| Number of levels                        | 1   |
| Number of connections                   | 2   |
| Color                                   | gray  |
| Insulating material                     | PA  |
| Inflammability class according to UL 94 | V0  |
| Maximum load current                    | 125 A (with 35 mm <sup>2</sup> conductor cross section) |
| Rated surge voltage                     | 8 kV  |
| Pollution degree                        | 3   |
| Surge voltage category                  | III   |
| Insulating material group               | I   |
| Connection in acc. with standard        | IEC 60947-7-1   |

## Bolt connection terminal block - RBO 6 - 3075896

### Technical data

#### General

|   |   |
|---|---|
| Nominal current $I_N$   | 125 A   |
| Nominal voltage $U_N$   | 800 V   |
| Open side panel   | nein  |
| Shock protection test specification   | DIN EN 50274 (VDE 0660-514):2002-11                 |
| Back of the hand protection   | guaranteed  |
| Surge voltage test setpoint   | 9.8 kV  |
| Result of surge voltage test  | Test passed   |
| Power frequency withstand voltage setpoint                                      | 2 kV  |
| Result of power-frequency withstand voltage test                                | Test passed   |
| Checking the mechanical stability of terminal points (5 x conductor connection) | Test passed   |
| Tight fit on carrier  | NS 32/NS 35   |
| Setpoint  | 10 N  |
| Result of tight fit test  | Test passed   |
| Requirements, voltage drop  | $\leq 3.2$ mV                                       |
| Result of voltage drop test   | Test passed   |
| Temperature-rise test   | Test passed   |
| Conductor cross section short circuit testing                                   | 35 mm <sup>2</sup>                                  |
| Short-time current  | 4.2 kA  |
| Short circuit stability result  | Test passed   |
| Proof of thermal characteristics (needle flame) effective duration              | 30 s  |
| Result of thermal test  | Test passed   |
| Test specification, oscillation, broadband noise                                | DIN EN 50155 (VDE 0115-200):2008-03                 |
| Test spectrum   | Service life test category 1, class B, body mounted |
| Test frequency  | $f_1 = 5$ Hz to $f_2 = 150$ Hz                      |
| ASD level   | 1.857 (m/s <sup>2</sup> ) <sup>2</sup> /Hz          |
| Acceleration  | 0.8 g   |
| Test duration per axis  | 5 h   |
| Test directions   | X-, Y- and Z-axis                                   |
| Oscillation, broadband noise test result  | Test passed   |
| Test specification, shock test  | DIN EN 50155 (VDE 0115-200):2008-03                 |
| Shock form  | Half-sine   |
| Acceleration  | 5 g   |
| Shock duration  | 30 ms   |
| Number of shocks per direction  | 3   |
| Test directions   | X-, Y- and Z-axis (pos. and neg.)                   |
| Shock test result   | Test passed   |

## Bolt connection terminal block - RBO 6 - 3075896

### Technical data

#### General

|   |        |
|---|--------|
| Temperature index, insulating material (DIN EN 60216-1 (VDE 0304-21)) | 130 °C |
| Static insulating material application in cold                        | -60 °C |

#### Dimensions

|                  |         |
|------------------|---------|
| Width            | 17 mm   |
| Length           | 80.8 mm |
| Height           | 48.6 mm |
| Height NS 35/7,5 | 49.8 mm |
| Height NS 35/15  | 57.3 mm |
| Height NS 32     | 54.7 mm |

#### Connection data

|   |                     |
|---|---------------------|
| Note  | Connection bolts    |
| Conductor cross section solid min.          | 2.5 mm <sup>2</sup> |
| Conductor cross section solid max.          | 35 mm <sup>2</sup>  |
| Conductor cross section AWG/kcmil min.      | 12                  |
| Conductor cross section AWG/kcmil max       | 2                   |
| Conductor cross section stranded min.       | 2.5 mm <sup>2</sup> |
| Conductor cross section stranded max.       | 35 mm <sup>2</sup>  |
| Min. AWG conductor cross section, stranded  | 12                  |
| Max. AWG conductor cross section, stranded  | 2                   |
| Min. cross section for cable lug connection | 6 mm <sup>2</sup>   |
| Max. cross section for cable lug connection | 35 mm <sup>2</sup>  |
| Connection method                           | Bolt connection     |
| Screw thread                                | M6                  |
| Tightening torque, min                      | 3.2 Nm              |
| Tightening torque max                       | 3.7 Nm              |

### Classifications

#### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 27141120 |
| eCl@ss 4.1 | 27141120 |
| eCl@ss 5.0 | 27141120 |
| eCl@ss 5.1 | 27141120 |
| eCl@ss 6.0 | 27141120 |
| eCl@ss 7.0 | 27141120 |
| eCl@ss 8.0 | 27141120 |

# Bolt connection terminal block - RBO 6 - 3075896

## Classifications

### ETIM

|          |          |
|----------|----------|
| ETIM 2.0 | EC000897 |
| ETIM 3.0 | EC000897 |
| ETIM 4.0 | EC000897 |
| ETIM 5.0 | EC000897 |

### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30211811 |
| UNSPSC 7.0901 | 39121410 |
| UNSPSC 11     | 39121410 |
| UNSPSC 12.01  | 39121410 |
| UNSPSC 13.2   | 39121410 |

## Approvals

### Approvals

---

#### Approvals

UL Recognized / cUL Recognized / GOST / cULus Recognized

---


#### Ex Approvals

---

#### Approvals submitted

---

## Approval details

|   |       |       |
|---|-------|-------|
| UL Recognized  |       |       |
|   | B     | C     |
| Nominal current I <sub>N</sub>  | 115 A | 115 A |
| Nominal voltage U <sub>N</sub>  | 600 V | 600 V |

## Bolt connection terminal block - RBO 6 - 3075896

### Approvals

|                                |       |       |
|--------------------------------|-------|-------|
| cUL Recognized                 |       |       |
|                                | B     | C     |
| Nominal current I <sub>N</sub> | 115 A | 115 A |
| Nominal voltage U <sub>N</sub> | 600 V | 600 V |

|      |  |  |
|------|--|--|
| GOST |  |  |
|------|--|--|

|                  |  |  |
|------------------|--|--|
| cULus Recognized |  |  |
|------------------|--|--|

### Accessories

#### Accessories

#### Bridge

Fixed bridge - FB 10-17 - 3075951



Fixed bridge, Number of positions: 10, Color: silver

#### Cover profile

Cover profile - AP RSC-T - 3059139



Cover profile, for covering terminal strips, directly snapped onto RBO... and RSC... test disconnect terminal blocks.  
Length supplied: 1 m

#### End block

## Bolt connection terminal block - RBO 6 - 3075896

### Accessories

End clamp - CLIPFIX 35 - 3022218



Quick mounting end clamp for NS 35/7,5 DIN rail or NS 35/15 DIN rail, with marking option, width: 9.5 mm, color: gray

---

End clamp - CLIPFIX 35-5 - 3022276



Quick mounting end clamp for NS 35/7,5 DIN rail or NS 35/15 DIN rail, with marking option, with parking option for FBS...5, FBS...6, KSS 5, KSS 6, width: 5.15 mm, color: gray

---

End clamp - E/NS 35 N - 0800886



End clamp, width: 9.5 mm, color: gray

---

End clamp - E/UK - 1201442



End clamp, for assembly on NS 32 or NS 35/7.5 DIN rail

---

End clamp - E/UK 1 - 1201413



End clamps, for supporting the ends of double-level and three-level terminal blocks, width: 10 mm, color: gray

---

End cover

## Bolt connection terminal block - RBO 6 - 3075896

### Accessories

End cover - D-RSC 6 - 3213098



End cover, Length: 80.8 mm, Width: 2.2 mm, Color: gray

---

### Labeled terminal marker

Zack marker strip - ZB 17 CUS - 0829393



Zack marker strip, Can be ordered: Strip, white, Labeled according to customer specifications, Mounting type: Snap into tall marker groove, For terminal block width: 17 mm, Lettering field: 17 x 10.5 mm

---

### Mounting rail

DIN rail - NS 32 PERF 2000MM - 1201002



G-profile DIN rail, material: Steel, perforated, height 15 mm, width 32 mm, length 2 m

---

DIN rail - NS 32 UNPERF 2000MM - 1201015



G-profile DIN rail, material: Steel, unperforated, height 15 mm, width 32 mm, length 2 m

---

DIN rail perforated - NS 35/ 7,5 PERF 2000MM - 0801733



DIN rail, material: steel galvanized and passivated with a thick layer, perforated, height 7.5 mm, width 35 mm, length: 2000 mm

## Bolt connection terminal block - RBO 6 - 3075896

### Accessories

---

DIN rail - NS 35/ 7,5 UNPERF 2000MM - 0801681



DIN rail, material: Steel, unperforated, height 7.5 mm, width 35 mm, length: 2 m

---

DIN rail - NS 35/ 7,5 WH PERF 2000MM - 1204119



DIN rail 35 mm (NS 35)

---

DIN rail - NS 35/ 7,5 WH UNPERF 2000MM - 1204122



DIN rail 35 mm (NS 35)

---

DIN rail, unperforated - NS 35/ 7,5 AL UNPERF 2000MM - 0801704



DIN rail, unperforated, Width: 35 mm, Height: 7.5 mm, Length: 2000 mm, Color: silver

---

DIN rail - NS 35/ 7,5 ZN PERF 2000MM - 1206421



DIN rail, material: Galvanized, perforated, height 7.5 mm, width 35 mm, length: 2 m

---



## Bolt connection terminal block - RBO 6 - 3075896

### Accessories

DIN rail - NS 35/ 7,5 ZN UNPERF 2000MM - 1206434



DIN rail, material: Galvanized, unperforated, height 7.5 mm, width 35 mm, length: 2 m

---

DIN rail - NS 35/ 7,5 CU UNPERF 2000MM - 0801762



DIN rail, material: Copper, unperforated, height 7.5 mm, width 35 mm, length: 2 m

---

End cap - NS 35/ 7,5 CAP - 1206560



DIN rail end piece, for DIN rail NS 35/7.5

---

DIN rail perforated - NS 35/15 PERF 2000MM - 1201730



DIN rail, material: steel galvanized and passivated with a thick layer, perforated, height 15 mm, width 35 mm, length: 2000 mm

---

DIN rail - NS 35/15 UNPERF 2000MM - 1201714



DIN rail, material: Steel, unperforated, height 15 mm, width 35 mm, length: 2 m

---

## Bolt connection terminal block - RBO 6 - 3075896

### Accessories

DIN rail - NS 35/15 WH PERF 2000MM - 0806602



DIN rail 35 mm (NS 35)

---

DIN rail - NS 35/15 WH UNPERF 2000MM - 1204135



DIN rail 35 mm (NS 35)

---

DIN rail, unperforated - NS 35/15 AL UNPERF 2000MM - 1201756



DIN rail, deep drawn, high profile, unperforated, 1.5 mm thick, material: aluminum, height 15 mm, width 35 mm, length 2000 mm

---

DIN rail - NS 35/15 ZN PERF 2000MM - 1206599



DIN rail, material: Galvanized, perforated, height 15 mm, width 35 mm, length: 2 m

---

DIN rail - NS 35/15 ZN UNPERF 2000MM - 1206586



DIN rail, material: Galvanized, unperforated, height 15 mm, width 35 mm, length: 2 m

---

## Bolt connection terminal block - RBO 6 - 3075896

### Accessories

DIN rail - NS 35/15 CU UNPERF 2000MM - 1201895



DIN rail, material: Copper, unperforated, 1.5 mm thick, height 15 mm, width 35 mm, length: 2 m

---

End cap - NS 35/15 CAP - 1206573



DIN rail end piece, for DIN rail NS 35/15

---

DIN rail - NS 35/15-2,3 UNPERF 2000MM - 1201798



DIN rail, material: Steel, unperforated, 2.3 mm thick, height 15 mm, width 35 mm, length: 2 m

---

### Partition plate

Separating plate - TS-KK 3 - 2770215



Separating plate, Length: 14 mm, Width: 1.5 mm, Height: 16 mm, Color: gray

---

### Socket spanner

Tool - SHN 13 - 1209923



Socket wrench, wrench size 13 mm

## Bolt connection terminal block - RBO 6 - 3075896

### Accessories

---

#### Terminal marking

Zack marker strip - ZB 17:UNBEDRUCKT - 0829391



Zack marker strip, Strip, white, Unlabeled, Can be labeled with: Plotter, Mounting type: Snap into tall marker groove, For terminal block width: 17 mm, Lettering field: 17 x 10.5 mm

---

### Drawings

#### Circuit diagram





Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.