


### Trench gate field-stop 600 V, 30 A high speed HB series IGBT



## Features

- Maximum junction temperature:  $T_J = 175 \text{ }^\circ\text{C}$
- High speed switching series
- Minimized tail current
- Low saturation voltage:  $V_{CE(\text{sat})} = 1.55 \text{ V (typ.)} @ I_C = 30 \text{ A}$
- Tight parameter distribution
- Safe paralleling
- Positive  $V_{CE(\text{sat})}$  temperature coefficient
- Low thermal resistance
- Very fast soft recovery antiparallel diode

## Applications

- Photovoltaic inverters
- High frequency converters

## Description

These devices are IGBTs developed using an advanced proprietary trench gate field-stop structure. These devices are part of the new HB series of IGBTs, which represent an optimum compromise between conduction and switching loss to maximize the efficiency of any frequency converter. Furthermore, the slightly positive  $V_{CE(\text{sat})}$  temperature coefficient and very tight parameter distribution result in safer paralleling operation.



Product status link
<a href="#">STGW30H60DFB</a>
<a href="#">STGWA30H60DFB</a>
<a href="#">STGWT30H60DFB</a>

## 1 Electrical ratings

**Table 1. Absolute maximum ratings**

Symbol	Parameter	Value	Unit
$V_{CES}$	Collector-emitter voltage ( $V_{GE} = 0$ V)	600	V
$I_C$	Continuous collector current at $T_C = 25$ °C	60	A
	Continuous collector current at $T_C = 100$ °C	30	
$I_{CP}^{(1)}$	Pulsed collector current	120	
$V_{GE}$	Gate-emitter voltage	$\pm 20$	V
	Transient gate-emitter voltage	$\pm 30$	
$I_F$	Continuous forward current at $T_C = 25$ °C	60	A
	Continuous forward current at $T_C = 100$ °C	30	
$I_{FP}^{(1)}$	Pulsed forward current	120	
$P_{TOT}$	Total power dissipation at $T_C = 25$ °C	260	W
$T_{STG}$	Storage temperature range	- 55 to 150	°C
$T_J$	Operating junction temperature range	- 55 to 175	

1. Pulse width limited by maximum junction temperature.

**Table 2. Thermal data**

Symbol	Parameter	Value	Unit
$R_{thJC}$	Thermal resistance junction-case IGBT	0.58	°C/W
$R_{thJC}$	Thermal resistance junction-case diode	2.08	
$R_{thJA}$	Thermal resistance junction-ambient	50	

## 2 Electrical characteristics

$T_C = 25^\circ\text{C}$  unless otherwise specified

**Table 3. Static characteristics**

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
$V_{(\text{BR})\text{CES}}$	Collector-emitter breakdown voltage	$V_{GE} = 0 \text{ V}, I_C = 2 \text{ mA}$	600			V
$V_{CE(\text{sat})}$	Collector-emitter saturation voltage	$V_{GE} = 15 \text{ V}, I_C = 30 \text{ A}$		1.55	2	V
		$V_{GE} = 15 \text{ V}, I_C = 30 \text{ A}, T_J = 125^\circ\text{C}$		1.65		
		$V_{GE} = 15 \text{ V}, I_C = 30 \text{ A}, T_J = 175^\circ\text{C}$		1.75		
$V_F$	Forward on-voltage	$I_F = 30 \text{ A}$		2	2.6	V
		$I_F = 30 \text{ A}, T_J = 125^\circ\text{C}$		1.7		
		$I_F = 30 \text{ A}, T_J = 175^\circ\text{C}$		1.6		
$V_{GE(\text{th})}$	Gate threshold voltage	$V_{CE} = V_{GE}, I_C = 1 \text{ mA}$	5	6	7	V
$I_{CES}$	Collector cut-off current	$V_{GE} = 0 \text{ V}, V_{CE} = 600 \text{ V}$			25	$\mu\text{A}$
$I_{GES}$	Gate-emitter leakage current	$V_{CE} = 0 \text{ V}, V_{GE} = \pm 20 \text{ V}$			$\pm 250$	nA

**Table 4. Dynamic characteristics**

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
$C_{ies}$	Input capacitance	$V_{CE} = 25 \text{ V}, f = 1 \text{ MHz}, V_{GE} = 0 \text{ V}$	-	3659	-	pF
$C_{oes}$	Output capacitance		-	101	-	
$C_{res}$	Reverse transfer capacitance		-	76	-	
$Q_g$	Total gate charge	$V_{CC} = 520 \text{ V}, I_C = 30 \text{ A}, V_{GE} = 0 \text{ to } 15 \text{ V}$ (see Figure 28. Gate charge test circuit)	-	149	-	nC
$Q_{ge}$	Gate-emitter charge		-	25	-	
$Q_{gc}$	Gate-collector charge		-	62	-	

**Table 5. IGBT switching characteristics (inductive load)**

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
$t_{d(on)}$	Turn-on delay time	$V_{CE} = 400 \text{ V}, I_C = 30 \text{ A}, V_{GE} = 15 \text{ V}, R_G = 10 \Omega$ (see <a href="#">Figure 27. Test circuit for inductive load switching</a> )	-	37	-	ns
$t_r$	Current rise time		-	14.6	-	ns
$(di/dt)_{on}$	Turn-on current slope		-	1643	-	A/ $\mu$ s
$t_{d(off)}$	Turn-off-delay time		-	146	-	ns
$t_f$	Current fall time		-	23	-	ns
$E_{on}^{(1)}$	Turn-on switching energy		-	383	-	$\mu$ J
$E_{off}^{(2)}$	Turn-off switching energy		-	293	-	$\mu$ J
$E_{ts}$	Total switching energy		-	676	-	$\mu$ J
$t_{d(on)}$	Turn-on delay time	$V_{CE} = 400 \text{ V}, I_C = 30 \text{ A}, V_{GE} = 15 \text{ V}, R_G = 10 \Omega, T_J = 175 \text{ }^\circ\text{C}$ (see <a href="#">Figure 27. Test circuit for inductive load switching</a> )	-	35	-	ns
$t_r$	Current rise time		-	16.1	-	ns
$(di/dt)_{on}$	Turn-on current slope		-	1496	-	A/ $\mu$ s
$t_{d(off)}$	Turn-off-delay time		-	158	-	ns
$t_f$	Current fall time		-	65	-	ns
$E_{on}^{(1)}$	Turn-on switching energy		-	794	-	$\mu$ J
$E_{off}^{(2)}$	Turn-off switching energy		-	572	-	$\mu$ J
$E_{ts}$	Total switching energy		-	1366	-	$\mu$ J

1. Including the reverse recovery of the diode.

2. Including the tail of the collector current.


**Table 6. Diode switching characteristics (inductive load)**

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
$t_{rr}$	Reverse recovery time	$I_F = 30 \text{ A}, V_R = 400 \text{ V}, V_{GE} = 15 \text{ V}, di/dt = 1000 \text{ A}/\mu\text{s}$ (see <a href="#">Figure 27. Test circuit for inductive load switching</a> )	-	53	-	ns
$Q_{rr}$	Reverse recovery charge		-	384	-	nC
$I_{rrm}$	Reverse recovery current		-	14.5	-	A
$dI_{rr}/dt$	Peak rate of fall of reverse recovery current during $t_b$		-	788	-	A/ $\mu$ s
$E_{rr}$	Reverse recovery energy		-	104	-	$\mu$ J
$t_{rr}$	Reverse recovery time	$I_F = 30 \text{ A}, V_R = 400 \text{ V}, V_{GE} = 15 \text{ V}, di/dt = 1000 \text{ A}/\mu\text{s}, T_J = 175 \text{ }^\circ\text{C}$ (see <a href="#">Figure 27. Test circuit for inductive load switching</a> )	-	104	-	ns
$Q_{rr}$	Reverse recovery charge		-	1352	-	nC
$I_{rrm}$	Reverse recovery current		-	26	-	A
$dI_{rr}/dt$	Peak rate of fall of reverse recovery current during $t_b$		-	310	-	A/ $\mu$ s
$E_{rr}$	Reverse recovery energy		-	407	-	$\mu$ J


## 2.1

### Electrical characteristics (curves)


**Figure 1. Power dissipation vs case temperature**




**Figure 2. Collector current vs case temperature**




**Figure 3. Output characteristics ( $T_J = 25 \text{ °C}$ )**




**Figure 4. Output characteristics ( $T_J = 175 \text{ °C}$ )**















**Figure 5.  $V_{\text{CE}(\text{sat})}$  vs junction temperature**









**Figure 6.  $V_{\text{CE}(\text{sat})}$  vs collector current**




**Figure 7. Collector current vs switching frequency**

**Figure 8. Forward bias safe operating area**

**Figure 9. Transfer characteristics**

**Figure 10. Diode  $V_F$  vs forward current**

**Figure 11. Normalized  $V_{GE(\text{th})}$  vs junction temperature**

**Figure 12. Normalized  $V_{(BR)CES}$  vs junction temperature**



**Figure 13. Capacitance variations**

**Figure 14. Gate charge vs. gate-emitter voltage**

**Figure 15. Switching energy vs collector current**

**Figure 16. Switching energy vs gate resistance**

**Figure 17. Switching energy vs temperature**

**Figure 18. Switching energy vs collector emitter voltage**


**Figure 19. Switching times vs collector current**

**Figure 20. Switching times vs gate resistance**

**Figure 21. Reverse recovery current vs diode current slope**

**Figure 22. Reverse recovery time vs diode current slope**

**Figure 23. Reverse recovery charge vs diode current slope**

**Figure 24. Reverse recovery energy vs diode current slope**


**Figure 25. Thermal impedance for IGBT**




**Figure 26. Thermal impedance for diode**




### 3 Test circuits

**Figure 27. Test circuit for inductive load switching**




AM01504v1

**Figure 28. Gate charge test circuit**




AM01505v1

**Figure 29. Switching waveform**



AM01506v1

**Figure 30. Diode reverse recovery waveform**



GADG180720171418SA


**4****Package information**

---

In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK packages, depending on their level of environmental compliance. ECOPACK specifications, grade definitions and product status are available at: [www.st.com](http://www.st.com). ECOPACK is an ST trademark.

## 4.1 TO-247 package information

Figure 31. TO-247 package outline




0075325\_9

**Table 7.** TO-247 package mechanical data

Dim.	mm		
	Min.	Typ.	Max.
A	4.85		5.15
A1	2.20		2.60
b	1.0		1.40
b1	2.0		2.40
b2	3.0		3.40
c	0.40		0.80
D	19.85		20.15
E	15.45		15.75
e	5.30	5.45	5.60
L	14.20		14.80
L1	3.70		4.30
L2		18.50	
ØP	3.55		3.65
ØR	4.50		5.50
S	5.30	5.50	5.70

## 4.2 TO-247 long leads package information

Figure 32. TO-247 long leads package outline




8463846\_2\_F

**Table 8. TO-247 long leads package mechanical data**

Dim.	mm		
	Min.	Typ.	Max.
A	4.90	5.00	5.10
A1	2.31	2.41	2.51
A2	1.90	2.00	2.10
b	1.16		1.26
b2			3.25
b3			2.25
c	0.59		0.66
D	20.90	21.00	21.10
E	15.70	15.80	15.90
E2	4.90	5.00	5.10
E3	2.40	2.50	2.60
e	5.34	5.44	5.54
L	19.80	19.92	20.10
L1			4.30
P	3.50	3.60	3.70
Q	5.60		6.00
S	6.05	6.15	6.25

#### 4.3 TO-3P package information

Figure 33. TO-3P package outline



8045950\_3

**Table 9.** TO-3P package mechanical data

Dim.	mm		
	Min.	Typ.	Max.
A	4.60	4.80	5.00
A1	1.45	1.50	1.65
A2	1.20	1.40	1.60
b	0.80	1.00	1.20
b1	1.80	2.00	2.20
b2	2.80	3.00	3.20
c	0.55	0.60	0.75
D	19.70	19.90	20.10
D1	13.70	13.90	14.10
E	15.40	15.60	15.80
E1	13.40	13.60	13.80
E2	9.40	9.60	9.90
e	5.15	5.45	5.75
L	19.80	20.00	20.20
L1	3.30	3.50	3.70
L2	18.20	18.40	18.60
ØP	3.30	3.40	3.50
ØP1	3.10	3.20	3.30
Q	4.80	5.00	5.20
Q1	3.60	3.80	4.00

## 5 Ordering information

**Table 10. Order codes**

Order code	Marking	Package	Packing
STGW30H60DFB	GW30H60DFB	TO-247	Tube
STGWA30H60DFB	GWA30H60DFB	TO-247 long leads	
STGWT30H60DFB	GWT30H60DFB	TO-3P	

## Revision history

**Table 11. Document revision history**

Date	Revision	Changes
01-Aug-2014	1	Initial version.
17-Feb-2016	2	Modified: <i>Table 2, Table 4 and 6</i> Modified: <i>Figure 16</i> Updated: <i>Section 3</i> Updated: <i>Section 4.1: TO-247, STGW30H60DFB</i> Minor text changes
04-Nov-2016	3	Added device in TO-247 long leads. Document updated accordingly. Minor text changes.
10-May-2019	4	Modified <i>Figure 3. Output characteristics (<math>T_J = 25^\circ\text{C}</math>), Figure 4. Output characteristics (<math>T_J = 175^\circ\text{C}</math>), Figure 9. Transfer characteristics, Figure 7. Collector current vs switching frequency, Figure 18. Switching energy vs collector emitter voltage.</i> Minor text changes.

## Contents

<b>1</b>	<b>Electrical ratings</b>	<b>2</b>
<b>2</b>	<b>Electrical characteristics</b>	<b>3</b>
<b>2.1</b>	Electrical characteristics (curves)	5
<b>3</b>	<b>Test circuits</b>	<b>10</b>
<b>4</b>	<b>Package mechanical data</b>	<b>11</b>
<b>4.1</b>	TO-247 package information	11
<b>4.2</b>	TO-247 long leads package information	13
<b>4.3</b>	TO-3P package information	15
<b>5</b>	<b>Ordering information</b>	<b>18</b>
	<b>Revision history</b>	<b>19</b>



**IMPORTANT NOTICE – PLEASE READ CAREFULLY**

STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice. Purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST's terms and conditions of sale in place at the time of order acknowledgement.

Purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of Purchasers' products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

ST and the ST logo are trademarks of ST. For additional information about ST trademarks, please refer to [www.st.com/trademarks](http://www.st.com/trademarks). All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2019 STMicroelectronics – All rights reserved



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

#### Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помошь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помошь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: [org@eplast1.ru](mailto:org@eplast1.ru)

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.