



H-TAP PART NUMBER	H-TAP & CLEAR COVER KIT PART NUMBER	CONDUCTOR SIZES CODE WIRE (FLEX CABLE)						WIRE STRIP LENGTH	CRIMP DIE COLOR CODE	PANDUIT INSTALLATION TOOLS		
		MAIN	TAP 1	TAP 2	TAP 3	CT-930 CT-930CH CT-940CH* CT-2940*	CT-920 CT-920CH CT920			CT-2931		
		CRIMP DIE NO./DIE INDEX NO. (# OF CRIMPS=1)										
HTCT8-8-1	HTWC8-8-1	8-14 (8-14)	8-14 (8-14)	--	--	19/32"	GREEN	CD-920H-8 PH8	CD-920H-8 PH8	CD-920H-8 PH8		
HTCT6-6-1	HTWC6-6-1	6-10 (6-10)	6-14 (6-14)	--	--	11/16"	ORANGE	CD-920H-6 PH6	CD-920H-6 PH6	CD-920H-6 PH6		
HTCT2-2-1	HTWC2-2-1	2-6 STR/SOL (2-8)	2-6 STR/SOL (2-8)	8-14 (8-14)	8-14 (8-14)	13/16"	BROWN	CD-920H-2 PH2	CD-920H-2 PH2	CD-920H-2 PH2		
HTCT250-8-1	HTWC250-8-1	250-2 (4/0-2)	8-14 (8-14)	8-14 (8-14)	--	1"	PURPLE	CD-930H-250 PH25	-	CD-930H-250 PH25		
HTCT250-2-1	HTWC250-2-1	250-2 (4/0-2)	2-6 STR/SOL (2-8)	8-14 (8-14)	--	1"	PURPLE	CD-930H-250 PH25	-	CD-930H-250 PH25		
HTCT250-250-1	HTWC250-250-1	250-2 (4/0-2)	250-2 (4/0-2)	--	--	1"	PURPLE	CD-930H-250 PH25	-	CD-930H-250 PH25		

*REQUIRES CD-940-DA ADAPTER

- NOTES:
1. MATERIAL: ANNEALED HIGH CONDUCTIVITY COPPER, TIN PLATED
 2. FOR USE WITH COPPER OR TIN PLATED COPPER CONDUCTORS ONLY.
 3. ACCOMODATES CODE CABLE, SOLID WIRE (WHERE SPECIFIED), FLEX LOCOMOTIVE (DLO), AND FLEX CLASSES G, H & I.
 4. ANY SINGLE TAP OR COMBINATION OF TAPS MAY BE USED IN CONJUNCTION WITH MAIN WIRE PORT.
 5. UL LISTED AND CSA CERTIFIED FOR APPLICATIONS UP TO 600V. TEMPERATURE RATING 90°C MAX.
 6. FLAME RETARDANT CABLE TIES (UL94 V-0 RATED NYLON WITH L.O.I.=28 MIN.) ARE PROVIDED WITH THE TAPS TO RETAIN THE WIRES IN POSITION FOR CRIMPING.
 7. TO ORDER H-TAP WITH INSULATING COVERS SEE PART NUMBERS IN TABLE.
 8. H-TAPS AND KITS ARE PACKAGED INDIVIDUALLY. (-1 PACKAGING CODE)



LISTED WIRE CONNECTOR



CERTIFIED

CAD FILENAME/LAYERS C41379_02

PANDUIT CORP TINLEY PARK, ILLINOIS

H-TAP SERIES COPPER COMPRESSION SMALL TAPS

UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: (.X) ± .XXX (.XX) ± .03 ANGLES ± .X

UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE GIVEN IN INCHES, THIRD ANGLE PROJECTION

REV	DATE	BY	CHK	DESCRIPTION	ECN #	PM	CUST
02	11/04	RGB		ADDED CT-2931 COLUMN TO THE TABLE			
01	05/03	RWK	RLS	REMOVED BLACK COVER KIT NUMBERS	10818	LSM	JAC
00	04/03	RWK	RLS	DRAWING RELEASED	10794	LSM	JAC

DRAWN BY	DATE	SCALE	DWG
RWK	4/21/03	NONE	B
CHK'D			
RLS			

SEE NOTES

DRAWING NO. C41379



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.