


# SLiC™ Fiber Aerial Closure 533 and 733

3M's SLiC fiber aerial closures are designed to enable service providers to cost-effectively deploy aerial fiber networks in the access network (FTTN, HFC, and FTTP). The free-breathing, weather-resistant, single-piece aerial closure can be very easily installed for new construction or maintenance applications.

The single-piece construction permits complete splice access after placement without the removal of the closure from the cable. These free-breathing closures are designed for strand-mount in-line, butt or taut sheath single or ribbon fiber applications.

The durable double-walled, blow-molded body resists cracking or breaking even in the harshest environments, providing the ultimate protection for fibers and splices.

The SLiC fiber closure portfolio consists of the 533 and 733 versions. The maximum splice capacity of the 533 closure is 144 single and 432 mass fusion splices. The 733 closure can accommodate up to 288 single and 864 mass fusion splices.



3M™ SLiC™ Fiber Aerial Closure 533 and 733

## Features and Benefits

|  |  |
|--|--|
| <b>One-piece construction</b>            | Easy installation and access to the cable splice without removing the closure or the terminal                        |
| <b>Double-walled molded construction</b> | Durable protection from bending and cracking in the most extreme environments  |
| <b>Spacious fiber management area</b>    | Slack storage basket provides separate area for routing, protecting, and “expressing” buffer tubes and ribbon fibers |
| <b>Multiple splicing applications</b>    | Accommodates inline and butt end span and midspan as well taut sheath applications                                   |
| <b>Quick-release latches</b>             | Easy installation and re-entry without the need for special tools  |
| <b>Interlocking Ends</b>                 | Permits the closure chamber to be extended to protect damaged sheath   |


3M SLiC Fiber Aerial Closures are tested to Bellcore GR-771-CORE Mechanical and Environmental Requirements for Free-Breathing Closures (FBCs). 3M SLiC fiber aerial closures are Rural Development (RUS) Listed.



|  | <b>533<br/>Fiber Aerial Closure - Taut Sheath</b>              | <b>533<br/>Fiber Aerial Closure</b>                            | <b>733<br/>Fiber Aerial Closure</b>                            |
|--|--|--|--|
| <b>Model #</b>                                   | SLFC-533-TS  | SLFC-533-SP  | SLFC-733-SP  |
| <b>Dimensions<br/>(LxHxW) inches</b>             | 33.0" x 5.0"   | 33.0" x 5.0"   | 33.0" x 7.0"   |
| <b>Cable Entry Ports &amp; Size<br/>(inches)</b> | 3 ports per end<br>Port 1: 0.6 - 2.2"<br>Port 2 & 3: 0.2 -1.4" | 3 ports per end<br>Port 1: 0.6 - 2.2"<br>Port 2 & 3: 0.2 -1.4" | 3 ports per end<br>Port 1: 0.6 - 2.2"<br>Port 2 & 3: 0.2 -1.4" |
| <b>Configuration</b>                             | Inline (taut sheath)   | Inline & butt (express)  | Inline & butt (express)  |
| <b>Taut-Sheath Application</b>                   | Yes; 26" sheath opening  | No   | No   |




3M™ SLiC Fiber Aerial Closure 533



3M™ Fiber Splice Organizer Tray 2527




3M™ SLiC Fiber Aerial Closure 733



3M™ Fiber Splice Organizer Tray 2523

# 3M™ SLiC™ Fiber Aerial Closure Configuration Guide



(Please see ordering information for specific products)

## Splice Tray Capacity

### SLiC 533

### SLiC 733

| Model # | Description   |   | Splice Capacity per Tray | Maximum # of trays per closure | Maximum Closure Splice Capacity | Maximum # of trays per closure | Maximum Closure Splice Capacity |
|---------|---|---|--------------------------|--------------------------------|---------------------------------|--------------------------------|---------------------------------|
| 2522    | Stackable hinged tray, fiber entry/exit at any corner of the tray | Single fusion (45 or 60 mm)             | 24                       | 3                              | 72                              | 6                              | 144                             |
|         |   | Single mechanical (3M™ Fibrlok™ Splice) | 12                       |                                | 36                              |                                | 72                              |
|         |   | Mass fusion                             | 120                      |                                | 360                             |                                | 720                             |
|         |   | Mass mechanical (Fibrlok splice)        | 96                       |                                | 288                             |                                | 576                             |
| 2523    | Stackable hinged tray, fiber entry/exit at any corner of the tray | Single fusion (45 or 60 mm)             | 48                       | 3                              | 144                             | 6                              | 288                             |
|         |   | Single mechanical (Fibrlok splice)      | 24                       |                                | 72                              |                                | 144                             |
|         |   | Mass fusion                             | 144                      |                                | 432                             |                                | 864                             |
|         |   | Mass mechanical (Fibrlok splice)        | 144                      |                                | 432                             |                                | 864                             |
| 2527    | Stackable tray, fiber entry/exit at any corner of the tray        | Single fusion (45 or 60 mm)             | 24                       | 3                              | 72                              | 6                              | 144                             |
|         |   | Single mechanical (Fibrlok splice)      | 12                       |                                | 36                              |                                | 72                              |
|         |   | Mass fusion                             | 144                      |                                | 432                             |                                | 864                             |
|         |   | Mass mechanical (Fibrlok splice)        | 72                       |                                | 216                             |                                | 432                             |

## 3M™ SLiC™ Terminal Closure Ordering Information

| Model #                      | Description   | 3M Stock Number |
|------------------------------|---|-----------------|
| <b>Closures</b>              |   |                 |
| SLFC-533-TS-1A               | 533 Fiber aerial closure, taut sheath, one 2527 tray    | 80611314420     |
| SLFC-533-SP-1A               | 533 Fiber aerial closure, one 2527 tray                 | 80611314404     |
| SLFC-733-SP-1A               | 733 Fiber aerial closure, one 2527 tray                 | 80611314446     |
| SLFC-533-SP-0X               | 533 Fiber aerial closure, no tray                       | 80611314412     |
| SLFC-733-SP-0X               | 733 Fiber aerial closure, no tray                       | 80611314453     |
| <b>Accessories</b>           |   |                 |
| 2527                         | Fiber optic splice organizer tray                       | 80611175581     |
| 2522                         | Fiber splice organizer tray small                       | 80610859904     |
| 2523                         | Fiber splice organizer tray large                       | 80610859912     |
| 2521-F                       | Fusion splice insert 2-pack                             | 80610859250     |
| 2521-FL                      | Fiblok splice inserts 2-pack                            | 80610859268     |
| SLiC-AC-HB2                  | Extended hanger bracket                                 | 80610846778     |
| SLiC/GATM-AC-HB3             | Extended hanger bracket                                 | 80611150220     |
| AC-HB4                       | Aerial offset hanger bracket, 4.0", set                 | 80611314701     |
| SLiC-ES/5TC/E SLiC Closures  | 5" Rubber end seal 3 port, Version E                    | 80611316540     |
| SLiC-ES/7TC/E SLiC Closures  | 7" Rubber end seal 3 port, Version E                    | 80611316532     |
| 4460-D/FO                    | 3M™ Scotchlok™ Shield Bond Connector Assembly 4460-D/FO | 80610844443     |
| 25T-BBE6                     | 1/2" X 25' bond braid w/eyelets 6"                      | 80610096150     |
| SLFC/SLFT-SPLICING-WS        | SLiC Fiber Splicing Workstation Kit                     | 80611321391     |
| SLFC/SLFT-SPLICING-WSCA      | SLiC Fiber Splicing Workstation Cleaver Arm             | 80611321896     |
| SLFC/SLFT-SPLICING-WS-STRAPS | Splicing Workstation Straps (Set of 2)                  | 80611321995     |
| SLFC/T-2-PORT                | SLiC 530/533/733 2-port 0.61" cable entry bracket       | 80611323447     |
| SLFC/T-6-PORT-FLAT           | SLiC Fiber 6-port flat drop/cable entry kit             | 80611317225     |
| <b>General Accessories</b>   |   |                 |
| 4414                         | Cable cleaning kit                                      | 80610582225     |
| 5025-KIT                     | Reflective lettering system kit                         | 80610133201     |
| 2529                         | Fiblok II Universal Optical Fiber Splice (250 X 900)    | 80610755896     |
| 2170                         | Fiber optic splice sleeve                               | 80610281380     |
| 2520                         | Fiber tube transport tubing (1 ft. length)              | 80610859276     |

3M, SLiC, Scotchlok and Fiblok are trademarks of 3M Company. All other trademarks used herein are the properties of their respective owners.

### Important Notice

All statements, technical information, and recommendations related to 3M's products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product which are not contained in 3M's current publications, or any contrary statements contained on your purchase order shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M.

### Warranty; Limited Remedy; Limited Liability.

This product will be free from defects in material and manufacture for a period of 12 months from the date of purchase. **3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. **Except where prohibited by law, 3M will not be liable for any loss or damage arising from this 3M product, whether indirect, special, incidental or consequential regardless of the legal theory asserted.**



### Communication Markets Division 3M Telecommunications

6801 River Place Blvd.  
Austin, TX 78726-9000  
800/426 8688  
Fax 800/626 0329  
www.3MTelecommunications.com

Please recycle. Printed in USA.  
© 3M 2007. All rights reserved.  
80-6113-1516-1



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.