


AX101792 Modular Connectors - Optimax Connector



For more Information
please call

1-800-Belden1



Description:

Optimax Field Installable Connector, SC, Single-mode (OS2), for 900 μ m tight buffered fiber

Usage (Overall)

Suitable Applications: Indoor termination of fiber cables: Patch panels, Communication outlets, Fiber-to-the-desk, Distribution frames, Direct termination to equipment, Fiber cable repair, Campus, Customer premise / Access network, Data Centers

Related Parts: Accessory kit for jacketed termination, Installation Tool kits, Breakout kits

Physical Characteristics (Connectivity)

Dimensions

Dimensions:

| Height (in.) | Width (in.) | Length (in.) |
|--------------|-------------|--------------|
| 0.362 | 0.394 | 1.752 |

Materials

Materials:

| Description | Type | Material | Color |
|----------------|------|----------|-------|
| Connector Body | N/A | Plastic | Blue |

Included Parts

Included Parts: 900 micron boot

Packaging

Packaging: Individually packaged in a plastic bag. Standard pack of 5 units, 500 units/box

Mechanical Characteristics (Connectivity)

Storage Temperature Range: -40°C To +70°C

Installation Temperature Range: -10°C To +60°C

Operating Temperature Range: -10°C To +60°C

Mechanical Specifications:

| Parameters | Specifications |
|---|--|
| Interconnection Compatibility | LC, SC and ST-Compatible connectors |
| Field Assembly Time | 1 minute for 900 μ m, 3 minutes for jacketed fiber |
| Durability (Multimode) | Less than 0.2 dB change, 500 cycles |
| Durability (Single-mode) | Less than 0.3 dB change, 500 cycles |
| Nominal Fiber OD | 125 μ m |
| Storage Temperature | -40°F to 149°F (-40°C to 65°C) |
| Operating Temperature | 32°F to 145°F (0°C to 60°C) |
| Tensile Load on jacketed fiber | 50 N (11.2 lbs. / 5.1 Kg) |
| Tensile Load on 900 micron tight buffered fiber | 6.7 N (1.5 lbs. / 0.68 Kg) |
| Ferrule | Ceramic |

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

EU Directive 2002/95/EC (RoHS): Yes

EU RoHS Compliance Date (mm/dd/yyyy): 07/01/2006

AX101792 Modular Connectors - Optimax Connector

| | |
|--------------------------------------|-------------|
| MII Order #39 (China RoHS): | EUP 50 |
| Telecommunications Standards: | TIA 568.C.3 |
| Safety Listing: | ACA |

Suitability

| | |
|------------------------------|--------------|
| Suitability - Indoor: | Yes - Indoor |
|------------------------------|--------------|

Transmission Characteristics (Connectivity)

Transmission Specifications:

| Parameters | Specifications |
|--|---------------------|
| Insertion Loss (Multimode and Single-mode) | 0.3 dB (typical) |
| Reflectance (Multimode) | -30 dB (typical) |
| Reflectance (Single-mode) | -40 dB (guaranteed) |

Notes (Overall)

Notes: Please see Installation Instruction Manual AX103148 (included in Installation Tool Kits, reference to NP271)

Notes (Cont'd.): For Optimax termination on jacketed fibers, please use the appropriate Accessory Kit LC - AX101984 SC - AX101794 ST - AX101793

Product Family

Part Number List:

| Description | Belden Part Number |
|---------------------------------------|--------------------|
| LC 62.5 μ m, Multimode | AX101981 |
| LC 50 μ m, Multimode | AX101982 |
| LC Single-mode | AX101983 |
| SC 62.5 μ m, Multimode | AX100029 |
| SC 50 μ m, Multimode | AX101077 |
| SC Single-mode | AX101792 |
| ST Compatible 62.5 μ m, Multimode | A0408835 |
| ST Compatible 50 μ m, Multimode | AX101075 |
| ST Compatible Single-mode | AX101791 |

Put Ups and Colors:

| Item # | Putup | Ship Weight | Color | Notes | Item Desc |
|----------|-------|-------------|-------|-------|-----------------------|
| AX101792 | 1 EA | 0.007 LB | | | OPTIMAX SC SINGLEMODE |

Revision Number: 0 Revision Date: 12-03-2010

© 2012 Belden, Inc.
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.