


## Glass Passivated Rectifiers

### FEATURES

- Glass passivated chip junction
- High current capability, Low VF
- High reliability
- High surge current capability
- Low power loss
- Compliant to RoHS Directive 2011/65/EU and in accordance to WEEE 2002/96/EC
- Halogen-free according to IEC 61249-2-21 definition



R-6



### MECHANICAL DATA

**Case:** R-6

Molding compound, UL flammability classification rating 94V-0

Base P/N with suffix "G" on packing code - green compound (halogen-free)

Base P/N with prefix "H" on packing code - AEC-Q101 qualified

**Terminal:** Matte tin plated leads, solderable per JESD22-B102

Meet JESD 201 class 1A whisker test

with prefix "H" on packing code meet JESD 201 class 2 whisker test

**Weight:** 1.65 g (approximately)

| MAXIMUM RATINGS AND ELECTRICAL CHARACTERSTICS (T <sub>A</sub> =25°C unless otherwise noted) |                    |           |           |           |           |           |           |            |      |
|---------------------------------------------------------------------------------------------|--------------------|-----------|-----------|-----------|-----------|-----------|-----------|------------|------|
| PARAMETER                                                                                   | SYMBOL             | 6A<br>05G | 6A<br>10G | 6A<br>20G | 6A<br>40G | 6A<br>60G | 6A<br>80G | 6A<br>100G | UNIT |
| Maximum repetitive peak reverse voltage                                                     | V <sub>RRM</sub>   | 50        | 100       | 200       | 400       | 600       | 800       | 1000       | V    |
| Maximum RMS voltage                                                                         | V <sub>RMS</sub>   | 35        | 70        | 140       | 280       | 420       | 560       | 700        | V    |
| Maximum DC blocking voltage                                                                 | V <sub>DC</sub>    | 50        | 100       | 200       | 400       | 600       | 800       | 1000       | V    |
| Maximum average forward rectified current                                                   | I <sub>F(AV)</sub> | 6         |           |           |           |           |           |            | A    |
| Peak forward surge current, 8.3 ms single half sine-wave superimposed on rated load         | I <sub>FSM</sub>   | 250       |           |           |           |           |           |            | A    |
| Maximum instantaneous forward voltage (Note 1)<br>@ 6 A                                     | V <sub>F</sub>     | 1.1       |           | 1.0       |           |           |           | V          |      |
| Maximum reverse current @ rated VR    T <sub>J</sub> =25 °C<br>                             |                    |           |           |           |           |           |           |            |      |

Note 1: Pulse Test with PW=300μs, 1% Duty Cycle

Note 2: Measured at 1 MHz and Applied Reverse Voltage of 4.0V D.C.

| ORDERING INFORMATION |                    |              |                     |         |                        |
|----------------------|--------------------|--------------|---------------------|---------|------------------------|
| PART NO.             | AEC-Q101 QUALIFIED | PACKING CODE | GREEN COMPOUND CODE | PACKAGE | PACKING                |
| 6A0xG<br>(Note 1)    | Prefix "H"         | A0           | Suffix "G"          | R-6     | 700 / Ammo box         |
|                      |                    | R0           |                     | R-6     | 1,000 / 13" Paper reel |
|                      |                    | B0           |                     | R-6     | 400 / Bulk packing     |

Note 1: "x" defines voltage from 50V (6A05G) to 1000V (6A100G)

| EXAMPLE       |          |                    |              |                     |                    |
|---------------|----------|--------------------|--------------|---------------------|--------------------|
| PREFERRED P/N | PART NO. | AEC-Q101 QUALIFIED | PACKING CODE | GREEN COMPOUND CODE | DESCRIPTION        |
| 6A05G A0      | 6A05G    |                    | A0           |                     |                    |
| 6A05G A0G     | 6A05G    |                    | A0           | G                   | Green compound     |
| 6A05GHA0      | 6A05G    | H                  | A0           |                     | AEC-Q101 qualified |

## RATINGS AND CHARACTERISTICS CURVES

(TA=25°C unless otherwise noted)

FIG.1- MAXMUM FORWARD CURRENT DERATING CURVE




FIG. 2- TYPICAL REVERSE CHARACTERISTICS




FIG. 3- MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT



FIG. 4- TYPICAL FORWARD CHARACTERISTICS






FIG. 5- TYPICAL JUNCTION CAPACITANCE



PACKAGE OUTLINE DIMENSIONS



| DIM. | Unit (mm) |      | Unit (inch) |       |
|------|-----------|------|-------------|-------|
|      | Min       | Max  | Min         | Max   |
| A    | 6.80      | 7.20 | 0.268       | 0.283 |
| B    | 1.20      | 1.30 | 0.047       | 0.051 |
| C    | 25.40     | -    | 1.000       | -     |
| D    | 8.60      | 9.10 | 0.339       | 0.358 |
| E    | 25.40     | -    | 1.000       | -     |

MARKING DIAGRAM



P/N =

Specific Device Code

G =

Green Compound

YWW =

Date Code

F =

Factory Code

### **Notice**

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf, assumes no responsibility or liability for any errors inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify TSC for any damages resulting from such improper use or sale.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.