Preferred Connector Products

Technology to Inspire Innovation

JAE



JAE Electronics, Inc.

For Additional Information Visit www.jae-connector.com

Japan Aviation Electronics Industry, Ltd. (JAE) is an international manufacturer and supplier of electronic components and systems. For over four decades, JAE has provided the electronics industry with solutions to complex design requirements. Since its founding, the Company has strived to contribute to society through market-driven, technology-based global business operations under the philosophy: "Technology to Inspire Innovation."

With worldwide and world-class manufacturing certified to ISO 9001 and QS 9000, JAE has made the commitment to meet the global requirements of our customer. In addition to a network of state of the art manufacturing facilities, JAE has technical service offices located around the world, staffed with experts in connector design and application.

This catalog contains a select overview of JAE Connector Products. For in-depth information on our complete product line, and information on new developments, visit JAE's online catalog at www.jae-connector.com.

Innovative design, quality oriented manufacturing, commitment to our customers and sensitivity to the environment assures JAE's leadership position in the 21st century.

Table of Contents

Product Series	Contact Spacing	Pages

Sockets/Memory Products

PCMCIA

JC22 — 1.27mm (.050") — 5

COMPACT FLASH

JC26C2 — 1.27mm (.050") — 6 - 7
JC26E — 1.27mm (.050") — 8
JC26F — 1.27mm (.050") — 9

PCI EXPRESS MINI CARD

MM60 — 0.8mm (.031") — 10

EXPRESSCARD

PX10/11 — 1.0mm (.039") — 11 - 12
PX20/22 — 1.0mm (.039") / 0.635mm (.025") — 13 -14

SMART/SIM CARD

SF2 — 2.54mm (.100") — 15
SF3 — 2.54mm (.100") — 16
SF6 — 2.54mm (.100") — 17
SF7 — 2.54mm (.100") — 18
SF7 (Slim) — 2.54mm (.100") — 19
SF9 — 2.54mm (.100") — 20

SECURE DIGITAL CARD

SG5 — 2.50mm (.098") — 21

MINI SECURE DIGITAL CARD (SD)

ST4 — 1.1mm (.043") — 22
SC1 — 2.50mm (.098") — 23

MICRO SD/TRANSFLASH™

ST1 — 1.1mm (.043") — 24
ST2 — 1.1mm (.043") — 25

Board-to-Board Connector Products

BOARD-TO-BOARD

AA03 — 0.40mm (.020") — 26
WA6 — 0.40mm (.020") — 27
WH1 — 0.40mm (.020") — 28
AA01A — 0.50mm (.020") — 29
IL-312 — 0.50mm (.020") — 30
WR — 0.50mm (.020") — 31 - 32
WB3 — 0.50mm (.020 ") — 33
IL-WX — 0.80mm (.031") — 34
KX14/15 — 0.80mm (.031") — 35 - 36
PM1 — 0.80mm (.031") — 37
WM1 — 1.00mm (.039) — 38
WM2 — 1.00mm (.039) — 39
TX24/TX25 — 1.27mm (.050") — 40

Table of Contents

Product Series	Contact Spacing	Pages

Board-to-Board Connector Products

WIRE-TO-BOARD
PCB-TO-FPC/FFC

FB3	0.30mm (.012")	41
FB5	0.30mm (.012")	42
FB6	0.30mm (.012")	43
FF02	0.30mm (.012")	44
FF02S	0.30mm (.012")	45
FB8	0.30mm (.012")	46
FA5	0.50mm (.020")	47
FF03	0.50mm (.020")	48
IL-FPR	0.50mm (.020")	49

PCB-TO-CABLE/FPC

FI-J	0.40mm (.016")	50 - 51
FI-R	0.50mm (.020")	52 - 53
FI-X	1.00mm (.039")	54 - 55
FI	1.25mm (.049")	56 - 58

PCB-TO-CABLE

DX2/3	0.80mm (.031")	59
FI-E	1.00mm (.039")	60 - 61
CN10		62 - 63
CV10		64
IL-Z	1.25mm (.049")	65 - 66
IL-S	2.00mm (.079")	67 - 68
LY	2.00mm (.079")	69
KD10/20	2.00mm (.079")	70
IL-G	2.50mm (.098")	71

Input/Output Connector Products

PCB-TO-CABLE

DD1	0.50mm (.020")	72 - 73
DD2	0.50mm (.020")	74 - 75
DG1	0.50mm (.020")	76
RA1	0.50mm (.020")	77
RC1	0.50mm (.020")	78
DA1	0.60mm (.024")	79
DE1	1.27mm (.050")	80
TX20A	1.27mm (.050")	81
DV2	1.905mm (.075")	82 - 84

CIRCULAR

JN1		85 - 86
JN2		87 - 88
JB5		89

Table of Contents

Product Series	*Contact Spacing*	*Pages*

Input/Output Connector Products

CIRCULAR

JL04V ..... 90 - 91
JL05 ..... 92 - 93
JB1 ..... 94 - 95
SRCN ..... 96 - 97
N/MS ..... 98 - 99

Fiber Optic Products

FO-FC 100
FO-EX 101

Automotive Connector Products

PCB-TO-CABLE

MX34 ..... 1.1mm (.043") 102
MX7 ..... 2.30mm (.091") 103
IL-AG7 ..... 2.50mm (.098") 104
MX17 ..... 2.50mm (.098") ..... 105 - 106
MX23A ..... 2.50mm (.098") ..... 107 - 108
MX10 ..... 2.50mm (.098") 109
MX5 ..... 3.00mm (.118") 110

PCB-TO-CABLE/CABLE-TO-CABLE

IL-AG5 ..... 2.50mm (.098") 111
IL-AG6 ..... 2.50mm (.098") 112
MX9 ..... 3.50mm (.138") 113
MX25 ..... 6.7mm (2.64") 114
MX36 ..... 2.50mm (.098") 115

CABLE-TO-CABLE

IL-AG9 ..... 2.50mm (.098") ..... 116 - 118
MX19 ..... 2.50mm (.098") 119

- All JAE connector products shown in this catalog are lead free.
- We reserve the right to modify designs in order to improve quality, keep pace with technological advancements or meet particular requirements in production.
- Products shown in this catalog are made for the applications specified. However, if the above-mentioned products are to be used in aerospace devices, marine cable-connection devices, atomic power control systems, medical equipment for life-support systems, or any other specific application requiring extremely high reliability, please contact JAE for further information. Recommended Applications: Computers, Office Machines, Measuring Devices, Telecommunications Devices (Terminals, Mobile Devices) AV Devices, Household Applications, FA Devices, etc.
- Refer to end of catalog for alphabetical index of products.

JAE

JC26C2 SERIES CONNECTORS

1.27mm (.050") Contact Spacing, Connectors for Compact Flash Type I/II

• • • • • • • • • • • • • •

JC26 series is a frame connector with card retention mechanism for Compact Flash. It is offered in a low-profile design or with a 1.6mm (.063") stand-off to allow for components to be mounted under the frame. The connector is available for automatic mounting. Applications include digital still cameras, handheld PCs, and other portable devices.

FEATURES

- Slot mechanism compliant with CFA (Compact Flash Association) Type I/II Card.
- Board mounting dimensions are the same for JC26A, JC26C, and JC26C2 making easy changes between series easy
- Designed with spring-loaded mechanism to prevent card from coming out
- Compared with existing JC26 series the JC26C2 series has an integrated frame structure allowing for a tighter tolerance and preventing misinsertion
- Three types of eject buttons are available: fixed, bendable, and double-push. Button location option: right or left
- Standard or reverse mounting with stand-off option
- Low-profile: 5.8mm height off board
- 1.6mm stand-off option: 7.4 mm height on board

Connector Profile (Ref.)





GENERAL SPECIFICATIONS

Number of Contacts	50
Contact Spacing	1.27mm (0.050"), 2 rows
Current Rating	0.5 Amp per contact
Dielectric Withstanding Voltage	500 VAC r.m.s. (for one minute)
Insulation Resistance	1000 megohms min.
Contact Resistance	40 milliohms max.
Operating Temperature	-20°C to +60°C
Contact Life Durability	10,000 Cycles

MATERIALS AND FINISHES

•Frame	
Description	Materials/Finishes
Spring	Stainless Steel
Lock	Glass Filled PBT
Button	Glass Filled PBT
Earth Lug	Copper Alloy
Lever	Stainless Steel
Plate	Stainless Steel
Cover	Stainless Steel
Frame	Glass filled PBT
•Base	
Components	Materials/Finishes
Insulator	Glass filled PPS (UL95V-0)
Contact	Copper Alloy Connecting Area: Gold Flash over Nickel-Lead SMT: Tin-Lead plating over Nickel
Hold Down	Phosphorous bronze/Tin-Lead plating over Nickel

1.27mm (.050") Contact Spacing, Connectors for Compact Flash Type I/II

JC26A
ORDERING INFORMATION

• Base

JC26A B B * E

Series
Base
Positioning Boss
B – With boss
N – Without Boss
Stand-off code
None – 0mm
16 – 1.6mm (.079")
E - Lead Free Version

JC26C2
ORDERING INFORMATION

• Frame (Fixed/Bendable Eject Button)

JC26C2 F S R * E

Series
Frame
Fixed/Bendable button
Mounting Type
S – Standard
R – Reverse
Button Type
R – Right bendable button
L – Left bendable button
M – Right fixed button
H – Left fixed button
Stand-off code
None – 0mm
16 – 1.6mm (.063")
Lead Free Version

• Frame (Double Push Button)

JC26C2 D S R * E

Series
Frame
Double Push Button
Mounting Type
S – Standard
R – Reverse
Button Type[1]
R – Right button (long)
L – Left button (long)
M – Right button (short)
H – Left button (short)
Stand-off code
None – 0mm
16 – 1.6mm (.063")
Lead Free Version

Note: Total length of button (from bottom side of card to top of button). Long: 37.9mm, Short 36.9mm

Dimensions in mm (inches).

Technology to Inspire Innovation

JAE

"Building Technologies to Connect Your World"

Printed in the U.S.A. 10M807TA SF3

Japan Aviation Electronics Industry, Limited
1-19, Aobadai 3-chome, Meguro-ku
Tokyo 153-8539, Japan
Telephone: 03-3780-2736
Fax: 03-3780-2883

JAE Electronics, Inc.
142 Technology Drive, Suite 100
Irvine, California 92618-2430, U.S.A.
Telephone: 949-753-2600
Fax: 949-753-2699
800-523-7278 Toll free in the U.S.A.

JAE Europe
Coliseum Business Centre
Riverside Way, Camberley
Surrey, GU15 3YL, England
Telephone: 44-1276-404000
Fax: 44-1276-404010

JAE Taiwan, Ltd.
4F-1, No. 88, Chung Hsiao E. Rd.
Sec. 2, Taipei, Taiwan, R.O.C.
Telephone: 886-2-2396-7676
Fax: 886-2-2392-5929

JAE Hong Kong, Ltd.
Suites 1407-11, 14/F, Tower 2, The Gateway,
25 Canton Road, Tsimshatsui, Kowloon, Hong Kong
Telephone: 852-2723-7782
Fax: 852-2723-9028

JAE Korea, Inc.
1602, Korea City Air Tower
159-9 Samsung-Dong, Kangnam-ku
Seoul, 135-973, Korea
Telephone: 82-2-551-8959
Fax: 82-2-551-8958

JAE Philippines, Inc.
PEZA Zone, Gateway Business Park, Javalera
General Trias, 4107 Cavite, Philippines
Telephone: 63-46-433-0285
Fax: 63-46-433-0287

JAE Singapore Pte., Ltd.
33 Tannery Lane, #02-01 Hoesteel
Industrial Building
Singapore 347789
Telephone: 65-6748-1332
Fax: 65-6748-2920

JAE Shanghai Co., Ltd.
RM 1407, Shanghai Mart 2299 Yanan Rd.
West Shanghai 200336 P.R.C.
Telephone: 86-21-6236-0322
Fax: 86-21-6236-1292

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

JAE Electronics:

JC26C2-FSH16E JC26C2-DRR16E JC26C2-DSL16E JC26C2-FSLE JC26C2-FSM16E JC26C2-FSME JC26C2-FSNE JC26C2-DSM16E JC26A-BN16E

Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits,General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)
Факс: 8 (812) 320-02-42
Электронная почта: org@eplast1.ru
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.