



Ideal for Class 2 applications including petrochemical, factory-automation and commercial-vehicle equipment, Brad® Micro-Change® M12 Harsh-Duty Receptacles offer a sealed connection with superior EMI/RFI shielding in high-vibration systems

Brad® Micro-Change® M12 Harsh-Duty Receptacles are designed to withstand harsh commercial and industrial environments. Their superior design ensures a reliable connection for control elements in commercial vehicle equipment, factory automation equipment and petrochemical markets. Receptacles are tooled for network connectivity in both Ethernet and Controller-Area Network (CAN bus) protocols, as well as passive applications such as discreet and analog sensor applications.


Receptacles are available in 4-pole D-code and 5-pole A-code configurations; additional pole count and code variations can be developed upon request. Heavy-duty diecast construction provides 360° EMI/RFI shielding in the rugged receptacle while keeping costs to a minimum.

Brad Micro-Change M12 Harsh-Duty Receptacles are designed to interface with numerous Molex cordsets, including Series 130048, 120108, 130027 and 130028.

For more information on Molex's broad portfolio of industrial and power products for harsh-duty applications, visit: www.molex.com/product/bradproducts.html

Brad® Micro-Change® M12 Harsh-Duty Receptacles

130299 Harsh-Duty
Receptacles



- A. 4-pole right-angle receptacle with coupling nut (Series 130299)
- B. 4-pole right-angle receptacle with O-ring (Series 130299)
- C. 4-pole right-angle receptacle, back view (Series 130299)
- D. Coupling nut (130299)

Features and Benefits

Robust housing with heavy-duty die-cast construction and IEC 61076-2-101 compliant design	Provides superior Electro Magnetic Interference (EMI) and Radio Frequency Interference (RFI) protection. Meets CE industry requirements
Waterproof sealed and IP67, IP69K compliant	Able to withstand high-pressure wash down
Rated to 250V AC/DC, up to 4.0A	Ideal for Class 2 power and network circuit applications
Receptacle designed with a vibration-resistant mounting nut	Withstands vibration for chassis applications
Tooled for Ethernet and Controller-Area Network (CAN bus) protocols and passive applications including discreet and analog sensors	Meet high-speed data bus requirements
Receptacle pull-strength of 1.5N initial-mate torque resistance and 34kg intermittent side-load withstand rating	Durable for harsh environments, exceeding twice the strength of standard M12 receptacles. Reduces chance of pin bending during mating
Receptacles available in right-angle and straight configurations and 5-Pole A-, 4-pole D-code keyway options	Provides a full range of options for design flexibility. Keyed for poka-yoke manufacturing processes (end-of-line rework)



Specifications

Reference Information

Packaging: 10 pack sleeve

RoHS: Yes

D-Code receptacle:

UL File No. E200650 Pending

A-Code receptacle:

UL File No. E152210 Pending

CSA File No. LR6837 Pending

Electrical

Voltage (max.): 250V AC

Current (max.): 4.0A

Contact Resistance: <10 milliohms

Dielectric Withstanding Voltage:

1500V AC

Insulation Resistance:


20 Megohms min.

Mechanical


Durability: 500 cycles



Left-to-right: Brad® Micro-Change® 4-pole straight receptacle, Micro-Change® 4-pole cordset



Robust shell isolates PCB poles; Right-Angle Receptacle for Ethernet Applications



Offset keying option example



4-pole straight receptacle with O-Ring

Applications

Commercial Vehicle Transportation

- Controllers and telematics
- Sensors, navigation devices
- Construction, agriculture, forestry machinery

Industrial Machinery

- Packaging, robot, welding, material handling device manufacturers

Harsh Commercial Products

- Outdoor displays, signs
- Carwashes

Marine

- Boats
- Large vessels

Military/Aerospace

- Tactical vehicles
- C4ISR systems
- Military shelters



Truck



GPS



Harvesting Machinery

Ordering Information

Order No.	Poles	Code	Orientation
130299-0100	4	D	Right Angle
130299-0200			Straight
130299-0300	5	A	Right Angle
130299-0400			Straight

www.molex.com/link/m12.html



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.