


HIGH PERFORMANCE

conga-QA3




- 3rd Gen. Intel® Atom™ / Celeron® processors
- High resolution Intel® Gen. 7 graphics
- Temperature range up to -40°C .. +85°



| | | | | |
|-----------------------------|--|---------------------------|-----------------------|----------|
| Formfactor | Qseven Form Factor Rev. 2.0 compliant 70x70 mm | | | |
| CPU | Intel® Atom™ E3845 | 1.91 GHz QuadCore | L2 cache 2MB | 10W TDP |
| | Intel® Atom™ E3827 | 1.75 GHz Dual Core | L2 cache 1MB | 8W TDP |
| | Intel® Atom™ E3826 | 1.46 GHz Dual Core | L2 cache 1MB | 7W TDP |
| | Intel® Atom™ E3825 | 1.33 GHz Dual Core | L2 cache 1MB | 6W TDP |
| | Intel® Atom™ E3815 | 1.46 GHz Single Core | L2 cache 512kB | 5W TDP |
| | Intel® Atom™ E3805 | 1.33 GHz Dual Core | L2 cache 1MB | 3W TDP |
| | Intel® Celeron J1900 | 2.0 GHz Quad Core | L2 cache 2MB | 10W TDP |
| | Intel® Celeron N2930 | 1.83 GHz Quad Core | L2 cache 2MB | 7.5W TDP |
| | Intel® Celeron N2807 | 1.58 GHz Dual Core | L2 cache 1MB | 4.5W TDP |
| DRAM | Dual Channel up to 8GB onboard DDR3L with 1333 MT/s | | | |
| Chipset | Integrated in SoC | | | |
| Ethernet | Intel® I210 Gigabit Ethernet controller | | | |
| I/O Interfaces | 6x USB 2.0 or 1x USB 3.0 and 5x USB 2.0 2x SATA 1x SDIO 3x PCIe I ² C Bus LPC bus 1x SPI | | | |
| Mass Storage | eMMC 5.0 onboard flash up to 64 GByte (optional only for Intel® Atom™) | | | |
| Sound | Intel® High Definition Audio (Intel® HD Audio) | | | |
| Graphics | Intel® HD Graphics with support for DirectX11 OpenGL 3.0 OpenCL 1.2 OpenGLES 2.0 full HW acceleration for decode/encode of MPEG2, H.264 MVC and dual simultaneous display support | | | |
| LVDS | Dual channel LVDS transmitter support for flat panels with 2x24 bit data mapping up to a resolution of 1920x1200@60Hz | | | |
| DisplayPort Interface (DDI) | DisplayPort 1.1 up to 2560x1600 or HDMI 1.4a up to 1920x1200 | | | |
| congatec Board controller | Multi Stage Watchdog non-volatile User Data Storage Manufacturing and Board Information Board Statistics I ² C bus (fast mode 400 kHz multi-master) Power Loss Control | | | |
| Embedded BIOS Features | AMI Aptio® UEFI 2.x firmware; 8 MByte serial SPI with congatec Embedded BIOS features (OEM Logo OEM CMOS Defaults LD Control Display Auto Detection Backlight Control Flash Update) | | | |
| Power Management | ACPI 5.0 compliant Smart Battery Management | | | |
| Operating Systems | Microsoft® Windows 8 Microsoft® Windows 8 embedded Microsoft® Windows 7 Microsoft® Windows 7 embedded compact Linux | | | |
| Power Consumption | Typ. application 4.5W...12W | | | |
| Temperature | Commercial : | Operating: 0 to +60°C | Storage: -20 to +80°C | |
| | Industrial : | Operating: -40 to +85°C | Storage: -45 to +85°C | |
| Humidity | Operating: | 10 to 90% r. H. non cond. | | |
| | Storage: | 5 to 95% r. H. non cond. | | |
| Size | 70 x 70 mm (2¾" x 2¾") | | | |

conga-QA3 | Block diagram



conga-QA3 | Order Information

| Article | PN | Description |
|----------------------------|--------|--|
| conga-QA3/E3845-2G eMMC4 | 015100 | Intel® Atom™ E3845 quad core processor, 1.91 GHz, 2MB L2 cache, 2GB 1333MT/s DDR3L onboard dual channel memory and 4GB eMMC onboard flash |
| conga-QA3/E3827-2G eMMC4 | 015101 | Intel® Atom™ E3827 dual core processor, 1.75 GHz, 1MB L2 cache, 2GB 1333MT/s DDR3L onboard dual channel memory and 4GB eMMC onboard flash |
| conga-QA3/E3826-2G eMMC4 | 015102 | Intel® Atom™ E3826 dual core processor, 1.46 GHz, 1MB L2 cache, 2GB 1066MT/s DDR3L onboard dual channel memory and 4GB eMMC onboard flash |
| conga-QA3/E3825-2G eMMC4 | 015103 | Intel® Atom™ E3825 dual core processor, 1.33 GHz, 1MB L2 cache, 2GB 1066MT/s DDR3L onboard single channel memory and 4GB eMMC onboard flash |
| conga-QA3/E3815-2G eMMC4 | 015104 | Intel® Atom™ E3815 single core processor, 1.46GHz, 512kB L2 cache, 2GB 1066MT/s DDR3L onboard single channel memory and 4GB eMMC onboard flash |
| conga-QA3/E3845-4G eMMC8 | 015105 | Intel® Atom™ E3845 quad core processor, 1.91GHz, 2MB L2 cache, 4GB 1333MT/s DDR3L onboard dual channel memory and 8GB eMMC onboard flash |
| conga-QA3/E3815-1G | 015106 | Intel® Atom™ E3815 single core processor, 1.46GHz, 512kB L2 cache, 1GB 1066MT/s DDR3L onboard single channel memory |
| conga-QA3/E3845-4G | 015107 | Intel® Atom™ E3845 quad core processor with 1.91GHz, 2MB L2 cache, 4GB 1333MT/s DDR3L onboard dual channel memory. No onboard eMMC |
| conga-QA3/E3827-4G | 015108 | Intel® Atom™ E3827 dual core processor with 1.75GHz, 1MB L2 cache, 4GB 1333MT/s DDR3L onboard dual channel memory. No onboard eMMC |
| conga-QA3/E3845-2G | 015109 | Intel® Atom™ E3845 quad core processor with 1.91GHz, 2MB L2 cache, 2GB 1333MT/s DDR3L onboard memory. No onboard eMMC. |
| conga-QA3/E3805-2G eMMC4 | 015130 | Intel® Atom™ E3805 dual core processor, 1.33GHz, 1MB L2 cache, 2GB 1067MT/s DDR3L onboard single channel memory and 4GB eMMC onboard flash |
| conga-QA3/i-E3845-2G eMMC4 | 015120 | Intel® Atom™ E3845 quad core processor, 1.91GHz, 2MB L2 cache, 2GB 1333MT/s DDR3L onboard dual channel memory and 4GB eMMC onboard flash Industrial grade temperature range from -40°C to 85°C |
| conga-QA3/i-E3827-2G eMMC4 | 015121 | Intel® Atom™ E3827 dual core processor, 1.75GHz, 1MB L2 cache, 2GB 1333MT/s DDR3L onboard dual channel memory and 4GB eMMC onboard flash Industrial grade temperature range from -40°C to 85°C |
| conga-QA3/i-E3825-2G eMMC4 | 015123 | Intel® Atom™ E3825 dual core processor, 1.33GHz, 1MB L2 cache, 2GB 1066MT/s DDR3L onboard single channel memory and 4GB eMMC onboard flash Industrial grade temperature range from -40°C to 85°C |
| conga-QA3/i-E3815-2G eMMC4 | 015124 | Intel® Atom™ E3815 single core processor, 1.46GHz, 512kB L2 cache, 2GB 1066MT/s DDR3L onboard single channel memory and 4GB eMMC onboard flash Industrial grade temperature range from -40°C to 85°C |
| conga-QA3/i-E3845-4G eMMC8 | 015125 | Intel® Atom™ E3845 quad core processor, 1.91GHz, 2MB L2 cache, 4GB 1333MT/s DDR3L onboard dual channel memory and 8GB eMMC onboard flash Industrial grade temperature range from -40°C to 85°C |
| conga-QA3/i-E3805-2G eMMC4 | 015126 | Intel® Atom™ E3805 dual core processor, 1.33GHz, 1MB L2 cache, 2GB 1067MT/s DDR3L onboard single channel memory and 4GB eMMC onboard flash Industrial grade temperature range from -40°C to 85°C |
| conga-QA3/J1900-2G | 015111 | Intel® Celeron J1900 quad core processor, 2.0 GHz, 2MB L2 cache, 2GB 1333MT/s DDR3L onboard dual channel memory. |
| conga-QA3/N2930-2G | 015112 | Intel® Celeron® N2930 quad core processor, 1.83GHz up to 2.16GHz, 2MB L2 cache and 2GB 1333MT/s DDR3L onboard dual channel memory. Low power consumption with 7.5W TD |
| conga-QA3/N2807-2G | 015113 | Intel® Celeron® N2807 dual core processor, 1.58GHz up to 2.16GHz, 2MB L2 cache and 2GB 1333MT/s DDR3L onboard single channel memory. Ultra-low power consumption with 4.5W TDP |
| conga-QA3/HSP-T | 015190 | Standard heatspreader for Qseven module conga-QA3. Standoff with 2.5mm thread |
| conga-QA3/HSP-B | 015191 | Standard heatspreader for Qseven module conga-QA3. All standoffs are with 2.7mm bore hole |
| conga-QA3/CSP-T | 015192 | Passive cooling solution for Qseven module conga-QA3. All standoffs are M2.5mm thread. |
| conga-QA3/CSP-B | 015193 | Passive cooling solution for Qseven module conga-QG. All standoffs are with 2.7mm bore hole. |

Accessories

| | | |
|--------------------------------|----------|--|
| conga-QEVAL 2.0 | 007003 | Evaluation platform for Qseven 2.0 |
| conga-QKIT | 077455 | Starterkit for Qseven including conga-QEVAL, conga-LDVI/EPI, conga-FPA2, Dual DVI-D ADD2 Card, ATX power supply... |
| conga-HDMI/DisplayPort adapter | 500014 | The conga-HDMI/DisplayPort adapter is used to convert the graphic ports Port-B, Port-C and Port-D of to the HDMI or DisplayPort interface. |
| conga-Qseven/SBM3 | 025485 | Mobility Starter Kit |
| conga-MCB/Qseven Cable Kit | 14000041 | Complete cable kit for Qseven mini carrier board |
| Qseven MXM connector Foxconn | 400017 | Socket for Qseven Carrier Boards. 10pcs package. Foxconn standard type, SMT, lead free, 230 positions, 0.50mm pitch, 7.8mm height. |
| Qseven MXM Connector Aces | 400018 | Socket for Qseven Carrier Boards. 10pcs package. ACES standard type, SMT, lead free, 230 positions, 0.50mm pitch, 7.8mm height. |
| conga-LDVI/EPI | 011115 | LVDS to DVI converter board for digital flat panels with onboard EEPROM |

© 2015 congatec AG. All rights reserved.

All data is for information purposes only. Although all the information contained within this document is carefully checked, no guarantee of correctness is implied or expressed. Product names, logos, brands, and other trademarks featured or referred are the property of their respective trademark holders. These trademark holders are not affiliated with congatec AG. Rev. Mai 19, 2015 MR



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.