



**Product:** [83554](#) 

Electronic, 4 C #22 Str TC, FEP Ins, OS+TC Brd, FEP Jkt, CMP

 [Request Sample](#)

## Product Description

High Temperature Electronic, 4 Conductor 22AWG (7x30) Tinned Copper, FEP Insulation, Overall Beldfoil®+Tinned Copper Braid(85%) Shield, FEP Outer Jacket, CMP

## Technical Specifications

### Product Overview

|                        |                                                                                                                                                                                                                                       |
|------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Suitable Applications: | extreme high/low temperature environments; chemical resistant; outdoor and burial applications; low voltage analog signals (4-20ma, 0-10v, ...); low voltage control (24v, ...); line level audio; voice communications; panel wiring |
|------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

### Physical Characteristics (Overall)

#### Conductor

| AWG | Stranding | Material           | No. of Conductors |
|-----|-----------|--------------------|-------------------|
| 22  | 7x30      | TC - Tinned Copper | 4                 |

|                  |   |
|------------------|---|
| Conductor Count: | 4 |
|------------------|---|

#### Insulation

| Material                             | Nominal Wall Thickness |
|--------------------------------------|------------------------|
| FEP - Fluorinated Ethylene Propylene | 0.0065 in              |

#### Color Chart

| Number | Color |
|--------|-------|
| 1      | Black |
| 2      | White |
| 3      | Red   |
| 4      | Green |

#### Outer Shield Material

| Type  | Layer | Material           | Material Trade Name | Coverage [%] |
|-------|-------|--------------------|---------------------|--------------|
| Tape  | 1     | Alum / Poly        | Beldfoil®           | 100 %        |
| Braid | 2     | TC - Tinned Copper |                     | 85 %         |

#### Outer Jacket Material

| Material                             | Nominal Diameter | Nominal Wall Thickness |
|--------------------------------------|------------------|------------------------|
| FEP - Fluorinated Ethylene Propylene | 0.159 in         | 0.014 in               |

### Electrical Characteristics

#### Conductor DCR

| Nominal Conductor DCR | Nominal Outer Shield DCR |
|-----------------------|--------------------------|
| 15.5 Ohm/1000ft       | 4.9 Ohm/1000ft           |

#### Capacitance

| Nom. Capacitance Conductor to Conductor | Nom. Capacitance Conductor to Other Conductor to Shield |
|-----------------------------------------|---------------------------------------------------------|
| 23 pF/ft                                | 40 pF/ft                                                |

Current

| Max. Recommended Current [A]  |
|-------------------------------|
| 2.2 Amps per conductor @ 25°C |

Voltage

| UL Voltage Rating |
|-------------------|
| 300 V RMS         |

Temperature Range

|                       |                 |
|-----------------------|-----------------|
| Operating Temp Range: | -70°C To +200°C |
|-----------------------|-----------------|

Mechanical Characteristics

|                                  |               |
|----------------------------------|---------------|
| Bulk Cable Weight:               | 25 lbs/1000ft |
| Max Recommended Pulling Tension: | 40 lbs        |
| Min Bend Radius/Minor Axis:      | 1.75 in       |

Standards

|                          |     |
|--------------------------|-----|
| NEC Articles:            | 800 |
| NEC/(UL) Specification:  | CMP |
| CEC/C(UL) Specification: | CMP |
| CPR Euroclass:           | Eca |

Applicable Environmental and Other Programs

|                                       |                               |
|---------------------------------------|-------------------------------|
| EU Directive 2000/53/EC (ELV):        | Yes                           |
| EU Directive 2003/96/EC (BFR):        | Yes                           |
| EU Directive 2011/65/EU (ROHS II):    | Yes                           |
| EU Directive 2012/19/EU (WEEE):       | Yes                           |
| EU Directive 2015/863/EU:             | Yes                           |
| EU Directive Compliance:              | EU Directive 2003/11/EC (BFR) |
| EU CE Mark:                           | Yes                           |
| EU RoHS Compliance Date (yyyy-mm-dd): | 2005-04-01                    |
| MII Order #39 (China RoHS):           | Yes                           |

Flammability, LSOH, Toxicity Testing

|                       |               |
|-----------------------|---------------|
| UL Flammability:      | NFPA 262      |
| CSA Flammability:     | FT6           |
| ISO/IEC Flammability: | IEC 60332-1-2 |
| UL voltage rating:    | 300 V RMS     |

Plenum/Non-Plenum

|               |     |
|---------------|-----|
| Plenum (Y/N): | Yes |
|---------------|-----|

Part Number

Variants

| Item #        | Color | Putup Type | Length   | UPC          |
|---------------|-------|------------|----------|--------------|
| 83554 002100  | Red   | Reel       | 100 ft   | 612825204954 |
| 83554 002500  | Red   | Reel       | 500 ft   | 612825204978 |
| 83554 0021000 | Red   | Reel       | 1,000 ft | 612825204961 |

|           |                        |
|-----------|------------------------|
| Footnote: | C - CRATE REEL PUT-UP. |
|-----------|------------------------|

Product Notes

|        |                                                                                                       |
|--------|-------------------------------------------------------------------------------------------------------|
| Notes: | Plenum Cables, except for Flamarrest® jacket, are suitable for Outdoor and Direct Burial application. |
|--------|-------------------------------------------------------------------------------------------------------|

History

|                      |                                                  |
|----------------------|--------------------------------------------------|
| Update and Revision: | Revision Number: 0.292 Revision Date: 04-28-2020 |
|----------------------|--------------------------------------------------|

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.