

Features

General Features:


- Siemens 900/1800/1900MHz MC55 GPRS modem (or as option: Selex RGM101 GSM-R with onboard or external SIM-card interface)
- 12-channel low power Fastrax iTrax03 GPS with NMEA and Binary protocols, +3.3V antennas
- Two available free 16C550 compatible RS-232/RS422/RS485 serial ports, two serial ports used by GPRS and GPS
- Audio I/O port for headset
- Two status LEDs indicating GPS status
- Jumperless configuration (addresses and IRQs)
- Setup stored on EEPROM
- Antenna starter kits available:
 - ACS-9110-00 (3-band GSM antenna kit) Refer to Technical Datasheet Td0019
 - ACS-9111-00 (GPS antenna kit) Refer to Technical Datasheet Td0006

RoHS:

- Fully RoHS (2002/95/CE) Compliant.

Supported Operating Systems:

- Windows CE®
- Linux®



The Eurotech COM-1289 integrates GSM/GPRS (optionally GSM-R) wireless cellular connectivity and a low power GPS receiver within a PC/104 module. This low power integrated telematics board is the ideal choice for onboard computing applications requiring GPRS roaming across three continents and precise GPS positioning. A standard SIM-card can be installed onboard into a locking card holder, or onto an external SIM card carrier.

The COM-1289 is available with the Fastrax iTrax03 12-channel GPS receiver and the Siemens MC55 GSM/GPRS modem, or as option the Selex RGM101 GSM-R modem. GSM-R is widely used in rail and rolling stock system devices throughout Europe and Asia.

Onboard features include a 4-channel 16C550 compatible UART with two multistandard RS-232/422/485 serial ports are free for other devices, while two ports are reserved for the onboard cellular GPRS modem and GPS receiver. Board configuration is performed in software eliminating banks of configuration, interrupt and base address jumpers. The setup information is stored in a non volatile EEPROM that is loaded upon power-up. Reconfiguring your COM-1289 is easy even after the system is completely assembled. The board supports full interrupt sharing for all the serial ports.

COM-1289

Main GPS Features

- Fastrax iTrax03 12-channel low power GPS receiver
- L1 frequency, C/A code (SPS)
- Update rate: 1fix/s (user configurable up to 3 Hz)
- Accuracy:
 - Position: 1.2m (CEP95)
 - Velocity: 0.1m/s
 - Time: 20ns rms (static mode)
- Reacquisition: 100ms (typical)
- Tracking sensitivity: -156 dBm
- Support for +3.3 active & passive external antennas
- Protocols: NMEA-0183 and proprietary iTalk™ binary protocol

Main GPRS Features

- Siemens MC55 900/1800/1900MHz
- Onboard or external 3V SIM card
- GPRS downlink data rate up to 85,6kbps
- 14,4kbps GSM data, group 3, class 2 fax services
- SMS and SMS cell broadcast
- GPRS mobile station class B and GPRS multi slot class 10 compliance
- WAP and MMS compliant
- Output power class 4 (2W) at 900MHz and class 1 (1W) at 1800/1900MHz

Main GSM-R Features (optional)

- Selex RGM101 GSM-R module
- Onboard or external 3V SIM card
- GPRS features:
 - Multi-slot capabilities: 4+1 max (class8)
 - Coding: CS1, CS2, CS3, CS4
- Output power:
 - class 4 (2W) GSM-R
 - class 1 (1W) DCS
- Sensivity: -102 dBm
- Frequency Band:

	UIC	E-GSM	DCS
UPLINK (MHz)	876 - 880	880 - 915	1710 - 1715
DOWNLINK (MHz)	921 - 925	925 - 960	1805 - 1880

Physical Characteristics

DIMENSIONS	90 x 96 mm (3.6" x 3.8")
HEIGHT	15 mm (0.6")
POWER SUPPLY	Single +5V DC +/- 5%
POWER CONSUMPTION	1.1 W (idle) 3.2 W (peak)
OPERATING TEMPERATURE	-20 ~ + 55°C (for GPRS) -40 ~ + 85°C (for GPS)
HUMIDITY	Up to 95% non-condensing

Options

- Conformal coating
- Selex RGM101 GSM-R radio modem

Typical Applications

- Vehicle and mobile computers
- Wireless Mobile Access Routers - MAR
- Telematics systems, onboard computing
- GSM-R Rail communication systems
- Fleet management
- Remote data acquisition and telemetry

About Eurotech

EuroTech delivers embedded computer systems for high capability and low power applications, networking and wearable computing solutions, and application framework middleware for multimedia, industrial, transportation, medical, and wireless applications. EuroTech platforms allow OEM and enterprise customers to focus on their core revenue-generating products and services and get to market quickly.

Note: The information in this document is subject to change without notice and should not be construed as a commitment by EUROTECH. While reasonable precautions have been taken, EUROTECH assumes no responsibility for any error that may appear in this document. All trademarks or registered trademarks are the properties of their respective companies.

ETH_COM-1289_DS071008

Americas

EUROTECH Inc
e-mail: sales-us@eurotech.com
tel: +1 301.490.4007
toll free: +1 888.941.2224

Western Europe

EUROTECH UK
e-mail: sales-uk@eurotech.com
tel: +44 (0) 1223 403.410

EUROTECH France
e-mail: sales-fr@eurotech.com
tel: +33 04.72.89.00.90

Central & Southern Europe

EUROTECH Italy
e-mail: sales-it@eurotech.com
tel: +39 0433.485.411

Northern & Eastern Europe

EUROTECH Finland
e-mail: sales-fi@eurotech.com
tel: +358 9.477.888.0



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.