



**Product:** [49747A](#)

D-Subminiature Assembly, 25 ft, (15) 24 AWG (7x32) TC, S-R PVC/PVC, Foil+TC Braid Shld, CM

[Request Sample](#)

## Product Description

Fifteen 24 AWG stranded (7x32) tinned copper conductors, S-R PVC insulation, Beldfoil® plus tinned copper braid shield, PVC jacket, twenty-five foot length.

## Technical Specifications

### Physical Characteristics (Overall)

#### Conductor

| AWG | Stranding | Material           | Nominal Diameter | No. of Conductors |
|-----|-----------|--------------------|------------------|-------------------|
| 24  | 7x32      | TC - Tinned Copper | 0.024 in         | 15                |

Conductor Count: 15

#### Insulation

| Material                                | Nominal Wall Thickness |
|---|------------------------|
| S-R PVC - Semi-Rigid Polyvinyl Chloride | 0.01 in                |

#### Outer Shield Material

| Type  | Layer | Material           | Material Trade Name | Coverage [%] |
|-------|-------|--------------------|---------------------|--------------|
| Tape  | 1     | Alum / Poly        | Beldfoil®           | 100%         |
| Braid | 2     | Tinned Copper (TC) |                     | 65%          |

#### Outer Jacket Material

| Material                 | Nominal Diameter | Nominal Wall Thickness |
|--------------------------|------------------|------------------------|
| PVC - Polyvinyl Chloride | 0.3 in           | 0.035 in               |

### Electrical Characteristics

#### Voltage

| UL Voltage Rating             |
|-------------------------------|
| 300 V RMS (UL AWM Style 2464) |

#### Temperature Range

|                 |                          |
|-----------------|--------------------------|
| UL Temp Rating: | 80°C (UL AWM Style 2464) |
|-----------------|--------------------------|

#### Standards

|                          |   |
|--------------------------|---|
| NEC/(UL) Compliance:     | CM (cable only)                         |
| UL AWM Style Compliance: | UL Style 2464 (300 V 80°C) (cable only) |

#### Applicable Environmental and Other Programs

|                             |                               |
|-----------------------------|-------------------------------|
| EU Directive Compliance:    | EU Directive 2003/11/EC (BFR) |
| MII Order #39 (China RoHS): | Yes                           |

#### Flammability, LSOH, Toxicity Testing

|                    |                               |
|--------------------|-------------------------------|
| UL voltage rating: | 300 V RMS (UL AWM Style 2464) |
|--------------------|-------------------------------|

## Plenum/Non-Plenum

Plenum (Y/N): No

## Part Number

### Variants

| Item #       | Color  | Length | UPC          |
|--------------|--------|--------|--------------|
| 49747A 060S2 | Chrome | 25 ft  | 612825154310 |

## Product Notes

Notes: Molded handles are 100% shielded to assist in FCC compliance and guard against EMI/RFI. All connectors tin-plated and male connectors have detents for positive ground connection. Wiring is point-to-point with the shield to connector shell.

## History

Update and Revision: Revision Number: 0.277 Revision Date: 04-28-2020

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.